

2,2-Dimethyloctane Safety Data Sheet 11001X3 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 12/22/2016 Version: 1.0

1.1. Identification	
	• • • • • • • • • • • • • • • • • • •
Product form	: Substance
Substance name	: 2,2-Dimethyloctane
CAS No	: 15869-87-1
Product code	: 1100-1-X3
Formula	: C10H22
Other means of identification	: MFCD00048900
1.2. Relevant identified uses of the s	substance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the sat	fety data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of Americ T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlabs	
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identificat	ion
2.1. Classification of the substance	
Flam. Liq. 3H226 - Flammable liquid and Skin Irrit. 2Skin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eyeSTOT SE 3H335 - May cause respirator	irritation
Eye Irrit. 2A H319 - Causes serious eye i STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	irritation
Flam. Liq. 3 H226 - Flammable liquid and Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye i STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	irritation
Flam. Liq. 3 H226 - Flammable liquid and Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye i STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	$\frac{1}{1}$
Flam. Liq. 3 H226 - Flammable liquid and Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye i STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements	n irritation ry irritation
Flam. Liq. 3 H226 - Flammable liquid and Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye i STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	$\frac{1}{1}$

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	P31. P32 P33. P33 P36. P37 P40 P40 P40	es, if present and easy to do. Continue rir 2 - Call a POISON CENTER or doctor/phy 1 - Specific treatment (see supplemental if 2+P313 - If skin irritation occurs: Get med 2+P364 - Take off contaminated clothing 2+P378 - In case of fire: Use dry sand, dr 3+P233 - Store in a well-ventilated place. 3+P235 - Store in a well-ventilated place. 5 - Store locked up 1 - Dispose of contents/container to an ap	vsician if you fer irst aid instructi ical advice/atter dical advice/atter and wash it befor y chemical or al Keep container Keep cool	ons on this label) ntion ention ore reuse cohol-resistant foam to extinguish tightly closed
2.3. Other hazards No additional information available				
2.4. Unknown acute toxicity (GHS US)				
Not applicable				
SECTION 3: Composition/informati	on on i	paredients		
3.1. Substance				
Substance type	: Mon	o-constituent		
Name			%	Classification (CHS-US)
2,2-Dimethyloctane		Product identifier (CAS No) 15869-87-1	% <= 100	Classification (GHS-US) Flam. Liq. 3, H226
(Main constituent)				Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Full text of H-phrases: see section 16				
3.2. Mixture				
Not applicable				
SECTION 4: First aid measures				
4.1. Description of first aid measures				
First-aid measures general		ase of accident or if you feel unwell, seek re possible). Move the affected personnel		
First-aid measures after inhalation		nove person to fresh air and keep comfort iration. Get medical advice/attention.	able for breathi	ng. If not breathing, give artificial
First-aid measures after skin contact		h with plenty of soap and water. Get med		
First-aid measures after eye contact	pres	ediately flush eyes thoroughly with water ent and easy to do. Continue rinsing. Get	medical advice	attention.
First-aid measures after ingestion		NOT induce vomiting. Never give anything th out with water. Get medical advice/atte		n unconscious person. Rinse
4.2. Most important symptoms and effe	ects, both	acute and delayed		
Symptoms/injuries		most important known symptoms and effe and/or in section 11.	ects are describ	ed in the labelling (see section
4.3. Indication of any immediate medic	al attenti	on and special treatment needed		
Treat symptomatically.				
SECTION 5: Firefighting measures				
5.1. Extinguishing media				
Suitable extinguishing media		hol resistant foam. Carbon dioxide. Dry p opriate for surrounding fire.	owder. Water s	pray. Use extinguishing media
5.2. Special hazards arising from the s	ubstance	or mixture		
Fire hazard		mal decomposition generates: Carbon ox		
Explosion hazard		of explosion if heated under confinement ainers. May form flammable/explosive va		ay or fog for cooling exposed
5.3. Advice for firefighters				
Firefighting instructions	: In ca	ase of fire: Evacuate area. Fight fire remo	•	•
				with self contained breathing

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures			
6.1. Personal precautions, protective equ	ipment and emergency procedures		
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes, vapor or spray.		
6.1.1. For non-emergency personnel			
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.		
6.1.2. For emergency responders			
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".		
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.		
6.2. Environmental precautions			
Avoid release to the environment. Notify authoritie	es if product enters sewers or public waters.		
6.3. Methods and material for containment	nt and cleaning up		
For containment	: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.		
Methods for cleaning up	: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.		
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".		
6.4. Reference to other sections			
No additional information available			
SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.		
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.		
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.		
7.2. Conditions for safe storage, including any incompatibilities			
Technical measures	: Comply with applicable regulations.		
Storage conditions	: Keep container closed when not in use. Keep away from ignition sources.		
Incompatible materials	: Refer to Section 10 on Incompatible Materials.		
Storage area	: Store in dry, cool, well-ventilated area.		

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

No additional information available

8.2. Exposure controls	
Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations			
SECTION 9: Physical and chemical properties			
9.1. Information on basic physical and chemical properties			
Physical state	: Liquid		
Color	: No data available		
Odor	: No data available		
Odor threshold	: No data available		
рН	: No data available		
Melting point	: No data available		
Freezing point	: No data available		
Boiling point	: 155 °C		
Flash point	: No data available		
Relative evaporation rate (butyl acetate=1)	: No data available		
Flammability (solid, gas)	: No data available		
Explosion limits	: No data available		
Explosive properties	: No data available		
Oxidizing properties	: No data available		
Vapor pressure	: No data available		
Relative density	: No data available		
Relative vapor density at 20 °C	: No data available		
Specific gravity / density	: 0.724 g/ml (@ 25 °C)		
Molecular mass	: 142.28 g/mol		
Solubility	: No data available		
Log Pow	: No data available		
Auto-ignition temperature	: No data available		
Decomposition temperature	: No data available		
Viscosity	: No data available		
Viscosity, kinematic	: No data available		
Viscosity, dynamic	: No data available		
9.2. Other information			
No additional information available			
SECTION 10: Stability and reactivity			
10.1. Reactivity			
No additional information available			
10.2. Chemical stability			
The product is stable at normal handling and storage conditions.			
10.3 Possibility of bazardous reactions			

10.3. Possibility of hazardous reactions No additional information available

10.4. Conditions to avoid

Keep away from heat, sparks and flame.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information			
11.1. Information on toxicological effects			
Acute toxicity	: Not classified		
Skin corrosion/irritation	: Causes skin irritation.		
Serious eye damage/irritation	: Causes serious eye irritation.		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	-
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity Specific target organ toxicity (single exposure)	: Not classified : May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information			
12.1.	Toxicity		
No additional information available			
12.2.	Persistence and degradability		
No additional information available			
12.3.	Bioaccumulative potential		
No additional information available			
12.4.	Mobility in soil		
No additional information available			
12.5.	Other adverse effects		
No additional information available			

SECTION 13: Disposal considerations			
13.1. Waste treatment methods			
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.		
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.		
Additional information	: Recycle the material as far as possible.		

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT Transport document description

UN-No.(DOT) Proper Shipping Name (DOT) Transport hazard class(es) (DOT) Hazard labels (DOT)

Packing group (DOT) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Symbols : UN1993 Flammable liquids, n.o.s., 3, III

: UN1993

- : Flammable liquids, n.o.s.
- : 3 Class 3 Flammable and combustible liquid 49 CFR 173.120
- : 3 Flammable liquid



: III - Minor Danger

: 203

- : 242
- : G Identifies PSN requiring a technical name

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	 B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 1993
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, N.O.S.
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
Air transport	
UN-No. (IATA)	: 1993
Proper Shipping Name (IATA)	: Flammable liquid, n.o.s.
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger
SECTION 15: Regulatory information	
15.1. US Federal regulations	
All companents of this product are listed, or ave	Judged from listing, on the United States Environmental Protection Agency Toxic

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

2,2-Dimethyloctane CAS N	15869-87-1 100%
--------------------------	-----------------

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

2,2-Dimethyloctane (15869-87-1)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Eye Irr	t. 2A	Serious eye damage/eye irritation Category 2A
Flam. I	.iq. 3	Flammable liquids Category 3
Skin In	it. 2	Skin corrosion/irritation Category 2
STOT	SE 3	Specific target organ toxicity (single exposure) Category 3
H226		Flammable liquid and vapor
H315		Causes skin irritation
H319		Causes serious eye irritation
H335		May cause respiratory irritation
NFPA health ha		 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given. 2 - Must be moderately heated or exposed to relatively high
NIT A life haza	u .	temperature before ignition can occur.
NFPA reactivity	:	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating		
Health		: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability		: 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)
Physical		: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.