

Safety Data Sheet 1100301 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 09/02/2016 Version: 1.0

1.1. Identification	
Product form	: Substance
Substance name	: Fluoromethane
CAS No	: 593-53-3
Product code	: 1100-3-01
Formula	: CH3F
Synonyms	: Methyl fluoride
	,
Other means of identification	: MFCD00039282
1.2. Relevant identified uses of the	substance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the sa	afety data sheet
SynQuest Laboratories, Inc.	· ·
P.O. Box 309	
Alachua, FL 32615 - United States of Amer	rica
T (386) 462-0788 - F (386) 462-7097 info@synguestlabs.com - <u>www.synguestlab</u>	bs.com
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identificat	tion
2.1. Classification of the substance	
Classification (GHS-US)	
Liquefied gas H280 - Contains gas under Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious ey	er pressure; may explode if heated tion ye irritation
Liquefied gasH280 - Contains gas underSkin Irrit. 2H315 - Causes skin irritatEye Irrit. 2AH319 - Causes serious eySTOT SE 3H335 - May cause respirat	er pressure; may explode if heated tion ye irritation
Liquefied gas H280 - Contains gas under Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16	er pressure; may explode if heated tion ye irritation
Liquefied gasH280 - Contains gas under Skin Irrit. 2Skin Irrit. 2H315 - Causes skin irritatEye Irrit. 2AH319 - Causes serious eySTOT SE 3H335 - May cause respiratFull text of H-phrases: see section 162.2.Label elements	er pressure; may explode if heated tion ye irritation
Liquefied gas H280 - Contains gas under Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	er pressure; may explode if heated tion ye irritation
Liquefied gas       H280 - Contains gas under Skin Irrit. 2         Skin Irrit. 2       H315 - Causes skin irritat         Eye Irrit. 2A       H319 - Causes serious ey         STOT SE 3       H335 - May cause respirat         Full text of H-phrases: see section 16         2.2.       Label elements         GHS-US labeling	er pressure; may explode if heated tion ye irritation atory irritation
Liquefied gas H280 - Contains gas under Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	er pressure; may explode if heated tion ye irritation atory irritation
Liquefied gas H280 - Contains gas under Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	er pressure; may explode if heated tion ye irritation atory irritation : CHS02 GHS02 GHS04 GHS04 GHS07 : Danger
Liquefied gas H280 - Contains gas under Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	<ul> <li>ier pressure; may explode if heated tion ye irritation atory irritation atory irritation</li> <li>: i i i i i i i i i i i i i i i i i i</li></ul>
Liquefied gas H280 - Contains gas under Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16	<ul> <li>ier pressure; may explode if heated tion ye irritation atory irritation</li> <li>i i i i i i i i i i i i i i i i i i i</li></ul>

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	P332 P337 P362 P377 P381 P403 P403 P405 P410	<ul> <li>Specific treatment (see supplemental +P313 - If skin irritation occurs: Get me +P313 - If eye irritation persists: Get me +P364 - Take off contaminated clothing</li> <li>Leaking gas fire: Do not extinguish, u</li> <li>Eliminate all ignition sources if safe to</li> <li>Store in a well-ventilated place</li> <li>+P233 - Store in a well-ventilated place</li> <li>Store locked up</li> <li>+P403 - Protect from sunlight. Store in a</li> <li>Dispose of contents/container to an a</li> </ul>	dical advice/atte adical advice/atte and wash it be nless leak can b o do so . Keep containe a well-ventilated	ention ention fore reuse be stopped safely er tightly closed d place
2.3. Other hazards Other hazards not contributing to the classification		e may form flammable/explosive vapor-a ted under confinement.	air mixture. May	v cause frostbite. Risk of explosion
2.4. Unknown acute toxicity (GHS US)				
Not applicable				
SECTION 3: Composition/informati	on on in	gredients		
3.1. Substance				
Substance type	: Mono	-constituent		
Name		Product identifier	%	Classification (GHS-US)
Fluoromethane (Main constituent)		(CAS No) 593-53-3	<= 100	Simple Asphy, H380 Flam. Gas 1, H220 Liquefied gas, H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Full text of H-phrases: see section 16				
3.2. Mixture				
Not applicable				
SECTION 4: First aid measures				
4.1. Description of first aid measures				
First-aid measures general	where	se of accident or if you feel unwell, seek possible). Move the affected personne	el away from the	e contaminated area.
First-aid measures after inhalation		ove person to fresh air and keep comfor ation. Get immediate medical advice/at		ing. If not breathing, give artificial
First-aid measures after skin contact		frosted parts with lukewarm water. Do e/attention.	no rub affected	area. Get immediate medical
First-aid measures after eye contact		ove contact lenses, if present and easy upper a set of the set of		
First-aid measures after ingestion	give a	o its physical form, exposure to this che anything by mouth to an unconscious pe e/attention.		
4.2. Most important symptoms and effe	ects, both	acute and delayed		
Symptoms/injuries		nost important known symptoms and ef nd/or in section 11.	fects are descri	bed in the labelling (see section
Symptoms/injuries after inhalation	: May o	cause drowsiness or dizziness.		
Symptoms/injuries after skin contact		act with the liquid the may cause cold bu		
Symptoms/injuries after eye contact		t contact with the liquefied gas may cau stbite from rapid liquid evaporation.	se severe and p	possibly permanent eye injury due
4.3. Indication of any immediate medic	al attentio	n and special treatment needed		
No additional information available				
SECTION 5: Firefighting measures				
5.1. Extinguishing media				
Suitable extinguishing media		ol resistant foam. Carbon dioxide. Dry p priate for surrounding fire.	oowder. Water s	spray. Use extinguishing media
5.2. Special hazards arising from the s				
Fire hazard		nal decomposition generates: Carbon o	xides. Hydroge	n fluoride.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion hazard	: Contains gas under pressure; may explode if heated. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.
5.3. Advice for firefighters	
Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection during firefighting	: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures			
6.1. Personal precautions, protective equipment and emergency procedures			
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.		
6.1.1. For non-emergency personnel			
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.		
6.1.2. For emergency responders			
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".		
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.		
6.2. Environmental precautions			
Avoid release to the environment. Notify authorities	es if product enters sewers or public waters.		
6.3. Methods and material for containme	nt and cleaning up		
For containment	: Stop leak if safe to do so.		
Methods for cleaning up	: Ventilate area.		
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".		
6.4. Reference to other sections			
No additional information available			
SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care because residual vapors are flammable. Close valve after each use and when empty.		
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.		
Safe handling of the gas receptacle	: Securely chain cylinders when in use and protect against physical damage.		
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.		
7.2. Conditions for safe storage, including any incompatibilities			
Technical measures	: Comply with applicable regulations.		
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use. Keep away from ignition sources.		
Incompatible materials	: Refer to Section 10 on Incompatible Materials.		
Storage area	: Store in dry, cool, well-ventilated area.		

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. **Control parameters**

No additional information available

8.2.	Exposure controls	
Appropria	ate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released.

# Safety Data Sheet according to Federal Register / V

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations		
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.	
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.	
Skin and body protection	: Wear suitable protective clothing.	
Respiratory protection	<ul> <li>In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.</li> </ul>	
Thermal hazard protection	: Cold insulating gloves.	
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.	

## **SECTION 9: Physical and chemical properties**

SECTION 9. Physical and chemical	i properties
9.1. Information on basic physical and	I chemical properties
Physical state	: Gas
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Melting point	: -114.8 °C
Freezing point	: No data available
Boiling point	: -78.5 °C
Critical temperature	: 97 °C
Critical pressure	: 44.6 psia
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: 552 psia (@ 21 °C)
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.8817 g/ml (@ -78.5 °C)
Molecular mass	: 34.03 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
9.2. Other information	
Refractive index	: 1.1674 (@ 25 °C)

SECTI	ON 10: Stability and reactivity		
10.1.	Reactivity		
No additi	ional information available		
10.2.	Chemical stability		
The product is stable at normal handling and storage conditions.			
10.3.	Possibility of hazardous reactions		
No additi	ional information available		
10.4.	Conditions to avoid		
Protect fi	rom sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.		
10.5.	Incompatible materials		

Strong oxidizing agents.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitization Germ cell mutagenicity Carcinogenicity Reproductive toxicity	<ul> <li>Causes skin irritation.</li> <li>Causes serious eye irritation.</li> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> </ul>
Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure)	<ul><li>May cause respiratory irritation.</li><li>Not classified</li></ul>
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation Symptoms/injuries after skin contact Symptoms/injuries after eye contact	<ul> <li>May cause drowsiness or dizziness.</li> <li>Contact with the liquid the may cause cold burns/frostbite.</li> <li>Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.</li> </ul>

SECTION 12: Ecological information			
12.1. Toxicity			
No additional information available			
12.2. Persistence and degradability			
No additional information available			
12.3. Bioaccumulative potential			
No additional information available			
12.4. Mobility in soil			
No additional information available			
12.5. Other adverse effects			
No additional information available			

SECTION 13: Disposal considerations			
13.1. Waste treatment methods			
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.		
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.		
Additional information	: Recycle the material as far as possible.		
SECTION 14: Transport information			
Department of Transportation (DOT)			

In accordance with DOT	
Transport document description	: UN2454 Methyl fluoride, 2.1
UN-No.(DOT)	: UN2454
Proper Shipping Name (DOT)	: Methyl fluoride
Transport hazard class(es) (DOT)	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT)	: 2.1 - Flammable gas
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304
DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: Forbidden
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Emergency Response Guide (ERG) Number	: 115
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 2454
Proper Shipping Name (IMDG)	: METHYL FLUORIDE (REFRIGERANT GAS R 41)
Class (IMDG)	: 2 - Gases
Air transport	
UN-No. (IATA)	: 2454
Proper Shipping Name (IATA)	: Methyl fluoride
Class (IATA)	: 2
CECTION 45. Desculators information	
SECTION 15: Regulatory information 15.1. US Federal regulations	
Fluoromethane (593-53-3)	

#### Fluoromethane (593-53-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### 15.2. International regulations

ANADA			
Fluoromethane (593-53-3)			
Listed on the Canadian NDSL (Non-Domestic Substances List)			
WHMIS Classification	Class A - Compressed Gas		

**EU-Regulations** 

No additional information available

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations
Fluoromethane (593-53-3)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on INSQ (Mexican national Inventory of Chemical Substances)

15.3. US State regulations		
Fluoromethane (593-53-3)		
State or local regulations	U.S New Jersey - Right to Know Hazardous Substance List	

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

#### **SECTION 16: Other information**

Full text of H-phrases:

1 411 10/11 01 11 p111 400001	
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Gas 1	Flammable gases Category 1
Liquefied gas	Gases under pressure Liquefied gas
Simple Asphy	Simple Asphyxiant
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H380	May displace oxygen and cause rapid suffocation
NFPA fire hazard	<ul> <li>residual injury even though prompt medical attention was given.</li> <li>4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.</li> <li>3 - Capable of detonation or explosive reaction, but requires a strong initiating source or must be heated under confinement before initiation, or reacts explosively with water.</li> </ul>
HMIS III Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	<ul> <li>4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below</li> <li>73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)</li> </ul>
Physical	: 3 Serious Hazard - Materials that may form explosive mixtures with water and are capable of detonation or explosive reaction in the presence of a strong initiating source. Materials may polymerize, decompose, self-react, or undergo other chemical change at normal temperature

#### SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.