

Safety Data Sheet 1100303 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Version: 1.0

Date of issue: 05/02/2016

SECTION 1: Identification	
1.1. Identification	
Product form	: Substance
Substance name	: Trifluoromethane
CAS No	: 75-46-7
Product code	: 1100-3-03
Formula	: CHF3
Synonyms	: Fluoroform; HFC-23
Other means of identification	: MFCD00000446
.2. Relevant identified uses of the	substance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the sa	afety data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of Amer T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - <u>www.synquestlat</u>	
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identificat	tion
2.1. Classification of the substance	
Classification (GHS-US)	
Liquefied gas H280 - Contains gas und Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious e	ye irritation
Liquefied gas H280 - Contains gas und Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious e STOT SE 3 H335 - May cause respira	er pressure; may explode if heated tion ye irritation
Liquefied gas H280 - Contains gas und Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respira Full text of H-phrases: see section 16	er pressure; may explode if heated tion ye irritation
Liquefied gas H280 - Contains gas und Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious e STOT SE 3 H335 - May cause respira Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	er pressure; may explode if heated tion ye irritation
Liquefied gas H280 - Contains gas und Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious e STOT SE 3 H335 - May cause respira Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	er pressure; may explode if heated tion ye irritation
Liquefied gas H280 - Contains gas und Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respira Full text of H-phrases: see section 16 2.2. Label elements	er pressure; may explode if heated tion ye irritation atory irritation
Liquefied gas H280 - Contains gas und Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respira Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	er pressure; may explode if heated tion ye irritation atory irritation
Liquefied gas H280 - Contains gas und Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respira Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	 Fer pressure; may explode if heated tion ye irritation atory irritation atory irritation Ferritation Ferritation Ferritation Ferrit

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Regist	ter / Vol. 77, No. 58 / Monday, March 2	6, 2012 / Rules and Regulations		
	P4(P4(P4	62+P364 - Take off contaminated clothing a 03+P233 - Store in a well-ventilated place. 05 - Store locked up 10+P403 - Protect from sunlight. Store in a 01 - Dispose of contents/container to an ap	Keep container to well-ventilated p	tightly closed place
2.3. Other hazar	ds			
Other hazards not con classification	tributing to the : Ma	y cause frostbite.		
2.4. Unknown a	cute toxicity (GHS US)			
Not applicable				
SECTION 3: Com	position/information on i	ngredients		
3.1. Substance				
Substance type	: Mo	no-constituent		
Name		Product identifier	%	Classification (GHS-US)
Trifluoromethane (Main constituent)		(CAS No) 75-46-7	<= 100	Simple Asphy, H380 Liquefied gas, H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Full text of H-phrases:	see section 16			
3.2. Mixture				
Not applicable				
SECTION 4: First				
	of first aid measures			
First-aid measures ger	whe	ase of accident or if you feel unwell, seek is possible). Move the affected personnel	away from the c	contaminated area.
First-aid measures afte	res	nove person to fresh air and keep comforta piration. Get immediate medical advice/atte	ention.	
First-aid measures after		sh with plenty of soap and water. Get med		
First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Immediately flush eyes thoroughly with water for at least 15 minutes. Get medical advice/attention.		ice/attention.		
First-aid measures afte	give	 to its physical form, exposure to this cherned anything by mouth to an unconscious per ice/attention. 		
4.2. Most impor	tant symptoms and effects, bot	h acute and delayed		
Symptoms/injuries		e most important known symptoms and effe) and/or in section 11.	ects are describe	ed in the labelling (see section
Symptoms/injuries after		y cause drowsiness or dizziness.		
Symptoms/injuries after		ntact with the liquid the may cause cold bu		
Symptoms/injuries afte		ect contact with the liquefied gas may caus rostbite from rapid liquid evaporation.	e severe and po	ssibly permanent eye injury due
4.3. Indication of No additional information		ion and special treatment needed		
SECTION 5: Firef	ighting measures		_	
5.1. Extinguishi				
Suitable extinguishing		ohol resistant foam. Carbon dioxide. Dry po propriate for surrounding fire.	owder. Water sp	ray. Use extinguishing media
5.2. Special haz	ards arising from the substance	e or mixture		
Fire hazard	: The	ermal decomposition generates: Carbon ox	ides. Hydrogen	fluoride.
Explosion hazard		ntains gas under pressure; may explode if l osed containers.	heated. Use wat	er spray or fog for cooling
5.3. Advice for f	irefighters			
Firefighting instruction	s : In c	ase of fire: Evacuate area. Fight fire remot	ely due to the ris	sk of explosion.
Protection during firefig		ar gas tight chemically protective clothing i aratus. For further information refer to sec		

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures			
6.1. Personal precautions, protective equipment and emergency procedures			
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.		
6.1.1. For non-emergency personnel			
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.		
6.1.2. For emergency responders			
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".		
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.		
6.2. Environmental precautions			
Avoid release to the environment. Notify authoritie	es if product enters sewers or public waters.		
6.3. Methods and material for containmer	nt and cleaning up		
For containment	: Stop leak if safe to do so.		
Methods for cleaning up	: Ventilate area.		
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".		
6.4. Reference to other sections			
No additional information available			
SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Close valve after each use and when empty.		
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes.		
Safe handling of the gas receptacle	: Securely chain cylinders when in use and protect against physical damage.		
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.		
7.2. Conditions for safe storage, including any incompatibilities			
Technical measures	: Comply with applicable regulations.		
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use.		
Incompatible materials	: Refer to Section 10 on Incompatible Materials.		
Storage area	: Store in dry, cool, well-ventilated area.		

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

No additional information available

8.2. Exposure controls	
Appropriate engineering controls	 Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Thermal hazard protection	: Cold insulating gloves.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. 77, No. 58 / Monda	according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations		
SECTION 9: Physical and chemical properties			
9.1. Information on basic physical and	9.1. Information on basic physical and chemical properties		
Physical state	: Gas		
Color	: No data available		
Odor	: No data available		
Odor threshold	: No data available		
рН	: No data available		
Melting point	: -160		
Freezing point	: No data available		
Boiling point	: -84		
Flash point	: No data available		
Relative evaporation rate (butyl acetate=1)	: No data available		
Flammability (solid, gas)	: No data available		
Explosion limits	: No data available		
Explosive properties	: No data available		
Oxidizing properties	: No data available		
Vapor pressure	: 649.0 psia (@ 21 °C)		
Relative density	: No data available		
Relative vapor density at 20 °C	: No data available		
Specific gravity / density	: 1.246 g/ml (@ -34 °C)		
Molecular mass	: 70.01 g/mol		
Solubility	: No data available		
Log Pow	: No data available		
Auto-ignition temperature	: No data available		
Decomposition temperature	: No data available		
Viscosity	: No data available		
Viscosity, kinematic	: No data available		
Viscosity, dynamic	: No data available		
9.2. Other information			
No additional information available			
SECTION 10: Stability and reactivit	У		
10.1. Reactivity			

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information			
11.1.	1.1. Information on toxicological effects		
Acute to	xicity	: Not classified	
Skin cor	rosion/irritation	: Causes skin irritation.	
Serious	eye damage/irritation	: Causes serious eye irritation.	

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

: Not classified
: Not classified
: Not classified
: Not classified
: May cause respiratory irritation.
: Not classified
: Not classified
: May cause drowsiness or dizziness.
: Contact with the liquid the may cause cold burns/frostbite.
: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

SECTIO	ON 12: Ecological information
12.1.	Toxicity
No additi	onal information available
12.2.	Persistence and degradability
No additi	onal information available
12.3.	Bioaccumulative potential
No additi	onal information available
12.4.	Mobility in soil
No additi	onal information available
12.5.	Other adverse effects
No additi	onal information available

SECTION 13: Disposal consideration	S
13.1. Waste treatment methods	
Waste treatment methods Waste disposal recommendations Additional information	 Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber. Dispose of contents/container in accordance with licensed collector's sorting instructions. Recycle the material as far as possible.
SECTION 14: Transport information	
Department of Transportation (DOT) In accordance with DOT Transport document description	: UN1984 Trifluoromethane, 2.2
UN-No.(DOT)	: UN1984
Proper Shipping Name (DOT)	: Trifluoromethane
Transport hazard class(es) (DOT)	: 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115
Hazard labels (DOT)	: 2.2 - Non-flammable gas
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304
DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	: 120 (UN3136);126 (UN1984)
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 1984
Proper Shipping Name (IMDG)	: TRIFLUOROMETHANE (REFRIGERANT GAS R 23)
Class (IMDG)	: 2 - Gases
Air transport	
UN-No. (IATA)	: 1984
Proper Shipping Name (IATA)	: Trifluoromethane
Class (IATA)	: 2

SECTION 15: Regulatory information

15.1. US Federal regulations

Trifluoromethane (75-46-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations		
CANADA		
Trifluoromethane (75-46-7)		
Listed on the Canadian DSL (Domestic Sustances List)		
WHMIS Classification	Class A - Compressed Gas	

EU-Regulations

No additional information available

National regulations

15.3. US State regulations	
Trifluoromethane (75-46-7)	
State or local regulations	U.S New Jersey - Right to Know Hazardous Substance List

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full tex	t of H-phrases:	
	Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
	Liquefied gas	Gases under pressure Liquefied gas
	Simple Asphy	Simple Asphyxiant
	Skin Irrit. 2	Skin corrosion/irritation Category 2
	STOT SE 3	Specific target organ toxicity (single exposure) Category 3
	H280	Contains gas under pressure; may explode if heated
	H315	Causes skin irritation
	H319	Causes serious eye irritation
	H335	May cause respiratory irritation
	H380	May displace oxygen and cause rapid suffocation
NFPA	health hazard fire hazard reactivity	 : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given. : 1 - Must be preheated before ignition can occur. : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
	II Rating	
Health		: 2 Moderate Hazard - Temporary or minor injury may occur
Flamm	ability	 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physic	al	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.