

1,1,1-Trifluoroethane Safety Data Sheet 1100307 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 06/20/2016 Version: 1.0

SECTION 1: Identification	
1.1. Identification	
Product form	: Substance
Substance name	: 1,1,1-Trifluoroethane
CAS No	: 420-46-2
Product code	: 1100-3-07
Formula	: C2H3F3
Synonyms	: R-143a
Other means of identification	: MFCD00013575
	substance or mixture and uses advised against
Use of the substance/mixture	Laboratory chemicals     Manufacture of substances     Scientific research and development
1.3. Details of the supplier of the sa	afety data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of Amer T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlab	
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identificat	tion
2.1. Classification of the substance	e or mixture
Classification (GHS-US)	
Flam. Gas 1H220 - Extremely flammaLiquefied gasH280 - Contains gas underSkin Irrit. 2H315 - Causes skin irritat	er pressure; may explode if heated tion
Flam. Gas 1H220 - Extremely flammaLiquefied gasH280 - Contains gas underSkin Irrit. 2H315 - Causes skin irritatEye Irrit. 2AH319 - Causes serious eySTOT SE 3H335 - May cause respirat	ble gas er pressure; may explode if heated tion ye irritation
Flam. Gas 1H220 - Extremely flammaLiquefied gasH280 - Contains gas underSkin Irrit. 2H315 - Causes skin irritatEye Irrit. 2AH319 - Causes serious eySTOT SE 3H335 - May cause respiratFull text of H-phrases: see section 16	ble gas er pressure; may explode if heated tion ye irritation
Flam. Gas 1H220 - Extremely flammaLiquefied gasH280 - Contains gas underSkin Irrit. 2H315 - Causes skin irritatEye Irrit. 2AH319 - Causes serious extremelySTOT SE 3H335 - May cause respiratFull text of H-phrases: see section 162.2.Label elements	ble gas er pressure; may explode if heated tion ye irritation
Flam. Gas 1       H220 - Extremely flamma         Liquefied gas       H280 - Contains gas under Skin Irrit. 2         Skin Irrit. 2       H315 - Causes skin irritat         Eye Irrit. 2A       H319 - Causes serious eyes         STOT SE 3       H335 - May cause respirat         Full text of H-phrases: see section 16         2.2.       Label elements         GHS-US labeling	ble gas er pressure; may explode if heated tion ye irritation
Flam. Gas 1 H220 - Extremely flamma Liquefied gas H280 - Contains gas undo Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respira Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	able gas er pressure; may explode if heated tion ye irritation atory irritation
Flam. Gas 1       H220 - Extremely flamma         Liquefied gas       H280 - Contains gas under Skin Irrit. 2         Skin Irrit. 2       H315 - Causes skin irritat         Eye Irrit. 2A       H319 - Causes serious ey         STOT SE 3       H335 - May cause respirat         Full text of H-phrases: see section 16         2.2.       Label elements         GHS-US labeling         Hazard pictograms (GHS-US)	<ul> <li>able gas er pressure; may explode if heated tion ye irritation atory irritation</li> <li>Constant of the steed toon ye irritation</li> <li>Constant of the steed toon toon toon toon toon toon toon too</li></ul>
Flam. Gas 1 H220 - Extremely flamma Liquefied gas H280 - Contains gas undo Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respira Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	able gas er pressure; may explode if heated tion ye irritation atory irritation
Flam. Gas 1 H220 - Extremely flamma Liquefied gas H280 - Contains gas under Skin Irrit. 2 H315 - Causes skin irritat Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	<ul> <li>able gas er pressure; may explode if heated tion ye irritation atory irritation</li> <li> <b>Constant of the state of the sta</b></li></ul>

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	P321 - Specific treatment (see s P332+P313 - If skin irritation oc P337+P313 - If eye irritation pel P362+P364 - Take off contamir P377 - Leaking gas fire: Do not P381 - Eliminate all ignition sou P403 - Store in a well-ventilated P403+P233 - Store in a well-ventilated P405 - Store locked up P410+P403 - Protect from sunli P501 - Dispose of contents/con	curs: Get medi sists: Get med ated clothing a extinguish, unl rces if safe to c place ntilated place. I ght. Store in a	cal advice/atter lical advice/atter ad wash it befor ess leak can be do so Keep container well-ventilated	ntion ntion pre reuse e stopped safely tightly closed place
2.3. Other hazards				
Other hazards not contributing to the classification	: May cause frostbite.			
2.4. Unknown acute toxicity (GHS US)				
Not applicable				
SECTION 3: Composition/information	on ingredients			
3.1. Substance				
Substance type	: Mono-constituent			
Name	Product identifier		%	Classification (GHS-US)
1,1,1-Trifluoroethane (Main constituent)	(CAS No) 420-46-2		<= 100	Simple Asphy, H380 Flam. Gas 1, H220 Liquefied gas, H280 Skin Irit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Full text of H-phrases: see section 16				
3.2. Mixture				
Not applicable				
SECTION 4: First aid measures				
4.1. Description of first aid measures First-aid measures general	: In case of accident or if you feel	upwell sook r	nodical advica	immodiately (show the label
Ū.	where possible). Move the affect	ted personnel	away from the	contaminated area.
First-aid measures after inhalation	: Remove person to fresh air and respiration. Get immediate med	•		ng. If not breathing, give artificial
First-aid measures after skin contact	: Thaw frosted parts with lukewar advice/attention.	m water. Do no	o rub affected a	area. Get immediate medical
First-aid measures after eye contact	: Remove contact lenses, if prese thoroughly with water for at leas			
First-aid measures after ingestion	: Due to its physical form, exposu give anything by mouth to an ur advice/attention.			y. Do NOT induce vomiting. Never uth out with water. Get medical
4.2. Most important symptoms and effects	s, both acute and delayed			
Symptoms/injuries	: The most important known sym 2.2) and/or in section 11.	ptoms and effe	cts are describ	ed in the labelling (see section
Symptoms/injuries after inhalation	: May cause drowsiness or dizzir	ess.		
Symptoms/injuries after skin contact	: Contact with the liquid the may	cause cold bur	ns/frostbite.	
Symptoms/injuries after eye contact	: Direct contact with the liquefied to frostbite from rapid liquid eva		e severe and po	ossibly permanent eye injury due
4.3. Indication of any immediate medical a	attention and special treatment	needed		
No additional information available				
SECTION 5: Firefighting measures				
5.1. Extinguishing media				
	: Alcohol resistant foam. Carbon appropriate for surrounding fire.	dioxide. Dry po	wder. Water sp	oray. Use extinguishing media
5.2. Special hazards arising from the subs				
	: Thermal decomposition generat	es: Carbon oxi	des. Hydrogen	fluoride.
	EN (English LIS)		SDS ID: 1100307	2/7

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion hazard	: Contains gas under pressure; may explode if heated. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.
5.3. Advice for firefighters	
Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection during firefighting	: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equipment and emergency procedures		
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.	
6.1.1. For non-emergency personnel		
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.	
6.1.2. For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.	
6.2. Environmental precautions		
Avoid release to the environment. Notify authoritie	s if product enters sewers or public waters.	
6.3. Methods and material for containment	t and cleaning up	
For containment	: Stop leak if safe to do so.	
Methods for cleaning up	: Ventilate area.	
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".	
6.4. Reference to other sections		
No additional information available		
SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care because residual vapors are flammable. Close valve after each use and when empty.	
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.	
Safe handling of the gas receptacle	: Securely chain cylinders when in use and protect against physical damage.	
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.	
7.2. Conditions for safe storage, including any incompatibilities		
Technical measures	: Comply with applicable regulations.	
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use. Keep away from ignition sources.	
Incompatible materials	: Refer to Section 10 on Incompatible Materials.	
Storage area	: Store in dry, cool, well-ventilated area.	

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. **Control parameters**

No additional information available

8.2.	Exposure controls	
Appropria	ate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released.

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations		
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.	
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.	
Skin and body protection	: Wear suitable protective clothing.	
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.	
Thermal hazard protection	: Cold insulating gloves.	
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.	

#### SECTION 9: Physical and chemical properties

OF CHICK S. I Hysical and Chemica	
9.1. Information on basic physical and	I chemical properties
Physical state	: Gas
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Melting point	: -111 °C
Freezing point	: No data available
Boiling point	: -47 °C
Flash point	: -90 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: 155.0 psig (@ 22 °C)
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.942 g/ml (@ 30 °C)
Molecular mass	: 84.04 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
9.2. Other information	

9.2. Other information

No additional information available

SECT	ION 10: Stability and reactivity	
10.1.	Reactivity	
No additional information available		
10.2.	Chemical stability	
The pro	duct is stable at normal handling and storage conditions.	
10.3.	Possibility of hazardous reactions	
No addi	tional information available	
10.4.	Conditions to avoid	
Protect from sunlight. Do not expose to temperatures exceeding 50 °C Keep away from heat, sparks and flame.		
10.5.	Incompatible materials	
Alkali m	etals. Finely divided metals (Al, Mg, Zn). Strong oxidizing agents.	

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

#### Acute toxicity

: Not classified

1,1,1-Trifluoroethane (420-46-2)	
LC50 inhalation rat (ppm)	> 591.000 ppm/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Contact with the liquid the may cause cold burns/frostbite.
Symptoms/injuries after eye contact	: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

SECTION 12: Ecological information
12.1. Toxicity
No additional information available
12.2. Persistence and degradability
No additional information available
12.3. Bioaccumulative potential
No additional information available
12.4. Mobility in soil
No additional information available
12.5. Other adverse effects
No additional information available

13.1. Waste treatment methods	
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Recycle the material as far as possible.

Department of Transportation (DOT) In accordance with DOT	
Transport document description	: UN2035 1,1,1-Trifluoroethane, 2.1
UN-No.(DOT)	: UN2035
Proper Shipping Name (DOT)	: 1,1,1-Trifluoroethane
Transport hazard class(es) (DOT)	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT)	: 2.1 - Flammable gas
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304
DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315
DOT Special Provisions (49 CFR 172.102)	: T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: Forbidden
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Emergency Response Guide (ERG) Number	: 115
Other information	: No supplementary information available.
<b>TDG</b> No additional information available	
Transport by sea	
UN-No. (IMDG)	: 2035
Proper Shipping Name (IMDG)	: 1,1,1-TRIFLUOROETHANE (REFRIGERANT GAS R 143a)
Class (IMDG)	: 2 - Gases
Air transport	
UN-No. (IATA)	: 2035
Proper Shipping Name (IATA)	: 1,1,1-Trifluoroethane
Class (IATA)	: 2
<b>SECTION 15: Regulatory information</b>	
15.1. US Federal regulations	

1,1,1-Trifluoroethane (420-46-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations		
CANADA		
1,1,1-Trifluoroethane (420-46-2)		
Listed on the Canadian DSL (Domestic Sustances List)		
WHMIS Classification	Class A - Compressed Gas	
	Class B Division 1 - Flammable Gas	

**EU-Regulations** 

No additional information available

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **National regulations**

#### 1,1,1-Trifluoroethane (420-46-2)

Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on INSQ (Mexican national Inventory of Chemical Substances)

Listed on Turkish inventory of chemical

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

#### SECTION 16: Other information

Full text of H-phrases:

t of filphilases.	
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Gas 1	Flammable gases Category 1
Liquefied gas	Gases under pressure Liquefied gas
Simple Asphy	Simple Asphyxiant
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H380	May displace oxygen and cause rapid suffocation
ire hazard	<ul> <li>: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.</li> <li>: 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.</li> </ul>
eactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
IRating	
	: 2 Moderate Hazard - Temporary or minor injury may occur
ability	: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)
al	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
	Eye Irrit. 2A Flam. Gas 1 Liquefied gas Simple Asphy Skin Irrit. 2 STOT SE 3 H220 H280 H315 H319 H335

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.