

1,1,1,2-Tetrafluoroethane Safety Data Sheet 1100309 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 06/20/2016 Version: 1.0

SECTION 1: Identification	
1.1. Identification	
Product form	: Substance
Substance name	: 1,1,1,2-Tetrafluoroethane
CAS No	: 811-97-2
Product code	: 1100-3-09
Formula	: C2H2F4
Synonyms	: Refrigerant 134a
Other means of identification	: MFCD00066608
1.2. Relevant identified uses of the	substance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the sa	fety data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of Ameri T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlab	
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
2.1. Classification of the substance Classification (GHS-US)	or mixture
Classification of the substanceClassification (GHS-US)Simple AsphyH380 - May displace oxygLiquefied gasH280 - Contains gas undeSkin Irrit. 2H315 - Causes skin irritatiEye Irrit. 2AH319 - Causes serious eySTOT SE 3H335 - May cause respirationFull text of H-phrases: see section 16	or mixture en and cause rapid suffocation er pressure; may explode if heated on e irritation
Classification (GHS-US)Simple AsphyH380 - May displace oxygLiquefied gasH280 - Contains gas undeSkin Irrit. 2H315 - Causes skin irritatiEye Irrit. 2AH319 - Causes serious ey	or mixture en and cause rapid suffocation er pressure; may explode if heated on e irritation
2.1. Classification of the substance Classification (GHS-US) Simple Asphy H380 - May displace oxyg Liquefied gas H280 - Contains gas unde Skin Irrit. 2 H315 - Causes skin irritati Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respiration Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	or mixture en and cause rapid suffocation er pressure; may explode if heated on e irritation
2.1.Classification of the substanceClassification (GHS-US)Simple AsphyH380 - May displace oxygLiquefied gasH280 - Contains gas undeSkin Irrit. 2H315 - Causes skin irritatiEye Irrit. 2AH319 - Causes serious eySTOT SE 3H335 - May cause respiraFull text of H-phrases: see section 162.2.Label elements	or mixture en and cause rapid suffocation er pressure; may explode if heated on e irritation

1,1,1,2-Tetrafluoroethane Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	P403+P233 - Store in a w P405 - Store locked up P410+P403 - Protect fron	ntaminated clothing and wash vell-ventilated place. Keep com n sunlight. Store in a well-venti ts/container to an approved wa	tainer tightly closed lated place
2.3. Other hazards			
Other hazards not contributing to the classification	: May cause frostbite.		
2.4. Unknown acute toxicity (GHS US	5)		
Not applicable			
SECTION 3: Composition/informa	tion on ingredients		
3.1. Substance	••		
Substance type	: Mono-constituent		
Name	Product identifie		Classification (GHS-US)
1,1,1,2-Tetrafluoroethane (Main constituent)	(CAS No) 811-97-2	<= 100	Simple Asphy, H380 Liquefied gas, H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Full text of H-phrases: see section 16			
3.2. Mixture			
Not applicable			
SECTION 4: First aid measures			
4.1. Description of first aid measures		au faal upwall, aaak madiaal a	dvice immediately (show the label
First-aid measures general First-aid measures after inhalation	where possible). Move th	e affected personnel away fror	
		e medical advice/attention.	earning. If not breathing, give artificial
First-aid measures after skin contact	: Thaw frosted parts with lu advice/attention.	ikewarm water. Do no rub affe	cted area. Get immediate medical
First-aid measures after eye contact		f present and easy to do. Cont at least 15 minutes. Get imme	inue rinsing. Immediately flush eyes diate medical advice/attention.
First-aid measures after ingestion			t likely. Do NOT induce vomiting. Never e mouth out with water. Get medical
4.2. Most important symptoms and e	ffects, both acute and delayed		
Symptoms/injuries	: The most important know 2.2) and/or in section 11.	n symptoms and effects are de	escribed in the labelling (see section
Symptoms/injuries after inhalation	: May cause drowsiness or		
Symptoms/injuries after skin contact	•	e may cause cold burns/frostbi	
Symptoms/injuries after eye contact	: Direct contact with the liq to frostbite from rapid liqu		and possibly permanent eye injury due
4.3. Indication of any immediate med	lical attention and special treat	ment needed	
No additional information available			
SECTION 5: Firefighting measure	S		
5.1. Extinguishing media			
Suitable extinguishing media	: Alcohol resistant foam. C appropriate for surroundir		ater spray. Use extinguishing media
5.2. Special hazards arising from the	substance or mixture		
Fire hazard		enerates: Carbon oxides. Hyd	-
Explosion hazard	: Contains gas under press exposed containers.	sure; may explode if heated. Us	se water spray or fog for cooling
5.3. Advice for firefighters			
Firefighting instructions		area. Fight fire remotely due to	
Protection during firefighting			ation with self contained breathing posure controls/personal protection".
12/06/2016	EN (English US)	SDS ID: 11	100309 2/7

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures			
6.1. Personal precautions, protective equipment and emergency procedures			
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.		
6.1.1. For non-emergency personnel			
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.		
6.1.2. For emergency responders			
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".		
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.		
6.2. Environmental precautions			
Avoid release to the environment. Notify authoritie	es if product enters sewers or public waters.		
6.3. Methods and material for containment	nt and cleaning up		
For containment	: Stop leak if safe to do so.		
Methods for cleaning up	: Ventilate area.		
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".		
6.4. Reference to other sections			
No additional information available			
SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Close valve after each use and when empty.		
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes.		
Safe handling of the gas receptacle	: Securely chain cylinders when in use and protect against physical damage.		
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.		
7.2. Conditions for safe storage, including any incompatibilities			
Technical measures	: Comply with applicable regulations.		
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use.		
Incompatible materials	: Refer to Section 10 on Incompatible Materials.		
Storage area	: Store in dry, cool, well-ventilated area.		
SECTION 8: Exposure controls/perso	and protoction		

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

No additional information available

8.2.	8.2. Exposure controls	
Approp	riate engineering controls	Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released.
Hand p	rotection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye pro	otection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin ar	nd body protection	: Wear suitable protective clothing.
Respira	atory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Therma	al hazard protection	: Cold insulating gloves.
Other i	nformation	: Safety shoes. 29 CFR 1910.136: Foot Protection.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations			
SECTION 9: Physical and chemical properties			
0.1. Information on basic physical and chemical properties			
Physical state	: Gas		
Color	: No data available		
Odor	: No data available		
Odor threshold	: No data available		
рН	: No data available		
Melting point	: -101 °C		
Freezing point	: No data available		
Boiling point	: -26.5 °C		
Flash point	: No data available		
Relative evaporation rate (butyl acetate=1)	: No data available		
Flammability (solid, gas)	: No data available		
Explosion limits	: No data available		
Explosive properties	: No data available		
Oxidizing properties	: No data available		
Vapor pressure	: 81.6 psig (@ 21 °C)		
Relative density	: No data available		
Relative vapor density at 20 °C	: No data available		
Specific gravity / density	: 1.21 g/ml (@ 21 °C)		
Molecular mass	: 102.03 g/mol		
Solubility	: No data available		
Log Pow	: No data available		
Auto-ignition temperature	: No data available		
Decomposition temperature	: No data available		
Viscosity	: No data available		
Viscosity, kinematic	: No data available		
Viscosity, dynamic	: No data available		
9.2. Other information			
No additional information available			
SECTION 10: Stability and reactivit	У		
10.1. Reactivity			
No additional information available			
10.2. Chemical stability			
The product is stable at normal handling and st	torage conditions.		
10.3. Possibility of hazardous reactions			
No additional information available			

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

10.5. Incompatible materials

Alkali metals. Finely divided metals (Al, Mg, Zn). Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

mects

1,1,1,2-Tetrafluoroethane (811-97-2)	
LC50 inhalation rat (mg/l)	1500 g/m³ (Exposure time: 4 h)

Acute toxicity

: Not classified

1,1,1,2-Tetrafluoroethane Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,1,1,2-Tetrafluoroethane (811-97-2)		
ATE US (vapors)	1500.000 mg/l/4h	
ATE US (dust, mist)	1500.000 mg/l/4h	
Skin corrosion/irritation	: Causes skin irritation.	
Serious eye damage/irritation	: Causes serious eye irritation.	
Respiratory or skin sensitization	: Not classified	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Reproductive toxicity	: Not classified	
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.	
Specific target organ toxicity (repeated exposure)	: Not classified	
Aspiration hazard	: Not classified	
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.	
Symptoms/injuries after skin contact	: Contact with the liquid the may cause cold burns/frostbite.	
Symptoms/injuries after eye contact	: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.	

SECTION 12: Ecological information				
12.1.	Toxicity			
No additi	No additional information available			
12.2.	Persistence and degradability			
No additi	onal information available			
12.3.	Bioaccumulative potential			
No additi	No additional information available			
12.4.	Mobility in soil			
No additional information available				
12.5.	Other adverse effects			
No additional information available				

SECTION 13: Disposal consideratio	ns		
13.1. Waste treatment methods			
Waste treatment methods	: Remove to an authorized i	ncinerator equipped with an afterburner and a flue gas scrubb	er.
Waste disposal recommendations	: Dispose of contents/contai	ner in accordance with licensed collector's sorting instructions	
Additional information	: Recycle the material as fai	as possible.	
SECTION 14: Transport information			
Department of Transportation (DOT)			
In accordance with DOT			
Transport document description	: UN3159 1,1,1,2-Tetrafluor	bethane, 2.2	
UN-No.(DOT)	: UN3159		
Proper Shipping Name (DOT)	: 1,1,1,2-Tetrafluoroethane		
Transport hazard class(es) (DOT)	: 2.2 - Class 2.2 - Non-flamr	nable compressed gas 49 CFR 173.115	
Hazard labels (DOT)	: 2.2 - Non-flammable gas		
	2		
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304		
DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315		
12/06/2016	EN (English US)	SDS ID: 1100309	5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	: 126
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 3159
Proper Shipping Name (IMDG)	: 1,1,1,2-TETRAFLUOROETHANE (REFRIGERANT GAS R 134a)
Class (IMDG)	: 2 - Gases
Air transport	
UN-No. (IATA)	: 3159
Proper Shipping Name (IATA)	: 1,1,1,2-Tetrafluoroethane
Class (IATA)	: 2
SECTION 15: Regulatory information	

SECTION 15: Regulatory information
15.1. US Federal regulations
1,1,1,2-Tetrafluoroethane (811-97-2)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations		
CANADA		
1,1,1,2-Tetrafluoroethane (811-97-2)		
Listed on the Canadian DSL (Domestic Sustances List)		
WHMIS Classification	Class A - Compressed Gas	

EU-Regulations

No additional information available

National regulations

 1,1,1,2-Tetrafluoroethane (811-97-2)

 Listed on the AICS (Australian Inventory of Chemical Substances)

 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

 Listed on the Japanese ISHL (Industrial Safety and Health Law)

 Listed on the Korean ECL (Existing Chemicals List)

 Listed on NZIoC (New Zealand Inventory of Chemicals and Chemical Substances)

 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

 Listed on Turkish inventory of chemical

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Liquefied gas	Gases under pressure Liquefied gas
Simple Asphy	Simple Asphyxiant
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H380	May displace oxygen and cause rapid suffocation
NFPA fire hazard NFPA reactivity	 : 1 - Must be preheated before ignition can occur. : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Health	
Health Flammability	 2 Moderate Hazard - Temporary or minor injury may occur * - Chronic (long-term) health effects may result from repeated overexposure 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.