

Safety Data Sheet 1100347 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/14/2017 Version: 1.0

.1. Identification	
Product form	: Substance
Substance name	: 2-Fluorobutane
CAS No	: 359-01-3
Product code	: 1100-3-47
Formula	: C4H9F
Synonyms	: sec-Butyl fluoride
Other means of identification	: MFCD02258657
1.2. Relevant identified uses of the	substance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the sa	afety data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of Ameri T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlab	
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identificat	tion
2.1. Classification of the substance	
Classification (GHS-US)	
Flam. Liq. 1H224 - Extremely flammatSkin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eyoSTOT SE 3H335 - May cause respirat	ion re irritation
Flam. Liq. 1H224 - Extremely flammatSkin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eyeSTOT SE 3H335 - May cause respiratFull text of H-phrases: see section 16	ble liquid and vapour ion re irritation
Flam. Liq. 1H224 - Extremely flammatsSkin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eyoSTOT SE 3H335 - May cause respirateFull text of H-phrases: see section 162.2.Label elements	ble liquid and vapour ion re irritation
Flam. Liq. 1 H224 - Extremely flammats Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirate Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	ble liquid and vapour ion re irritation
Flam. Liq. 1 H224 - Extremely flammat Skin Irrit. 2 H315 - Causes skin irritatio Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	 ble liquid and vapour ion re irritation itory irritation i ve irritation itory irritation i ve irritation
Flam. Liq. 1 H224 - Extremely flammatic Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirate Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	 ble liquid and vapour ion re irritation itory irritation tory irritation i view of the second second
Flam. Liq. 1H224 - Extremely flammatSkin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eyeSTOT SE 3H335 - May cause respiratFull text of H-phrases: see section 16	 ble liquid and vapour ion re irritation itory irritation : Vertical of the second second

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact
lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER or doctor/physician if you feel unwell
P321 - Specific treatment (see supplemental first aid instructions on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P410+P403 - Protect from sunlight. Store in a well-ventilated place
P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
2-Fluorobutane (Main constituent)	(CAS No) 359-01-3	<= 100	Liquefied gas, H280 Flam. Liq. 1, H224 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

Full text of H-phrases: see section 16

Mixture 3.2. Not applicable SECTION 4: First aid measures **Description of first aid measures** 4.1. : In case of accident or if you feel unwell, seek medical advice immediately (show the label First-aid measures general where possible). Move the affected personnel away from the contaminated area. : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial First-aid measures after inhalation respiration. Get medical advice/attention. : Wash with plenty of soap and water. Get medical advice/attention. First-aid measures after skin contact First-aid measures after eye contact Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention. First-aid measures after ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention. Most important symptoms and effects, both acute and delayed 4.2. The most important known symptoms and effects are described in the labelling (see section Symptoms/injuries 2.2) and/or in section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECT	ION 5: Firefighting measures	
5.1.	Extinguishing media	
Suitable	e extinguishing media	: Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.
5.2.	Special hazards arising from the sul	bstance or mixture
Fire ha	zard	: Thermal decomposition generates: Carbon oxides. Hydrogen fluoride.
Explosi	on hazard	: Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.
5.3.	Advice for firefighters	
Firefigh	ting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Safety Data Sheet

50 / Ma а

Protection during firefighting	: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".
SECTION 6: Accidental release mea	sures
6.1. Personal precautions, protective eq	uipment and emergency procedures
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.
6.1.1. For non-emergency personnel	
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.
6.2. Environmental precautions	
Avoid release to the environment. Notify authorit	ies if product enters sewers or public waters.
6.3. Methods and material for containme	ent and cleaning up
For containment	: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.
Methods for cleaning up	: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".
6.4. Reference to other sections	
No additional information available	
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care because residual vapors are flammable. Close valve after each use and when empty.
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.
Safe handling of the gas receptacle	: Securely chain cylinders when in use and protect against physical damage.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, includi	ng any incompatibilities
Fechnical measures	: Comply with applicable regulations.
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use. Keep away from ignition sources.
Storage conditions	
Incompatible materials	: Refer to Section 10 on Incompatible Materials.

8.1. Control parameters

No additional information available

8.2. Exposure controls			
Appropriate engineering controls	should be available in the imm	work station. Emergency eye wash fountains a lediate vicinity of any potential exposure. Syster checked for leakage. Oxygen detectors should l leased.	ms under
Hand protection	: Protective gloves. 29 CFR 191	10.138: Hand Protection.	
Eye protection	: Chemical goggles or safety gla	asses. Face shield. 29 CFR 1910.133: Eye and	Face Protection.
Skin and body protection	: Wear suitable protective clothi	ng.	
08/14/2017	EN (English US)	SDS ID: 1100347	3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Thermal hazard protection	: Cold insulating gloves.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

OF OTION 2. I HABICAL AND CHEMICAL	pre	perties
9.1. Information on basic physical and	che	mical properties
Physical state	:	Liquid
Color	:	No data available
Odor	:	No data available
Odor threshold	:	No data available
рН	:	No data available
Melting point	:	-121 °C
Freezing point	:	No data available
Boiling point	:	25 °C
Flash point	:	No data available
Relative evaporation rate (butyl acetate=1)	:	No data available
Flammability (solid, gas)	:	No data available
Explosion limits	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Vapor pressure	:	No data available
Relative density	:	No data available
Relative vapor density at 20 °C	:	No data available
Specific gravity / density	:	0.77 g/ml (@ 15 °C)
Molecular mass	:	76.11 g/mol
Solubility	:	No data available
Log Pow	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available
9.2. Other information		
Refractive index	:	1.3299 (@ 20 °C)

10.1. Reactivity

No additional information available

10.2. **Chemical stability**

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

SECTION 10: Stability and reactivity

No additional information available

10.4. **Conditions to avoid**

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

10.5. **Incompatible materials**

Alkali metals. Finely divided metals (Al, Mg, Zn). Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

Safety Data Sheet

ccording to Federal Register / Vol. 77, No. 58 / Monday	, March 26, 2012 / Rules and Regulations
SECTION 11: Toxicological information	tion
11.1. Information on toxicological effects	ŝ
Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
SECTION 12: Ecological information	n
12.1. Toxicity	
No additional information available	
12.2. Persistence and degradability	
No additional information available	
12.3. Bioaccumulative potential	
No additional information available	
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	
No additional information available	

No additional information available

SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.	
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.	
Additional information	: Recycle the material as far as possible.	

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT Transport document description

UN-No.(DOT) Proper Shipping Name (DOT) Transport hazard class(es) (DOT) Hazard labels (DOT)

Packing group (DOT) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Symbols

: UN1993 Flammable liquids, n.o.s., 3, I

- : UN1993
- : Flammable liquids, n.o.s.
- : 3 Class 3 Flammable and combustible liquid 49 CFR 173.120
- : 3 Flammable liquid



- : I Great Danger
- : 201
- : 243

: G - Identifies PSN requiring a technical name

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	 T11 - 6 178.274(d)(2) Normal 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 30 L
DOT Vessel Stowage Location	: E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 1993
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, N.O.S.
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: I - substances presenting high danger
Air transport	
UN-No. (IATA)	: 1993
Proper Shipping Name (IATA)	: Flammable liquid, n.o.s.
	: 3 - Flammable Liquids
Class (IATA)	

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

	2-Fluorobutane		CAS No 359-01-3	100%
--	----------------	--	-----------------	------

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

2-Fluorobutane (359-01-3) Listed on the Japanese ISHL (Industrial Safety and Health Law)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full tex	t of H-phrases:	
	Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
	Flam. Liq. 1	Flammable liquids Category 1
	Liquefied gas	Gases under pressure Liquefied gas
	Skin Irrit. 2	Skin corrosion/irritation Category 2
	STOT SE 3	Specific target organ toxicity (single exposure) Category 3
	H224	Extremely flammable liquid and vapor
	H280	Contains gas under pressure; may explode if heated
	H315	Causes skin irritation
	H319	Causes serious eye irritation
	H335	May cause respiratory irritation
NFPA health hazard		 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given. 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.
NFPA reactivity		: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating		
Health		: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability		: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)
Physical		: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.