

2,2-Difluorobutane

Safety Data Sheet 1100398

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 12/28/2017

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form	: Substance
Substance name	: 2,2-Difluorobutane
CAS No	: 353-81-1
Product code	: 1100-3-98
Formula	: C4H8F2
Other means of identification	: MFCD20489351

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
------------------------------	--

1.3. Details of the supplier of the safety data sheet

SynQuest Laboratories, Inc.
P.O. Box 309
Alachua, FL 32615 - United States of America
T (386) 462-0788 - F (386) 462-7097
info@synquestlabs.com - www.synquestlabs.com

1.4. Emergency telephone number

Emergency number	: (844) 523-4086 (3E Company - Account 10069)
------------------	---

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Classification (GHS-US)


Flam. Liq. 1	H224 - Extremely flammable liquid and vapour
Skin Irrit. 2	H315 - Causes skin irritation
Eye Irrit. 2A	H319 - Causes serious eye irritation
STOT SE 3	H335 - May cause respiratory irritation

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H224 - Extremely flammable liquid and vapor
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation

Precautionary statements (GHS-US)

: P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing fumes, gas, mist, spray, vapors
P264 - Wash skin thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P302+P352 - If on skin: Wash with plenty of soap and water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

2,2-Difluorobutane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER or doctor/physician if you feel unwell
P321 - Specific treatment (see supplemental first aid instructions on this label)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
2,2-Difluorobutane (Main constituent)	(CAS No) 353-81-1	<= 100	Flam. Liq. 1, H224 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

Full text of H-phrases: see section 16

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Immediately flush eyes thoroughly with water for at least 15 minutes. Get medical advice/attention.

First-aid measures after ingestion : Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

Symptoms/injuries after inhalation : May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Contact with the liquid may cause cold burns/frostbite.

Symptoms/injuries after eye contact : Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen fluoride.

Explosion hazard : Contains gas under pressure; may explode if heated. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

2,2-Difluorobutane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so.

Methods for cleaning up : Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care because residual vapors are flammable. Close valve after each use and when empty.

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.

Safe handling of the gas receptacle : Securely chain cylinders when in use and protect against physical damage.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use. Keep away from ignition sources.

Incompatible materials : Refer to Section 10 on Incompatible Materials.

Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularly checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released.

Hand protection : Protective gloves. 29 CFR 1910.138: Hand Protection.

Eye protection : Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing.

2,2-Difluorobutane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: -114 °C
Freezing point	: No data available
Boiling point	: 30 - 31 °C
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.916 g/ml (@ 10 °C)
Molecular mass	: 94.1031 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

Refractive index	: 1.3192 (@ 10 °C)
------------------	--------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

10.5. Incompatible materials

Strong acids. Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

2,2-Difluorobutane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Contact with the liquid the may cause cold burns/frostbite.
Symptoms/injuries after eye contact	: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Recycle the material as far as possible.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN1993 Flammable liquids, n.o.s., 3, I
UN-No.(DOT)	: UN1993
Proper Shipping Name (DOT)	: Flammable liquids, n.o.s.
Transport hazard class(es) (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid



Packing group (DOT)	: I - Great Danger
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 201
DOT Packaging Bulk (49 CFR 173.xxx)	: 243
DOT Symbols	: G - Identifies PSN requiring a technical name

2,2-Difluorobutane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- DOT Special Provisions (49 CFR 172.102) : T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 1 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 30 L
- DOT Vessel Stowage Location : E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.
- Other information : No supplementary information available.

TDG

No additional information available

Transport by sea

- UN-No. (IMDG) : 1993
- Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S.
- Class (IMDG) : 3 - Flammable liquids
- Packing group (IMDG) : I - substances presenting high danger

Air transport

- UN-No. (IATA) : 1993
- Proper Shipping Name (IATA) : Flammable liquid, n.o.s.
- Class (IATA) : 3 - Flammable Liquids
- Packing group (IATA) : I - Great Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

2,2-Difluorobutane	CAS No 353-81-1	100%
--------------------	-----------------	------

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

2,2-Difluorobutane (353-81-1)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

2,2-Difluorobutane

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 1	Flammable liquids Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H224	Extremely flammable liquid and vapor
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation

NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health

: 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable for any damage resulting from handling or from contact with the above product.