

Safety Data Sheet 11003A4 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 06/20/2016 Version: 1.0

1.1. Identification	
	: Mixture
Product form Product name	: Mixture : R-404a
CAS No	: 150743-07-0
Product code	: 1100-3-A4
	: HP62; 404A
Synonyms	
	Ibstance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the safe	ty data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of America T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlabs.	
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identificatio	on
2.1. Classification of the substance of	
Classification (GHS-US)	
Liquefied gas H280 - Contains gas under	pressure; may explode if heated
Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirato Full text of H-phrases: see section 16	irritation
Eye Irrit. 2A H319 - Causes serious eye	irritation
Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirato Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	<ul> <li>irritation any irritation</li> <li>: irritation</li> <li>: irritation</li> <li>: irritation</li> <li>: Warning</li> <li>: H280 - Contains gas under pressure; may explode if heated</li> </ul>
Eye Irrit. 2AH319 - Causes serious eyeSTOT SE 3H335 - May cause respiratoFull text of H-phrases: see section 162.2.Label elements	irritation ny irritation : Varning
Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirato Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	<ul> <li>irritation any irritation</li> <li>: irritation</li> <li>: irritation</li> <li>: irritation</li> <li>: irritation</li> <li>: irritation</li> <li>: H280 - Contains gas under pressure; may explode if heated</li> <li>H315 - Causes skin irritation</li> <li>H319 - Causes serious eye irritation</li> <li>H335 - May cause respiratory irritation</li> </ul>

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P410+P403 - Protect from sunlight. Store in a well-ventilated place P501 - Dispose of contents/container to an approved waste disposal plant

#### 2.3. Other hazards

Other hazards not contributing to the classification

: May cause frostbite. May produce irregular heart beat and nervous symptoms.

## 2.4. Unknown acute toxicity (GHS US)

Not applicable

### SECTION 3: Composition/information on ingredients

3.1. Substance

## Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
1,1,1-Trifluoroethane	(CAS No) 420-46-2	52	Simple Asphy, H380 Flam. Gas 1, H220 Liquefied gas, H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Pentafluoroethane	(CAS No) 354-33-6	44	Simple Asphy, H380 Liquefied gas, H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
1,1,1,2-Tetrafluoroethane	(CAS No) 811-97-2	4	Simple Asphy, H380 Liquefied gas, H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

#### Full text of H-phrases: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.
First-aid measures after skin contact	: Thaw frosted parts with lukewarm water. Do no rub affected area. Get immediate medical advice/attention.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Immediately flush eyes thoroughly with water for at least 15 minutes. Get immediate medical advice/attention.
First-aid measures after ingestion	: Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention.
4.2. Most important symptoms and effects	s, both acute and delayed
Symptoms/injuries	: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Contact with the liquid the may cause cold burns/frostbite.
Symptoms/injuries after eye contact	: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

## 4.3. Indication of any immediate medical attention and special treatment needed

#### No additional information available

SECT	ION 5: Firefighting measures			
5.1.	Extinguishing media			
Suitable	e extinguishing media	: Alcohol resistant foam. Carbon dioxid appropriate for surrounding fire.	le. Dry powder. Water spray. Use extinguishing med	ia
5.2.	Special hazards arising from the sul	bstance or mixture		
Fire haz	zard	: Thermal decomposition generates: C	arbon oxides. Hydrogen fluoride.	
Explosio	on hazard	: Contains gas under pressure; may exposed containers.	xplode if heated. Use water spray or fog for cooling	
12/06/20	16	EN (English US)	SDS ID: 11003A4	2/8

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Advice for firefighters	
Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection during firefighting	: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".
SECTION 6: Accidental release n	neasures
6.1. Personal precautions, protectiv	e equipment and emergency procedures
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.
6.1.1. For non-emergency personnel	
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.
6.2. Environmental precautions	
void release to the environment. Notify au	horities if product enters sewers or public waters.
.3. Methods and material for conta	inment and cleaning up
For containment	: Stop leak if safe to do so.
Methods for cleaning up	: Ventilate area.
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".
6.4. Reference to other sections	
No additional information available	
SECTION 7: Handling and storage	e
7.1. Precautions for safe handling	
Additional hazards when processed	<ul> <li>Pressurized container: Do not pierce or burn, even after use. Close valve after each use and when empty.</li> </ul>
Precautions for safe handling	Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes.
Safe handling of the gas receptacle	: Securely chain cylinders when in use and protect against physical damage.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, inc	luding any incompatibilities
Fechnical measures	: Comply with applicable regulations.
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use.
ncompatible materials	: Refer to Section 10 on Incompatible Materials.
Storage area	: Store in dry, cool, well-ventilated area.

# SECTION 8: Exposure controls/personal protection

#### 8.1. **Control parameters**

No additional information available

8.2. Exposure controls	
Appropriate engineering controls	Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Thermal hazard protection	: Cold insulating gloves.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

#### SECTION 9: Physical and chemical properties

9.1. Information on basic physical and	d chemical properties
Physical state	: Gas
Color	: Colourless.
Odor	: Odourless.
Odor threshold	: No data available
рН	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: -46.2 °C
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: 9410.0 mm Hg (@ 25 °C)
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.044 g/ml (@ 25 °C)
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

#### 10.3. Possibility of hazardous reactions

No additional information available

#### 10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

#### 10.5. Incompatible materials

Alkali metals. Finely divided metals (Al, Mg, Zn). Strong oxidizing agents.

#### **10.6.** Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

### SECTION 11: Toxicological information

11.1. Information on toxicological effects

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity	: Not classified	
1,1,1,2-Tetrafluoroethane (811-97-2)		
LC50 inhalation rat (mg/l)	1500 g/m <sup>3</sup> (Exposure time: 4 h)	
ATE US (vapors)	1500.000 mg/l/4h	
ATE US (dust, mist)	1500.000 mg/l/4h	
1,1,1-Trifluoroethane (420-46-2)		
LC50 inhalation rat (ppm)	> 591.000 ppm/4h	
Pentafluoroethane (354-33-6)		
LC50 inhalation rat (mg/l)	2910 g/m <sup>3</sup> (Exposure time: 4 h)	
ATE US (vapors)	2910.000 mg/l/4h	
ATE US (dust, mist)	2910.000 mg/l/4h	
Skin corrosion/irritation	: Causes skin irritation.	
Serious eye damage/irritation	: Causes serious eye irritation.	
Respiratory or skin sensitization	: Not classified	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Reproductive toxicity	: Not classified	
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.	
Specific target organ toxicity (repeated exposure)	: Not classified	
Aspiration hazard	: Not classified	
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.	
Symptoms/injuries after skin contact	: Contact with the liquid the may cause cold burns/frostbite.	
Symptoms/injuries after eye contact	: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.	
<b>SECTION 12: Ecological information</b>		
40.4 Texisity		

### 12.1. Toxicity

No additional information available

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the global warming

: No known ecological damage caused by this product.

<b>SECTION 13: Disposal consideration</b>	IS
13.1. Waste treatment methods	
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Recycle the material as far as possible.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## **SECTION 14: Transport information**

In accordance with DOT Transport document description	: UN3337 Refrigerant gas R 404A, 2.2
UN-No.(DOT)	: UN3337
Proper Shipping Name (DOT)	: Refrigerant gas R 404A
Transport hazard class(es) (DOT)	: 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115
Hazard labels (DOT)	: 2.2 - Non-flammable gas
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304
DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315
DOT Special Provisions (49 CFR 172.102)	: T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 3337
Proper Shipping Name (IMDG)	: REFRIGERANT GAS R 404A
Class (IMDG)	: 2 - Gases
Air transport	
UN-No. (IATA)	: 3337
Proper Shipping Name (IATA)	: Refrigerant gas R 404a
Class (IATA)	: 2

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations		
CANADA		
1,1,1,2-Tetrafluoroethane (811-97-2)		
Listed on the Canadian DSL (Domestic Sustances List)		
WHMIS Classification	Class A - Compressed Gas	

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,1,1-Trifluoroethane (420-46-2)		
Listed on the Canadian DSL (Domestic Sustances List)		
Class A - Compressed Gas Class B Division 1 - Flammable Gas		
Pentafluoroethane (354-33-6)		
Listed on the Canadian DSL (Domestic Sustances List)		
Uncontrolled product according to WHMIS classification criteria		

#### **EU-Regulations**

No additional information available

#### **National regulations**

### 1,1,1,2-Tetrafluoroethane (811-97-2)

roemane (611-97-2)
S (Australian Inventory of Chemical Substances) (Inventory of Existing Chemical Substances Produced or Imported in China) anese ENCS (Existing & New Chemical Substances) inventory anese ISHL (Industrial Safety and Health Law) ean ECL (Existing Chemicals List) New Zealand Inventory of Chemicals) (Philippines Inventory of Chemicals and Chemical Substances) <i>M</i> exican national Inventory of Chemical Substances) inventory of chemical
nane (420-46-2)
S (Australian Inventory of Chemical Substances) (Inventory of Existing Chemical Substances Produced or Imported in China) anese ENCS (Existing & New Chemical Substances) inventory anese ISHL (Industrial Safety and Health Law) New Zealand Inventory of Chemicals) (Philippines Inventory of Chemicals and Chemical Substances) <i>M</i> exican national Inventory of Chemical Substances) inventory of chemical
ne (354-33-6)
S (Australian Inventory of Chemical Substances) (Inventory of Existing Chemical Substances Produced or Imported in China) anese ENCS (Existing & New Chemical Substances) inventory anese ISHL (Industrial Safety and Health Law) New Zealand Inventory of Chemicals) (Philippines Inventory of Chemicals and Chemical Substances) <i>I</i> exican national Inventory of Chemical Substances) <i>I</i> exican national Inventory of Chemical Substances) inventory of chemical

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

## **SECTION 16: Other information**

Full text of H-phrases:

Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Gas 1	Flammable gases Category 1
Liquefied gas	Gases under pressure Liquefied gas
Simple Asphy	Simple Asphyxiant
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H380	May displace oxygen and cause rapid suffocation

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard	: 1 - Must be preheated before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	
Health	<ul> <li>2 Moderate Hazard - Temporary or minor injury may occur</li> <li>* - Chronic (long-term) health effects may result from repeated overexposure</li> </ul>
Flammability	: 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.