

**2-Chloro-1,1,1-trifluoroethane** Safety Data Sheet 1100710 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Version: 1.0

Date of issue: 02/26/2016

I.1. Identification	
Product form	: Substance
Substance name	: 2-Chloro-1,1,1-trifluoroethane
CAS No	: 75-88-7
Product code	: 1100-7-10
Formula	: C2H2CIF3
Synonyms	: 2,2,2-Trifluoroethyl chloride
Other means of identification	: MFCD00039361
1.2. Relevant identified uses of the s	substance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the sa	fety data sheet
SynQuest Laboratories, Inc.	·
P.O. Box 309	
Alachua, FL 32615 - United States of Americ	ca
T (386) 462-0788 - F (386) 462-7097 info@synguestlabs.com - www.synguestlab	IS COM
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identificat	ion
2.1. Classification of the substance	or mixture
Classification (GHS-US)Simple AsphyH380 - May displace oxygLiquefied gasH280 - Contains gas undeSkin Irrit. 2H315 - Causes skin irritatiEye Irrit. 2AH319 - Causes serious eySTOT SE 3H335 - May cause respiration	re irritation tory irritation
Classification (GHS-US)Simple AsphyH380 - May displace oxygLiquefied gasH280 - Contains gas undeSkin Irrit. 2H315 - Causes skin irritatiEye Irrit. 2AH319 - Causes serious eySTOT SE 3H335 - May cause respiraOzone 1H420 - Harms public healt	er pressure; may explode if heated ion re irritation
Classification (GHS-US)Simple AsphyH380 - May displace oxygLiquefied gasH280 - Contains gas undeSkin Irrit. 2H315 - Causes skin irritatiEye Irrit. 2AH319 - Causes serious eySTOT SE 3H335 - May cause respiraOzone 1H420 - Harms public healtFull text of H-phrases: see section 16	er pressure; may explode if heated ion re irritation tory irritation
Classification (GHS-US)Simple AsphyH380 - May displace oxygLiquefied gasH280 - Contains gas undeSkin Irrit. 2H315 - Causes skin irritatiEye Irrit. 2AH319 - Causes serious eySTOT SE 3H335 - May cause respiraOzone 1H420 - Harms public healtFull text of H-phrases: see section 16	er pressure; may explode if heated ion re irritation tory irritation
Classification (GHS-US)Simple Asphy Liquefied gasH380 - May displace oxyg H280 - Contains gas under Skin Irrit. 2Skin Irrit. 2 Eye Irrit. 2AH315 - Causes skin irritati Full P - Causes serious ey STOT SE 3 H335 - May cause respira Ozone 1Ozone 1H420 - Harms public healt Full text of H-phrases: see section 162.2.Label elements	er pressure; may explode if heated ion re irritation tory irritation
Classification (GHS-US)Simple AsphyH380 - May displace oxygLiquefied gasH280 - Contains gas undeSkin Irrit. 2H315 - Causes skin irritatiEye Irrit. 2AH319 - Causes serious eySTOT SE 3H335 - May cause respiraOzone 1H420 - Harms public healtFull text of H-phrases: see section 162.2.Label elementsGHS-US labeling	er pressure; may explode if heated ion re irritation itory irritation th and the environment by destroying ozone in the upper atmosphere
Classification (GHS-US) Simple Asphy H380 - May displace oxyg Liquefied gas H280 - Contains gas unde Skin Irrit. 2 H315 - Causes skin irritati Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respira Ozone 1 H420 - Harms public healt Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	The pressure; may explode if heated tion re irritation tory irritation th and the environment by destroying ozone in the upper atmosphere : : : : : : : :

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse P403+P233 - Store in a well-ventilated place. Keep container tightly closed P405 - Store locked up P410+P403 - Protect from sunlight. Store in a well-ventilated place P501 - Dispose of contents/container to an approved waste disposal plant P502 - Refer to manufacturer/supplier for information on recovery/recycling					
2.3. Other hazards						
Other hazards not contributing to the classification	er hazards not contributing to the : May cause frostbite.					
2.4. Unknown acute toxicity (GHS US)	2.4. Unknown acute toxicity (GHS US)					
Not applicable						
<b>SECTION 3: Composition/information</b>	on ingredients					
3.1. Substance						
Substance type	: Mono-constituent					
Name	Product identifier	%	Classification (GHS-US)			
2-Chloro-1,1,1-trifluoroethane (Main constituent)	(CAS No) 75-88-7	<= 100	Simple Asphy, H380 Liquefied gas, H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Ozone 1, H420			
Full text of H-phrases: see section 16						
3.2. Mixture						
Not applicable						
SECTION 4: First aid measures						
4.1. Description of first aid measures						
Ū.	: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.					
	Remove person to fresh air and keep co respiration. Get immediate medical advi	ce/attention.				
	: Thaw frosted parts with lukewarm water advice/attention.					
	: Remove contact lenses, if present and e thoroughly with water for at least 15 min	utes. Get immediate	medical advice/attention.			
First-aid measures after ingestion	: Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention.					
4.2. Most important symptoms and effects	s, both acute and delayed					
Symptoms/injuries :	Symptoms/injuries : The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.					
	: May cause drowsiness or dizziness.					
	Contact with the liquid the may cause co					
Symptoms/injuries after eye contact	ymptoms/injuries after eye contact : Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.					
4.3. Indication of any immediate medical a	attention and special treatment needed					
No additional information available						
SECTION 5: Firefighting measures						
5.1. Extinguishing media						
Suitable extinguishing media	: Alcohol resistant foam. Carbon dioxide. appropriate for surrounding fire.	Dry powder. Water sp	oray. Use extinguishing media			
.2. Special hazards arising from the substance or mixture						
Fire hazard :	: Thermal decomposition generates: Carbon oxides. Hydrogen chloride. Hydrogen fluoride.					
xplosion hazard       : Contains gas under pressure; may explode if heated. Use water spray or fog for cooling exposed containers.						

## 2-Chloro-1,1,1-trifluoroethane Safety Data Sheet

5.3. Advice for firefighters	
Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection during firefighting	: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".
SECTION 6: Accidental release m	easures
6.1. Personal precautions, protective	equipment and emergency procedures
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.
6.1.1. For non-emergency personnel	
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.
6.2. Environmental precautions	
Avoid release to the environment. Notify auth	orities if product enters sewers or public waters.
6.3. Methods and material for contair	nment and cleaning up
For containment	: Stop leak if safe to do so.
Methods for cleaning up	: Ventilate area.
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".
6.4. Reference to other sections	
No additional information available	
SECTION 7: Handling and storage	•
7.1. Precautions for safe handling	
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Close valve after each use and when empty.
Precautions for safe handling	Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes.
Safe handling of the gas receptacle	: Securely chain cylinders when in use and protect against physical damage.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, inclu	uding any incompatibilities
Technical measures	: Comply with applicable regulations.
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use.
Incompatible materials	: Refer to Section 10 on Incompatible Materials.

#### 8.1. **Control parameters**

No additional information available

8.2. Exposure controls	
Appropriate engineering controls	Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Thermal hazard protection	: Cold insulating gloves.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

#### SECTION 9: Physical and chemical properties

9.1. Information on basic physical and ch		
Physical state	:	Gas
Color	:	No data available
Odor	:	No data available
Odor threshold	:	No data available
рН	:	No data available
Melting point	:	-105.5 °C
Freezing point	:	No data available
Boiling point	:	6.9 °C
Flash point	:	No data available
Relative evaporation rate (butyl acetate=1)	:	No data available
Flammability (solid, gas)	:	No data available
Explosion limits	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Vapor pressure	:	10.3 psig (@ 21 °C)
Relative density	:	No data available
Relative vapor density at 20 °C	:	No data available
Specific gravity / density	:	1.389 g/ml (@ 0 °C)
Molecular mass	:	118.49 g/mol
Solubility	:	No data available
Log Pow	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available

9.2. Other information

No additional information available

#### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

#### 10.5. Incompatible materials

Alkali metals. Finely divided metals (Al, Mg, Zn). Strong bases. Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

# 2-Chloro-1,1,1-trifluoroethane Safety Data Sheet

SECTION 11: Toxicological informat	ion
1.1. Information on toxicological effects	
	. Net slope if ad
Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
2-Chloro-1,1,1-trifluoroethane (75-88-7)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Contact with the liquid the may cause cold burns/frostbite.
Symptoms/injuries after eye contact	: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.
SECTION 12: Ecological information	
12.1. Toxicity	
No additional information available	
12.2. Persistence and degradability	
No additional information available	
12.3. Bioaccumulative potential	
No additional information available	
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	
Other information	: Class II ozone-depleting substance.
SECTION 13: Disposal consideration	ns
13.1. Waste treatment methods	
Naste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Recycle the material as far as possible.
SECTION 14: Transport information	
Department of Transportation (DOT)	
In accordance with DOT	

Transport document description	: UN1983 1-Chloro-2,2,2-trifluoroethane, 2.2
UN-No.(DOT)	: UN1983
Proper Shipping Name (DOT)	: 1-Chloro-2,2,2-trifluoroethane
Transport hazard class(es) (DOT)	: 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT)	: 2.2 - Non-flammable gas
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304
DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315
DOT Special Provisions (49 CFR 172.102)	: T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number	: 126
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 1983
Proper Shipping Name (IMDG)	: 1-CHLORO-2,2,2-TRIFLUOROETHANE (REFRIGERANT GAS R 133a)
Class (IMDG)	: 2 - Gases
Air transport	
UN-No. (IATA)	: 1983
Proper Shipping Name (IATA)	: 1-Chloro-2,2,2-trifluoroethane
Class (IATA)	: 2

#### SECTION 15: Regulatory information

Chloro-1,1,1-trifluoroethane (75-88-7)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313		
EPA TSCA Regulatory Flag	S - S - indicates a substance that is identified in a proposed or final Significant New Uses Rule.	
SARA Section 313 - Emission Reporting	1.0 %	

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

2-Chloro-1,1,1-trifluoroethane	CAS No 75-88-7	100%
--------------------------------	----------------	------

15.2	Internatio	onal red	nulations
15.2.	miernau	Unai reg	guiauons

CANADA		
2-Chloro-1,1,1-trifluoroethane (75-88-7)		
Listed on the Canadian NDSL (Non-Domestic Substances List)		
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects	

#### **EU-Regulations**

No additional information available

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations	
2-Chloro-1,1,1-trifluoroethane (75-88-7)	
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Japanese Pollutant Release and Transfer Register Law (PRTR Law)	
Listed on INSQ (Mexican national Inventory of Chemical Substances)	

2-Chloro-1,1,1-trifluoroethane (75-88-7)	
State or local regulations	U.S New Jersey - Right to Know Hazardous Substance List

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

#### **SECTION 16: Other information**

	Eye Irrit. 2A		Serious eye damage/eye irritation Category 2A
	Liquefied gas		Gases under pressure Liquefied gas
	Ozone 1		Hazardous to the ozone layer Category 1
	Simple Asphy		Simple Asphyxiant
	Skin Irrit. 2		Skin corrosion/irritation Category 2
	STOT SE 3		Specific target organ toxicity (single exposure) Category 3
	H280		Contains gas under pressure; may explode if heated
	H315		Causes skin irritation
	H319		Causes serious eye irritation
	H335		May cause respiratory irritation
	H380		May displace oxygen and cause rapid suffocation
	H420		Harms public health and the environment by destroying ozone in the upper atmosphere
NFPA	health hazard		cause serious temporary or gh prompt medical attention was
	health hazard fire hazard	residual injury even thoug	gh prompt medical attention was
NFPA		residual injury even thoug given. : 0 - Materials that will not	ch prompt medical attention was burn. under fire exposure conditions,
NFPA NFPA	fire hazard	residual injury even thoug given. : 0 - Materials that will not : 0 - Normally stable, even	ch prompt medical attention was burn. under fire exposure conditions,
NFPA NFPA	fire hazard reactivity II Rating	<ul> <li>residual injury even thoug given.</li> <li>0 - Materials that will not</li> <li>0 - Normally stable, even and are not reactive with</li> </ul>	ch prompt medical attention was burn. under fire exposure conditions,
NFPA NFPA HMIS I	fire hazard reactivity II Rating	<ul> <li>residual injury even thoug given.</li> <li>0 - Materials that will not</li> <li>0 - Normally stable, even and are not reactive with</li> </ul>	gh prompt medical attention was burn. under fire exposure conditions, water.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.