

## Safety Data Sheet 1100720

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## **SECTION 1: Identification**

### 1.1. Identification

Product form : Substance

Substance name : 1-Chloro-1,1,2,2-tetrafluoroethane

CAS No : 354-25-6
Product code : 1100-7-20
Formula : C2HCIF4
Other means of identification : MFCD00069099

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

### 1.3. Details of the supplier of the safety data sheet

SynQuest Laboratories, Inc.

P.O. Box 309

Alachua, FL 32615 - United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

### 1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

# **SECTION 2: Hazard(s) identification**

### 2.1. Classification of the substance or mixture

## **Classification (GHS-US)**

Simple Asphy H380 - May displace oxygen and cause rapid suffocation Liquefied gas H280 - Contains gas under pressure; may explode if heated

Skin Irrit. 2 H315 - Causes skin irritation
Eye Irrit. 2A H319 - Causes serious eye irritation
STOT SE 3 H335 - May cause respiratory irritation

Ozone 1 H420 - Harms public health and the environment by destroying ozone in the upper atmosphere

Full text of H-phrases: see section 16

## 2.2. Label elements

## **GHS-US** labeling

Hazard pictograms (GHS-US)





GHS04 GHS07

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H280 - Contains gas under pressure; may explode if heated

H315 - Causes skin irritation H319 - Causes serious eye irritation H335 - May cause respiratory irritation

H380 - May displace oxygen and cause rapid suffocation

H420 - Harms public health and the environment by destroying ozone in the upper atmosphere

Precautionary statements (GHS-US) : P261 - Avoid breathing fumes, gas, mist, spray, vapors

P264 - Wash skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P302+P352 - If on skin: Wash with plenty of soap and water

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER or doctor/physician if you feel unwell

P321 - Specific treatment (see supplemental first aid instructions on this label)

P332+P313 - If skin irritation occurs: Get medical advice/attention

12/06/2016 EN (English US) SDS ID: 1100720 Page 1

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P337+P313 - If eye irritation persists: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P410+P403 - Protect from sunlight. Store in a well-ventilated place P501 - Dispose of contents/container to an approved waste disposal plant P502 - Refer to manufacturer/supplier for information on recovery/recycling

#### 2.3. Other hazards

Other hazards not contributing to the classification

: May cause frostbite.

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substance

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
1-Chloro-1,1,2,2-tetrafluoroethane (Main constituent)	(CAS No) 354-25-6	<= 100	Simple Asphy, H380 Liquefied gas, H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Ozone 1, H420

Full text of H-phrases: see section 16

#### 3.2. Mixture

Not applicable

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

First-aid measures general

: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.

First-aid measures after skin contact

Thaw frosted parts with lukewarm water. Do no rub affected area. Get immediate medical advice/attention.

First-aid measures after eye contact

: Remove contact lenses, if present and easy to do. Continue rinsing. Immediately flush eyes thoroughly with water for at least 15 minutes. Get immediate medical advice/attention.

First-aid measures after ingestion

Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries

: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

Symptoms/injuries after inhalation

: May cause drowsiness or dizziness.

Symptoms/injuries after skin contact

Contact with the liquid the may cause cold burns/frostbite.

Symptoms/injuries after eye contact

: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

## 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media

: Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

## 5.2. Special hazards arising from the substance or mixture

Fire hazard

: Thermal decomposition generates: Carbon oxides. Hydrogen chloride. Hydrogen fluoride.

Explosion hazard

: Contains gas under pressure; may explode if heated. Use water spray or fog for cooling exposed containers.

### 5.3. Advice for firefighters

Firefighting instructions

: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

12/06/2016 EN (English US) SDS ID: 1100720 2/7

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting

: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.

## 6.1.1. For non-emergency personnel

**Emergency procedures** 

: Only qualified personnel equipped with suitable protective equipment may intervene.

### 6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground

level.

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so.

Methods for cleaning up : Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

## 6.4. Reference to other sections

No additional information available

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Additional hazards when processed

: Pressurized container: Do not pierce or burn, even after use. Close valve after each use and

when empty.

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal

protective equipment. Avoid contact with skin and eyes.

Safe handling of the gas receptacle

: Securely chain cylinders when in use and protect against physical damage.

Hygiene measures

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Comply with applicable regulations.

Storage conditions

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed

when not in use.

Incompatible materials

: Refer to Section 10 on Incompatible Materials.

Storage area

: Store in dry, cool, well-ventilated area.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

#### 8.2. Exposure controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released.

Hand protection

: Protective gloves. 29 CFR 1910.138: Hand Protection.

Eye protection

: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection

: Wear suitable protective clothing.

Respiratory protection

: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory

Protection.

Thermal hazard protection

: Cold insulating gloves.

Other information

: Safety shoes. 29 CFR 1910.136: Foot Protection.

12/06/2016 EN (English US) SDS ID: 1100720 3/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available

Melting point : -117 °C

Freezing point : No data available

Boiling point : -10.2 °C

Flash point : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : No data available
Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available

Vapor pressure : 760 mm Hg (@ -10.2 °C)

Relative density : No data available Relative vapor density at 20 °C : No data available Specific gravity / density 1.379 g/ml (@ 20 °C) Molecular mass : 136.48 g/mol Solubility : No data available Log Pow : No data available Auto-ignition temperature : No data available Decomposition temperature No data available Viscosity No data available : No data available Viscosity, kinematic

## 9.2. Other information

No additional information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Viscosity, dynamic

No additional information available

### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

### 10.3. Possibility of hazardous reactions

No additional information available

#### 10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C Keep away from heat, sparks and flame.

: No data available

## 10.5. Incompatible materials

Alkali metals. Finely divided metals (Al, Mg, Zn). Strong bases. Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

1-Chloro-1,1,2,2-tetrafluoroethane (354-25-6)	
LC50 inhalation rat (mg/l)	1220 g/m³ (Exposure time: 4 h)

12/06/2016 EN (English US) SDS ID: 1100720 4/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Contact with the liquid the may cause cold burns/frostbite.

Symptoms/injuries after eye contact : Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due

to frostbite from rapid liquid evaporation.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

No additional information available

## 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Other information : Class II ozone-depleting substance.

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Waste disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

## **SECTION 14: Transport information**

## **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN3163 Liquefied gas, n.o.s., 2.2

UN-No.(DOT) : UN3163

Proper Shipping Name (DOT) : Liquefied gas, n.o.s.

Transport hazard class(es) (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : 304 DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

DOT Symbols : G - Identifies PSN requiring a technical name

12/06/2016 EN (English US) SDS ID: 1100720 5/7

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102) : T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the

applicable liquefied compressed gases are authorized to be transported in portable tanks in

accordance with the requirements of 173.313 of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

**DOT Vessel Stowage Location** : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Other information : No supplementary information available.

**TDG** 

No additional information available

Transport by sea

UN-No. (IMDG) : 3163

Proper Shipping Name (IMDG) : LIQUEFIED GAS, N.O.S.

Class (IMDG) : 2 - Gases

Air transport

UN-No. (IATA) : 3163

Proper Shipping Name (IATA) : Liquefied gas, n.o.s.

Class (IATA) : 2

## **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

## 1-Chloro-1,1,2,2-tetrafluoroethane (354-25-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 SARA Section 313 - Emission Reporting 1.0 %

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

1-Chloro-1,1,2,2-tetrafluoroethane CAS No 354-25-6 100%

### 15.2. International regulations

#### **CANADA**

## 1-Chloro-1,1,2,2-tetrafluoroethane (354-25-6)

Listed on the Canadian DSL (Domestic Sustances List)

#### **EU-Regulations**

No additional information available

#### **National regulations**

# 1-Chloro-1,1,2,2-tetrafluoroethane (354-25-6)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on NZIoC (New Zealand Inventory of Chemicals)

### 15.3. US State regulations

## 1-Chloro-1,1,2,2-tetrafluoroethane (354-25-6)

State or local regulations U.S. - New Jersey - Right to Know Hazardous Substance List

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

### **SECTION 16: Other information**

12/06/2016 EN (English US) SDS ID: 1100720 6/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Full text of H-phrases:

74 O. 11 p4000.	
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Liquefied gas	Gases under pressure Liquefied gas
Ozone 1	Hazardous to the ozone layer Category 1
Simple Asphy	Simple Asphyxiant
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H380	May displace oxygen and cause rapid suffocation
H420	Harms public health and the environment by destroying ozone in the upper atmosphere

NFPA health hazard : 3 - Short exposure could cause serious temporary or


residual injury even though prompt medical attention was

given.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

12/06/2016 EN (English US) SDS ID: 1100720 7/7