

Safety Data Sheet 1100742 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 02/10/2016 Version: 1.0

SECTION 1: Identification		
1.1. Identification		
Product form	: Substance	
Substance name	: 2-Chloro-1,1,1,3,3,3-hexafluo	ropropane
CAS No	: 431-87-8	
Product code	: 1100-7-42	
Formula	: C3HCIF6	
Other means of identification	: MFCD01698452	
1.2. Relevant identified uses of the su	ubstance or mixture and uses advi	sed against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and develo	opment
1.3. Details of the supplier of the safe	ety data sheet	
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of America T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlabs. 1.4. Emergency telephone number		
Emergency number	: (844) 523-4086 (3E Company	/ - Account 10069)
SECTION 2: Hazard(s) identification		
2.1. Classification of the substance of	or mixture	
Classification (GHS-US)		
Skin Irrit. 2 H315 - Causes skin irritatio		
Skin Irrit. 2H315 - Causes skin irritatioEye Irrit. 2AH319 - Causes serious eyeSTOT SE 3H335 - May cause respirateOzone 1H420 - Harms public health	n e irritation	zone in the upper atmosphere
Skin Irrit. 2H315 - Causes skin irritatioEye Irrit. 2AH319 - Causes serious eyeSTOT SE 3H335 - May cause respirateOzone 1H420 - Harms public healthFull text of H-phrases: see section 16	n e irritation ory irritation	zone in the upper atmosphere
Skin Irrit. 2H315 - Causes skin irritatioEye Irrit. 2AH319 - Causes serious eyeSTOT SE 3H335 - May cause respirateOzone 1H420 - Harms public healthFull text of H-phrases: see section 16	n e irritation ory irritation	ozone in the upper atmosphere
Skin Irrit. 2 H315 - Causes skin irritatio Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirate Ozone 1 H420 - Harms public health Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	n e irritation bory irritation n and the environment by destroying of the environment by destroying of	ozone in the upper atmosphere
Skin Irrit. 2 H315 - Causes skin irritatio Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirate Ozone 1 H420 - Harms public health Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	in e irritation bry irritation in and the environment by destroying of GHS04 GHS04 GHS07	ozone in the upper atmosphere
Skin Irrit. 2 H315 - Causes skin irritatio Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirate Ozone 1 H420 - Harms public health Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	n e irritation by irritation h and the environment by destroying of the environment by destroying of th	ressure; may explode if heated ritation r irritation
Skin Irrit. 2 H315 - Causes skin irritatio Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirate Ozone 1 H420 - Harms public health Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	n a irritation by irritation and the environment by destroying of and the environment by destroying of	ressure; may explode if heated ritation i riritation and cause rapid suffocation nd the environment by destroying ozone in the upper atmosphere s, gas, mist, spray, vapors after handling n a well-ventilated area s/protective clothing/eye protection/face protection in with plenty of soap and water ove person to fresh air and keep comfortable for breathing : Rinse cautiously with water for several minutes. Remove contact

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	,	· · · · · · · · · · · · · · · · · · ·		
	P362+P36 P403+P23 P405 - Sto P410+P40 P501 - Dis	 3 - If eye irritation persists: Get m 4 - Take off contaminated clothing 3 - Store in a well-ventilated place 3 - Protect from sunlight. Store in a pose of contents/container to an a fer to manufacturer/supplier for inf 	g and wash it before A Keep container a well-ventilated approved waste co	ore reuse · tightly closed place lisposal plant
2.3. Other hazards				
Other hazards not contributing to the lassification	: May cause	e frostbite.		
2.4. Unknown acute toxicity (GHS US)				
Not applicable				
SECTION 3: Composition/informat	ion on ingree	dients		
3.1. Substance				
Substance type	: Mono-con	stituent		
Name	Pro	oduct identifier	%	Classification (GHS-US)
2-Chloro-1,1,1,3,3,3-hexafluoropropane (Main constituent)	(CA	S No) 431-87-8	<= 100	Simple Asphy, H380 Liquefied gas, H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Ozone 1, H420
Full text of H-phrases: see section 16			-	-
3.2. Mixture				
Not applicable				
SECTION 4: First aid measures				
4.1. Description of first aid measures				
irst-aid measures general		accident or if you feel unwell, see sible). Move the affected personn		
First-aid measures after inhalation		Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.		
First-aid measures after skin contact	advice/atte	Thaw frosted parts with lukewarm water. Do no rub affected area. Get immediate medical advice/attention.		
First-aid measures after eye contact	thoroughly	Remove contact lenses, if present and easy to do. Continue rinsing. Immediately flush eyes thoroughly with water for at least 15 minutes. Get immediate medical advice/attention.		
First-aid measures after ingestion		ing by mouth to an unconscious p		y. Do NOT induce vomiting. Never uth out with water. Get medical
4.2. Most important symptoms and eff				
Symptoms/injuries		important known symptoms and e r in section 11.	ffects are describ	ed in the labelling (see section
Symptoms/injuries after inhalation	•	e drowsiness or dizziness.		
Symptoms/injuries after skin contact		th the liquid the may cause cold b		
Symptoms/injuries after eye contact		tact with the liquefied gas may cau from rapid liquid evaporation.	use severe and p	ossibly permanent eye injury due
4.3. Indication of any immediate medi	cal attention and	d special treatment needed		
No additional information available				
SECTION 5: Firefighting measures				
5.1. Extinguishing media				
Suitable extinguishing media		sistant foam. Carbon dioxide. Dry e for surrounding fire.	powder. Water s	pray. Use extinguishing media
5.2. Special hazards arising from the s	substance or mi	xture		
Fire hazard	: Thermal d	ecomposition generates: Carbon of	oxides. Hydrogen	chloride. Hydrogen fluoride.
Explosion hazard	: Contains g exposed c	gas under pressure; may explode i ontainers.	f heated. Use wa	ater spray or fog for cooling
5.3. Advice for firefighters				
Firefighting instructions	: In case of	fire: Evacuate area. Fight fire rem	otely due to the r	isk of explosion.
12/06/2016	EN (English L	JS)	SDS ID: 1100742	2 2/7

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting	: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".
SECTION 6: Accidental release mea	isures
5.1. Personal precautions, protective ed	quipment and emergency procedures
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.
5.1.1. For non-emergency personnel	
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.
5.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.
6.2. Environmental precautions	
Avoid release to the environment. Notify authori	ities if product enters sewers or public waters.
3.3. Methods and material for containm	ent and cleaning up
For containment	: Stop leak if safe to do so.
Aethods for cleaning up	: Ventilate area.
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".
3.4. Reference to other sections	
No additional information available	
SECTION 7: Handling and storage	
1. Precautions for safe handling	
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Close valve after each use and when empty.
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal
	protective equipment. Avoid contact with skin and eyes.
Safe handling of the gas receptacle	protective equipment. Avoid contact with skin and eyes. : Securely chain cylinders when in use and protect against physical damage.
Safe handling of the gas receptacle Hygiene measures	
	 Securely chain cylinders when in use and protect against physical damage. Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
lygiene measures	 Securely chain cylinders when in use and protect against physical damage. Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Hygiene measures 7.2. Conditions for safe storage, includ	 Securely chain cylinders when in use and protect against physical damage. Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Aygiene measures 7.2. Conditions for safe storage, includ Technical measures	 Securely chain cylinders when in use and protect against physical damage. Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. ing any incompatibilities Comply with applicable regulations. Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

No additional information available

8.2.	Exposure controls			
Approp	riate engineering controls	should be ava	e good ventilation of the work station. Emergency eye wash fountains and safety showe I be available in the immediate vicinity of any potential exposure. Systems under ure should be regularily checked for leakage. Oxygen detectors should be used when xiating gases may be released.	
Hand p	rotection	: Protective glo	ves. 29 CFR 1910.138: Hand Protection.	
Eye pro	otection	: Chemical gog	mical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.	
Skin an	nd body protection	: Wear suitable	protective clothing.	
Respira	atory protection	: In case of inac Protection.	dequate ventilation wear respiratory protection. 29 CFR 1910.1	34: Respiratory
Therma	al hazard protection	: Cold insulating	g gloves.	
Other in	nformation	: Safety shoes.	29 CFR 1910.136: Foot Protection.	
12/06/20	016	EN (English US)	SDS ID: 1100742	3/7

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemica	Il properties
9.1. Information on basic physical an	
Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Melting point	: -119.6 °C
Freezing point	: No data available
Boiling point	: 14.1 °C
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.5414 g/ml (@ 4 °C)
Molecular mass	: 186.48 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
9.2. Other information	
No additional information available	
SECTION 10: Stability and reactivi	ity

CECTION 10. Clability a	narcactivity		
10.1. Reactivity			
No additional information availa	ıble		
10.2. Chemical stability			
The product is stable at normal	handling and storage conditions.		
10.3. Possibility of hazar	lous reactions		
No additional information availa	ıble		
10.4. Conditions to avoid			
Protect from sunlight. Do not e	pose to temperatures exceeding 50 °C Keep away	from heat, sparks and flame.	
10.5. Incompatible mater	als		
Alkali metals. Finely divided me	etals (Al, Mg, Zn). Strong bases. Strong oxidizing ag	jents.	
10.6. Hazardous decomp	osition products		
Under normal conditions of sto fire, see Section 5.	rage and use, hazardous decomposition products s	hould not be produced. Hazardous decompos	sition products in case o
SECTION 11: Toxicolog	ical information		
11.1. Information on toxi	ological effects		
Acute toxicity	: Not classified		
Skin corrosion/irritation	: Causes skin irritation.		
Serious eye damage/irritation	: Causes serious eye irritation.		
12/06/2016	EN (English LIC)		A/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or skin sensitization Germ cell mutagenicity	: Not classified : Not classified
Carcinogenicity Reproductive toxicity Specific target organ toxicity (single exposure)	 Not classified Not classified May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Contact with the liquid the may cause cold burns/frostbite.
Symptoms/injuries after eye contact	: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.
SECTION 12: Ecological information	

12.1.	Toxicity
No addi	tional information available
12.2.	Persistence and degradability
No addi	tional information available
12.3.	Bioaccumulative potential
No addi	tional information available
12.4.	Mobility in soil
No addi	tional information available
12.5.	Other adverse effects

Other information

: Class II ozone-depleting substance.

SECTION 13: Disposal considerat	ions
13.1. Waste treatment methods	
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Recycle the material as far as possible.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT Transport document description

UN-No.(DOT) Proper Shipping Name (DOT) Transport hazard class(es) (DOT) Hazard labels (DOT) : UN3163 Liquefied gas, n.o.s., 2.2

- : UN3163
- : Liquefied gas, n.o.s.
- : 2.2 Class 2.2 Non-flammable compressed gas 49 CFR 173.115
- : 2.2 Non-flammable gas



- DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Symbols
- DOT Special Provisions (49 CFR 172.102)
- DOT Packaging Exceptions (49 CFR 173.xxx)
- G Identifies PSN requiring a technical name
 T50 When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.

x) : 306

: 304

: 314;315

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

:	150 kg
:	A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
:	No supplementary information available.
:	3163
:	LIQUEFIED GAS, N.O.S.
:	2 - Gases
:	3163
:	Liquefied gas, n.o.s.
	·· ·· ·· ·· ·· ·· ·· ·· ·· ·· ·· ·· ··

SECTION 15: Regulatory information	
15.1. US Federal regulations	

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

: 2

2-Chloro-1,1,1,3,3,3-hexafluoropropane CAS No 431-87-8 100%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Class (IATA)

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full tex	t of H-phrases:	
	Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
	Liquefied gas	Gases under pressure Liquefied gas
	Ozone 1	Hazardous to the ozone layer Category 1
	Simple Asphy	Simple Asphyxiant
	Skin Irrit. 2	Skin corrosion/irritation Category 2
	STOT SE 3	Specific target organ toxicity (single exposure) Category 3
	H280	Contains gas under pressure; may explode if heated
	H315	Causes skin irritation
	H319	Causes serious eye irritation
	H335	May cause respiratory irritation
	H380	May displace oxygen and cause rapid suffocation
	H420	Harms public health and the environment by destroying ozone in the upper atmosphere
NFPA health hazard NFPA fire hazard NFPA reactivity		 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given. 0 - Materials that will not burn. 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating Health Flammability		 2 Moderate Hazard - Temporary or minor injury may occur 0 Minimal Hazard - Materials that will not burn

SDS US (GHS HazCom 2012)

Physical

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.