

Safety Data Sheet 1100B53 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 08/15/2016 Version: 1.0

SECTION 1: Identification		
1.1. Identification		
Product form	: Substance	
Substance name	: 1-Bromo-1,1-difluoroethane	
CAS No : 420-43-9		
Product code	: 1100-B-53	
Formula	: C2H3BrF2	
Other means of identification	: MFCD00045067	
1.2. Relevant identified uses of the su	ubstance or mixture and uses adv	ised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and devel	opment
1.3. Details of the supplier of the safe	ety data sheet	
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of America T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlabs. 1.4. Emergency telephone number		
Emergency number	: (844) 523-4086 (3E Compan	y - Account 10069)
SECTION 2: Hazard(s) identification		
2.1. Classification of the substance o	r mixture	
Classification (GHS-US)		
Skin Irrit. 2 H315 - Causes skin irritation		
Skin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eyeSTOT SE 3H335 - May cause respirateOzone 1H420 - Harms public health	n irritation	ozone in the upper atmosphere
Skin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eyeSTOT SE 3H335 - May cause respirateOzone 1H420 - Harms public healthFull text of H-phrases: see section 16	n Firritation Dry irritation	ozone in the upper atmosphere
Skin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eyeSTOT SE 3H335 - May cause respirateOzone 1H420 - Harms public healthFull text of H-phrases: see section 16	n Firritation Dry irritation	ozone in the upper atmosphere
Skin Irrit. 2       H315 - Causes skin irritation         Eye Irrit. 2A       H319 - Causes serious eye         STOT SE 3       H335 - May cause respirate         Ozone 1       H420 - Harms public health         Full text of H-phrases: see section 16         2.2.       Label elements         GHS-US labeling	n e irritation bory irritation a and the environment by destroying	ozone in the upper atmosphere
Skin Irrit. 2       H315 - Causes skin irritation         Eye Irrit. 2A       H319 - Causes serious eye         STOT SE 3       H335 - May cause respirate         Ozone 1       H420 - Harms public health         Full text of H-phrases: see section 16         2.2.       Label elements         GHS-US labeling         Hazard pictograms (GHS-US)	n e irritation bry irritation a and the environment by destroying K K K K K K K K	ozone in the upper atmosphere
Skin Irrit. 2       H315 - Causes skin irritation         Eye Irrit. 2A       H319 - Causes serious eye         STOT SE 3       H335 - May cause respirate         Ozone 1       H420 - Harms public health         Full text of H-phrases: see section 16         2.2.       Label elements         GHS-US labeling	n e irritation bry irritation and the environment by destroying GHS04 CHS04 CHS07 : Warning : H280 - Contains gas under p H315 - Causes skin irritation H319 - Causes serious eye in H335 - May cause respirator H380 - May displace oxygen	ressure; may explode if heated rritation y irritation
Skin Irrit. 2       H315 - Causes skin irritation         Eye Irrit. 2A       H319 - Causes serious eye         STOT SE 3       H335 - May cause respirate         Ozone 1       H420 - Harms public health         Full text of H-phrases: see section 16         2.2.       Label elements         GHS-US labeling         Hazard pictograms (GHS-US)         Signal word (GHS-US)	n e irritation bry irritation and the environment by destroying and the environment by destroying if description GHS04 if description GHS04 if description GHS04 if description GHS04 if description GHS07 if Warning if H280 - Contains gas under p H315 - Causes skin irritation H319 - Causes serious eye in H335 - May cause respirator H380 - May displace oxygen H420 - Harms public health a if P261 - Avoid breathing fume P264 - Wash skin thoroughly P271 - Use only outdoors or P280 - Wear protective glove P302+P352 - If on skin: Was P304+P340 - If inhaled: Rem P305+P351+P338 - If in eyes lenses, if present and easy to P312 - Call a POISON CENT P321 - Specific treatment (see	ressure; may explode if heated ritation y irritation and cause rapid suffocation and the environment by destroying ozone in the upper atmosphere s, gas, mist, spray, vapors after handling in a well-ventilated area is/protective clothing/eye protection/face protection h with plenty of soap and water ove person to fresh air and keep comfortable for breathing s: Rinse cautiously with water for several minutes. Remove contact

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	P337+P313 - If eye irritation persists P362+P364 - Take off contaminated P403+P233 - Store in a well-ventilat P405 - Store locked up P410+P403 - Protect from sunlight. P501 - Dispose of contents/containe P502 - Refer to manufacturer/suppli	I clothing and wash it b ed place. Keep contain Store in a well-ventilate er to an approved wast	efore reuse her tightly closed ed place e disposal plant
2.3. Other hazards			
No additional information available			
2.4. Unknown acute toxicity (GHS U	IS)		
Not applicable			
SECTION 3: Composition/information	ation on ingredients		
3.1. Substance			
Substance type	: Mono-constituent		
Name	Product identifier	%	Classification (GHS-US)
1-Bromo-1,1-difluoroethane (Main constituent)	(CAS No) 420-43-9	<= 100	Simple Asphy, H380 Liquefied gas, H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Ozone 1, H420
Full text of H-phrases: see section 16		I	
3.2. Mixture			
Not applicable			
SECTION 4: First aid measures			
4.1. Description of first aid measure	95		
First-aid measures general	: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.		
First-aid measures after inhalation	<ul> <li>Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.</li> </ul>		
First-aid measures after skin contact	: Wash with plenty of soap and water	. Get medical advice/a	ttention.
First-aid measures after eye contact	: Remove contact lenses, if present a thoroughly with water for at least 15		
First-aid measures after ingestion	: Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention.		
4.2. Most important symptoms and o	effects, both acute and delayed		
Symptoms/injuries	: The most important known symptom 2.2) and/or in section 11.	ns and effects are desc	ribed in the labelling (see section
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.		
Symptoms/injuries after skin contact	: Contact with the liquid the may caus		
Symptoms/injuries after eye contact	: Direct contact with the liquefied gas to frostbite from rapid liquid evapora		d possibly permanent eye injury due
4.3. Indication of any immediate me No additional information available	dical attention and special treatment need	led	
SECTION 5: Firefighting measure	es		
5.1. Extinguishing media			
Suitable extinguishing media	: Alcohol resistant foam. Carbon diox appropriate for surrounding fire.	ide. Dry powder. Wate	r spray. Use extinguishing media
5.2. Special hazards arising from the	e substance or mixture		
Fire hazard	: Thermal decomposition generates:	Carbon oxides. Hydrog	jen bromide. Hydrogen fluoride.
Explosion hazard	: Contains gas under pressure; may e exposed containers.		
5.3. Advice for firefighters			
Firefighting instructions	: In case of fire: Evacuate area. Fight	fire remotely due to th	e risk of explosion.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release meas	ures
6.1. Personal precautions, protective equ	ipment and emergency procedures
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.
6.1.1. For non-emergency personnel	
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.
6.2. Environmental precautions	
Avoid release to the environment. Notify authoritie	es if product enters sewers or public waters.
6.3. Methods and material for containment	nt and cleaning up
For containment	: Stop leak if safe to do so.
Methods for cleaning up	: Ventilate area.
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".
6.4. Reference to other sections	
No additional information available	
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Close valve after each use and when empty.
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes.
Safe handling of the gas receptacle	: Securely chain cylinders when in use and protect against physical damage.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, includin	g any incompatibilities
Technical measures	: Comply with applicable regulations.
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use.
Incompatible materials	: Refer to Section 10 on Incompatible Materials.
Storage area	: Store in dry, cool, well-ventilated area.
SECTION & Evenesuse controls/page	

## **SECTION 8: Exposure controls/personal protection**

### 8.1. **Control parameters**

No additional information available

8.2. Exposure controls	
Appropriate engineering controls	Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Thermal hazard protection	: Cold insulating gloves.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>SECTION 9: Physical and chemical</b>	Inroperties
9.1. Information on basic physical and	
Physical state	: Gas
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 14.4 °C
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Molecular mass	: 144.95 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
9.2. Other information	
No additional information available	
<b>SECTION 10: Stability and reactivit</b>	ty

10.1. Reactivity

No additional information available

#### 10.2. **Chemical stability**

The product is stable at normal handling and storage conditions.

#### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. **Conditions to avoid**

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

#### 10.5. **Incompatible materials**

Alkali metals. Finely divided metals (Al, Mg, Zn). Strong acids. Strong bases. Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information		
11.1. Information on toxicological effects		
Acute toxicity	: Not classified	
Skin corrosion/irritation	: Causes skin irritation.	
Serious eye damage/irritation	: Causes serious eye irritation.	
Respiratory or skin sensitization	: Not classified	

Respiratory or skin sensitization

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Germ cell mutagenicity Carcinogenicity	: Not classified : Not classified
Reproductive toxicity Specific target organ toxicity (single exposure)	: Not classified : May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Contact with the liquid the may cause cold burns/frostbite.
Symptoms/injuries after eye contact	: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

<b>SECTION 12: Ecological information</b>	
12.1. Toxicity	
No additional information available	
12.2. Persistence and degradability	
No additional information available	
12.3. Bioaccumulative potential	
No additional information available	
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	
Other information	: Class I - Group VII ozone-depleting substance.
SECTION 13: Disposal consideration	ns

13.1. Waste tr	eatment methods		
Waste treatment m	ethods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.	
Waste disposal rec	commendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.	
Additional informat	ion	: Recycle the material as far as possible.	

## **SECTION 14: Transport information**

## **Department of Transportation (DOT)**

In accordance with DOT Transport document description

UN-No.(DOT) Proper Shipping Name (DOT) Transport hazard class(es) (DOT) Hazard labels (DOT)

: UN3161 Liquefied gas, flammable, n.o.s., 2.1

: UN3161

: Liquefied gas, flammable, n.o.s.

: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

: G - Identifies PSN requiring a technical name

accordance with the requirements of 173.313 of this subchapter.

: 2.1 - Flammable gas



: 304

: 306

: 314;315

DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Symbols DOT Special Provisions (49 CFR 172.102)

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail : Forbidden (49 CFR 173.27)

: T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>S S S</b>	
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 3161
Proper Shipping Name (IMDG)	: LIQUEFIED GAS, FLAMMABLE, N.O.S.
Class (IMDG)	: 2 - Gases
Air transport	
UN-No. (IATA)	: 3161
Proper Shipping Name (IATA)	: Liquefied gas, flammable, n.o.s.
Class (IATA)	: 2

## **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic

Substances Control Act (TSCA) inventory except for:		
1-Bromo-1,1-difluoroethane	CAS No 420-43-9	100%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

### 15.2. International regulations

**CANADA** 

No additional information available

**EU-Regulations** No additional information available

### **National regulations**

No additional information available

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

## **SECTION 16: Other information**

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:	
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Liquefied gas	Gases under pressure Liquefied gas
Ozone 1	Hazardous to the ozone layer Category 1
Simple Asphy	Simple Asphyxiant
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H380	May displace oxygen and cause rapid suffocation
H420	Harms public health and the environment by destroying ozone in the upper atmosphere
NFPA health hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard	: 1 - Must be preheated before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	<ul> <li>1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)</li> </ul>
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.