

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS ID: 1100J01SH

Issue date: 10/28/2022 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : lodotrifluoromethane, 0.5M in hexanes

Product code : 1100-J-01SH

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

1.3. Supplier

SynQuest Laboratories, Inc. Inc.

P.O. Box 309

Alachua, FL, Alachua, 32615

United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319	Causes serious eye irritation
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Specific target organ toxicity – Single exposure, Category 3,	H335	May cause respiratory irritation
Respiratory tract irritation		
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs through prolonged or repeated
		exposure
Aspiration hazard Category 1	H304	May be fatal if swallowed and enters airways

Hazardous to the aquatic environment – Acute Hazard Category 2 H401 Toxic to aquatic life

Hazardous to the aquatic environment – Chronic Hazard Category 2 H411 Toxic to aquatic life with long lasting effects

Full text of H statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)









Signal word (GHS US) : Danger

Safety Data Sheet

Precautionary statements (GHS US)

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P264 - Wash skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 - If swallowed: Immediately call a poison center or doctor.

P302+P352 - If on skin: Wash with plenty of soap and water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell

P314 - Get medical advice/attention if you feel unwell.

P321 - Specific treatment (see supplemental first aid instructions on this label)

P331 - Do NOT induce vomiting.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P391 - Collect spillage.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

10/28/2022 (Issue date) EN (English US) 2/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Hexane(s)	-	99.2 – 99.7	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Iodotrifluoromethane	CAS-No.: 2314-97-8	0.3 – 0.8	Press. Gas (Liq.), H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Muta. 2, H341 STOT SE 3, H335

Full text of hazard classes and H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial

respiration. Get medical advice/attention.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

Symptoms/effects after inhalation : May cause drowsiness or dizziness.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

5.2. Specific hazards arising from the chemical

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen fluoride. Hydrogen iodide.

Explosion hazard : Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed

containers. May form flammable/explosive vapor-air mixture.

10/28/2022 (Issue date) EN (English US) 3/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions

: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting

: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures

: Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures

 Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment

: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

Methods for cleaning up

: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.

Other information

: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed Precautions for safe handling

- : Handle empty containers with care because residual vapors are flammable.
- : Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.

Hygiene measures

: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Comply with applicable regulations.

Storage conditions

: Keep container closed when not in use. Keep away from ignition sources. Moisture sensitive.

Keep contents under inert gas. Direct sunlight.

Incompatible materials

: Refer to Section 10 on Incompatible Materials. Direct sunlight.

Storage area

: Store in dry, cool, well-ventilated area.

10/28/2022 (Issue date) EN (English US) 4/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

lodotrifluoromethane, 0.5M in hexanes

No additional information available

Hexane(s)

No additional information available

lodotrifluoromethane (2314-97-8)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

protective gloves. 29 CFR 1910.138: Hand Protection

Eye protection:

Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

Personal protective equipment symbol(s):









Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Colorless

Odor : Mixture contains one or more component(s) which have the following odour:

Odor threshold : No data available pH : No data available

Melting point : -95 °C

Freezing point : No data available Boiling point : $68 - 70 \, ^{\circ}\mathrm{C}$ Flash point : $-23 \, ^{\circ}\mathrm{C}$

Relative evaporation rate (butyl acetate=1) : No data available

10/28/2022 (Issue date) EN (English US) 5/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability (solid, gas) : No data available : No data available Vapor pressure Relative vapor density at 20 °C : No data available Relative density : No data available Density : 0.672 g/ml (@ 25 °C) : No data available Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature Decomposition temperature No data available : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available **Explosion limits** : No data available Explosive properties Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from heat, sparks and flame. Direct sunlight.

10.5. Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	, ,
STOT-single exposure :	May cause drowsiness or dizziness. May cause respiratory irritation.
Hexane(s)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
lodotrifluoromethane (2314-97-8)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure :	May cause damage to organs through prolonged or repeated exposure.
Hexane(s)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard :	May be fatal if swallowed and enters airways.
Viscosity, kinematic :	No data available
Symptoms/effects :	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.
Symptoms/effects after inhalation :	May cause drowsiness or dizziness.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber. Product/Packaging disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Dispose of contents of the content o

Additional information : Recycle the material as far as possible.

SECTION 14: Transport information

14.1. UN number

DOT NA NO : UN1208 UN-No. (TDG) : Not applicable

UN-No. (IMDG) : 1208 UN-No. (IATA) : 1208

10/28/2022 (Issue date) EN (English US) 7/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Hexanes
Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : HEXANES
Proper Shipping Name (IATA) : Hexanes

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 3 Hazard labels (DOT) : 3



TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : 3
Hazard labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



14.4. Packing group

Packing group (DOT) : II

Packing group (TDG) : Not applicable

Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Dangerous for the environment : Yes
Marine pollutant : Yes



Other information : No supplementary information available.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1208

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 $\,$

kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59)

F) and 50 C (122 F), respectively.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : 5 L
CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

DOT Vessel Stowage Location : E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.

TDG

Emergency Response Guide (ERG) Number : 128

IMDG

Limited quantities (IMDG) : 1 L

Excepted quantities (IMDG) : E2

Packing instructions (IMDG) : P001

IBC packing instructions (IMDG) : IBC02

Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP2

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS

EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS

: 60 L

Stowage category (IMDG) : E

Properties and observations (IMDG) : Colourless, volatile liquids with a faint odour. Explosive limits: 1.1% to 7.5% n-HEXANE:

flashpoint -22°C c.c. boiling point 69°C. NEOHEXANE: flashpoint -48°C c.c. boiling point 50°C.

Immiscible with water. Slightly irritating to skin, eyes and mucous membranes.

IATA

: E2 PCA Excepted quantities (IATA) PCA Limited quantities (IATA) Y341 PCA limited quantity max net quantity (IATA) 1L PCA packing instructions (IATA) 353 PCA max net quantity (IATA) : 5L : 364 CAO packing instructions (IATA) CAO max net quantity (IATA) : 60L ERG code (IATA) : 3H

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

10/28/2022 (Issue date) EN (English US) 9/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Hexane(s) CAS-No. 99.2 – 99.7%

15.2. International regulations

CANADA

lodotrifluoromethane (2314-97-8)

Listed on the Canadian NDSL (Non-Domestic Substances List)

EU-Regulations

lodotrifluoromethane (2314-97-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

lodotrifluoromethane (2314-97-8)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on the Japanese ENCS (Existing New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on NZIoC (New Zealand Inventory of Chemicals)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

: 0 - Material that in themselves are normally stable, even under fire

conditions.



Hazard Rating

Flammability

Physical

NFPA reactivity

Health : 2 Moderate Hazard - Temporary or minor injury may occur

: * - Chronic (long-term) health effects may result from repeated overexposure

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB IC)

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Safety Data Sheet (SDS), USA

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.