

Safety Data Sheet 1300103 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Version: 1.0

Date of issue: 09/23/2016

.1. Identification	
Product form	: Substance
Substance name	: Allene
CAS No	: 463-49-0
Product code	: 1300-1-03
Formula	: C3H4
Synonyms	: Propadiene
Other means of identification	: MFCD00008566
	substance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the saf	fety data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of Americ T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlabs	
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identificati	
2.1. Classification of the substance	or mixture
Classification (GHS-US)	
Flam. Gas 1 H220 - Extremely flammab Liquefied gas H280 - Contains gas unde Skin Irrit. 2 H315 - Causes skin irritatio Eye Irrit. 2A H319 - Causes serious eye	ble gas er pressure; may explode if heated on re irritation
Flam. Gas 1H220 - Extremely flammabLiquefied gasH280 - Contains gas undeSkin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eyeSTOT SE 3H335 - May cause respirat	ble gas er pressure; may explode if heated on re irritation
Flam. Gas 1H220 - Extremely flammabLiquefied gasH280 - Contains gas undeSkin Irrit. 2H315 - Causes skin irritatioEye Irrit. 2AH319 - Causes serious eyeSTOT SE 3H335 - May cause respiratFull text of H-phrases: see section 16	ble gas er pressure; may explode if heated on re irritation
Flam. Gas 1 H220 - Extremely flammab Liquefied gas H280 - Contains gas unde Skin Irrit. 2 H315 - Causes skin irritatio Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	ble gas er pressure; may explode if heated on re irritation
Flam. Gas 1 H220 - Extremely flammab Liquefied gas H280 - Contains gas unde Skin Irrit. 2 H315 - Causes skin irritatio Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	ble gas er pressure; may explode if heated on re irritation
Flam. Gas 1 H220 - Extremely flammab Liquefied gas H280 - Contains gas unde Skin Irrit. 2 H315 - Causes skin irritatio Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	ble gas er pressure; may explode if heated on e irritation tory irritation
Flam. Gas 1 H220 - Extremely flammab Liquefied gas H280 - Contains gas unde Skin Irrit. 2 H315 - Causes skin irritatio Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirat Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	ble gas er pressure; may explode if heated on e irritation tory irritation
Flam. Gas 1H220 - Extremely flammabLiquefied gasH280 - Contains gas undeSkin Irrit. 2H315 - Causes skin irritatioEye Irrit. 2AH319 - Causes serious eyeSTOT SE 3H335 - May cause respiratFull text of H-phrases: see section 16	 ble gas er pressure; may explode if heated on re irritation tory irritation Constant of the state of the

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	P332 P337 P362 P377 P381 P403 P403 P405 P410	 Specific treatment (see supplemental +P313 - If skin irritation occurs: Get med +P313 - If eye irritation persists: Get med +P364 - Take off contaminated clothing Leaking gas fire: Do not extinguish, ur Eliminate all ignition sources if safe to Store in a well-ventilated place +P233 - Store in a well-ventilated place Store locked up +P403 - Protect from sunlight. Store in a Dispose of contents/container to an application 	dical advice/atte dical advice/atte and wash it bef nless leak can b do so . Keep containe a well-ventilated	ention ention ore reuse se stopped safely r tightly closed I place
2.3. Other hazards				
Other hazards not contributing to the classification	: May	cause frostbite.		
2.4. Unknown acute toxicity (GHS US)				
Not applicable				
SECTION 3: Composition/information	on on in	gredients		
3.1. Substance				
Substance type	: Mono	p-constituent		
Name		Product identifier	%	Classification (GHS-US)
Allene (Main constituent)		(CAS No) 463-49-0	<= 100	Simple Asphy, H380 Flam. Gas 1, H220 Liquefied gas, H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Full text of H-phrases: see section 16				
3.2. Mixture				
Not applicable				
SECTION 4: First aid measures				
4.1. Description of first aid measures				
First-aid measures general	where	se of accident or if you feel unwell, seek e possible). Move the affected personne	l away from the	contaminated area.
First-aid measures after inhalation	respi	ove person to fresh air and keep comformation. Get immediate medical advice/att	tention.	
First-aid measures after skin contact	advic	r frosted parts with lukewarm water. Do r e/attention.		
First-aid measures after eye contact	thoro	ove contact lenses, if present and easy t ughly with water for at least 15 minutes.	Get immediate	medical advice/attention.
First-aid measures after ingestion	give a	: Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention.		
4.2. Most important symptoms and effe	ects, both	acute and delayed		
Symptoms/injuries		nost important known symptoms and eff and/or in section 11.	ects are descrit	bed in the labelling (see section
Symptoms/injuries after inhalation	: May	cause drowsiness or dizziness.		
Symptoms/injuries after skin contact		act with the liquid the may cause cold bu		
Symptoms/injuries after eye contact	: Direc to fro	t contact with the liquefied gas may caus stbite from rapid liquid evaporation.	se severe and p	possibly permanent eye injury due
4.3. Indication of any immediate medic	al attentio	n and special treatment needed		
No additional information available				
SECTION 5: Firefighting measures				
5.1. Extinguishing media				
Suitable extinguishing media		nol resistant foam. Carbon dioxide. Dry popriate for surrounding fire.	oowder. Water s	pray. Use extinguishing media
5.2. Special hazards arising from the s	ubstance	or mixture		
Fire hazard	: Therr	nal decomposition generates: Carbon o	xides.	
12/06/2016	EN (En	alish US)	SDS ID: 130010	3 2/7

Safety Data Sheet

according to Federal Register / Vol. 77	No. 58 / Monday, March 26, 201	2 / Rules and Regulations

Explosion hazard	: Contains gas under pressure; may explode if heated. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.
5.3. Advice for firefighters	
Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection during firefighting	: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures			
6.1. Personal precautions, protective ed	quipment and emergency procedures		
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.		
6.1.1. For non-emergency personnel			
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.		
6.1.2. For emergency responders			
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".		
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.		
6.2. Environmental precautions			
Avoid release to the environment. Notify author	ties if product enters sewers or public waters.		
6.3. Methods and material for containm	ent and cleaning up		
For containment	: Stop leak if safe to do so.		
Methods for cleaning up	: Ventilate area.		
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".		
6.4. Reference to other sections			
No additional information available			
SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care because residual vapors are flammable. Close valve after each use and when empty.		
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.		
Safe handling of the gas receptacle	: Securely chain cylinders when in use and protect against physical damage.		
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.		
7.2. Conditions for safe storage, includ	ing any incompatibilities		
Technical measures	: Comply with applicable regulations.		
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use. Keep away from ignition sources.		
Incompatible materials	: Refer to Section 10 on Incompatible Materials.		
Storage area	: Store in dry, cool, well-ventilated area.		

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2.	Exposure controls	
Appropri	ate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. 77, No. 56 / Monday, March 26, 2012 / Rules and Regulations		
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.	
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.	
Skin and body protection	: Wear suitable protective clothing.	
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.	
Thermal hazard protection	: Cold insulating gloves.	
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.	

SECTION 9: Physical and chemical properties

ocorrow 5. r nysical and chemical		
9.1. Information on basic physical and chemical properties		
Physical state	: Gas	
Color	: No data available	
Odor	: No data available	
Odor threshold	: No data available	
рН	: No data available	
Melting point	: -136 °C	
Freezing point	: No data available	
Boiling point	: -34.5 °C	
Critical temperature	: 120 °C	
Critical pressure	: 759.8 psia	
Flash point	: No data available	
Relative evaporation rate (butyl acetate=1)	: No data available	
Flammability (solid, gas)	: No data available	
Explosion limits	: No data available	
Explosive properties	: No data available	
Oxidizing properties	: No data available	
Vapor pressure	: 103 psig (@ 21 °C)	
Relative density	: No data available	
Relative vapor density at 20 °C	: No data available	
Specific gravity / density	: 0.647 g/ml (@ -20 °C)	
Molecular mass	: 40.06 g/mol	
Solubility	: No data available	
Log Pow	: No data available	
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	
Viscosity	: No data available	
Viscosity, kinematic	: No data available	
Viscosity, dynamic	: No data available	
9.2. Other information		
Refractive index	: 1.4137 (@ -30 °C)	

SECTION	DN 10: Stability and reactivity
10.1.	Reactivity
No additio	onal information available
10.2.	Chemical stability
The prod	uct is stable at normal handling and storage conditions.
10.3.	Possibility of hazardous reactions
No additio	onal information available
10.4.	Conditions to avoid
Protect fr	om sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.
10.5.	Incompatible materials
Strong ba	ises. Strong oxidizing agents.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitization Germ cell mutagenicity Carcinogenicity Reproductive toxicity	 Causes skin irritation. Causes serious eye irritation. Not classified Not classified Not classified Not classified Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation Symptoms/injuries after skin contact Symptoms/injuries after eye contact	 May cause drowsiness or dizziness. Contact with the liquid the may cause cold burns/frostbite. Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

SECTION 12: Ecological in	formation	
12.1. Toxicity		
No additional information available		
12.2. Persistence and degrad	ability	
No additional information available		
12.3. Bioaccumulative potent	ial	
No additional information available		
12.4. Mobility in soil		
No additional information available		
12.5. Other adverse effects		
No additional information available		

SECTION 13: Disposal considera	ations
13.1. Waste treatment methods	
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Recycle the material as far as possible.
SECTION 14: Transport informat	ion
Department of Transportation (DOT)	

In accordance with DOT	
Transport document description	: UN2200 Propadiene, stabilized, 2.1
UN-No.(DOT)	: UN2200
Proper Shipping Name (DOT)	: Propadiene, stabilized
Transport hazard class(es) (DOT)	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT)	: 2.1 - Flammable gas
	2
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304
DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315
DOT Packaging Exceptions (49 CFR 173.xxx)	: None
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: Forbidden
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Emergency Response Guide (ERG) Number	: 116P
Other information	: No supplementary information available.
TDG No additional information available	
Transport by sea	
UN-No. (IMDG)	: 2200
Proper Shipping Name (IMDG)	: PROPADIENE, STABILIZED
Class (IMDG)	: 2 - Gases
Air transport	
UN-No. (IATA)	: 2200
Proper Shipping Name (IATA)	: Propadiene, stabilized
Class (IATA)	: 2

15.1. US Federal regulations	
Allene (463-49-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Allene (463-49-0) Listed on the Canadian DSL (Domestic Sustances List)

EU-Regulations No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations

Allene (463-49-0)		
Listed on the AICS (Australian Inventory of Chemical Substances)		
Listed on the Japanese ISHL (Industrial Safety and Health Law		
Listed on the Korean ECL (Existing Chemicals List)		
Listed on NZIoC (New Zealand Inventory of Chemicals)		
Listed on PICCS (Philippines Inventory of Chemicals and Chen	ical Substances)	
Listed on INSQ (Mexican national Inventory of Chemical Subst	nces)	

15.3. US State regulations	
Allene (463-49-0)	
State or local regulations	U.S New Jersey - Right to Know Hazardous Substance List

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Gas 1	Flammable gases Category 1
Liquefied gas	Gases under pressure Liquefied gas
Simple Asphy	Simple Asphyxiant
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H380	May displace oxygen and cause rapid suffocation

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.