

2-Methylprop-1-ene Safety Data Sheet 1300106 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 10/03/2016 Version: 1.0

SECTION 1: Identification		
1.1. Identification		
Product form	: Substance	
Substance name	: 2-Methylprop-1-ene	
CAS No	: 115-11-7	
Product code	: 1300-1-06	
Formula	: C4H8	
Synonyms	: Isobutylene; Isobutene	
Other means of identification	: MFCD0008898	
1.2. Relevant identified uses of the su	ubstance or mixture and uses advised against	
Use of the substance/mixture	: Laboratory chemicals	
	Manufacture of substances Scientific research and development	
1.3. Details of the supplier of the safe	ty data sheet	
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of America T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlabs.c		
1.4. Emergency telephone number		
Emergency number	: (844) 523-4086 (3E Company - Account 10069)	
SECTION 2: Hazard(s) identificatio	on	
2.1. Classification of the substance or	r mixture	
Classification (GHS-US)		
······································		
Liquefied gas H280 - Contains gas under STOT SE 3 H336 - May cause drowsine STOT SE 3 H335 - May cause respirator	pressure; may explode if heated ess or dizziness	
Liquefied gas H280 - Contains gas under p STOT SE 3 H336 - May cause drowsine STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16	pressure; may explode if heated ess or dizziness	
Liquefied gas H280 - Contains gas under p STOT SE 3 H336 - May cause drowsine STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements	pressure; may explode if heated ess or dizziness	
Liquefied gas H280 - Contains gas under p STOT SE 3 H336 - May cause drowsine STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	ressure; may explode if heated ess or dizziness any irritation	
Liquefied gas H280 - Contains gas under p STOT SE 3 H336 - May cause drowsine STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	 Pressure; may explode if heated ess or dizziness or dizziness or y irritation Constant Constant Constant Constant Constant 	
Liquefied gas H280 - Contains gas under p STOT SE 3 H336 - May cause drowsine STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	 Pressure; may explode if heated ess or dizziness or dizziness or y irritation 	
Liquefied gas H280 - Contains gas under p STOT SE 3 H336 - May cause drowsine STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16	 Pressure; may explode if heated ess or dizziness or dizziness or y irritation Constant Constant Constant Constant Constant Constant Constant Constant Constant Constant Constant Constant	
Liquefied gas H280 - Contains gas under p STOT SE 3 H336 - May cause drowsine STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	 Pressure; may explode if heated ess or dizziness or dizziness or dizziness or y irritation : Operating the set of the set	

2-Methylprop-1-ene Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. 77, No. 58 / Monday, N	larch 26, 2012 / Rules and Regulations		
2.3. Other hazards			
Other hazards not contributing to the classification	: May cause frostbite.		
2.4. Unknown acute toxicity (GHS US)			
Not applicable			
SECTION 3: Composition/information	on ingredients		
3.1. Substance	-		
Substance type	: Mono-constituent		. <u>.</u>
Name	Product identifier	%	Classification (GHS-US)
2-Methylprop-1-ene (Main constituent)	(CAS No) 115-11-7	<= 100	Simple Asphy, H380 Flam. Gas 1, H220 Liquefied gas, H280 STOT SE 3, H336 STOT SE 3, H335
Full text of H-phrases: see section 16			
3.2. Mixture			
Not applicable			
SECTION 4: First aid measures			
4.1. Description of first aid measures			
u u u u u u u u u u u u u u u u u u u	: In case of accident or if you feel unwe where possible). Move the affected pe	ersonnel away from the	e contaminated area.
	: Remove person to fresh air and keep respiration. Get immediate medical ac	lvice/attention.	
	: Thaw frosted parts with lukewarm wat advice/attention.		
First-aid measures after eye contact	: Remove contact lenses, if present and thoroughly with water for at least 15 m		
First-aid measures after ingestion	: Due to its physical form, exposure to t give anything by mouth to an unconsc advice/attention.		, .
4.2. Most important symptoms and effects	s, both acute and delayed		
Symptoms/injuries	: The most important known symptoms 2.2) and/or in section 11.	and effects are descri	bed in the labelling (see section
	: May cause drowsiness or dizziness.		
Symptoms/injuries after skin contact	: Contact with the liquid the may cause		
	: Direct contact with the liquefied gas m to frostbite from rapid liquid evaporation	on.	possibly permanent eye injury due
4.3. Indication of any immediate medical a	attention and special treatment neede	d	
No additional information available			
SECTION 5: Firefighting measures			
5.1. Extinguishing media			
Suitable extinguishing media	: Alcohol resistant foam. Carbon dioxide appropriate for surrounding fire.	e. Dry powder. Water	spray. Use extinguishing media
5.2. Special hazards arising from the subs	stance or mixture		
Fire hazard	: Thermal decomposition generates: Ca		
Explosion hazard	: Contains gas under pressure; may ex exposed containers. May form flamma		
5.3. Advice for firefighters			
Firefighting instructions	: In case of fire: Evacuate area. Fight fi	re remotely due to the	risk of explosion.
Protection during firefighting	: Wear gas tight chemically protective of apparatus. For further information refe		
SECTION 6: Accidental release measure			
6.1. Personal precautions, protective equ			
General measures	: Evacuate unnecessary personnel. En reducing oxygen available for breathir		

2-Methylprop-1-ene Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / N

N/-

y, March 26, 2012 / Rules and Regulations
: Only qualified personnel equipped with suitable protective equipment may intervene.
: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.
rities if product enters sewers or public waters.
nent and cleaning up
: Stop leak if safe to do so.
: Ventilate area.
: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".
Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care because residual vapors are flammable. Close valve after each use and when empty.
Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.
: Securely chain cylinders when in use and protect against physical damage.
: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
ling any incompatibilities
: Comply with applicable regulations.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use. Keep away from ignition sources.
: Refer to Section 10 on Incompatible Materials.
: Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

2-Methylprop-1-ene (115-11-7)		
ACGIH	ACGIH TWA (ppm)	250 ppm
ACGIH	Remark (ACGIH)	URT irr; body weight eff

8.2. Exposure controls	
Appropriate engineering controls	Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Thermal hazard protection	: Cold insulating gloves.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. 77, No. 58 / Monda	ay, March 26, 2012 / Rules and Regulations
SECTION 9: Physical and chemica	I properties
9.1. Information on basic physical and	I chemical properties
Physical state	: Gas
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: -140 °C
Freezing point	: No data available
Boiling point	: -6.9 °C
Critical temperature	: 144.7 °C
Critical pressure	: 580.2 psia
Flash point	: -80 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: 39 psia (@ 21.1 °C)
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.5879 g/ml (@ 25 °C)
Molecular mass	: 56.11 g/mol
Solubility	: Water: 263 mg/l (at 20 °C)
Log Pow	: 2.11 (at 23 °C)
Auto-ignition temperature	: 465 °C
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
9.2. Other information	
Refractive index	: 1.3926 (@ -25 °C)
SECTION 10: Stability and reactivit	ty
10.1. Reactivity	
No additional information available	
10.2. Chemical stability	
The product is stable at normal handling and s	storage conditions.
10.3. Possibility of hazardous reactions	
No additional information available	·
10.4. Conditions to avoid Protect from suplight. Do not expose to tempo	ratures exceeding 50 % Keep away from best enarge and flame
	ratures exceeding 50 °C. Keep away from heat, sparks and flame.
10.5. Incompatible materials	
Halogens. Strong acids. Strong oxidizing agen	its.
10.6. Hazardous decomposition produc	ts
Under normal conditions of storage and use, h fire, see Section 5.	nazardous decomposition products should not be produced. Hazardous decomposition products in case of
· · · · · · · · · · · · · · · · · · ·	ation
SECTION 11: Toxicological inform	
11.1. Information on toxicological effec	ts
Acute toxicity	: Not classified

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-Methylprop-1-ene (115-11-7)	
LC50 inhalation rat (mg/l)	620 mg/l/4h
ATE US (vapors)	620.000 mg/l/4h
ATE US (dust, mist)	620.000 mg/l/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
2-Methylprop-1-ene (115-11-7)	
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness. May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Contact with the liquid the may cause cold burns/frostbite.
Symptoms/injuries after eye contact	: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

12.1.	Toxicity	
No addit	ional information available	
12.2.	Persistence and degradability	
No addit	ional information available	
12.3.	Bioaccumulative potential	
2-Meth	ylprop-1-ene (115-11-7)	
Log Po	W	2.11 (at 23 °C)
Log Po 12.4.	w Mobility in soil	2.11 (at 23 °C)
12.4.		2.11 (at 23 °C)
12.4.	Mobility in soil	2.11 (at 23 °C)

SECTION 13: Disposal consider	ations
13.1. Waste treatment methods	
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Recycle the material as far as possible.
SECTION 14: Transport informa	tion
Department of Transportation (DOT)	

: UN1055 Isobutylene (see also Petroleum gases, liquefied), 2.1
: UN1055
: Isobutylene
see also Petroleum gases, liquefied
: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT)	: 2.1 - Flammable gas
DOT Backaging Non Bulk (40 CEP 172 yyy)	: 304
DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315
DOT Special Provisions (49 CFR 172.102)	: 19 - For domestic transportation only, the identification number UN1075 may be used in place
	 of the identification number specified in column (4) of the 172.101 table. The identification number used must be consistent on package markings, shipping papers and emergency response information. T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: Forbidden
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a
	passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Emergency Response Guide (ERG) Number	: 115 (UN1055)
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 1055
Proper Shipping Name (IMDG)	: ISOBUTYLENE
Class (IMDG)	: 2 - Gases
Air transport	
UN-No. (IATA)	: 1055
Proper Shipping Name (IATA)	: Isobutylene
Class (IATA)	: 2
SECTION 15: Regulatory information	
15.1. US Federal regulations	
2-Methylprop-1-ene (115-11-7)	
Listed on the United States TSCA (Toxic Subst	ances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

2-Methylprop-1-ene (115-11-7)

Listed on the Canadian DSL (Domestic Sustances List)

EU-Regulations No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

tional regulations
-Methylprop-1-ene (115-11-7)
isted on the AICS (Australian Inventory of Chemical Substances)
isted on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
isted on the Japanese ENCS (Existing & New Chemical Substances) inventory
isted on the Korean ECL (Existing Chemicals List)
isted on NZIoC (New Zealand Inventory of Chemicals)
isted on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
isted on INSQ (Mexican national Inventory of Chemical Substances)

15.3. US State regulations		
2-Methylprop-1-ene (115-11-7)		
State or local regulations	U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List	

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

i un tez	a or ri-prilases.	
	Flam. Gas 1	Flammable gases Category 1
	Liquefied gas	Gases under pressure Liquefied gas
	Simple Asphy	Simple Asphyxiant
	STOT SE 3	Specific target organ toxicity (single exposure) Category 3
	STOT SE 3	Specific target organ toxicity (single exposure) Category 3
	H220	Extremely flammable gas
	H280	Contains gas under pressure; may explode if heated
	H335	May cause respiratory irritation
	H336	May cause drowsiness or dizziness
	H380	May displace oxygen and cause rapid suffocation
	fire hazard reactivity	 injury even if no treatment is given. 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily. 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS	II Rating	
Health		: 1 Slight Hazard - Irritation or minor reversible injury possible
		* - Chronic (long-term) health effects may result from repeated overexposure
		: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)
Physic	al	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.