

Safety Data Sheet 1300123

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification

1.1. Identification

Product form : Substance
Trade name : Methylallene
CAS No : 590-19-2
Product code : 1300-1-23
Formula : C4H6
Synonyms : Methylallene
Other means of identification : MFCD00039911

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

1.3. Details of the supplier of the safety data sheet

SynQuest Laboratories, Inc.

P.O. Box 309

Alachua, FL 32615 - United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Gas 1 H220 - Extremely flammable gas

Liquefied gas H280 - Contains gas under pressure; may explode if heated

Acute Tox. 4 (Inhalation:gas)
Skin Irrit. 2
Eye Irrit. 2A
STOT SE 3

H332 - Harmful if inhaled
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS02

2 GHS04

GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H220 - Extremely flammable gas

H280 - Contains gas under pressure; may explode if heated

H315 - Causes skin irritation H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

Precautionary statements (GHS-US) : P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P264 - Wash skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P302+P352 - If on skin: Wash with plenty of soap and water

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER or doctor/physician if you feel unwell

05/01/2018 EN (English US) SDS ID: 1300123 Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P321 - Specific treatment (see supplemental first aid instructions on this label)

P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse

P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely

P381 - Eliminate all ignition sources if safe to do so

P403 - Store in a well-ventilated place

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P410+P403 - Protect from sunlight. Store in a well-ventilated place P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards

Other hazards not contributing to the classification

: In use may form flammable/explosive vapor-air mixture. May cause frostbite.

Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

Substance

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
1,2-Butadiene (Main constituent)	(CAS No) 590-19-2	<= 100	Flam. Gas 1, H220 Liquefied gas, H280 Acute Tox. 4 (Inhalation:gas), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3. H335

Full text of H-phrases: see section 16

Mixture 3.2.

Not applicable

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label

where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial

respiration. Get immediate medical advice/attention.

First-aid measures after skin contact Thaw frosted parts with lukewarm water. Do no rub affected area. Get immediate medical

advice/attention.

First-aid measures after eye contact Remove contact lenses, if present and easy to do. Continue rinsing. Immediately flush eyes

thoroughly with water for at least 15 minutes. Get immediate medical advice/attention.

First-aid measures after ingestion : Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never

give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical

advice/attention.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries The most important known symptoms and effects are described in the labelling (see section

2.2) and/or in section 11.

Symptoms/injuries after inhalation : May cause drowsiness or dizziness.

Symptoms/injuries after skin contact Contact with the liquid the may cause cold burns/frostbite.

Symptoms/injuries after eye contact Direct contact with the liquefied gas may cause severe and possibly permanent eve injury due

to frostbite from rapid liquid evaporation.

Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

Extinguishing media 5.1.

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Special hazards arising from the substance or mixture

Fire hazard : Thermal decomposition generates: Carbon oxides.

05/01/2018 EN (English US) SDS ID: 1300123 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

: Contains gas under pressure; may explode if heated. Use water spray or fog for cooling Explosion hazard exposed containers. May form flammable/explosive vapor-air mixture.

Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

: Do not attempt to take action without suitable protective equipment. For further information Protective equipment

refer to section 8: "Exposure controls/personal protection".

: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground **Emergency procedures**

level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.

Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so.

Methods for cleaning up Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13: "Disposal considerations".

Reference to other sections

No additional information available

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care because residual vapors are flammable. Close valve after each use and when empty.

Precautions for safe handling Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal

protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Safe handling of the gas receptacle Securely chain cylinders when in use and protect against physical damage.

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or Hygiene measures

smoke when using this product. Always wash hands after handling the product.

Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed

when not in use. Keep away from ignition sources.

Incompatible materials : Refer to Section 10 on Incompatible Materials.

Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

Control parameters

No additional information available

Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers

should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when

asphyxiating gases may be released.

SDS ID: 1300123 05/01/2018 EN (English US) 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hand protection : Protective gloves. 29 CFR 1910.138: Hand Protection.

Eye protection : Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory

Protection.

Thermal hazard protection : Cold insulating gloves.

Other information : Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available

Melting point : -136 °C

Freezing point : No data available

Boiling point : 10.8 °C (@ 760 mm Hg)

Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available : No data available Flammability (solid, gas) **Explosion limits** : No data available : No data available Explosive properties : No data available Oxidizing properties Vapor pressure : 6.5 psig (@ 20 °C) Relative density : No data available Relative vapor density at 20 °C : No data available Specific gravity / density 0.676 g/ml (@ 0 °C) Molecular mass : 54.0904 g/mol Solubility : No data available Log Pow No data available Auto-ignition temperature No data available Decomposition temperature : No data available Viscosity No data available

9.2. Other information

Refractive index : 1.4205 (@ 1 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

Viscosity, kinematic

Viscosity, dynamic

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

: No data available

: No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

05/01/2018 EN (English US) SDS ID: 1300123 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:gas: Harmful if inhaled.

Methylallene (590-19-2)	
ATE US (gases)	4500.000 ppmV/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Contact with the liquid the may cause cold burns/frostbite.
Symptoms/injuries after eye contact	: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Waste disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1010 Butadienes, stabilized (containing more than 40% butadienes), 2.1

UN-No.(DOT) : UN1010

Proper Shipping Name (DOT) : Butadienes, stabilized

containing more than 40% butadienes

Transport hazard class(es) (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

05/01/2018 EN (English US) SDS ID: 1300123 5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : 304 DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

DOT Special Provisions (49 CFR 172.102) : T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the

applicable liquefied compressed gases are authorized to be transported in portable tanks in

accordance with the requirements of 173.313 of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Other information : No supplementary information available.

TDG

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Methylallene (590-19-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Methylallene (590-19-2)

Listed on the Canadian DSL (Domestic Sustances List)

EU-Regulations

No additional information available

National regulations

Methylallene (590-19-2)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the Korean ECL (Existing Chemicals List)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

05/01/2018 EN (English US) SDS ID: 1300123 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

Acute Tox. 4 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 4
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Gas 1	Flammable gases Category 1
Liquefied gas	Gases under pressure Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation

NFPA health hazard : 2 - Intense or continued exposure could cause temporary

incapacitation or possible residual injury unless prompt


medical attention is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure

and temperature, or is readily dispersed in air and will burn

: 0 - Normally stable, even under fire exposure conditions, NFPA reactivity

and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below Flammability

73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)

: 3 Serious Hazard - Materials that may form explosive mixtures with water and are capable of **Physical** detonation or explosive reaction in the presence of a strong initiating source. Materials may

polymerize, decompose, self-react, or undergo other chemical change at normal temperature

and pressure with moderate risk of explosion

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

SDS ID: 1300123 05/01/2018 EN (English US) 7/7