

Safety Data Sheet 1300126

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 02/07/2019 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Substance
Substance name : 3-Methyl-1-butene

CAS No : 563-45-1
Product code : 1300-1-26
Formula : C5H10

Synonyms : 3-Methylbut-1-ene; Isoamylene; Isopentene; Isopropylethylene

Other means of identification : MFCD00008937

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

1.3. Details of the supplier of the safety data sheet

SynQuest Laboratories. Inc.

P.O. Box 309

Alachua, FL 32615 - United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 1 H224 - Extremely flammable liquid and vapour

Skin Irrit. 2 H315 - Causes skin irritation
Eye Irrit. 2A H319 - Causes serious eye irritation
STOT SE 3 H335 - May cause respiratory irritation

Asp. Tox. 1 H304 - May be fatal if swallowed and enters airways

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS07



GHS08

GHS02

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H224 - Extremely flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H319 - Causes serious eye irritation H335 - May cause respiratory irritation

Precautionary statements (GHS-US) : P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ventilating/lighting equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge P261 - Avoid breathing fumes, gas, mist, spray, vapors P264 - Wash skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301+P310 - If swallowed: Immediately call a poison center/doctor/...

P302+P352 - If on skin: Wash with plenty of soap and water

02/07/2019 EN (English US) SDS ID: 1300126 Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER or doctor/physician if you feel unwell

P321 - Specific treatment (see supplemental first aid instructions on this label)

P331 - Do NOT induce vomiting

P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention

P362+P364 - Take off contaminated clothing and wash it before reuse

P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to an approved waste disposal plant

Other hazards 2.3

No additional information available

Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
3-Methyl-1-butene (Main constituent)	(CAS No) 563-45-1	<= 100	Flam. Liq. 1, H224 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Asp. Tox. 1, H304

Full text of H-phrases: see section 16

3.2. **Mixture**

Not applicable

SECTION 4: First aid measures

Description of first aid measures

: In case of accident or if you feel unwell, seek medical advice immediately (show the label First-aid measures general where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial

respiration. Get immediate medical advice/attention.

First-aid measures after skin contact : Wash with plenty of soap and water. Get immediate medical advice/attention.

Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if First-aid measures after eye contact present and easy to do. Continue rinsing. Get immediate medical advice/attention.

: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse First-aid measures after ingestion mouth out with water. Get immediate medical advice/attention.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries : The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Thermal decomposition generates: Carbon oxides.

Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed Explosion hazard

containers. May form flammable/explosive vapor-air mixture.

Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

02/07/2019 EN (English US) SDS ID: 1300126 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting

: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures

: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.

6.1.1. For non-emergency personnel

Emergency procedures

: Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures

Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.

Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

Methods and material for containment and cleaning up

For containment

: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

Methods for cleaning up

: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.

Other information

For disposal of solid materials or residues refer to section 13: "Disposal considerations".

Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care because residual vapors are flammable. Close valve after each use and when empty.

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.

Safe handling of the gas receptacle

Securely chain cylinders when in use and protect against physical damage.

Hygiene measures

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Conditions for safe storage, including any incompatibilities

Technical measures

Incompatible materials

: Comply with applicable regulations.

Storage conditions

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use. Keep away from ignition sources.

Refer to Section 10 on Incompatible Materials.

Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

Control parameters

No additional information available

Exposure controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released.

Protective gloves. 29 CFR 1910.138: Hand Protection. Hand protection

Eye protection Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.

: Wear suitable protective clothing. Skin and body protection

02/07/2019 EN (English US) SDS ID: 1300126 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection : In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory

Protection.

Other information : Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : No data available Odor : No data available Odor threshold : No data available pH : No data available Melting point : -168.5 (≥ -168) °C Freezing point : No data available

Boiling point : $20 \, ^{\circ}\text{C}$ Flash point : $-57 \, ^{\circ}\text{C}$

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available **Explosion limits** : No data available : No data available Explosive properties Oxidizing properties : No data available : 773.9 mm Hg (@ 20 °C) Vapor pressure Relative density No data available Relative vapor density at 20 °C : No data available

Specific gravity / density : 0.627 g/ml (@ 25 °C)

Molecular mass : 70.13 g/mol

Solubility : No data available

Log Pow : No data available

Auto-ignition temperature : 365 °C

Decomposition temperature : No data available Viscosity : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

02/07/2019 EN (English US) SDS ID: 1300126 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity : Not classified

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard

: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Waste disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN2561 3-Methyl-1-butene, 3, I

UN-No.(DOT) : UN2561

Proper Shipping Name (DOT) : 3-Methyl-1-butene

Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : I - Great Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 201 DOT Packaging Bulk (49 CFR 173.xxx) : 243

02/07/2019 EN (English US) SDS ID: 1300126 5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102) : T11 -

: T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C

(59 F) and 50 C (122 F), respectively.

DOT Packaging Exceptions (49 CFR 173.xxx) : None DOT Quantity Limitations Passenger aircraft/rail : 1 L (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

DOT Vessel Stowage Location : E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

TDG

No additional information available

Transport by sea

UN-No. (IMDG) : 2561

Proper Shipping Name (IMDG) : 3-METHYL-1-BUTENE Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : I - substances presenting high danger

Air transport

UN-No. (IATA) : 2561

Proper Shipping Name (IATA) : 3-Methyl-1-butene
Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : I - Great Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

3-Methyl-1-butene (563-45-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

3-Methyl-1-butene (563-45-1)

Listed on the Canadian DSL (Domestic Sustances List)

EU-Regulations

No additional information available

02/07/2019 EN (English US) SDS ID: 1300126 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations

3-Methyl-1-butene (563-45-1)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the Korean ECL (Existing Chemicals List)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on INSQ (Mexican national Inventory of Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

3-Methyl-1-butene (563-45-1)		
State or local regulations	U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List	

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

ox of 11 philades.				
	Asp. Tox. 1	Aspiration hazard Category 1		
	Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A		
	Flam. Liq. 1	Flammable liquids Category 1		
	Skin Irrit. 2	Skin corrosion/irritation Category 2		
	STOT SE 3	Specific target organ toxicity (single exposure) Category 3		
	H224	Extremely flammable liquid and vapor		
	H304	May be fatal if swallowed and enters airways		
	H315	Causes skin irritation		
	H319	Causes serious eye irritation		
	H335	May cause respiratory irritation		

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual

injury even if no treatment is given.


NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure

and temperature, or is readily dispersed in air and will burn

readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below

73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

02/07/2019 EN (English US) SDS ID: 1300126 7/7