

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations SDS ID: 1300307

Issue date: 11/23/2015 Revision date: 8/31/2022 Version: 1.1

### **SECTION 1: Identification**

#### 1.1. Identification

Product form : Substance

Substance name : 1,1,3,3,3-Pentafluoropropene

CAS-No. : 690-27-7
Product code : 1300-3-07
Formula : C3HF5

Synonyms : 2H-Pentafluoropropene Other means of identification : MFCD00042591

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

### 1.3. Supplier

SynQuest Laboratories, Inc.

P.O. Box 309

Alachua, FL 32615 - United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

#### 1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

### **SECTION 2: Hazard(s) identification**

### 2.1. Classification of the substance or mixture

### **GHS US classification**

Flammable gases Category 1 H220 Extremely flammable gas

Gases under pressure Liquefied gas H280 Contains gas under pressure; may explode if heated

Skin corrosion/irritation Category 2

H315

Causes skin irritation

Causes skin irritation

Causes skin irritation

Causes serious eye irritation

Causes serious eye irritation

Causes serious eye irritation

H319

Causes serious eye irritation

May cause drowsiness or dizziness

Specific target organ toxicity – Single exposure, Category 3, H335

May cause respiratory irritation

Respiratory tract irritation

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

#### **GHS US labeling**

Hazard pictograms (GHS US)



Danger





Signal word (GHS US)

Hazard statements (GHS US) : H220 - Extremely flammable gas

H280 - Contains gas under pressure; may explode if heated

H315 - Causes skin irritation

### Safety Data Sheet

Precautionary statements (GHS US)

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

smoking.

P261 - Avoid breathing fumes, gas, mist, spray, vapors.

P264 - Wash skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 - If on skin: Wash with plenty of soap and water

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell

P321 - Specific treatment (see supplemental first aid instructions on this label)

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 - Eliminate all ignition sources if safe to do so.

P403 - Store in a well-ventilated place.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

P501 - Dispose of contents/container to an approved waste disposal plant

#### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : May cause frostbite.

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### **SECTION 3: Composition/Information on ingredients**

### 3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%	GHS US classification
1,1,3,3,3-Pentafluoropropene (Main constituent)	CAS-No.: 690-27-7	≤ 100	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

#### 3.2. Mixtures

Not applicable

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 4: First-aid measures**

### 4.1. Description of first aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label where

possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.

First-aid measures after skin contact : Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Immediately flush eyes thoroughly with water for at least 15 minutes. Get immediate medical advice/attention.

First-aid measures after ingestion : Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate

medical advice/attention.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

Symptoms/effects after inhalation : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Contact with the liquid the may cause cold burns/frostbite.

Symptoms/effects after eye contact : Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

## 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

### **SECTION 5: Fire-fighting measures**

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen fluoride.

Explosion hazard : Contains gas under pressure; may explode if heated. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.

### 6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

8/31/2022 (Revision date) EN (English US) 3/10

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground

level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of

ignition.

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so.

Methods for cleaning up : Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

#### 6.4. Reference to other sections

No additional information available

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care

because residual vapors are flammable. Close valve after each use and when empty.

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or

smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed

when not in use. Keep away from ignition sources.

Incompatible materials : Refer to Section 10 on Incompatible Materials.

Storage area : Store in dry, cool, well-ventilated area.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### 1,1,3,3,3-Pentafluoropropene (690-27-7)

No additional information available

#### 8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released. Gas detectors should be used when toxic gases may be released.

8/31/2022 (Revision date) EN (English US) 4/10

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

protective gloves. 29 CFR 1910.138: Hand Protection

#### Eye protection:

Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

#### Thermal hazard protection:

Cold insulating gloves.

#### Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Gas

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available

Melting point : -153 °C

Freezing point : No data available

Boiling point : -21 °C Flash point : No data available

Flash point Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Vapor pressure : 531 kPa (@ 7 °C) : No data available Relative vapor density at 20 °C Relative density : No data available Density : 1.336 g/ml (@ 20 °C) Molecular mass : 132.03 g/mol : No data available Solubility Partition coefficient n-octanol/water (Log Pow) : No data available : No data available Auto-ignition temperature : No data available Decomposition temperature Viscosity, kinematic : No data available Viscosity, dynamic : No data available : No data available **Explosion limits** Explosive properties : No data available

### 9.2. Other information

Oxidizing properties

No additional information available

8/31/2022 (Revision date) EN (English US) 5/10

: No data available

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

### 10.3. Possibility of hazardous reactions

May polymerize.

### 10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

### 10.5. Incompatible materials

Alkali metals. Finely divided metals (Al, Mg, Zn). Oxidizing agents. Peroxides. Strong acids.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2)

and/or in section 11.

Symptoms/effects after inhalation : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Contact with the liquid the may cause cold burns/frostbite.

Symptoms/effects after eye contact : Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to

frostbite from rapid liquid evaporation.

### **SECTION 12: Ecological information**

### 12.1. Toxicity

No additional information available

### 12.2. Persistence and degradability

No additional information available

8/31/2022 (Revision date) EN (English US) 6/10

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

### **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

### **SECTION 14: Transport information**

### 14.1. UN number

DOT NA No : UN3161 UN-No. (TDG) : Not applicable UN-No. (IMDG) : 3161

UN-No. (IATA) : 3161

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Liquefied gas, flammable, n.o.s.

Proper Shipping Name (TDG) : Not applicable

Proper Shipping Name (IMDG) : LIQUEFIED GAS, FLAMMABLE, N.O.S.

Proper Shipping Name (IATA) : Liquefied gas, flammable, n.o.s.

### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : 2.1 Hazard labels (DOT) : 2.1



TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : 2.1 Hazard labels (IMDG) : 2.1



### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### IATA

Transport hazard class(es) (IATA) : 2.1 Hazard labels (IATA) : 2.1



### 14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (TDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

DOT

UN-No.(DOT) : UN3161

DOT Special Provisions (49 CFR 172.102) : T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the

applicable liquefied compressed gases are authorized to be transported in portable tanks in

accordance with the requirements of 173.313 of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : 304

DOT Packaging Bulk (49 CFR 173.xxx) : 314, 315

DOT Quantity Limitations Passenger aircraft/rail (49 : Forbidden

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)
DOT Vessel Stowage Location

CFR 175.75)

: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger

vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

TDG

Emergency Response Guide (ERG) Number : 115

**IMDG** 

Special provision (IMDG): 274Limited quantities (IMDG): 0Excepted quantities (IMDG): E0Packing instructions (IMDG): P200Tank instructions (IMDG): T50

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

: 150 kg

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : D

IATA

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Forbidden
PCA limited quantity max net quantity (IATA) : Forbidden
PCA packing instructions (IATA) : Forbidden
PCA max net quantity (IATA) : Forbidden
CAO packing instructions (IATA) : 200

8/31/2022 (Revision date) EN (English US) 8/10

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CAO max net quantity (IATA) : 150kg Special provision (IATA) : A1, A807 ERG code (IATA) : 10L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

#### 1,1,3,3,3-Pentafluoropropene (690-27-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### 15.2. International regulations

#### CANADA

#### 1,1,3,3,3-Pentafluoropropene (690-27-7)

Listed on the Canadian NDSL (Non-Domestic Substances List)

#### **EU-Regulations**

#### 1,1,3,3,3-Pentafluoropropene (690-27-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### **National regulations**

### 1,1,3,3,3-Pentafluoropropene (690-27-7)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ISHL (Industrial Safety and Health Law)

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

### **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 08/31/2022

Full text of H-phrases		
H220	Extremely flammable gas	
H280	Contains gas under pressure; may explode if heated	
H315	Causes skin irritation	
H319	Causes serious eye irritation	
H335	May cause respiratory irritation	

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases					
H336	May cause drowsine	May cause drowsiness or dizziness			
NFPA health ha	zard	: 1 - Materials that, under emergency conditions, can cause significant irritation.			
NFPA fire hazar	d	: 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.			
NFPA reactivity		: 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.			
Hazard Rating					
Health		: 1 Slight Hazard - Irritation or minor reversible injury possible			
Flammability		: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)			
Physical		: 3 Serious Hazard - Materials that may form explosive mixtures with water and are capable of detonation or explosive reaction in the presence of a strong initiating source. Materials may polymerize, decompose, self-react, or undergo other chemical change at normal temperature and pressure with moderate risk of explosion			

Safety Data Sheet (SDS), USA

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.