

Safety Data Sheet 1300309 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Version: 1.0

Date of issue: 06/13/2016

1.1. Identification		
	. Cultateres	
Product form	: Substance	
Substance name	: Allyl fluoride	
CAS No	: 818-92-8	
Product code	: 1300-3-09	
Formula	: C3H5F	
Synonyms	: 3-Fluoro-1-propene; 3-Fluoropropylene	
Other means of identification	: MFCD00069109	
1.2. Relevant identified uses of the subs	stance or mixture and uses advised against	
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development	
1.3. Details of the supplier of the safety of	data sheet	
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of America T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com	<u>n</u>	
1.4. Emergency telephone number		
Emergency number	: (844) 523-4086 (3E Company - Account 10069)	
SECTION 2: Hazard(s) identification		
2.1. Classification of the substance or m	nxture	
	essure; may explode if heated	
Skin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eye irritSTOT SE 3H336 - May cause drowsinessSTOT SE 3H335 - May cause respiratory i	tation or dizziness	
Skin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eye irritSTOT SE 3H336 - May cause drowsinessSTOT SE 3H335 - May cause respiratory i	tation or dizziness	
Skin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eye irritSTOT SE 3H336 - May cause drowsinessSTOT SE 3H335 - May cause respiratory iFull text of H-phrases: see section 16	tation or dizziness	
Skin Irrit. 2       H315 - Causes skin irritation         Eye Irrit. 2A       H319 - Causes serious eye irrit         STOT SE 3       H336 - May cause drowsiness         STOT SE 3       H335 - May cause respiratory i         Full text of H-phrases: see section 16         2.2.       Label elements         GHS-US labeling	tation or dizziness	
Skin Irrit. 2       H315 - Causes skin irritation         Eye Irrit. 2A       H319 - Causes serious eye irrit         STOT SE 3       H336 - May cause drowsiness         STOT SE 3       H335 - May cause respiratory i         Full text of H-phrases: see section 16         2.2.       Label elements         GHS-US labeling	tation or dizziness	
Skin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eye irritSTOT SE 3H336 - May cause drowsinessSTOT SE 3H335 - May cause respiratory iFull text of H-phrases: see section 162.2.Label elements	tation or dizziness irritation	
Skin Irrit. 2       H315 - Causes skin irritation         Eye Irrit. 2A       H319 - Causes serious eye irrit         STOT SE 3       H336 - May cause drowsiness         STOT SE 3       H335 - May cause respiratory i         Full text of H-phrases: see section 16         2.2.       Label elements         GHS-US labeling         Hazard pictograms (GHS-US)	tation or dizziness irritation	
Skin Irrit. 2       H315 - Causes skin irritation         Eye Irrit. 2A       H319 - Causes serious eye irrit         STOT SE 3       H336 - May cause drowsiness         STOT SE 3       H335 - May cause respiratory i         Full text of H-phrases: see section 16         2.2.       Label elements         GHS-US labeling         Hazard pictograms (GHS-US)	tation or dizziness irritation	contact

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards	P3 <sup>-</sup> P3; P3; P3; P3; P3; P4; P4( P4; P4; P4;	ses, if present and easy to do. Con 12 - Call a POISON CENTER or d 21 - Specific treatment (see supple 32+P313 - If skin irritation occurs: 37+P313 - If eye irritation persists: 62+P364 - Take off contaminated 77 - Leaking gas fire: Do not exting 81 - Eliminate all ignition sources i 03 - Store in a well-ventilated plac 03+P233 - Store in a well-ventilated 03+P233 - Store in a well-ventilated 05 - Store locked up 10+P403 - Protect from sunlight. S 01 - Dispose of contents/container	octor/physician if you emental first aid instru Get medical advice/a : Get medical advice/a clothing and wash it b guish, unless leak car f safe to do so e ad place. Keep contair Store in a well-ventilate	actions on this label) ttention attention before reuse h be stopped safely her tightly closed ed place
Other hazards not contributing to the classification	: Ma	y cause frostbite.		
2.4. Unknown acute toxicity (GHS US)				
Not applicable				
SECTION 3: Composition/informat	ion on i	ingredients		
3.1. Substance				
Substance type	: Mo	no-constituent		
Name		Product identifier	%	Classification (GHS-US)
Allyl fluoride (Main constituent)		(CAS No) 818-92-8	<= 100	Simple Asphy, H380 Flam. Gas 2, H221 Liquefied gas, H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 STOT SE 3, H335
Full text of H-phrases: see section 16				
3.2. Mixture				
Not applicable				
SECTION 4: First aid measures				
4.1. Description of first aid measures First-aid measures general	: In c	case of accident or if you feel unwe	all, sook modical advi	co immodiately (show the label
nistaid measures general	whe	ere possible). Move the affected p	ersonnel away from the	he contaminated area.
First-aid measures after inhalation		move person to fresh air and keep piration. Get immediate medical a		thing. If not breathing, give artificial
First-aid measures after skin contact		aw frosted parts with lukewarm wa rice/attention.	ter. Do no rub affecte	d area. Get immediate medical
First-aid measures after eye contact	tho	move contact lenses, if present an roughly with water for at least 15 r	ninutes. Get immedia	te medical advice/attention.
First-aid measures after ingestion	give	e to its physical form, exposure to e anything by mouth to an uncons vice/attention.		kely. Do NOT induce vomiting. Never nouth out with water. Get medical
4.2. Most important symptoms and ef	ects, bot	h acute and delayed		
Symptoms/injuries	2.2	e most important known symptoms ) and/or in section 11.	s and effects are desc	ribed in the labelling (see section
Symptoms/injuries after inhalation		y cause drowsiness or dizziness.		
Symptoms/injuries after skin contact		ntact with the liquid the may cause		h nossibly permanent evo inium due
Symptoms/injuries after eye contact	to f	rostbite from rapid liquid evaporation	ion.	d possibly permanent eye injury due
<b>4.3.</b> Indication of any immediate medi No additional information available	cal attent	ion and special treatment neede	ed	
SECTION 5: Firefighting measures				
5.1. Extinguishing media				
Suitable extinguishing media		ohol resistant foam. Carbon dioxic propriate for surrounding fire.	de. Dry powder. Wate	r spray. Use extinguishing media

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Special hazards aris	Special hazards arising from the substance or mixture			
Fire hazard	: Thermal decomposition generates: Carbon oxides. Hydrogen fluoride.			
Explosion hazard	: Contains gas under pressure; may explode if heated. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.			
5.3. Advice for firefighter	'S			
Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.			
Protection during firefighting	: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".			

<b>SECTION 6: Accidental release meas</b>	ures			
6.1. Personal precautions, protective equ	Personal precautions, protective equipment and emergency procedures			
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.			
6.1.1. For non-emergency personnel				
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.			
6.1.2. For emergency responders				
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".			
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.			

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3.	Methods and material for containment and cleaning up		
For con	tainment	: Stop leak if safe to do so.	
Method	s for cleaning up	: Ventilate area.	
Other in	nformation	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".	
6.4	Deference to other continue		

6.4. Reference to other sections

**Environmental precautions** 

No additional information available

6.2.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care because residual vapors are flammable. Close valve after each use and when empty.
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.
Safe handling of the gas receptacle	: Securely chain cylinders when in use and protect against physical damage.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, includi	ng any incompatibilities
Technical measures	: Comply with applicable regulations.
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use. Keep away from ignition sources.
Incompatible materials	: Refer to Section 10 on Incompatible Materials.
Storage area	: Store in dry, cool, well-ventilated area.

### SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2.	Exposure controls		
Appro	priate engineering controls	Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released.	
Hand	protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.	
Eye p	rotection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.	
Skin a	and body protection	: Wear suitable protective clothing.	
Respi	ratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.	
Therm	nal hazard protection	: Cold insulating gloves.	
Other	information	: Safety shoes. 29 CFR 1910.136: Foot Protection.	

### **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and c	he	mical properties
Physical state	:	Gas
Color	:	No data available
Odor	:	No data available
Odor threshold	:	No data available
рН	:	No data available
Melting point	:	No data available
Freezing point	:	No data available
Boiling point	:	-10 °C
Flash point	:	No data available
Relative evaporation rate (butyl acetate=1)	:	No data available
Flammability (solid, gas)	:	No data available
Explosion limits	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Vapor pressure	:	No data available
Relative density	:	No data available
Relative vapor density at 20 °C	:	No data available
Molecular mass	:	60.07 g/mol
Solubility	:	No data available
Log Pow	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available

#### 9.2. **Other information**

No additional information available

SECTION 10: Stability and reactivity
10.1. Reactivity
No additional information available
10.2. Chemical stability
The product is stable at normal handling and storage conditions.
10.3. Possibility of hazardous reactions
No additional information available
10.4. Conditions to avoid
Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.
10.5. Incompatible materials
Strong acids. Strong bases. Strong oxidizing agents.

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitization Germ cell mutagenicity Carcinogenicity Reproductive toxicity Specific target organ toxicity (single exposure)	<ul> <li>Causes skin irritation.</li> <li>Causes serious eye irritation.</li> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> <li>May cause drowsiness or dizziness. May cause respiratory irritation.</li> </ul>
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation Symptoms/injuries after skin contact Symptoms/injuries after eye contact	<ul> <li>May cause drowsiness or dizziness.</li> <li>Contact with the liquid the may cause cold burns/frostbite.</li> <li>Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.</li> </ul>

SECTION 12: Ecological information
12.1. Toxicity
No additional information available
12.2. Persistence and degradability
No additional information available
12.3. Bioaccumulative potential
No additional information available
12.4. Mobility in soil
No additional information available
12.5. Other adverse effects
No additional information available

<b>SECTION 13: Disposal consider</b>	ations
13.1. Waste treatment methods	
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Recycle the material as far as possible.
SECTION 14: Transport informa	tion
Department of Transportation (DOT)	

In accordance with DOT	
Transport document description	: UN3161 Liquefied gas, flammable, n.o.s., 2.1
UN-No.(DOT)	: UN3161
Proper Shipping Name (DOT)	: Liquefied gas, flammable, n.o.s.
Transport hazard class(es) (DOT)	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT)	:	2.1 - Flammable gas
DOT Packaging Non Bulk (49 CFR 173.xxx)	:	304
DOT Packaging Bulk (49 CFR 173.xxx)	:	314;315
DOT Symbols	:	G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102)	:	T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx)	:	306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	Forbidden
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	150 kg
DOT Vessel Stowage Location	:	D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.
DOT Vessel Stowage Other	:	40 - Stow "clear of living quarters"
Other information	:	No supplementary information available.
TDG		
No additional information available		
Transport by sea		
UN-No. (IMDG)		3161
Proper Shipping Name (IMDG)		LIQUEFIED GAS, FLAMMABLE, N.O.S.
Class (IMDG)	:	2 - Gases
Air transport		
UN-No. (IATA)	:	3161
Proper Shipping Name (IATA)	:	Liquefied gas, flammable, n.o.s.
Class (IATA)	:	2

### SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Allyl fluoride CAS No 818-92-8 100%						
		CAS No 818-92-8	100%			

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

### 15.2. International regulations

#### **CANADA**

No additional information available

#### **EU-Regulations**

No additional information available

#### **National regulations**

No additional information available

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 16: Other information**

	Eye Irrit. 2A		Serious eye damage/eye irritation Category 2A	
	Flam. Gas 2		Flammable gases Category 2	
	Liquefied gas		Gases under pressure Liquefied gas	
	Simple Asphy		Simple Asphyxiant	
	Skin Irrit. 2		Skin corrosion/irritation Category 2	
	STOT SE 3		Specific target organ toxicity (single exposure) Category 3	
	STOT SE 3		Specific target organ toxicity (single exposure) Category 3	
	H221		Flammable gas	
	H280		Contains gas under pressure; may explode if heated	
	H315		Causes skin irritation	
	H319		Causes serious eye irritation	
	H335		May cause respiratory irritation	
	H336		May cause drowsiness or dizziness	
	H380		May displace oxygen and cause rapid suffocation	
	health hazard fire hazard	given.	n prompt medical attention was	
		ambient conditions.		
NFPA	reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.			
HMIS I	II Rating			
Health	Health : 2 Moderate Hazard - Temporary or minor injury may		nporary or minor injury may occur	
Flamm	ability	<ul> <li>3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB &amp; IC)</li> </ul>		
Physic	al	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.		

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.