

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations SDS ID: 1300312

Issue date: 31.05.2016 Revision date: 18.12.2023 Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form : Substance

Substance name : 3,3,4,4,4-Pentafluorobutene-1

 CAS-No.
 : 374-27-6

 Product code
 : 1300-3-12

 Formula
 : C4H3F5

 Other means of identification
 : MFCD00042086

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

1.3. Supplier

SynQuest Laboratories, Inc. Inc.

P.O. Box 309

Alachua, FL, Alachua, 32615

United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable gases Category 2 H221 Flammable gas

Gases under pressure Liquefied gas H280 Contains gas under pressure; may explode if heated

Skin corrosion/irritation Category 2

H315
Causes skin irritation
Serious eye damage/eye irritation Category 2A
H319
Causes serious eye irritation
Specific target organ toxicity – Single exposure, Category 3,
H335
May cause respiratory irritation

Respiratory tract irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H221 - Flammable gas

H280 - Contains gas under pressure; may explode if heated

H315 - Causes skin irritation

Safety Data Sheet

Precautionary statements (GHS US)

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 - Avoid breathing fumes, gas, mist, spray, vapors.

P264 - Wash skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 - If on skin: Wash with plenty of soap and water

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell

P321 - Specific treatment (see supplemental first aid instructions on this label)

P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.

P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 - Eliminate all ignition sources if safe to do so.

P403 - Store in a well-ventilated place.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%	GHS US classification
3,3,4,4,4-Pentafluorobutene-1 (Main constituent)	CAS-No.: 374-27-6	≤ 100	Flam. Gas 2, H221 Press. Gas (Liq.), H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

Full text of hazard classes and H-statements: see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

18.12.2023 (Revision date) EN (English US) 2/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eve contact : Remove contact lenses, if present and easy to do. Continue rinsing. Immediately flush eyes

thoroughly with water for at least 15 minutes. Get medical advice/attention.

thoroughly with water for at least 15 minutes. Get medical advice/attention.

First-aid measures after ingestion : Due to its physical form, exposure to this chemical is not likely. Do NOT inc

: Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical

advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2)

and/or in section 11.

Symptoms/effects after inhalation : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Contact with the liquid the may cause cold burns/frostbite.

Symptoms/effects after eye contact : Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to

frostbite from rapid liquid evaporation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

5.2. Specific hazards arising from the chemical

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen fluoride.

Explosion hazard : Contains gas under pressure; may explode if heated. Use water spray or fog for cooling exposed

containers. May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting : Wear gas tight chemically protective clothing in combination with self contained breathing

apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by

reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.

18.12.2023 (Revision date) EN (English US) 3/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so.

Methods for cleaning up : Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care

because residual vapors are flammable. Close valve after each use and when empty.

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Ensure good

ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or

smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed

when not in use. Keep away from ignition sources.

Incompatible materials : Refer to Section 10 on Incompatible Materials.

Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

3,3,4,4,4-Pentafluorobutene-1 (374-27-6)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers

should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating

gases may be released.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

protective gloves. 29 CFR 1910.138: Hand Protection

Eye protection:

Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection

18.12.2023 (Revision date) EN (English US) 4/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

Personal protective equipment symbol(s):









Thermal hazard protection:

Cold insulating gloves.

Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available

Boiling point : 3-6 °C

: No data available Flash point : No data available Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) No data available Vapor pressure No data available Relative vapor density at 20 °C : No data available : No data available Relative density Molecular mass : 146,06 g/mol Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic No data available **Explosion limits** No data available Explosive properties No data available Oxidizing properties No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

10.5. Incompatible materials

Alkali metals. Finely divided metals (Al, Mg, Zn). Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2)

and/or in section 11.

Symptoms/effects after inhalation : May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Contact with the liquid the may cause cold burns/frostbite.

Symptoms/effects after eye contact : Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to

frostbite from rapid liquid evaporation.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

3,3,4,4,4-Pentafluorobutene-1 (374-27-6)

Persistence and degradability

Not readily biodegradable. May cause long-term adverse effects in the environment. PBT Persistent, Bioaccumulative and Toxic.

18.12.2023 (Revision date) EN (English US) 6/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

3,3,4,4,4-Pentafluorobutene-1 (374-27-6)

Bioaccumulative potential Perfluorinated alkanes (PFAs, "forever chemicals") are long lasting, widely used chemicals that break down slowly over time. The potential hazards of PFAs are under investigation and have

not been established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods

Sewage disposal recommendations

Product/Packaging disposal recommendations

Additional information

Ecology - waste materials

- : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
- : See the EPA's Interim Guidance on PFAS Destruction and Disposal.
- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Recycle the material as far as possible.
- : This material is considered to be a "Forever chemical". Prevent any possible release to the environment. Do not discharge into drains. Take all necessary measures to prevent accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems, or emergency response.

SECTION 14: Transport information

14.1. UN number

DOT NA No : UN3161 UN-No. (TDG) : Not applicable

UN-No. (IMDG) : 3161 UN-No. (IATA) : 3161

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Liquefied gas, flammable, n.o.s.

Proper Shipping Name (TDG) : Not applicable

Proper Shipping Name (IMDG) : LIQUEFIED GAS, FLAMMABLE, N.O.S.

Proper Shipping Name (IATA) : Liquefied gas, flammable, n.o.s.

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 2.1 Hazard labels (DOT) : 2.1



TDG

Transport hazard class(es) (TDG) : Not applicable

18.12.2023 (Revision date) EN (English US) 7/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IMDG

Transport hazard class(es) (IMDG) : 2.1 Hazard labels (IMDG) : 2.1



IATA

Transport hazard class(es) (IATA) : 2.1 Hazard labels (IATA) : 2.1



14.4. Packing group

Packing group (DOT): Not applicablePacking group (TDG): Not applicablePacking group (IMDG): Not applicablePacking group (IATA): Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN3161

DOT Special Provisions (49 CFR 172.102) : T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the

applicable liquefied compressed gases are authorized to be transported in portable tanks in

accordance with the requirements of 173.313 of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : 304

DOT Packaging Bulk (49 CFR 173.xxx) : 314, 315

DOT Quantity Limitations Passenger aircraft/rail (49 : Forbidden

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel

carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger

vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

TDG

No data available

IMDG

Special provision (IMDG) : 274
Limited quantities (IMDG) : 0
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P200
Tank instructions (IMDG) : T50

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : D

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IATA

PCA Excepted quantities (IATA) : E0 PCA Limited quantities (IATA) : Forbidden PCA limited quantity max net quantity (IATA) : Forbidden PCA packing instructions (IATA) : Forbidden PCA max net quantity (IATA) : Forbidden CAO packing instructions (IATA) : 200 CAO max net quantity (IATA) : 150kg Special provision (IATA) : A1, A807 ERG code (IATA) : 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

3,3,4,4,4-Pentafluorobutene-1 CAS-No. 374-27-6 100%

15.2. International regulations

CANADA

No additional information available

EU-Regulations

3,3,4,4,4-Pentafluorobutene-1 (374-27-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

3,3,4,4,4-Pentafluorobutene-1 (374-27-6)

Listed on the Japanese ISHL (Industrial Safety and Health Law)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 18.12.2023

Full text of H-phrases	
H221	Flammable gas
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phra	ases
H335	May cause respiratory irritation

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or


permanent injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can

be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire

conditions.



Hazard Rating

: 2 Moderate Hazard - Temporary or minor injury may occur

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Flammability Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well

as liquids with flash points between 73 F and 100 F. (Classes IB IC)

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Physical

Safety Data Sheet (SDS), USA