

2-(Trifluoromethyl)propene Safety Data Sheet 1300314 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Version: 1.0

Date of issue: 09/22/2016

Product form	: Substance
Substance name	: 2-(Trifluoromethyl)propene
CAS No	: 374-00-5
Product code	: 1300-3-14
Formula	: C4H5F3
Synonyms	: 3,3,3-Trifluoro-2-methylprop-1-ene
Other means of identification	: MFCD00042093
1.2. Relevant identified uses of the	substance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the sa	afety data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of Amer T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - <u>www.synquestlal</u>	
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identifica	tion
2.1. Classification of the substance	
Simple AsphyH380 - May displace oxyFlam. Gas 2H221 - Flammable gasLiquefied gasH280 - Contains gas undSkin Irrit. 2H315 - Causes skin irritalEye Irrit. 2AH319 - Causes serious e	ye irritation
Simple AsphyH380 -May displace oxyFlam. Gas 2H221 -Flammable gasLiquefied gasH280 -Contains gas undSkin Irrit. 2H315 -Causes skin irritatEye Irrit. 2AH319 -Causes serious eSTOT SE 3H335 -May cause respirat	ler pressure; may explode if heated tion ye irritation
Flam. Gas 2H221 - Flammable gasLiquefied gasH280 - Contains gas undSkin Irrit. 2H315 - Causes skin irritatEye Irrit. 2AH319 - Causes serious e	ler pressure; may explode if heated tion ye irritation
Simple AsphyH380 - May displace oxyFlam. Gas 2H221 - Flammable gasLiquefied gasH280 - Contains gas undSkin Irrit. 2H315 - Causes skin irritatEye Irrit. 2AH319 - Causes serious eSTOT SE 3H335 - May cause respiratFull text of H-phrases: see section 16	ler pressure; may explode if heated tion ye irritation
Simple AsphyH380 -May displace oxyFlam. Gas 2H221 -Flammable gasLiquefied gasH280 -Contains gas undSkin Irrit. 2H315 -Causes skin irritatEye Irrit. 2AH319 -Causes serious eSTOT SE 3H335 -May cause respiratFull text of H-phrases: see section 162.2.Label elements	ler pressure; may explode if heated tion ye irritation
Simple Asphy Flam. Gas 2 Liquefied gas Kin Irrit. 2 STOT SE 3 Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	ler pressure; may explode if heated tion ye irritation atory irritation
Simple Asphy H380 - May displace oxy, Flam. Gas 2 H221 - Flammable gas Liquefied gas H280 - Contains gas und Skin Irrit. 2 H315 - Causes skin irrital Eye Irrit. 2A H319 - Causes serious er STOT SE 3 H335 - May cause respira Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	ler pressure; may explode if heated tion ye irritation atory irritation

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	P321 - Specific treatment (see supplemental first aid instructions on this label) P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely P381 - Eliminate all ignition sources if safe to do so P403 - Store in a well-ventilated place P403+P233 - Store in a well-ventilated place. Keep container tightly closed P405 - Store locked up P410+P403 - Protect from sunlight. Store in a well-ventilated place P501 - Dispose of contents/container to an approved waste disposal plant		ntion ention ore reuse e stopped safely tightly closed place	
2.3.	Other hazards			
	onal information available			
 2.4. Not applic 	Unknown acute toxicity (GHS US)			
	ON 3: Composition/information	on ingradiants		
3.1.	Substance	on ingredients		
Substance		Mono-constituent		
Name	- 91 -	Product identifier	%	Classification (GHS-US)
2-(Trifluo	romethyl)propene	(CAS No) 374-00-5	<= 100	Simple Asphy, H380
(Main cons	tituent)			Flam. Gas 2, H221 Liquefied gas, H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Full text o	f H-phrases: see section 16		·	
3.2.	Mixture			
Not applic				
SECTIC	ON 4: First aid measures			
	Description of first aid measures			
		In case of accident or if you feel unwell, where possible). Move the affected pers	onnel away from the	contaminated area.
	neasures after inhalation :	Remove person to fresh air and keep co respiration. Get immediate medical advice	ce/attention.	
		Wash with plenty of soap and water. Ge		
-irst-aid n	neasures after eye contact	Remove contact lenses, if present and e thoroughly with water for at least 15 min		
First-aid n	neasures after ingestion :	 thoroughly with water for at least 15 minutes. Get medical advice/attention. Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention. 		
4.2.	Most important symptoms and effects	, both acute and delayed		
Symptom		The most important known symptoms ar 2.2) and/or in section 11.	nd effects are describ	ed in the labelling (see section
	,	May cause drowsiness or dizziness.	Lathermore H and the	
	•	Contact with the liquid the may cause co		oppibly permanent ave internation
Symptom	s/injuries after eye contact :	Direct contact with the liquefied gas may to frostbite from rapid liquid evaporation.		ussibily permanent eye injury due
4.3.	Indication of any immediate medical a	ttention and special treatment needed		
	and the forward of the stand the balance			
	onal information available			
No additic	DN 5: Firefighting measures			
No additic SECTIC				
No additic SECTIC 5.1.	DN 5: Firefighting measures Extinguishing media	Alcohol resistant foam. Carbon dioxide. appropriate for surrounding fire.	Dry powder. Water sj	oray. Use extinguishing media
No additic SECTIO 5.1. Suitable e	DN 5: Firefighting measures Extinguishing media	appropriate for surrounding fire.	Dry powder. Water sj	oray. Use extinguishing media
No additic SECTIC 5.1. Suitable e	ON 5: Firefighting measures Extinguishing media extinguishing media Special hazards arising from the subs rd	appropriate for surrounding fire. tance or mixture Thermal decomposition generates: Carb	on oxides. Hydrogen	fluoride.
No additic SECTIO 5.1. Suitable e 5.2.	ON 5: Firefighting measures Extinguishing media extinguishing media Special hazards arising from the subs rd	appropriate for surrounding fire. tance or mixture	on oxides. Hydrogen ode if heated. Use wa	fluoride. ter spray or fog for cooling

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Advice for firefighter	S		
Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.		
Protection during firefighting	: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".		
SECTION 6: Accidental release measures			
1. Personal precautions, protective equipment and emergency procedures			

General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.	
6.1.1. For non-emergency personnel Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.	
6.1.2. For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.	
6.2. Environmental precautions		

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3.	Methods and material for containment and cleaning up		
For con	tainment	: Stop leak if safe to do so.	
Method	s for cleaning up	: Ventilate area.	
Other ir	formation	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".	
6.4	Reference to other sections		

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage	
SECTION 7. Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care because residual vapors are flammable. Close valve after each use and when empty.
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.
Safe handling of the gas receptacle	: Securely chain cylinders when in use and protect against physical damage.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, includi	ng any incompatibilities
Technical measures	: Comply with applicable regulations.
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C Keep container closed when not in use. Keep away from ignition sources.
Incompatible materials	: Refer to Section 10 on Incompatible Materials.
Storage area	: Store in dry, cool, well-ventilated area.

Exposure controls/p	

8.1. Control parameters

No additional information available

8.2.	Exposure controls			
Approp	riate engineering controls	should be available in the im	ne work station. Emergency eye wash fountains a imediate vicinity of any potential exposure. Syster y checked for leakage. Oxygen detectors should b released.	ms under
Hand p	rotection	: Protective gloves. 29 CFR 1	910.138: Hand Protection.	
Eye pro	otection	: Chemical goggles or safety	glasses. Face shield. 29 CFR 1910.133: Eye and	Face Protection.
12/06/20	016	EN (English US)	SDS ID: 1300314	3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Thermal hazard protection	: Cold insulating gloves.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and o	chemical properties
Physical state	: Gas
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 6 - 7 °C
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: 25 psia (@ 20 °C)
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Molecular mass	: 110.08 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
0.2 Other information	

9.2. Other information
No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

10.5. Incompatible materials

Alkali metals. Finely divided metals (Al, Mg, Zn). Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological informat	lion
11.1. Information on toxicological effects	
Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Contact with the liquid the may cause cold burns/frostbite.
Symptoms/injuries after eye contact	: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

SECTION 12: Ecological information 12.1. Toxicity No additional information available 12.2. Persistence and degradability No additional information available **Bioaccumulative potential** 12.3. No additional information available 12.4. Mobility in soil No additional information available 12.5. Other adverse effects No additional information available

SECTION 13: Disposal consideration	ons
13.1. Waste treatment methods	
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Recycle the material as far as possible.
SECTION 14: Transport information	
Department of Transportation (DOT)	
In accordance with DOT	
Transport document description	: UN3161 Liquefied gas, flammable, n.o.s., 2.1
UN-No.(DOT)	: UN3161
Proper Shipping Name (DOT)	: Liquefied gas, flammable, n.o.s.
Transport hazard class(es) (DOT)	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT)	: 2.1 - Flammable gas
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315
DOT Symbols	: G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102)	: T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: Forbidden
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 3161
Proper Shipping Name (IMDG)	: LIQUEFIED GAS, FLAMMABLE, N.O.S.
Class (IMDG)	: 2 - Gases
Air transport	
UN-No. (IATA)	: 3161
Proper Shipping Name (IATA)	: Liquefied gas, flammable, n.o.s.
Class (IATA)	: 2

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

2-(Trifluoromethyl)propene CAS No 374-00-5 100%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

2-(Trifluoromethyl)propene (374-00-5)	
Listed on the Japanese ISHL (Industrial Safety and Health Law)	

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full tex	t of H-phrases:		
	Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A	
	Flam. Gas 2	Flammable gases Category 2	
	Liquefied gas	Gases under pressure Liquefied gas	
	Simple Asphy	Simple Asphyxiant	
	Skin Irrit. 2	Skin corrosion/irritation Category 2	
	STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
	H221	Flammable gas	
	H280	Contains gas under pressure; may explode if heated	
	H315	Causes skin irritation	
	H319	Causes serious eye irritation	
	H335	May cause respiratory irritation	
	H380	May displace oxygen and cause rapid suffocation	
NFPA health hazard NFPA fire hazard		 : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given. : 3 - Liquids and solids that can be ignited under almost all ambient conditions. 	
NFPA reactivity		: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.	
HMIS I	II Rating		
Health		: 2 Moderate Hazard - Temporary or minor injury may occur	
Flammability		 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC) 	
Physical		: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.	

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.