

**1,1,2,3,3-Pentafluoropropene** Safety Data Sheet 1300332 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 09/06/2017 Version: 1.0

1.1. Identification	
Product form	: Substance
Substance name	: 1,1,2,3,3-Pentafluoropropene
CAS No	: 433-66-9
Product code	: 1300-3-32
Formula	: C3HF5
Synonyms	: 1,1,2,3,3-Pentafluoroprop-1-ene
Other means of identification	: MFCD07777211
1.2. Relevant identified uses of the	substance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the sa	afety data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of Ameri T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlab	
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identificat	tion
2.1. Classification of the substance	
Flam. Gas 2 Liquefied gas Skin Irrit. 2 H221 - Flammable gas H280 - Contains gas under H315 - Causes skin irritati	
Flam. Gas 2H221 - Flammable gasLiquefied gasH280 - Contains gas underSkin Irrit. 2H315 - Causes skin irritatiEye Irrit. 2AH319 - Causes serious eySTOT SE 3H335 - May cause respiration	er pressure; may explode if heated tion ye irritation
Flam. Gas 2H221 - Flammable gasLiquefied gasH280 - Contains gas underSkin Irrit. 2H315 - Causes skin irritatiEye Irrit. 2AH319 - Causes serious eySTOT SE 3H335 - May cause respirationFull text of H-phrases: see section 16	er pressure; may explode if heated tion ye irritation
Flam. Gas 2       H221 - Flammable gas         Liquefied gas       H280 - Contains gas under         Skin Irrit. 2       H315 - Causes skin irritati         Eye Irrit. 2A       H319 - Causes serious ey         STOT SE 3       H335 - May cause respiration         Full text of H-phrases: see section 16         2.2.       Label elements         GHS-US labeling	er pressure; may explode if heated tion ye irritation
Flam. Gas 2 H221 - Flammable gas Liquefied gas H280 - Contains gas under Skin Irrit. 2 H315 - Causes skin irritati Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respiration Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	er pressure; may explode if heated tion ye irritation atory irritation
Flam. Gas 2 H221 - Flammable gas Liquefied gas H280 - Contains gas unde Skin Irrit. 2 H315 - Causes skin irritati Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respira Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	er pressure; may explode if heated tion ye irritation atory irritation : CHS04 CHS04 CHS07 : Warning
Flam. Gas 2 H221 - Flammable gas Liquefied gas H280 - Contains gas under Skin Irrit. 2 H315 - Causes skin irritati Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respiration Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	er pressure; may explode if heated tion ye irritation atory irritation
Flam. Gas 2 H221 - Flammable gas Liquefied gas H280 - Contains gas unde Skin Irrit. 2 H315 - Causes skin irritati Eye Irrit. 2A H319 - Causes serious ey STOT SE 3 H335 - May cause respira Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	er pressure; may explode if heated tion ye irritation atory irritation

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards	P332+P313 - If skin P337+P313 - If eye P362+P364 - Take of P377 - Leaking gas P381 - Eliminate all P403 - Store in a we P403+P233 - Store i P405 - Store locked P410+P403 - Proteo	in a well-ventilated place.	dical advice/atte dical advice/atte and wash it befo nless leak can b do so Keep container a well-ventilated	ntion ention ore reuse e stopped safely <sup>•</sup> tightly closed place
Other hazards not contributing to the classification	: May cause frostbite.			
2.4. Unknown acute toxicity (GHS US)				
Not applicable				
SECTION 3: Composition/informat	tion on ingredients			
3.1. Substance				
Substance type	: Mono-constituent			
Name	Product ider	ntifier	%	Classification (GHS-US)
1,1,2,3,3-Pentafluoropropene (Main constituent)	(CAS No) 433-6	6-9	<= 100	Simple Asphy, H380 Flam. Gas 2, H221 Liquefied gas, H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Full text of H-phrases: see section 16				
B.2. Mixture				
Not applicable				
SECTION 4: First aid measures				
I.1. Description of first aid measures				
First-aid measures general	where possible). Mo	ve the affected personne	I away from the	
First-aid measures after inhalation	respiration. Get imm	ediate medical advice/att	ention.	ng. If not breathing, give artificial
First-aid measures after skin contact	advice/attention.			area. Get immediate medical
First-aid measures after eye contact	thoroughly with wate	Remove contact lenses, if present and easy to do. Continue rinsing. Immediately flush eyes thoroughly with water for at least 15 minutes. Get immediate medical advice/attention.		
First-aid measures after ingestion		: Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention.		
4.2. Most important symptoms and ef	fects, both acute and dela	ayed		
Symptoms/injuries		: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.		
Symptoms/injuries after inhalation	: May cause drowsine	: May cause drowsiness or dizziness.		
Symptoms/injuries after skin contact		: Contact with the liquid the may cause cold burns/frostbite.		
Symptoms/injuries after eye contact	: Direct contact with the to frostbite from rapi		se severe and p	ossibly permanent eye injury due
4.3. Indication of any immediate medi No additional information available	cal attention and special	treatment needed		
SECTION 5: Firefighting measures				
5.1. Extinguishing media Suitable extinguishing media			owder. Water s	pray. Use extinguishing media
	appropriate for surro			
5.2. Special hazards arising from the Fire hazard		tion generates: Carbon o	xides. Hydrogen	fluoride.
1/00/0000				

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion hazard	: Contains gas under pressure; may explode if heated. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.
5.3. Advice for firefighters	
Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
Protection during firefighting	: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures			
6.1. Personal precautions, protective equipment and emergency procedures			
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.		
6.1.1. For non-emergency personnel			
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.		
6.1.2. For emergency responders			
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".		
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.		
6.2. Environmental precautions			
Avoid release to the environment. Notify authoriti	es if product enters sewers or public waters.		
6.3. Methods and material for containme	nt and cleaning up		
For containment	: Stop leak if safe to do so.		
Methods for cleaning up	: Ventilate area.		
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".		
6.4. Reference to other sections			
No additional information available			
SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care because residual vapors are flammable. Close valve after each use and when empty.		
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.		
Safe handling of the gas receptacle	: Securely chain cylinders when in use and protect against physical damage.		
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.		
7.2. Conditions for safe storage, including	ng any incompatibilities		
Technical measures	: Comply with applicable regulations.		
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use. Keep away from ignition sources.		
Incompatible materials	: Refer to Section 10 on Incompatible Materials.		
Storage area	: Store in dry, cool, well-ventilated area.		

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. **Control parameters**

No additional information available

8.2.	Exposure controls	
Appropri	ate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released.

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Thermal hazard protection	: Cold insulating gloves.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

#### **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and	chemical properties
Physical state	: Gas
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Melting point	: -101.2 °C
Freezing point	: No data available
Boiling point	: 1-2°C
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.4607 g/ml (@ 0 °C)
Molecular mass	: 132.03 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
9.2 Other information	

#### 9.2. Other information

No additional information available

SECTION 10: Stability and reactivity			
10.1. Reactivity			
No additional information available			
10.2. Chemical stability			
The product is stable at normal handling and storage conditions.			
10.3. Possibility of hazardous reactions			
No additional information available			
10.4. Conditions to avoid			
Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.			
10.5. Incompatible materials			
Alkali metals. Finely divided metals (Al, Mg, Zn). Strong oxidizing agents.			

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>SECTION 11: Toxicological information</b>	tion
11.1. Information on toxicological effects	;
Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Contact with the liquid the may cause cold burns/frostbite.
Symptoms/injuries after eye contact	: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

#### **SECTION 12: Ecological information** 12.1. Toxicity No additional information available 12.2. Persistence and degradability No additional information available 12.3. **Bioaccumulative potential** No additional information available 12.4. Mobility in soil No additional information available Other adverse effects 12.5. No additional information available

<b>SECTION 13: Disposal consideratio</b>	ns
13.1. Waste treatment methods	
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Recycle the material as far as possible.
<b>SECTION 14: Transport information</b>	
Department of Transportation (DOT)	
In accordance with DOT	
Transport document description	: UN3161 Liquefied gas, flammable, n.o.s., 2.1
UN-No.(DOT)	: UN3161
Proper Shipping Name (DOT)	: Liquefied gas, flammable, n.o.s.
Transport hazard class(es) (DOT)	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT)	: 2.1 - Flammable gas
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315
DOT Symbols	: G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102)	: T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail 49 CFR 173.27)	: Forbidden
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 3161
Proper Shipping Name (IMDG)	: LIQUEFIED GAS, FLAMMABLE, N.O.S.
Class (IMDG)	: 2 - Gases
Air transport	
JN-No. (IATA)	: 3161
Proper Shipping Name (IATA)	: Liquefied gas, flammable, n.o.s.
Class (IATA)	: 2

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

1,1,2,3,3-Pentafluoropropene	CAS No 433-66-9	100%
------------------------------	-----------------	------

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### 15.2. International regulations

CANADA

No additional information available

**EU-Regulations** 

No additional information available

National regulations No additional information available

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

#### SECTION 16: Other information

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:		
Eye Irrit.	2A	Serious eye damage/eye irritation Category 2A
Flam. Ga	as 2	Flammable gases Category 2
Liquefied	d gas	Gases under pressure Liquefied gas
Simple A	Asphy	Simple Asphyxiant
Skin Irrit	. 2	Skin corrosion/irritation Category 2
STOT SI	E 3	Specific target organ toxicity (single exposure) Category 3
H221		Flammable gas
H280		Contains gas under pressure; may explode if heated
H315		Causes skin irritation
H319		Causes serious eye irritation
H335		May cause respiratory irritation
H380		May displace oxygen and cause rapid suffocation

NFPA health hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.		
NFPA fire hazard	: 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.		
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.		
HMIS III Rating			
Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given		
Flammability	: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)		
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.		
SDS US (GHS HazCom 2012)			

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.