

Safety Data Sheet 1300704

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification

1.1. Identification

Product form : Substance

Substance name : 1-Chloro-2-fluoroethylene

CAS No : 460-16-2
Product code : 1300-7-04
Formula : C2H2CIF
Other means of identification : MFCD00040333

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

1.3. Details of the supplier of the safety data sheet

SynQuest Laboratories, Inc.

P.O. Box 309

Alachua, FL 32615 - United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Simple Asphy H380 - May displace oxygen and cause rapid suffocation

Flam. Gas 2 H221 - Flammable gas

Liquefied gas H280 - Contains gas under pressure; may explode if heated

Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye irritation

STOT SE 3 H336 - May cause drowsiness or dizziness STOT SE 3 H335 - May cause respiratory irritation

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Signal word (GHS-US)

Hazard pictograms (GHS-US)





: Warning

HS04 GHS07

Hazard statements (GHS-US) : H221 - Flammable gas

azard statements (GHS-US) H221 - Flammable gas

H280 - Contains gas under pressure; may explode if heated

H315 - Causes skin irritation

H319 - Causes serious eye irritation H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness

H380 - May displace oxygen and cause rapid suffocation

Precautionary statements (GHS-US) : P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking

P261 - Avoid breathing fumes, gas, mist, spray, vapors

P264 - Wash skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P302+P352 - If on skin: Wash with plenty of soap and water

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

12/06/2016 EN (English US) SDS ID: 1300704 Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P312 - Call a POISON CENTER or doctor/physician if you feel unwell

P321 - Specific treatment (see supplemental first aid instructions on this label)

P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse

P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely

P381 - Eliminate all ignition sources if safe to do so

P403 - Store in a well-ventilated place

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P410+P403 - Protect from sunlight. Store in a well-ventilated place P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards

Other hazards not contributing to the classification

: May cause frostbite.

Unknown acute toxicity (GHS US) 2.4.

Not applicable

SECTION 3: Composition/information on ingredients

3.1. **Substance**

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
1-Chloro-2-fluoroethylene (Main constituent)	(CAS No) 460-16-2	<= 100	Simple Asphy, H380 Flam. Gas 2, H221 Liquefied gas, H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 STOT SE 3, H335

Full text of H-phrases: see section 16

Mixture 3.2.

Not applicable

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label

where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial

respiration. Get immediate medical advice/attention.

First-aid measures after skin contact Thaw frosted parts with lukewarm water. Do no rub affected area. Get immediate medical

advice/attention.

Remove contact lenses, if present and easy to do. Continue rinsing. Immediately flush eyes First-aid measures after eye contact

thoroughly with water for at least 15 minutes. Get immediate medical advice/attention.

Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never First-aid measures after ingestion give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical

advice/attention.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries The most important known symptoms and effects are described in the labelling (see section

2.2) and/or in section 11.

Symptoms/injuries after inhalation : May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Contact with the liquid the may cause cold burns/frostbite.

Symptoms/injuries after eye contact Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due

to frostbite from rapid liquid evaporation.

Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

Extinguishing media

: Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media Suitable extinguishing media appropriate for surrounding fire.

12/06/2016 EN (English US) SDS ID: 1300704 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Special hazards arising from the substance or mixture

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen chloride. Hydrogen fluoride.

Explosion hazard : Contains gas under pressure; may explode if heated. Use water spray or fog for cooling

exposed containers. May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting : Wear gas tight chemically protective clothing in combination with self contained breathing

apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. En

: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection"."

Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground

level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of

ignition.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so.

Methods for cleaning up : Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Handle empty containers with

care because residual vapors are flammable. Close valve after each use and when empty.

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Ensure good

ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Safe handling of the gas receptacle : Securely chain cylinders when in use and protect against physical damage.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed

when not in use. Keep away from ignition sources.

Incompatible materials : Refer to Section 10 on Incompatible Materials.

Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

12/06/2016 EN (English US) SDS ID: 1300704 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers

should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when

asphyxiating gases may be released.

Hand protection : Protective gloves. 29 CFR 1910.138: Hand Protection.

Eye protection : Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory

Protection.

Thermal hazard protection : Cold insulating gloves.

Other information : Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available

Boiling point : 10 °C

Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) No data available **Explosion limits** : No data available Explosive properties : No data available Oxidizing properties : No data available Vapor pressure : No data available Relative density No data available Relative vapor density at 20 °C : No data available Molecular mass 80.49 g/mol Solubility : No data available Log Pow : No data available No data available Auto-ignition temperature Decomposition temperature No data available Viscosity No data available No data available Viscosity, kinematic

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Viscosity, dynamic

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

May polymerize.

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C Keep away from heat, sparks and flame.

: No data available

10.5. Incompatible materials

Alkali metals. Finely divided metals (Al, Mg, Zn). Strong oxidizing agents.

12/06/2016 EN (English US) SDS ID: 1300704 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness. May cause respiratory irritation.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Contact with the liquid the may cause cold burns/frostbite.

Symptoms/injuries after eye contact : Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due

to frostbite from rapid liquid evaporation.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Waste disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3161 Liquefied gas, flammable, n.o.s., 2.1

UN-No.(DOT) : UN3161

Proper Shipping Name (DOT) : Liquefied gas, flammable, n.o.s.

Transport hazard class(es) (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

12/06/2016 EN (English US) SDS ID: 1300704 5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : 304 DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the

applicable liquefied compressed gases are authorized to be transported in portable tanks in

accordance with the requirements of 173.313 of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel

carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger

vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Other information : No supplementary information available.

TDG

No additional information available

Transport by sea

UN-No. (IMDG) : 3161

Proper Shipping Name (IMDG) : LIQUEFIED GAS, FLAMMABLE, N.O.S.

Class (IMDG) : 2 - Gases

Air transport

UN-No. (IATA) : 3161

Proper Shipping Name (IATA) : Liquefied gas, flammable, n.o.s.

Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

1-Chloro-2-fluoroethylene	CAS No 460-16-2	100%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

12/06/2016 EN (English US) SDS ID: 1300704 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

Full text of H-phrases:

tt of 11 princeoe.	
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Gas 2	Flammable gases Category 2
Liquefied gas	Gases under pressure Liquefied gas
Simple Asphy	Simple Asphyxiant
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H221	Flammable gas
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H380	May displace oxygen and cause rapid suffocation

NFPA health hazard

: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity

: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with

some release of energy, but not violently.



HMIS III Rating

Health

: 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

Physical

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo

hazardous polymerization in the absence of inhibitors.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

12/06/2016 EN (English US) SDS ID: 1300704 7/7