

Safety Data Sheet 13007Z4 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1.1. Identification	
Product form	: Substance
Substance name	: (Z)-1-Chloro-2-fluoroethylene
CAS No	: 2268-31-7
Product code	: 1300-7-Z4
Formula	: C2H2CIF
Synonyms	: cis-1-Chloro-2-fluoroethylene
Other means of identification	: MFCD08461574
1.2. Relevant identified uses of the substa	ance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the safety da	ata sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of America T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com 1.4. Emergency telephone number	
	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identification	
2.1. Classification of the substance or mix	xture
Classification (GHS-US)	
Flam. Gas 2 H221 - Flammable gas Liquefied gas H280 - Contains gas under pres Skin Irrit. 2 H315 - Causes skin irritation	sure; may explode if heated
Flam. Gas 2H221 - Flammable gasLiquefied gasH280 - Contains gas under presSkin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eye irritaSTOT SE 3H336 - May cause drowsiness oSTOT SE 3H335 - May cause respiratory irr	sure; may explode if heated ition r dizziness
Flam. Gas 2H221 - Flammable gasLiquefied gasH280 - Contains gas under presSkin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eye irritaSTOT SE 3H336 - May cause drowsiness oSTOT SE 3H335 - May cause respiratory irrFull text of H-phrases: see section 16	sure; may explode if heated ition r dizziness
Flam. Gas 2H221 - Flammable gasLiquefied gasH280 - Contains gas under presSkin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eye irritaSTOT SE 3H336 - May cause drowsiness oSTOT SE 3H335 - May cause respiratory irrFull text of H-phrases: see section 162.2.Label elements	sure; may explode if heated ition r dizziness
Flam. Gas 2H221 -Flammable gasLiquefied gasH280 -Contains gas under presSkin Irrit. 2H315 -Causes skin irritationEye Irrit. 2AH319 -Causes serious eye irritaSTOT SE 3H336 -May cause drowsiness oSTOT SE 3H335 -May cause respiratory irrFull text of H-phrases: see section 162.2.Label elementsGHS-US labeling	sure; may explode if heated ition r dizziness
Flam. Gas 2 H221 - Flammable gas Liquefied gas H280 - Contains gas under pres Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye irrita STOT SE 3 H336 - May cause drowsiness o STOT SE 3 H335 - May cause respiratory irr Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	sure; may explode if heated tion r dizziness ritation : $\bigvee_{GHS04} \bigvee_{GHS07}^{V}$
Flam. Gas 2 H221 - Flammable gas Liquefied gas H280 - Contains gas under pres Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye irrita STOT SE 3 H336 - May cause drowsiness o STOT SE 3 H335 - May cause respiratory irr Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	sure; may explode if heated tion r dizziness ritation
Flam. Gas 2 H221 - Flammable gas Liquefied gas H280 - Contains gas under pres Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye irrita STOT SE 3 H336 - May cause drowsiness o STOT SE 3 H335 - May cause respiratory irr Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	sure; may explode if heated tion r dizziness ritation : $\bigvee_{GHS04} \bigvee_{GHS07}^{V}$

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other hazards Differ hazards not contributing to the lassification	P31 P32 P33 P36 P37 P38 P40 P40 P40 P41 P50	ses, if present and easy to do. Co 2 - Call a POISON CENTER or d 1 - Specific treatment (see supple 2+P313 - If skin irritation occurs: 7+P313 - If eye irritation persists: 52+P364 - Take off contaminated 7 - Leaking gas fire: Do not exting 1 - Eliminate all ignition sources in 3 - Store in a well-ventilated plac 13+P233 - Store in a well-ventilated 5 - Store locked up 0+P403 - Protect from sunlight. S 1 - Dispose of contents/container	loctor/physician if you emental first aid instru Get medical advice/at : Get medical advice/at clothing and wash it b guish, unless leak can if safe to do so e ed place. Keep contair Store in a well-ventilate	ctions on this label) ttention uttention efore reuse a be stopped safely her tightly closed ed place
2.4. Unknown acute toxicity (GHS US)				
lot applicable				
SECTION 3: Composition/informat	ion on i	ngredients		
S.1. Substance				
Substance type	: Mor	no-constituent		
Name		Product identifier	%	Classification (GHS-US)
(Z)-1-Chloro-2-fluoroethylene (Main constituent)		(CAS No) 2268-31-7	<= 100	Simple Asphy, H380 Flam. Gas 2, H221 Liquefied gas, H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 STOT SE 3, H335
Full text of H-phrases: see section 16				
3.2. Mixture				
Not applicable				
SECTION 4: First aid measures				
Description of first aid measures First-aid measures general	: In c	ase of accident or if you feel unw	oll sook modical advir	co immodiately (show the label
inst-aid measures general		are possible). Move the affected p		
irst-aid measures after inhalation		nove person to fresh air and keep biration. Get immediate medical a		thing. If not breathing, give artificial
irst-aid measures after skin contact	adv	w frosted parts with lukewarm wa ice/attention.		
irst-aid measures after eye contact	thor	oughly with water for at least 15 r	minutes. Get immedia	
irst-aid measures after ingestion	give			kely. Do NOT induce vomiting. Never nouth out with water. Get medical
.2. Most important symptoms and eff	ects, botl	n acute and delayed		
Symptoms/injuries		most important known symptoms and/or in section 11.	s and effects are desc	ribed in the labelling (see section
Symptoms/injuries after inhalation		cause drowsiness or dizziness.		
Symptoms/injuries after skin contact		tact with the liquid the may cause		I populate portrained and the set
Symptoms/injuries after eye contact		ect contact with the liquefied gas r ostbite from rapid liquid evaporat		l possibly permanent eye injury due
4.3. Indication of any immediate medic	al attenti	on and special treatment need	ed	
No additional information available				
SECTION 5: Firefighting measures				
.1. Extinguishing media				
Suitable extinguishing media		ohol resistant foam. Carbon dioxic ropriate for surrounding fire.	de. Dry powder. Water	r spray. Use extinguishing media

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2.	Special hazards arising from the substance or mixture			
Fire hazard		: Thermal decomposition generates: Carbon oxides. Hydrogen chloride. Hydrogen fluoride.		
Explosion hazard		: Contains gas under pressure; may explode if heated. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.		
5.3. Advice for firefighters				
Firefighting instructions		: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.		
Protection during firefighting		: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".		

SECTION 6: Accidental release measures				
6.1. Personal precautions, protective equipment and emergency procedures				
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.			
6.1.1. For non-emergency personnel				
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.			
6.1.2. For emergency responders				
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".			
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.			
6.2. Environmental precautions				

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and materia	3. Methods and material for containment and cleaning up		
For containment	: Stop leak if safe to do so.		
Methods for cleaning up	: Ventilate area.		
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".		
C.4. Defenses to other a			

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care because residual vapors are flammable. Close valve after each use and when empty.		
Precautions for safe handling	Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.		
Safe handling of the gas receptacle	: Securely chain cylinders when in use and protect against physical damage.		
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.		
7.2. Conditions for safe storage, includ	ing any incompatibilities		
Technical measures	: Comply with applicable regulations.		
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C Keep container closed when not in use. Keep away from ignition sources.		
Incompatible materials	: Refer to Section 10 on Incompatible Materials.		
Storage area	: Store in dry, cool, well-ventilated area.		

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2.	Exposure controls	
Appropriate engineering controls		Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released.
Hand	d protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye	protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin	and body protection	: Wear suitable protective clothing.
Resp	piratory protection	 In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Ther	mal hazard protection	: Cold insulating gloves.
Othe	er information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and	che	mical properties
Physical state	:	Gas
Color	:	No data available
Odor	:	No data available
Odor threshold	:	No data available
рН	:	No data available
Melting point	:	No data available
Freezing point	:	No data available
Boiling point	:	15 - 15.5 °C
Flash point	:	No data available
Relative evaporation rate (butyl acetate=1)	:	No data available
Flammability (solid, gas)	:	No data available
Explosion limits	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Vapor pressure	:	No data available
Relative density	:	No data available
Relative vapor density at 20 °C	:	No data available
Specific gravity / density	:	1.117 g/ml (@ 20 °C)
Molecular mass	:	80.49 g/mol
Solubility	:	No data available
Log Pow	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity		
10.1.	Reactivity	
No addi	tional information available	
10.2.	Chemical stability	
The pro	duct is stable at normal handling and storage conditions.	
10.3.	Possibility of hazardous reactions	
May pol	ymerize.	
10.4.	Conditions to avoid	
Drotoot	from sublight. Do not eveness to temperatures eveneding 50 °C. Keep away from best, aparka and flome	

Protect from sunlight. Do not expose to temperatures exceeding 50 °C Keep away from heat, sparks and flame.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials

Alkali metals. Finely divided metals (Al, Mg, Zn). Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information		
11.1.	1. Information on toxicological effects	

Acute toxicity	: Not classified
Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitization Germ cell mutagenicity Carcinogenicity	 Causes skin irritation. Causes serious eye irritation. Not classified Not classified Not classified Not classified
Reproductive toxicity Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure)	 Not classified May cause drowsiness or dizziness. May cause respiratory irritation. Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation Symptoms/injuries after skin contact Symptoms/injuries after eye contact	 May cause drowsiness or dizziness. Contact with the liquid the may cause cold burns/frostbite. Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

SECT	ION 12: Ecological information
12.1.	Toxicity
No add	tional information available
12.2.	Persistence and degradability
No add	tional information available
12.3.	Bioaccumulative potential
No addi	tional information available
12.4.	Mobility in soil
No addi	tional information available
12.5.	Other adverse effects
No add	tional information available

SECTION 13: Disposal considera	tions		
13.1. Waste treatment methods			
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.		
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.		
Additional information	: Recycle the material as far as possible.		
SECTION 14: Transport informati	on		
Department of Transportation (DOT)			

Transport document description : L	: UN3161 Liquefied gas, flammable, n.o.s., 2.1	
Proper Shipping Name (DOT) : L	JN3161 .iquefied gas, flammable, n.o.s. .1 - Class 2.1 - Flammable gas 49 CFR 173.115	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT)	2.1 - Flammable gas		
DOT Packaging Non Bulk (49 CFR 173.xxx)	304		
DOT Packaging Bulk (49 CFR 173.xxx)	314;315		
DOT Symbols	G - Identifies PSN requiring a technical name		
DOT Special Provisions (49 CFR 172.102)	: T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter.		
DOT Packaging Exceptions (49 CFR 173.xxx)	306		
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	Forbidden		
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	150 kg		
DOT Vessel Stowage Location	D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.		
DOT Vessel Stowage Other	40 - Stow "clear of living quarters"		
Other information	No supplementary information available.		
TDG			
No additional information available			
Transport by sea			
UN-No. (IMDG)	3161		
Proper Shipping Name (IMDG)	LIQUEFIED GAS, FLAMMABLE, N.O.S.		
Class (IMDG)	2 - Gases		
Air transport			
UN-No. (IATA)	3161		
Proper Shipping Name (IATA)	Liquefied gas, flammable, n.o.s.		
Class (IATA)	2		

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

(Z)-1-Chloro-2-fluoroethylene CAS No 2268-31-7 100%		
	CAS No 2268-31-7	100%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

Full text of H-phrases:

y 3 y 3		
y 3		
Causes serious eye irritation		
May cause respiratory irritation		
May cause drowsiness or dizziness		
May displace oxygen and cause rapid suffocation		
`		
 ambient conditions. 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently. 		
: 2 Moderate Hazard - Temporary or minor injury may occur		
: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)		
: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.		
i		

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.