

Safety Data Sheet 1600B11 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 07/31/2018 Version: 1.0

1.1. Identification	
Product form	: Substance
Substance name	: 1-Bromo-3,4,5-trifluorobenzene
CAS No	: 138526-69-9
Product code	: 1600-B-11
Formula	: C6H2BrF3
Synonyms	: 5-Bromo-1,2,3-trifluorobenzene / 5- Bromo- 1,2,3- trifluorobenzene
Other means of identification	: MFCD00070738
1.2. Relevant identified uses of the s	substance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the saf	fety data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of Americ T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - <u>www.synquestlab</u> s	
1.4.Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identificati	ion
2.1. Classification of the substance	
Classification (GHS-US)	
Eye Dam. 1H318 - Causes seriousCarc. 2H351 - Suspected of c	s eye damage causing cancer
Eye Dam. 1H318 - Causes seriousCarc. 2H351 - Suspected of cSTOT SE 3H335 - May cause resAquatic Acute 2H401 - Toxic to aquati	ritation s eye damage causing cancer piratory irritation
Eye Dam. 1H318 - Causes seriousCarc. 2H351 - Suspected of cSTOT SE 3H335 - May cause resAquatic Acute 2H401 - Toxic to aquatiAquatic Chronic 2H411 - Toxic to aquatiFull text of H-phrases: see section 16	ritation s eye damage causing cancer piratory irritation c life
Eye Dam. 1H318 - Causes seriousCarc. 2H351 - Suspected of cSTOT SE 3H335 - May cause resAquatic Acute 2H401 - Toxic to aquatiAquatic Chronic 2H411 - Toxic to aquatiFull text of H-phrases: see section 162.2.Label elements	ritation s eye damage causing cancer piratory irritation c life
Eye Dam. 1H318 - Causes seriousCarc. 2H351 - Suspected of cSTOT SE 3H335 - May cause resAquatic Acute 2H401 - Toxic to aquatiAquatic Chronic 2H411 - Toxic to aquatiFull text of H-phrases: see section 162.2.Label elementsGHS-US labeling	ritation s eye damage causing cancer piratory irritation c life
Eye Dam. 1H318 - Causes seriousCarc. 2H351 - Suspected of cSTOT SE 3H335 - May cause resAquatic Acute 2H401 - Toxic to aquatiAquatic Chronic 2H411 - Toxic to aquatiFull text of H-phrases: see section 162.2.Label elementsGHS-US labeling	ritation s eye damage causing cancer piratory irritation c life
Eye Dam. 1H318 - Causes seriousCarc. 2H351 - Suspected of cSTOT SE 3H335 - May cause resAquatic Acute 2H401 - Toxic to aquatiAquatic Chronic 2H411 - Toxic to aquatiFull text of H-phrases: see section 162.2.Label elements	ritation s eye damage causing cancer piratory irritation c life c life with long lasting effects
Eye Dam. 1 H318 - Causes serious Carc. 2 H351 - Suspected of c STOT SE 3 H335 - May cause res Aquatic Acute 2 H401 - Toxic to aquati Aquatic Chronic 2 H411 - Toxic to aquati Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	ritation is eye damage causing cancer piratory irritation c life ic life with long lasting effects $\frac{1}{1000} = 1000 \text{ Life with long lasting effects}$

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

0. 56 / Monuay, March 20, 20	
P264 - V	Vash skin thoroughly after handling
P271 - L	Jse only outdoors or in a well-ventilated area
P273 - A	woid release to the environment
P280 - V	Vear protective gloves/protective clothing/eye protection/face protection
P302+P3	352 - If on skin: Wash with plenty of soap and water
	361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse
skin with	water/shower
P304+P3	340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P3	351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact
lenses, i	f present and easy to do. Continue rinsing
P308+P3	313 - If exposed or concerned: Get medical advice/attention
P310 - Ir	mmediately call a POISON CENTER or doctor/ physician
P321 - S	Specific treatment (see supplemental first aid instructions on this label)
P332+P3	313 - If skin irritation occurs: Get medical advice/attention
P362+P3	364 - Take off contaminated clothing and wash it before reuse
P370+P3	378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P391 - C	Collect spillage
P403+P2	233 - Store in a well-ventilated place. Keep container tightly closed
	235 - Store in a well-ventilated place. Keep cool
	Store locked up
P501 - D	Dispose of contents/container to an approved waste disposal plant

#### Other hazards 2.3.

No additional information available

Unknown acute toxicity (GHS US) 2.4.

Not applicable

### **SECTION 3: Composition/information on ingredients**

2.4	Cubatanaa
3.1.	Substance
	ousolarioo

Substance type

: Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
1-Bromo-3,4,5-trifluorobenzene (Main constituent)	(CAS No) 138526-69-9	<= 100	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 Carc. 2, H351 STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

### Full text of H-phrases: see section 16

3.2.	Mixture	
Not app	blicable	
SECT	ION 4: First aid measures	
4.1.	Description of first aid measures	
First-aid	d measures general	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.
First-aid	d measures after inhalation	Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.
First-aid	d measures after skin contact	: Wash with plenty of soap and water. Get immediate medical advice/attention.
First-aid	d measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
First-aid	d measures after ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.
4.2.	Most important symptoms and effects	s, both acute and delayed
Sympto	ms/injuries	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.
4.3.	Indication of any immediate medical a	ttention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Special hazards arising from the substance or mixture			
Explos	ion hazard	: Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.	
5.3.	Advice for firefighters		
Firefigh	nting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.	
Protection during firefighting		: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".	
		apparatus. For further information refer to section 8: "Exposure controls/personal protection".	
SECT	TION 6: Accidental release n		
SECT 6.1.			
6.1.		measures	
6.1.	Personal precautions, protectiv	measures ve equipment and emergency procedures : Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes vapor or spray.	

6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	<ul> <li>Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.</li> </ul>

### 6.2. **Environmental precautions** Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3.	Methods and material for containment and cleaning up		
For containment		: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.	
Methods for cleaning up		Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.	
Other	information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".	
6.4.	Reference to other sections		

No additional information available

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, including	ng any incompatibilities
Technical measures	: Comply with applicable regulations.
Storage conditions	: Keep container closed when not in use. Keep away from ignition sources.
Incompatible materials	: Refer to Section 10 on Incompatible Materials.
Storage area	: Store in dry, cool, well-ventilated area.

SECTION 8: EX	posure controls/	personal	protection

#### 8.1. **Control parameters**

No additional information available

2=/24/2242			
Hand protection	: Protective gloves. 29 CFR 1	910.138: Hand Protection.	
Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety s should be available in the immediate vicinity of any potential exposure.		nd safety showers
8.2. Exposure controls			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

### **SECTION 9: Physical and chemical properties**

SECTION 9: Physical and chemical	properties
9.1. Information on basic physical and	chemical properties
Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Melting point	: <-20 °C
Freezing point	: No data available
Boiling point	: 47 - 49 °C (@ 60 mm Hg)
Flash point	: 45 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.767 g/ml (@ 20 °C)
Molecular mass	: 210.979 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
9.2. Other information	
Refractive index	: 1.48 (@ 20 °C)
SECTION 10, Stability and reactivit	
SECTION 10: Stability and reactivit 10.1. Reactivity	y
No additional information available	
10.2. Chemical stability	
The product is stable at normal handling and s	torage conditions.
10.3. Possibility of hazardous reactions	
No additional information available	
10.4. Conditions to avoid	
Keep away from heat, sparks and flame.	
10.5 Incompatible materials	

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations		
SECTION 11: Toxicological informat	lion	
11.1. Information on toxicological effects		
Acute toxicity	: Not classified	
Skin corrosion/irritation	: Causes skin irritation.	
Serious eye damage/irritation	: Causes serious eye damage. : Not classified	
Respiratory or skin sensitization Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Suspected of causing cancer.	
Reproductive toxicity	: Not classified	
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.	
Specific target organ toxicity (repeated exposure)	: Not classified	
Aspiration hazard	: Not classified	
SECTION 12: Ecological information		
12.1. Toxicity		
No additional information available		
12.2. Persistence and degradability		
No additional information available		
12.3. Bioaccumulative potential		
No additional information available		
12.4. Mobility in soil		
No additional information available		

Other adverse effects 12.5.

No additional information available

SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.	
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.	
Additional information	: Recycle the material as far as possible.	

# **SECTION 14: Transport information**

## **Department of Transportation (DOT)**

In accordance with DOT Transport document description

UN-No.(DOT) Proper Shipping Name (DOT) Transport hazard class(es) (DOT) Hazard labels (DOT)

Packing group (DOT) Dangerous for the environment

- : UN1993 Flammable liquids, n.o.s., 3, III
- : UN1993
- : Flammable liquids, n.o.s.
- : 3 Class 3 Flammable and combustible liquid 49 CFR 173.120
- : 3 Flammable liquid



- : III Minor Danger
- : Yes

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

bulk packaging requirements of 173.241 flash point of less than 38 C (100 F), ther subchapter are applicable. B52 - Notwithstanding the provisions of 1 relief devices are authorized on DOT 57 p IB3 - Authorized IBCs: Metal (31A, 31B a (31HZ1 and 31HA2, 31HB2, 31HN2, 31H with a vapor pressure less than or equal to C (1.3 bar at 131 F) are authorized, excep 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal1 TP1 - The maximum degree of filling mus following: Degree of filling = 97 / 1 + a (tr during transport, and tf is the temperature TP29 - A portable tank having a minimum provided the calculated test pressure is 1	
<ul> <li>DOT Packaging Bulk (49 CFR 173.xxx)</li> <li>DOT Symbols</li> <li>C - Identifies PSN requiring a technical n</li> <li>DOT Special Provisions (49 CFR 172.102)</li> <li>B1 - If the material has a flash point at or bulk packaging requirements of 173.241 flash point of less than 38 C (100 F), ther subchapter are applicable.</li> <li>B52 - Notwithstanding the provisions of 1 relief devices are authorized on DOT 57 plB3 - Authorized IBCs: Metal (31A, 31B a (31HZ1 and 31HA2, 31HB2, 31HN2, 31HN2, 31H with a vapor pressure less than or equal to C (1.3 bar at 131 F) are authorized, exception UN2672).</li> <li>T4 - 2.65 178.274(d)(2) Normal</li></ul>	
<ul> <li>DOT Symbols</li> <li>DOT Special Provisions (49 CFR 172.102)</li> <li>B1 - If the material has a flash point at or bulk packaging requirements of 173.241 flash point of less than 38 C (100 F), ther subchapter are applicable.</li> <li>B52 - Notwithstanding the provisions of 1 relief devices are authorized on DOT 57 plB3 - Authorized IBCs: Metal (31A, 31B a (31HZ1 and 31HA2, 31HB2, 31HN2, 31HN2, 31H with a vapor pressure less than or equal to C (1.3 bar at 131 F) are authorized, excel 2 for UN2672).</li> <li>T4 - 2.65 178.274(d)(2) Normal</li></ul>	
<ul> <li>DOT Special Provisions (49 CFR 172.102)</li> <li>B1 - If the material has a flash point at or bulk packaging requirements of 173.241 of flash point of less than 38 C (100 F), ther subchapter are applicable.</li> <li>B52 - Notwithstanding the provisions of 1 relief devices are authorized on DOT 57 plB3 - Authorized IBCs: Metal (31A, 31B a (31HZ1 and 31HA2, 31HB2, 31HN2, 31H with a vapor pressure less than or equal for C (1.3 bar at 131 F) are authorized, excep 2 for UN2672).</li> <li>T4 - 2.65 178.274(d)(2) Normal</li></ul>	
<ul> <li>bulk packaging requirements of 173.241 flash point of less than 38 C (100 F), ther subchapter are applicable.</li> <li>B52 - Notwithstanding the provisions of 1 relief devices are authorized on DOT 57 plB3 - Authorized IBCs: Metal (31A, 31B a (31HZ1 and 31HA2, 31HB2, 31HN2, 31H with a vapor pressure less than or equal to C (1.3 bar at 131 F) are authorized, excep 2 for UN2672).</li> <li>T4 - 2.65 178.274(d)(2) Normal</li></ul>	ame
DOT Quantity Limitations Passenger aircraft/rail : 60 L	nd 31N); Rigid plastics (31H1 and 31H2); Composite D2 and 31HH2). Additional Requirement: Only liquids o 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 ot for UN2672 (also see Special Provision IP8 in Table
(49 CT K 173.27)	
DOT Quantity Limitations Cargo aircraft only (49 : 220 L CFR 175.75)	
DOT Vessel Stowage Location : A - The material may be stowed "on deck passenger vessel.	" or "under deck" on a cargo vessel and on a
Other information : No supplementary information available.	
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG) : 1993	
Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S.	
Class (IMDG) : 3 - Flammable liquids	
Packing group (IMDG) : III - substances presenting low danger	
Air transport	
JN-No. (IATA) : 1993	
Proper Shipping Name (IATA) : Flammable liquid, n.o.s.	
Class (IATA) : 3 - Flammable Liquids	
Packing group (IATA) : III - Minor Danger	
SECTION 15: Regulatory information	
15.1. US Federal regulations	
All components of this product are listed, or excluded from listing, on the United States Envir Substances Control Act (TSCA) inventory except for:	

 1-Bromo-3,4,5-trifluorobenzene
 CAS No 138526-69-9
 100%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **15.2. International regulations**

### **CANADA**

No additional information available

### **EU-Regulations**

## 1-Bromo-3,4,5-trifluorobenzene (138526-69-9)

Listed on ELINCS (European List of Notified Chemical Substances)

#### National regulations

1-Bromo-3,4,5-trifluorobenzene (138526-69-9) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on the TCSI (Taiwan Chemical Substance Inventory)

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

### SECTION 16: Other information

Full text of H-phrases:

Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2	
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2	
Carc. 2	Carcinogenicity Category 2	
Eye Dam. 1	Serious eye damage/eye irritation Category 1	
Flam. Liq. 3	Flammable liquids Category 3	
Skin Irrit. 2	Skin corrosion/irritation Category 2	
STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
H226	Flammable liquid and vapor	
H315	Causes skin irritation	
H318	Causes serious eye damage	
H335	May cause respiratory irritation	
H351	Suspected of causing cancer	
H401	Toxic to aquatic life	
H411	Toxic to aquatic life with long lasting effects	
NFPA fire hazard	residual injury even though prompt medical attention was given. : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.	
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.	
HMIS III Rating		
Health	: 2 Moderate Hazard - Temporary or minor injury may occur	
Flammability	2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)	
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NO react with water, polymerize, decompose, condense, or self-react. Non-Explosives.	
SDS US (GHS HazCom 2012)		

### SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.