

# **Material Safety Data Sheet**

Transportation Emergency: 1-800-451-8346

Date last revised: August 9, 2013 Date printed: August 9, 2013

# SECTION 1. ----- CHEMICAL IDENTIFICATION-----

CATALOG #: 1700-5-X8

NAME: 4-CHLOROBENZYL CHLORIDE

SYNONYMS: 1-CHLORO-4-(CHLOROMETHYL)BENZENE; ALPHA,4-DICHLOROTOLUENE

# SECTION 2. ---- COMPOSITION/INFORMATION ON INGREDIENTS -----

CAS NUMBER: 104-83-6

MOLECULAR FORMULA: C7H6Cl<sub>2</sub> MOLECULAR WEIGHT: 161.03

### SECTION 3. ------HAZARDS IDENTIFICATION -----

#### LABEL PRECAUTIONARY STATEMENTS

HARMFUL.

HARMFUL BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.

IRRITANT.

IRRITANT TO RESPIRATORY TRACT, TO SKIN AND EYES.

HARMFUL TO AQUATIC LIFE.

# SECTION 4. ----- FIRST-AID MEASURES-----

## ORAL EXPOSURE

IF SWALLOWED, WASH OUT MOUTH WITH WATER PROVIDED PERSON IS CONSCIOUS. CONSULT A PHYSICIAN.

## INHALATION EXPOSURE

IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CONSULT A PHYSICIAN.

#### EYE EXPOSURE

ASSURE ADEQUATE FLUSHING OF THE EYES BY SEPARATING THE EYELIDS WITH FINGERS. CONSULT A PHYSYCIAN.

#### DERMAL EXPOSURE

IN CASE OF CONTACT, WASH SKIN IMMEDIATELY WITH SOAP AND COPIOUS AMOUNTS OF WATER. CONSULT A PHYSICIAN.

# SECTION 5. ----- FIRE FIGHTING MEASURES -----

#### FLASH POINT

107 °C - CLOSED CUP.

#### **EXTINGUISHING MEDIA**

SUITABLE: FOR SMALL (INCIPIENT) FIRES, USE MEDIA SUCH AS

"ALCOHOL" FOAM, DRY CHEMICAL, OR CARBON DIOXIDE. FOR LARGE

FIRES, APPLY WATER FROM AS FAR AS POSSIBLE. USE VERY LARGE

QUANTITIES (FLOODING) OF WATER APPLIED AS A MIST OR SPRAY; SOLID

STREAMS OF WATER MAY BE INEFFECTIVE. COOL ALL AFFECTED

CONTAINERS WITH FLOODING QUANTITIES OF WATER.

#### **FIREFIGHTING**

PROTECTIVE EQUIPMENT: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN AND EYES. SPECIFIC METHOD(S) OF FIRE FIGHTING: USE WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS.

SPECIFIC HAZARD(S): EMITS TOXIC FUMES UNDER FIRE CONDITIONS.

### SECTION 6. ----- ACCIDENTAL RELEASE MEASURES-----

PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL

EVACUATE PERSONNEL TO A SAFE PLACE.

PROCEDURE(S) OF PERSONAL PRECAUTION(S)

WEAR SELF-CONTAINED BREATHING APPARATUS, RUBBER BOOTS, AND HEAVY RUBBER GLOVES. AVOID DUST FORMATION. AVOID BREATHING DUST, VAPORS, MIST OR GAS. ENSURE ADEQUATE VENTILATION.

**ENVIRONMENTAL PRECAUTIONS** 

DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

METHODS FOR CLEANING UP

SWEEP UP OR ABSORB ON DRY SAND OR VERMICULITE, SWEEP UP MATERIAL AND DISPOSE OF AS HAZARDOUS WASTE. PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS.

# SECTION 7. ----- HANDLING AND STORAGE-----

### **HANDLING**

USER EXPOSURE: AVOID CONTACT WITH SKIN, CLOTHING AND EYES. AVOID FORMATION OF DUST AND AEROSOLS. PROVIDE APPROPRIATE EXHAUST VENTILATION AT PLACES WHERE DUST IS FORMED. NORMAL MEASURES FOR PREVENTIVE FIRE PROTECTION. STORAGE

SUITABLE: KEEP CONTAINER TIGHTLY CLOSED. STORE IN A COOL DRY PLACE. MOISTURE SENSITIVE. STORE UNDER INERT GAS. AVOID DIRECT SUNLIGHT.

# SECTION 8. ----- EXPOSURE CONTROLS/PERSONAL PROTECTION-----

#### **ENGINEERING CONTROLS**

SAFETY SHOWER AND EYE BATH. MECHANICAL EXHAUST REQUIRED.

# PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY: WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE

APPROPRIATE USE A DUST MASK TYPE N95 (US) OR TYPE P1 (EN 143) RESPIRATOR.

USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE

GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

HAND: HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. WASH AND DRY HANDS.

EYE: TIGHTLY FITTING CHEMICAL SAFETY GOGGLES.

## GENERAL HYGIENE MEASURES

WASH HANDS THOROUGHLY AFTER HANDLING. AVOID CONTACT WITH SKIN, EYES AND CLOTHING.

#### SECTION 9. ----- PHYSICAL AND CHEMICAL PROPERTIES -----

## APPEARANCE AND ODOR

LOW MELTING SOLID

PHYSICAL PROPERTIES

MELTING POINT: 26 - 30 °C BOILING POINT: 216 - 222 °C

#### SECTION 10. -----STABILITY AND REACTIVITY -----

## **STABILITY**

STABLE: STABLE UNDER RECOMMENDED CONDITIONS.

CONDITIONS TO AVOID: OPEN FIRE AND FLAMES, EXTREMES OF TEMPERATURE, MOISTURE AND DIRECT SUNLIGHT.

MATERIALS TO AVOID: STRONG OXIDIZING AGENTS, STRONG ACIDS AND BASES, ALCOHOLS, AMINES.

#### HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON OXIDES, HYDROGEN CHLORIDE GAS. HAZARDOUS POLYMERIZATION

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

#### SECTION 11. ----- TOXICOLOGICAL INFORMATION -----

## ROUTE OF EXPOSURE

INHALATION: HARMFUL IF INHALED. CAUSES RESPIRATORY TRACT IRRITATION.

INGESTION: HARMFUL IF SWALLOWED.

SKIN: HARMFUL IF ABSORBED THROUGH SKIN. CAUSES SKIN IRRITATION.

EYES: CAUSES EYE IRRITATION.

# SIGNS AND SYMPTOMS OF EXPOSURE

TO THE BEST OF OUR KNOWLEDGE, THE TOXICOLOGICAL PROPERTIES OF THIS PRODUCT HAVE NOT BEEN FULLY DETERMINED.

# 

SECTION 16.----- OTHER INFORMATION-----

TSCA: LISTED ON TSCA INVENTORY; FOR R&D USE ONLY

SAFETY STATEMENTS: 13-22-23-24/25-26-36/37/39-45-61

RISK STATEMENTS: 20/21/22-36/37/38 -52

US CLASSIFICATION AND LABEL TEXT

THE ABOVE INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. SYNQUEST LABS, INC. SHALL NOT BE HELD LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING OR FROM CONTACT WITH THE ABOVE PRODUCT.