

Material Safety Data Sheet

Transportation Emergency: 1-800-451-8346

Date last revised: August 13, 2010 Date printed: August 13, 2010

SECTION 1. ----- CHEMICAL IDENTIFICATION-----

CATALOG #: 1700-7-32

NAME: 3-CHLORO-2-FLUOROTOLUENE

SYNONYM: 1-CHLORO-2-FLUORO-3-METHYLBENZENE

SECTION 2. ---- COMPOSITION/INFORMATION ON INGREDIENTS -----

CAS #: 85089-31-2 MF: C₇H₆ClF = 144.58

SECTION 3, ----- HAZARDS IDENTIFICATION -----

LABEL PRECAUTIONARY STATEMENTS COMBUSTIBLE (USA) FLAMMABLE (EU). IRRITANT.

IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.

SECTION 4. ----- FIRST-AID MEASURES-----

ORAL EXPOSURE

IF SWALLOWED, WASH OUT MOUTH WITH WATER PROVIDED PERSON IS CONSCIOUS. CALL A PHYSICIAN.

INHALATION EXPOSURE

IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING GIVE

ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN.

DERMAL EXPOSURE

IN CASE OF CONTACT, IMMEDIATELY WASH SKIN WITH SOAP AND COPIOUS AMOUNTS OF WATER.

EYE EXPOSURE

IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MINUTES.

SECTION 5. ----- FIRE FIGHTING MEASURES -----

EXPLOSION HAZARDS

VAPOR MAY TRAVEL CONSIDERABLE DISTANCE TO SOURCE OF IGNITION AND FLASH BACK.

FLASH POINT

118 °F / 48 °C METHOD: CLOSED CUP

EXTINGUISHING MEDIA

SUITABLE: FOR SMALL (INCIPIENT) FIRES, USE MEDIA SUCH AS "ALCOHOL" FOAM, DRY CHEMICAL, OR CARBON DIOXIDE. FOR LARGE FIRES, APPLY WATER FROM AS FAR AS POSSIBLE. USE VERY LARGE QUANTITIES (FLOODING) OF WATER APPLIED AS A MIST OR SPRAY; SOLID STREAMS OF WATER MAY BE INEFFECTIVE. COOL ALL AFFECTED CONTAINERS WITH FLOODING QUANTITIES OF WATER.

FIREFIGHTING

PROTECTIVE EQUIPMENT: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN AND EYES. SPECIFIC HAZARD(S): COMBUSTIBLE LIQUID. EMITS TOXIC FUMES UNDER FIRE CONDITIONS. VAPOR MAY TRAVEL CONSIDERABLE DISTANCE TO SOURCE OF IGNITION AND FLASH BACK.

EXPOSURE HAZARD(S)

MATERIAL: IRRITANT.

SECTION 6. ----- ACCIDENTAL RELEASE MEASURES-----

PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL

EVACUATE AREA.

PROCEDURE(S) OF PERSONAL PRECAUTION(S)

WEAR SELF-CONTAINED BREATHING APPARATUS, RUBBER BOOTS, AND HEAVY RUBBER GLOVES.

METHODS FOR CLEANING UP

COVER WITH DRY LIME OR SODA ASH, PICK UP, KEEP IN A CLOSED CONTAINER, AND HOLD FOR WASTE DISPOSAL. VENTILATE AREA AND WASH SPILL SITE AFTER MATERIAL PICKUP IS COMPLETE.

SECTION 7. ----- HANDLING AND STORAGE-----

HANDLING

USER EXPOSURE: DO NOT BREATHE VAPOR. AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. AVOID PROLONGED OR REPEATED EXPOSURE. STORAGE

SUITABLE: KEEP TIGHTLY CLOSED. KEEP AWAY FROM HEAT AND OPEN FLAME. STORE IN A COOL DRY PLACE.

SECTION 8. ----- EXPOSURE CONTROLS/PERSONAL PROTECTION-----

ENGINEERING CONTROLS

SAFETY SHOWER AND EYE BATH. MECHANICAL EXHAUST REQUIRED.

PERSONAL PROTECTIVE EQUIPMENT

OTHER: WEAR APPROPRIATE GOVERNMENT APPROVED RESPIRATOR, CHEMICAL-RESISTANT GLOVES, SAFETY GOGGLES, OTHER PROTECTIVE CLOTHING.

GENERAL HYGIENE MEASURES

WASH THOROUGHLY AFTER HANDLING. WASH CONTAMINATED CLOTHING BEFORE REUSE.

SECTION 9. ----- PHYSICAL AND CHEMICAL PROPERTIES -----

APPEARANCE AND ODOR

COLORLESS LIQUID

PHYSICAL PROPERTIES

BOILING POINT: 92 - 94 °C @ 86 mmHg

FLASHPOINT: 118 °F / 48 °C METHOD: CLOSED CUP

SPECIFIC GRAVITY: 1.2 g/cm^3

SECTION 10. -----STABILITY AND REACTIVITY -----

STABILITY

MATERIALS TO AVOID: STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE, HYDROGEN CHLORIDE GAS, HYDROGEN FLUORIDE.

SECTION 11. ----- TOXICOLOGICAL INFORMATION -----

ROUTE OF EXPOSURE

SKIN CONTACT: CAUSES SKIN IRRITATION.

MULTIPLE ROUTES: VAPOR OR MIST IS IRRITATING TO THE EYES, MUCOUS MEMBRANES, AND UPPER RESPIRATORY TRACT. MAY BE HARMFUL BY

INHALATION, INGESTION, OR SKIN ABSORPTION.

SIGNS AND SYMPTOMS OF EXPOSURE

TO THE BEST OF OUR KNOWLEDGE, THE CHEMICAL, PHYSICAL, AND TOXICOLOGICAL PROPERTIES HAVE NOT BEEN THOROUGHLY INVESTIGATED.

SECTION 12. ----- ECOLOGICAL INFORMATION -----

DATA NOT YET AVAILABLE.

SECTION 13. ----- DISPOSAL CONSIDERATIONS -----

APPROPRIATE METHOD OF DISPOSAL OF SUBSTANCE OR PREPARATION THIS COMBUSTIBLE MATERIAL MAY BE BURNED IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER. OBSERVE ALL FEDERAL, STATE, AND LOCAL ENVIRONMENTAL REGULATIONS.

SECTION 14. ----- TRANSPORT INFORMATION -----

DOT

PROPER SHIPPING NAME: FLAMMABLE LIQUID, N.O.S.

UN#: 1993 CLASS: 3

PACKING GROUP: PACKING GROUP III HAZARD LABEL: FLAMMABLE LIQUID

SECTION 15. ----- REGULATORY INFORMATION -----

EU ADDITIONAL CLASSIFICATION

SYMBOL OF DANGER: Xi

INDICATION OF DANGER: IRRITANT.

R: 10-36/37/38

RISK STATEMENTS: FLAMMABLE. IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.

S: 16-26-36/37/39

SAFETY STATEMENTS: KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING. IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK MEDICAL ADVICE. WEAR SUITABLE PROTECTIVE CLOTHING, GLOVES, AND EYE/FACE PROTECTION.

US CLASSIFICATION AND LABEL TEXT

INDICATION OF DANGER: COMBUSTIBLE (USA) FLAMMABLE (EU). IRRITANT. RISK STATEMENTS: IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN. SAFETY STATEMENTS: KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING. IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK MEDICAL ADVICE. WEAR SUITABLE PROTECTIVE CLOTHING, GLOVES, AND EYE/FACE PROTECTION. UNITED STATES REGULATORY INFORMATION

TSCA LISTED: NO

SECTION 16. ----- OTHER INFORMATION-----

THE ABOVE INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. SYNQUEST LABS, INC. SHALL NOT BE HELD LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING OR FROM CONTACT WITH THE ABOVE PRODUCT.