

2,3,4,5,6-Pentafluorobenzyl bromide Safety Data Sheet 1700B01 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 01/08/2015 Version: 1.0

Product form	: Substance		
Substance name	: 2,3,4,5,6-Pentafluorobenzyl br	omide	
CAS No	: 1765-40-8		
Product code	: 1700-B-01		
Formula	: C7H2BrF5		
Synonyms	: Bromo(pentafluorophenyl)meth	nane	
Other means of identification	: MFCD00000299		
1.2. Relevant identified uses of the sul	ostance or mixture and uses advis	ed against	
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and develo	oment	
1.3. Details of the supplier of the safet	y data sheet		
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of America T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlabs.co 1.4. Emergency telephone number	<u>om</u>		
Emergency number	: (844) 523-4086 (3E Company	Account 10060)	
Flam. Liq. 4H227 - Combustible liquidSkin Corr. 1AH314 - Causes severe skin bEye Dam. 1H318 - Causes serious eye dSTOT SE 3H335 - May cause respiratoryFull text of H-phrases: see section 16	amage		
2.2. Label elements			
GHS-US labeling			
Hazard pictograms (GHS-US) Signal word (GHS-US) Hazard statements (GHS-US)	: GHS05 GHS05 CHS07 : Danger : H227 - Combustible liquid H314 - Causes severe skin bu		
Precautionary statements (GHS-US)	 H335 - May cause respiratory P210 - Keep away from heat/s P260 - Do not breathe fumes, P264 - Wash skin thoroughly a P271 - Use only outdoors or in P280 - Wear protective gloves, P301+P330+P331 - If swallow P303+P361+P353 - If on skin skin with water/shower P304+P340 - If inhaled: Remo P305+P351+P338 - If in eyes: lenses, if present and easy to o P310 - Immediately call a POIS P321 - Specific treatment (see P363 - Wash contaminated cloped) 	irritation parks/open flames/hot surfaces. No smoking mist, spray, vapors fiter handling a well-ventilated area /protective clothing/eye protection/face protected: rinse mouth. Do NOT induce vomiting (or hair): Take off immediately all contaminate ve person to fresh air and keep comfortable f Rinse cautiously with water for several minute do. Continue rinsing SON CENTER or doctor/ physician supplemental first aid instructions on this lab	ed clothing. Rinse or breathing es. Remove contac el)
12/06/2016	EN (English US)	SDS ID: 1700B01	Page 1

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	P403- P405	P233 - Store in a well-ventilated place. P235 - Store in a well-ventilated place. - Store locked up - Dispose of contents/container to an ap	Keep cool	
2.3. Other hazards				
Other hazards not contributing to the classification	: Lachr	ymator.		
2.4. Unknown acute toxicity (GHS US)				
Not applicable				
SECTION 3: Composition/information	on in	gredients		
3.1. Substance				
Substance type	: Mono	-constituent		
Name		Product identifier	%	Classification (GHS-US)
2,3,4,5,6-Pentafluorobenzyl bromide (Main constituent)		(CAS No) 1765-40-8	<= 100	Flam. Liq. 4, H227 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335
Full text of H-phrases: see section 16				
3.2. Mixture				
Not applicable				
SECTION 4: First aid measures				
4.1. Description of first aid measures				
First-aid measures general		e of accident or if you feel unwell, seek repossible). Move the affected personnel		
First-aid measures after inhalation		ve person to fresh air and keep comforta ation. Get immediate medical advice/atte		ng. If not breathing, give artificial
First-aid measures after skin contact		with plenty of soap and water. Remove al advice/attention.	contaminated c	lothing and shoes. Get immediate
First-aid measures after eye contact		Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.		
First-aid measures after ingestion		 Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention. 		
4.2. Most important symptoms and effect	s, both a	acute and delayed		
Symptoms/injuries	: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.			
Symptoms/injuries after inhalation	: Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.			
4.3. Indication of any immediate medical	attentio	n and special treatment needed		
Treat symptomatically.				
SECTION 5: Firefighting measures				
5.1. Extinguishing media				
Suitable extinguishing media		ol resistant foam. Carbon dioxide. Dry po priate for surrounding fire.	owder. Water sp	oray. Use extinguishing media
5.2. Special hazards arising from the sub	stance o	or mixture		
Fire hazard	: Thern	nal decomposition generates: Carbon ox	ides. Hydrogen	bromide. Hydrogen fluoride.
Explosion hazard		of explosion if heated under confinement iners. May form flammable/explosive vap		ay or fog for cooling exposed
5.3. Advice for firefighters				
Firefighting instructions	: In cas	e of fire: Evacuate area. Fight fire remot	ely due to the ri	isk of explosion.
Protection during firefighting		gas tight chemically protective clothing i atus. For further information refer to sect		
SECTION 6: Accidental release meas				
6.1. Personal precautions, protective equ				
General measures		ate unnecessary personnel. Ensure ade or spray.	equate air ventil	ation. Do not breathe gas, fumes,

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.1. For non-emergency personnel	
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.
6.2. Environmental precautions	
Avoid release to the environment. Notify authoritie	es if product enters sewers or public waters.
6.3. Methods and material for containment	nt and cleaning up
For containment	: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.
Methods for cleaning up	: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".
6.4. Reference to other sections	
No additional information available	
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good
	ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, includin	g any incompatibilities
Technical measures	: Comply with applicable regulations.
Storage conditions	: Keep container closed when not in use. Keep away from ignition sources. Keep contents under inert gas.
Incompatible materials	: Refer to Section 10 on Incompatible Materials.
Storage area	: Store in dry, cool, well-ventilated area.
CECTION OF Every control of	
SECTION 8: Exposure controls/perso	nar protection
8.1. Control parameters	
No additional information available	
8.2. Exposure controls	. Ensure good ventilation of the work station. Emergency are used for station and effects the sure
Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.
SECTION 9: Physical and chemical p	roperties
9.1. Information on basic physical and ch	

9.1.	Information on basic physical ar	nd chemical properties	
Physica	I state	: Liquid	
Appeara	ance	: Low melting solid.	
Color		: No data available	
Odor		: No data available	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. 77, No. 58 / Monda	y, March 26, 2012 / Rules and Regulations
Odor threshold	: No data available
pH	: No data available
Melting point	: 19 - 20 °C
Freezing point	: No data available
Boiling point	: 174 - 175 °C
Flash point	: 83 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.844 g/ml (@ 20 °C)
Molecular mass	: 260.99 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
9.2. Other information	
Refractive index	: 1.471 (@ 20 °C)
SECTION 10: Stability and reactivit	У
10.1. Reactivity	
No additional information available	
10.2. Chemical stability	
The product is stable at normal handling and st	torage conditions.
10.3. Possibility of hazardous reactions	
No additional information available	
10.4. Conditions to avoid	
Keep away from heat, sparks and flame.	
10.5. Incompatible materials Strong bases. Strong oxidizing agents.	
10.6. Hazardous decomposition produc	
Under normal conditions of storage and use, ha	azardous decomposition products should not be produced. Hazardous decomposition products in case of
SECTION 11: Toxicological informa	ation
11.1. Information on toxicological effect	S
Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Pospiratory or skip consitization	· Not clossified

Reproductive toxicity

: May cause respiratory irritation.

: Not classified

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

SECT	TION 12: Ecological information	
12.1.	Toxicity	
No add	ditional information available	
12.2.	Persistence and degradability	
No add	ditional information available	
12.3.	Bioaccumulative potential	
No add	ditional information available	
12.4.	Mobility in soil	
No add	ditional information available	
10.5	Other a human affects	
12.5.	Other adverse effects	

No additional information available

SECTION 13: Disposal considerations				
13.1. Waste treatment methods				
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.			
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.			
Additional information	: Recycle the material as far as possible.			

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT Transport document description

UN-No.(DOT) Proper Shipping Name (DOT) Transport hazard class(es) (DOT) Hazard labels (DOT)

Packing group (DOT)

- DOT Packaging Non Bulk (49 CFR 173.xxx)
- DOT Packaging Bulk (49 CFR 173.xxx)
- DOT Symbols

DOT Special Provisions (49 CFR 172.102)

- : UN3265 Corrosive liquid, acidic, organic, n.o.s., 8, III
- : UN3265
- : Corrosive liquid, acidic, organic, n.o.s.
- : 8 Class 8 Corrosive material 49 CFR 173.136
- : 8 Corrosive



- : III Minor Danger
- : 203
- : 241
- : G Identifies PSN requiring a technical name

: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

: 154

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

(49 CFR 173.27)	il : 5L
DOT Quantity Limitations Cargo aircraft only (4 CFR 175.75)	9 : 60 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 3265
Proper Shipping Name (IMDG)	: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.
Class (IMDG)	: 8 - Corrosive substances
Packing group (IMDG)	: III - substances presenting low danger
Air transport	
UN-No. (IATA)	: 3265
Proper Shipping Name (IATA)	: Corrosive liquid, acidic, organic, n.o.s.
Class (IATA)	: 8 - Corrosives
Packing group (IATA)	: III - Minor Danger
SECTION 15: Regulatory information	on
15.1. US Federal regulations	
All components of this product are listed, or e Substances Control Act (TSCA) inventory exe	xcluded from listing, on the United States Environmental Protection Agency Toxic cept for:
2,3,4,5,6-Pentafluorobenzyl bromide	CAS No 1765-40-8 100%

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

2,3,4,5,6-Pentafluorobenzyl bromide (1765-40-8)	
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on NZIoC (New Zealand Inventory of Chemicals)	

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:	
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1A	Skin corrosion/irritation Category 1A
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H335	May cause respiratory irritation
NFPA health hazard NFPA fire hazard NFPA reactivity	 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given. 1 - Must be preheated before ignition can occur. 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	
Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.