

# **Material Safety Data Sheet**

Transportation Emergency: 1-800-451-8346

Date last revised: February 28, 2013 Date printed: February 28, 2013

SECTION 1. ----- CHEMICAL IDENTIFICATION-----

CATALOG #: 2101-3-X6

NAME: 2,2-BIS(TRIFLUOROMETHYL)PROPAN-1-OL

SECTION 2. ---- COMPOSITION/INFORMATION ON INGREDIENTS -----

CAS NUMBER: 2927-17-5

MOLECULAR FORMULA: C₅H₀F₀O MOLECULAR WEIGHT: 196.09

SECTION 3. ----- HAZARDS IDENTIFICATION -----

LABEL PRECAUTIONARY STATEMENTS

FLAMMABLE SOLID.

IRRITANT.

IRRITANT TO RESPIRATORY TRACT, TO SKIN AND EYES.

SECTION 4. ----- FIRST-AID MEASURES-----

ORAL EXPOSURE

IF SWALLOWED, WASH OUT MOUTH WITH WATER PROVIDED PERSON IS CONSCIOUS. CONSULT A PHYSICIAN.

INHALATION EXPOSURE

IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CONSULT A PHYSICIAN.

EYE EXPOSURE

ASSURE ADEQUATE FLUSHING OF THE EYES BY SEPARATING THE EYELIDS WITH FINGERS. CONSULT A PHYSYCIAN.

DERMAL EXPOSURE

IN CASE OF CONTACT, WASH SKIN IMMEDIATELY WITH SOAP AND COPIOUS AMOUNTS OF WATER. CONSULT A PHYSICIAN.

## SECTION 5. ----- FIRE FIGHTING MEASURES -----

#### FLASH POINT

35 °C (CALCULATED)

#### **EXTINGUISHING MEDIA**

SUITABLE: FOR SMALL (INCIPIENT) FIRES, USE MEDIA SUCH AS "ALCOHOL" FOAM, DRY CHEMICAL, OR CARBON DIOXIDE. FOR LARGE FIRES, APPLY WATER FROM AS FAR AS POSSIBLE. USE VERY LARGE QUANTITIES (FLOODING) OF WATER APPLIED AS A MIST OR SPRAY; SOLID STREAMS OF WATER MAY BE INEFFECTIVE. COOL ALL AFFECTED CONTAINERS WITH FLOODING QUANTITIES OF WATER.

#### **FIREFIGHTING**

PROTECTIVE EQUIPMENT: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN AND EYES. SPECIFIC METHOD(S) OF FIRE FIGHTING: USE WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS.

SPECIFIC HAZARD(S): EMITS TOXIC FUMES UNDER FIRE CONDITIONS.

#### SECTION 6. ----- ACCIDENTAL RELEASE MEASURES-----

#### PERSONAL PROTECTION

AVOID BREATHING VAPOR MIST, OR GAS. ENSURE ADEQYATE VENTILATION. WEAR PROTECTIVE EQUIPMENT INCLUDING RUBBER GLOVES, AND EYE PROTECTION. KEEP UNPROTECTED PERSONS AWAY.

REMOVE ALL SOURCES OF IGNITION. BEWARE OF VAPORS ACCUMULATING TO FORM EXPLOSIVE CONCENTRATIONS. VAPORS CAN ACCUMULATE IN LOW AREAS.

#### **ENVIRONMENTAL PROTECTION**

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. TAKE PRECAUTIONS TO ENSURE PRODUCT DOES NOT CONTAMINATE THE GROUND OR ENTER THE DRAINAGE SYSTEM.

## COLLECTION

CONTAIN SPILLAGE AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS.

# SECTION 7. ----- HANDLING AND STORAGE-----

#### HANDLING

USER EXPOSURE: AVOID INHALATION. AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. AVOID PROLONGED OR REPEATED EXPOSURE.
USE EXPLOSION-PROOF EQUIPMENT. KEEP AWAY FROM SOURCES OF IGNITION. TAKE MEASURES TO PREVENT THE BUILD UP OF ELECTROSTATIC CHARGE.
STORAGE

SUITABLE: TIGHTLY CLOSED CONTAINERS IN A DRY AND WELL-VENTILATED PLACE. CONTAINERS WHICH ARE OPENED MUST BE CAREFULLY RESEALED AND KEPT UPRIGHT TO PREVENT LEAKAGE. STORE IN COOL, DRY PLACE. AVOID DIRECT SUNLIGHT. STORE UNDER INERT GAS. RECOMMENDED STORAGE TEMPERATURE: 2 – 8 °C.

## SECTION 8. ----- EXPOSURE CONTROLS/PERSONAL PROTECTION-----

#### **ENGINEERING CONTROLS**

SAFETY SHOWER AND EYE BATH. MECHANICAL EXHAUST REQUIRED.

#### PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY: WHERE RISK ASSESSMENT SHOWS AIR-PURIFYING RESPIRATORS ARE

APPROPRIATE USE A DUST MASK TYPE N95 (US) OR TYPE P1 (EN 143) RESPIRATOR.

USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE

GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

HAND: HANDLE WITH GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE. USE PROPER GLOVE REMOVAL TECHNIQUE (WITHOUT TOUCHING GLOVE'S OUTER SURFACE) TO AVOID SKIN CONTACT WITH THIS PRODUCT. WASH AND DRY HANDS.

EYE: TIGHTLY FITTING CHEMICAL SAFETY GOGGLES.

## GENERAL HYGIENE MEASURES

WASH HANDS THOROUGHLY AFTER HANDLING. AVOID CONTACT WITH SKIN, EYES AND CLOTHING.

#### SECTION 9. ----- PHYSICAL AND CHEMICAL PROPERTIES -----

## APPEARANCE AND ODOR

LOW MELTING SOLID

PHYSICAL PROPERTIES

MELTING POINT: 35 °C BOILING POINT: 90 °C

#### SECTION 10. -----STABILITY AND REACTIVITY -----

## **STABILITY**

STABLE: STABLE UNDER RECOMMENDED CONDITIONS.

CONDITIONS TO AVOID: OPEN FIRE AND FLAMES, EXTREMES OF TEMPERATURE, MOISTURE AND DIRECT SUNLIGHT.

MATERIALS TO AVOID: STRONG OXIDIZING AGENTS, STRONG BASES.

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON OXIDES, HYDROGEN FLUORIDE.

HAZARDOUS POLYMERIZATION

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

#### SECTION 11. ----- TOXICOLOGICAL INFORMATION -----

#### ROUTE OF EXPOSURE

INHALATION: MAY BE HARMFUL IF INHALED. CAUSES RESPIRATORY TRACT IRRITATION. INGESTION: MAY BE HARMFUL IF SWALLOWED.

SKIN: MAY BE HARMFUL IF ABSORBED THROUGH SKIN. CAUSES SKIN IRRITATION.

EYES: CAUSES EYE IRRITATION.

SIGNS AND SYMPTOMS OF EXPOSURE

TO THE BEST OF OUR KNOWLEDGE, THE TOXICOLOGICAL PROPERTIES OF THIS PRODUCT HAVE NOT BEEN FULLY DETERMINED.

## SECTION 12. ----- ECOLOGICAL INFORMATION -----

DATA NOT YET AVAILABLE.

## SECTION 13. ----- DISPOSAL CONSIDERATIONS -----

APPROPRIATE METHOD OF DISPOSAL OF SUBSTANCE OR PREPARATION
BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER
BUT EXERT EXTRA CARE IN IGNITING AS THIS MATERIAL IS HIGHLY FLAMMABLE. OFFER
SURPLUS AND NON-RECYCLABLE SOLUTIONS TO A LICENSED DISPOSAL COMPANY.
CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS
MATERIAL. OBSERVE ALL FEDERAL, STATE, AND LOCAL ENVIRONMENTAL REGULATIONS.

# SECTION 14. ----- TRANSPORT INFORMATION -----

DOT

UN1325 - HC: 4.1 - PG: III

#### SECTION 15. ----- REGULATORY INFORMATION -----

EU ADDITIONAL CLASSIFICATION

SYMBOL OF DANGER: Xi

INDICATION OF DANGER: IRRITANT.

RISK STATEMENTS: 10-18-36/37/38

SAFETY STATEMENTS: 13-16-22-23-24/25-26-33-36/37/39-45

US CLASSIFICATION AND LABEL TEXT

TSCA: NOT LISTED ON TSCA INVENTORY; FOR R&D USE ONLY

#### SECTION 16. ----- OTHER INFORMATION-----

THE ABOVE INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. SYNQUEST LABS, INC. SHALL NOT BE HELD LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING OR FROM CONTACT WITH THE ABOVE PRODUCT.