

1,1,1-Trifluorobutan-2-ol Safety Data Sheet 2102305 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 08/07/2017 Version: 1.0

I.1. Identification	
Product form	: Substance
Substance name	: 1,1,1-Trifluorobutan-2-ol
CAS No	: 431-36-7
Product code	: 2102-3-05
Formula	: C4H7F3O
Other means of identification	: MFCD00462509
1.2. Relevant identified uses of the s	substance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the saf	fety data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of Americ T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlabs	
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identificati	ion
2.1. Classification of the substance	
Classification (GHS-US)	
Flam. Liq. 3 Bkin Irrit. 2 Eye Irrit. 2A STOT SE 3 H226 - Flammable liquid and H315 - Causes skin irritation H319 - Causes serious eye i H335 - May cause respirator	irritation
Flam. Liq. 3 H226 - Flammable liquid and Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye i STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16	irritation
Flam. Liq. 3 H226 - Flammable liquid and Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye i STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	irritation
Flam. Liq. 3 H226 - Flammable liquid and Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye i STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements	riritation ry irritation
Flam. Liq. 3 H226 - Flammable liquid and Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye i STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	rritation ry irritation
Flam. Liq. 3 H226 - Flammable liquid and Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye i STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	riritation ry irritation

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

lenses, if present and easy to do. Continue rinsing P312 - Call a POISON CENTER or doctor/physician if you feel unwell P321 - Specific treatment (see supplemental first aid instructions on this label) P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extingu P403+P233 - Store in a well-ventilated place. Keep container tightly closed P403+P235 - Store in a well-ventilated place. Keep cool P405 - Store locked up P501 - Dispose of contents/container to an approved waste disposal plant		ttions on this label) ention tention efore reuse alcohol-resistant foam to extinguish er tightly closed	
2.3. Other hazards No additional information available			
2.4. Unknown acute toxicity (GHS US)			
Not applicable			
SECTION 3: Composition/information	on ingredients		
3.1. Substance			
Substance type	: Mono-constituent		
Name	Product identifier	%	Classification (GHS-US)
1,1,1-Trifluorobutan-2-ol (Main constituent)	(CAS No) 431-36-7	<= 100	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Full text of H-phrases: see section 16	· ·		-
3.2. Mixture			
Not applicable			
SECTION 4: First aid measures			
4.1. Description of first aid measures			
-	: In case of accident or if you feel unwell where possible). Move the affected per	sonnel away from the	e contaminated area.
First-aid measures after inhalation	: Remove person to fresh air and keep c respiration. Get medical advice/attention	n.	
	: Wash with plenty of soap and water. G		
,	: Immediately flush eyes thoroughly with present and easy to do. Continue rinsir	ng. Get medical advid	ce/attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Never give a mouth out with water. Get medical advi		an unconscious person. Rinse
4.2. Most important symptoms and effects	· ·		
Symptoms/injuries	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.		
4.3. Indication of any immediate medical a Treat symptomatically.	attention and special treatment needed		
SECTION 5: Firefighting measures			
5.1. Extinguishing media		D	
Suitable extinguishing media	: Alcohol resistant foam. Carbon dioxide appropriate for surrounding fire.	. Dry powder. Water	spray. Use extinguishing media
5.2. Special hazards arising from the sub-			
	: Thermal decomposition generates: Car		
Explosion hazard	: Risk of explosion if heated under confir containers. May form flammable/explose		
5.3. Advice for firefighters			
	: In case of fire: Evacuate area. Fight fire	-	
Protection during firefighting	: Wear gas tight chemically protective cle apparatus. For further information refer		

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measu	Ires	
6.1. Personal precautions, protective equi		
	: Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes, vapor or spray.	
6.1.1. For non-emergency personnel		
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.	
6.1.2. For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.	
6.2. Environmental precautions		
Avoid release to the environment. Notify authoritie	s if product enters sewers or public waters.	
6.3. Methods and material for containmen	t and cleaning up	
For containment	: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.	
Methods for cleaning up	: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.	
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".	
6.4. Reference to other sections		
No additional information available		
SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.	
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.	
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.	
7.2. Conditions for safe storage, including any incompatibilities		
Technical measures	: Comply with applicable regulations.	
Storage conditions	: Keep container closed when not in use. Keep away from ignition sources. Keep contents under inert gas.	
Incompatible materials	: Refer to Section 10 on Incompatible Materials.	
Storage temperature	2 - 8 °C Use explosion proof refrigerator	
Storage area	: Store in dry, well-ventilated area.	

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

No additional information available

8.2. Exposure controls	
Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

according to Federal Register / Vol. 77, No. 58 / Monda	
SECTION 9: Physical and chemica	
9.1. Information on basic physical and	• •
Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 90.8 - 91.8 °C (@ 752 mm Hg)
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.166 g/ml (@ 20 °C)
Molecular mass	: 128.09 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
9.2. Other information	
Refractive index	: 1.3403 (@ 20 °C)
SECTION 10: Stability and reactivity	ty .
10.1. Reactivity	
No additional information available	
10.2. Chemical stability	
The product is stable at normal handling and s	storage conditions.
10.3. Possibility of hazardous reactions	-
No additional information available	
10.4. Conditions to avoid Keep away from heat sparks and flame	
Keep away from heat, sparks and flame.	
10.5. Incompatible materials	
Strong acids. Strong bases. Strong oxidizing a	igents.
10.6. Hazardous decomposition produc	
Under normal conditions of storage and use, h fire, see Section 5.	nazardous decomposition products should not be produced. Hazardous decomposition products in case of
SECTION 11: Toxicological information	ation
11.1. Information on toxicological effec	
Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	
	: Causes serious eye irritation.
08/07/2017	SDS ID: 2102205

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

SECT	ON 12: Ecological information
12.1.	Toxicity
No addit	tional information available
12.2.	Persistence and degradability
No addi	tional information available
12.3.	Bioaccumulative potential
No addi	tional information available
12.4.	Mobility in soil
No addi	tional information available
12.5.	Other adverse effects
No addi	tional information available

SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.	
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.	
Additional information	: Recycle the material as far as possible.	

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT Transport document description

UN-No.(DOT) Proper Shipping Name (DOT) Transport hazard class(es) (DOT) Hazard labels (DOT)

Packing group (DOT) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) : UN1987 Alcohols, n.o.s., 3, III

: UN1987

- : Alcohols, n.o.s.
- : 3 Class 3 Flammable and combustible liquid 49 CFR 173.120
- : 3 Flammable liquid



- : III Minor Danger
- : 203
- : 242

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	 172 - This entry includes alcohol mixtures containing up to 5% petroleum products. B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal
DOT Packaging Exceptions (49 CFR 173.xxx)	: 4b;150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 1987
Proper Shipping Name (IMDG)	: ALCOHOLS, N.O.S.
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
Air transport	
UN-No. (IATA)	: 1987
Proper Shipping Name (IATA)	: Alcohols, n.o.s.
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger
SECTION 15: Regulatory information	
15.1. US Federal regulations	
All second sector of this was deal and listed an even	

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

1,1,1-Trifluorobutan-2-ol CAS No 431-36-7 100%	Substances Control Act (13CA) inventory exception.		
	1,1,1-Trifluorobutan-2-ol	CAS No 431-36-7	100%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations No additional information available

National regulations No additional information available

15.3. US State regulations

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
NFPA fire hazard	 given. 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur. 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high temperatures before ignition will occur. Includes liquids having a flash point at or ab but below 200 F. (Classes II & IIIA)	
Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions react with water, polymerize, decompose, condense, or self-react. Non-Explosive:	

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.