

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations SDS ID: 2107334 Issue date: 21.10.2016 Revision date: 18.12.2023 Version: 1.1

SECTION 1: Identification

1.1. Identification		
Product form Substance name CAS-No. Product code Formula Synonyms Other means of identification	 Substance Pentafluoroethyl methyl ether 22410-44-2 2107-3-34 C3H3F5O 1,1,1,2,2-Pentafluoro-2-methoxyethane MFCD03094117 	
1.2. Recommended use and restrictions on use		
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development	
1.3. Supplier		
SynQuest Laboratories, Inc. Inc. P.O. Box 309 Alachua, FL, Alachua, 32615 United States of America T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlabs.com		
1.4. Emergency telephone number		
Emergency number	: (844) 523-4086 (3E Company - Account 10069)	

SECTION 2: Hazard(s) identification

GHS US classification

Gases under pressure Liquefied gas	H280	Contains gas under pressure; may explode if heated
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319	Causes serious eye irritation
Specific target organ toxicity - Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Specific target organ toxicity – Single exposure, Category 3,	H335	May cause respiratory irritation
Respiratory tract irritation		
Full text of H statements : see section 16		

GHS US labeling

Hazard pictograms (GHS US)

 $\langle \hat{} \rangle \langle \hat{} \rangle$

Signal word (GHS US) Hazard statements (GHS US) : Warning

: H280 - Contains gas under pressure; may explode if heated

H315 - Causes skin irritation H319 - Causes serious eye irritation

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	H335 - May cause respiratory irritation
	H336 - May cause drowsiness or dizziness
Precautionary statements (GHS US)	: P261 - Avoid breathing fumes, gas, mist, spray, vapors.
	P264 - Wash skin thoroughly after handling
	P271 - Use only outdoors or in a well-ventilated area.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P302+P352 - If on skin: Wash with plenty of soap and water
	P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P312 - Call a POISON CENTER or doctor/physician if you feel unwell
	P321 - Specific treatment (see supplemental first aid instructions on this label)
	P332+P313 - If skin irritation occurs: Get medical advice/attention.
	P337+P313 - If eye irritation persists: Get medical advice/attention.
	P362+P364 - Take off contaminated clothing and wash it before reuse.
	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
	P405 - Store locked up.
	P410+P403 - Protect from sunlight. Store in a well-ventilated place.
	P501 - Dispose of contents/container to an approved waste disposal plant
2.3. Other hazards which do not result	in classification

Other hazards which do not result in classification : May cause frostbite.

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type

: Mono-constituent

Name	Product identifier	%	GHS US classification
Pentafluoroethyl methyl ether (Main constituent)	CAS-No.: 22410-44-2	≤ 100	Press. Gas (Liq.), H280 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general	: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.
First-aid measures after skin contact	: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after eye contact First-aid measures after ingestion	 Remove contact lenses, if present and easy to do. Continue rinsing. Immediately flush eyes thoroughly with water for at least 15 minutes. Get immediate medical advice/attention. Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention. 	
4.2. Most important symptoms and effects (acute and delayed)		
Symptoms/effects	: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.	
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.	

Symptoms/effects after skin contact Symptoms/effects after eye contact

- : Contact with the liquid the may cause cold burns/frostbite.
- : Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures		
5.1. Suitable (and unsuitable) extinguishing media		
Suitable extinguishing media	: Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.	
5.2. Specific hazards arising from the chemical		
Fire hazard Explosion hazard	 Thermal decomposition generates: Carbon oxides. Hydrogen fluoride. Contains gas under pressure; may explode if heated. Use water spray or fog for cooling expose containers. 	
5.3. Special protective equipment and precautions for fire-fighters		
Firefighting instructions Protection during firefighting	 In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection". 	

SECTION 6: Accidental release measures 6.1. Personal precautions, protective equipment and emergency procedures			
			General measures
6.1.1. For non-emergency personnel			
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.		
6.1.2. For emergency responders			
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".		
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.		
6.2. Environmental precautions			

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up	
For containment Methods for cleaning up Other information	 Stop leak if safe to do so. Ventilate area. For disposal of solid materials or residues refer to section 13 : "Disposal considerations".
6.4. Reference to other sections	

No additional information available

SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Close valve after each use and when empty.	
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes.	
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.	
7.2. Conditions for safe storage, including any incompatibilities		
Technical measures Storage conditions	 Comply with applicable regulations. Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use. 	
Incompatible materials Storage area	Refer to Section 10 on Incompatible Materials.Store in dry, cool, well-ventilated area.	

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Pentafluoroethyl methyl ether (22410-44-2)
No additional information available	
8.2. Appropriate engineering controls	
Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains and safety should be available in the immediate vicinity of any potential exposure. Systems under pr should be regularily checked for leakage. Oxygen detectors should be used when asphysicate gases may be released.	

8.3. Individual protection measures/Personal protective equipment

Hand protection:	
protective gloves. 29 CFR 1910.138: Hand Protection	
Eye protection:	
Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection	
Skin and body protection:	
Wear suitable protective clothing	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

Personal protective equipment symbol(s):



Thermal hazard protection:

Cold insulating gloves.

Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Melting point	: -115,1 – -114,4 °C
Freezing point	: No data available
Boiling point	: 6 °C (@ 738 mm Hg)
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 1,28 g/ml (@ 23 °C)
Molecular mass	: 150,05 g/mol
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects	: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Contact with the liquid the may cause cold burns/frostbite.
Symptoms/effects after eye contact	: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available	
12.2. Persistence and degradability	
Pentafluoroethyl methyl ether (22410-44-2)	
Persistence and degradability	Not readily biodegradable. May cause long-term adverse effects in the environment. PBT - Persistent, Bioaccumulative and Toxic.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential		
Pentafluoroethyl methyl ether (22410-4	4-2)	
Bioaccumulative potential	Perfluorinated alkanes (PFAs, "forever chemicals") are long lasting, widely used chemicals that break down slowly over time. The potential hazards of PFAs are under investigation and have not been established.	
12.4. Mobility in soil		
No additional information available		
12.5. Other adverse effects		
No additional information available		

SECTION 13: Disposal considerations	
13.1. Disposal methods	
Waste treatment methods Sewage disposal recommendations Product/Packaging disposal recommendations Additional information Ecology - waste materials	 Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber. See the EPA's Interim Guidance on PFAS Destruction and Disposal. Dispose of contents/container in accordance with licensed collector's sorting instructions. Recycle the material as far as possible. This material is considered to be a "Forever chemical". Prevent any possible release to the environment. Do not discharge into drains. Take all necessary measures to prevent accidental discharge of products into drains and waterways due to the rupture of containers or transfer systems, or emergency response.

SECTION 14: Transport information	
14.1. UN number	
DOT NA No UN-No. (TDG) UN-No. (IMDG) UN-No. (IATA)	: UN3163 : Not applicable : 3163 : 3163
14.2. UN proper shipping name	
Proper Shipping Name (DOT) Proper Shipping Name (TDG) Proper Shipping Name (IMDG) Proper Shipping Name (IATA)	 Liquefied gas, n.o.s. Not applicable LIQUEFIED GAS, N.O.S. Liquefied gas, n.o.s.
14.3. Transport hazard class(es)	
DOT Transport hazard class(es) (DOT) Hazard labels (DOT)	: 2.2 : 2.2
TDG Transport hazard class(es) (TDG)	: Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IMDG Transport hazard class(es) (IMDG) Hazard labels (IMDG)	: 2.2 : 2.2
АТА	
Transport hazard class(es) (IATA) Hazard labels (IATA)	: 2.2 : 2.2
14.4. Packing group	
Packing group (DOT)	: Not applicable
Packing group (TDG)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable
14.5. Environmental hazards Other information	· No supplementary information available
	: No supplementary information available.
14.6. Special precautions for user	
DOT UN-No.(DOT)	: UN3163
DOT Special Provisions (49 CFR 172.102)	: T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in
DOT Packaging Exceptions (49 CFR 173.xxx)	accordance with the requirements of 173.313 of this subchapter. : 306
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304
DOT Packaging Bulk (49 CFR 173.xxx)	: 314, 315
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
TDG No data available	
IMDG	
Special provision (IMDG)	: 274
Limited quantities (IMDG)	: 120 ml
Excepted quantities (IMDG) Packing instructions (IMDG)	: E1 : P200
Tank instructions (IMDG)	: T50
EmS-No. (Fire)	: F-C - FIRE SCHEDULE Charlie - NON-FLAMMABLE GASES
EmS-No. (Spillage)	: S-V - SPILLAGE SCHEDULE Victor - GASES (NON-FLAMMABLE, NON-TOXIC)
Stowage category (IMDG)	: A
IATA PCA Excepted quantities (IATA)	: E1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PCA Limited quantities (IATA)		Forbidden
PCA limited quantity max net quantity (IATA)		Forbidden
PCA packing instructions (IATA)		200
PCA max net quantity (IATA)		75kg
CAO packing instructions (IATA)	:	200
CAO max net quantity (IATA)		150kg
ERG code (IATA)	:	2L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Pentafluoroethyl methyl ether

CAS-No. 22410-44-2

100%

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

Pentafluoroethyl methyl ether (22410-44-2)

Listed on the Japanese ENCS (Existing New Chemical Substances) inventory

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date : 18.12.2023

Full text of H-phrases		
H280 Contains gas under pressure; may explode if heated		
H315	Causes skin irritation	
H319	Causes serious eye irritation	
H335	335 May cause respiratory irritation	
H336	May cause drowsiness or dizziness	

NFPA health hazard

: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA fire hazard	: 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.
NFPA reactivity	 0 - Material that in themselves are normally stable, even under fire conditions.
Hazard Rating Health Flammability Physical	 2 Moderate Hazard - Temporary or minor injury may occur 0 Minimal Hazard - Materials that will not burn 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Safety Data Sheet (SDS), USA