

Safety Data Sheet 2107703 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 02/01/2017 Version: 1.0

1.1. Identification	
Product form	: Substance
Substance name	: 2-Chloro-1,1,2-trifluoroethyl methyl ether
CAS No	: 425-87-6
Product code	: 2107-7-03
Formula	: C3H4CIF3O
Synonyms	: 2-Chloro-1,1,2-trifluoro-1-methoxyethane
Other means of identification	: MFCD00039335
	substance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the sa	fety data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of Ameri T (386) 462-0788 - F (386) 462-7097 Info@synquestlabs.com - www.synquestlab	
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identificat	ion
2.1. Classification of the substance	
Classification (GHS-US)	
Flam. Liq. 4 H227 - Combustible liquid Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H336 - May cause drowsine	irritation
Flam. Liq. 4 H227 - Combustible liquid Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye	irritation ess or dizziness
Flam. Liq. 4H227 - Combustible liquidSkin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eyeSTOT SE 3H336 - May cause drowsineSTOT SE 3H335 - May cause respirator	irritation ess or dizziness
Flam. Liq. 4 H227 - Combustible liquid Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H336 - May cause drowsine STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	irritation ess or dizziness
Flam. Liq. 4 H227 - Combustible liquid Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H336 - May cause drowsine STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements	irritation ess or dizziness
Flam. Liq. 4 H227 - Combustible liquid Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H336 - May cause drowsine STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	irritation ess or dizziness ry irritation : : : : : : : : : : : : : : : : : : :
Flam. Liq. 4 H227 - Combustible liquid Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H336 - May cause drowsine STOT SE 3 H335 - May cause respirator Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	irritation ess or dizziness ry irritation : : : : GHS07

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	P337+P313 - If eye irritation pers P362+P364 - Take off contamina P370+P378 - In case of fire: Use P403+P233 - Store in a well-ven P403+P235 - Store in a well-ven P405 - Store locked up P501 - Dispose of contents/conta	ted clothing and wash it be dry sand, dry chemical or ilated place. Keep contain ilated place. Keep cool	efore reuse alcohol-resistant foam to extinguish er tightly closed
2.3. Other hazards			
No additional information available			
2.4. Unknown acute toxicity (GHS US	S)		
Not applicable			
SECTION 3: Composition/informa	ation on ingredients		
3.1. Substance			
Substance type	: Mono-constituent		
Name	Product identifier	%	Classification (GHS-US)
2-Chloro-1,1,2-trifluoroethyl methyl ether (Main constituent)	(CAS No) 425-87-6	<= 100	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H336 STOT SE 3, H335
Full text of H-phrases: see section 16			
3.2. Mixture			
Not applicable			
SECTION 4: First aid measures			
4.1. Description of first aid measures	S		
First-aid measures general	: In case of accident or if you feel where possible). Move the affect		
First-aid measures after inhalation	: Remove person to fresh air and respiration. Get medical advice/a	ttention.	
First-aid measures after skin contact	: Wash with plenty of soap and wa		
First-aid measures after eye contact	present and easy to do. Continue	rinsing. Get medical advid	
First-aid measures after ingestion	: Do NOT induce vomiting. Never mouth out with water. Get medic		an unconscious person. Rinse
4.2. Most important symptoms and e			
Symptoms/injuries	: The most important known symp 2.2) and/or in section 11.	toms and effects are descr	ibed in the labelling (see section
Symptoms/injuries after inhalation	: May cause drowsiness or dizzine	SS.	
4.3. Indication of any immediate med	dical attention and special treatment n	eeded	
Treat symptomatically.			
SECTION 5: Firefighting measure	es		
5.1. Extinguishing media			
Suitable extinguishing media	: Alcohol resistant foam. Carbon c appropriate for surrounding fire.	ioxide. Dry powder. Water	spray. Use extinguishing media
5.2. Special hazards arising from the	e substance or mixture		
Fire hazard	: Thermal decomposition generate	s: Carbon oxides. Hydroge	en chloride. Hydrogen fluoride.
Explosion hazard	: Risk of explosion if heated under containers. May form flammable,		
5.3. Advice for firefighters			
Firefighting instructions	: In case of fire: Evacuate area. Fi	- ·	
Protection during firefighting	: Wear gas tight chemically protec apparatus. For further informatio		n with self contained breathing sure controls/personal protection".

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release mea			
6.1. Personal precautions, protective equipment and emergency procedures			
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes, vapor or spray.		
6.1.1. For non-emergency personnel			
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.		
6.1.2. For emergency responders			
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".		
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.		
6.2. Environmental precautions			
Avoid release to the environment. Notify authorit	ies if product enters sewers or public waters.		
6.3. Methods and material for containme	ent and cleaning up		
For containment	: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.		
Methods for cleaning up	: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.		
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".		
6.4. Reference to other sections			
No additional information available			
SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.		
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.		
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.		
7.2. Conditions for safe storage, including any incompatibilities			
Technical measures	: Comply with applicable regulations.		
Storage conditions	: Keep container closed when not in use. Keep away from ignition sources.		
Incompatible materials	: Refer to Section 10 on Incompatible Materials.		
Storage area	: Store in dry, cool, well-ventilated area.		
-			

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

No additional information available

8.2. Exposure controls	
Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical		
9.1. Information on basic physical and		
Physical state	: Liquid	
Color	: No data available	
Odor	: No data available	
Odor threshold	: No data available	
pH	: No data available	
Melting point	: No data available	
Freezing point	: No data available	
Boiling point	: 64.4 °C (@ 630 mm Hg)	
Flash point	: 66 °C	
Relative evaporation rate (butyl acetate=1)	: No data available	
Flammability (solid, gas)	: No data available	
Explosion limits	: No data available	
Explosive properties	: No data available	
Oxidizing properties	: No data available	
Vapor pressure	: No data available	
Relative density	: No data available	
Relative vapor density at 20 °C	: No data available	
Specific gravity / density	: 1.3632 g/ml (@ 20 °C)	
Molecular mass	: 148.51 g/mol	
Solubility	: No data available	
Log Pow	: No data available	
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	
Viscosity	: No data available	
Viscosity, kinematic	: No data available	
Viscosity, dynamic	: No data available	
9.2. Other information		
Refractive index	: 1.3338 (@ 20 °C)	
SECTION 10: Stability and reactivit	у	
10.1. Reactivity		
No additional information available		
10.2. Chemical stability		
The product is stable at normal handling and storage conditions.		
10.3. Possibility of hazardous reactions		
No additional information available		
10.4. Conditions to avoid		
Keep away from heat, sparks and flame.		
10.5. Incompatible materials		
Strong oxidizing agents.		
10.6. Hazardous decomposition products		
Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.		
SECTION 11: Toxicological informa	ntion	
11.1. Information on toxicological effect		
A quite toxicity	: Not classified	
Acute toxicity 2-Chloro-1,1,2-trifluoroethyl methyl ether (
LD50 oral rat 5130 mg/kg		
02/01/2017	EN (English US) SDS ID: 2107703 4/7	
02/01/2011	Liv (Lingholi 00) 500 ID. 210/703 4/7	

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-Chloro-1,1,2-trifluoroethyl methyl ether (425-87-6)		
ATE US (oral)	5130.000 mg/kg body weight	
Skin corrosion/irritation	: Causes skin irritation.	
Serious eye damage/irritation	: Causes serious eye irritation.	
Respiratory or skin sensitization	: Not classified	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Reproductive toxicity	: Not classified	
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness. May cause respiratory irritation.	
Specific target organ toxicity (repeated exposure)	: Not classified	
Aspiration hazard	: Not classified	
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.	

SECTION 12: Ecological information			
12.1.	Toxicity		
No additional information available			
12.2.	Persistence and degradability		
No additio	onal information available		
12.3.	Bioaccumulative potential		
No additio	onal information available		
12.4.	Mobility in soil		
No additional information available			
12.5.	Other adverse effects		

No additional information available

SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.	
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.	
Additional information	: Recycle the material as far as possible.	
SECTION 14: Transport informat	ion	

Department of Transportation (DOT)

Department of Transportation (DOT)	
In accordance with DOT	
Transport document description	: NA1993 Combustible liquid, n.o.s., 3, III
UN-No.(DOT)	: NA1993
Proper Shipping Name (DOT)	: Combustible liquid, n.o.s.
Transport hazard class(es) (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT)	: III - Minor Danger
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Symbols	: D - Proper shipping name for domestic use only, or to and from Canada,G - Identifies PSN requiring a technical name

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	-
DOT Special Provisions (49 CFR 172.102)	 IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HD2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T1 - 1.5 178.274(d)(2) Normal
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Other information	: No supplementary information available.
TDG	

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic

 Substances Control Act (TSCA) inventory except for:

 2-Chloro-1,1,2-trifluoroethyl methyl ether

 CAS No 425-87-6

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

2-Chloro-1,1,2-trifluoroethyl methyl ether (425-87-6)	
Listed on the AICS (Australian Inventory of Chemical Substance	ces)
Listed on the Japanese ISHL (Industrial Safety and Health Law	v)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

100%

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full tex	t of H-phrases:	
	Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
	Flam. Liq. 4	Flammable liquids Category 4
	Skin Irrit. 2	Skin corrosion/irritation Category 2
	STOT SE 3	Specific target organ toxicity (single exposure) Category 3
	STOT SE 3	Specific target organ toxicity (single exposure) Category 3
	H227	Combustible liquid
	H315	Causes skin irritation
	H319	Causes serious eye irritation
	H335	May cause respiratory irritation
	H336	May cause drowsiness or dizziness
	ïre hazard reactivity	 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given. 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur. 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
	II Rating	
Health		: 2 Moderate Hazard - Temporary or minor injury may occur
Flamm	ability	 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)
Physica	al	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.