

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations SDS ID: 2116212

SDS ID: 2116212 Issue date: 16.08.2022 Revision date: 18.12.2023 Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form : Substance

Substance name : Perfluoro-2-methyl-3-oxabutanoyl fluoride

CAS-No. : 2927-83-5
Product code : 2116-2-12
Formula : C4F802

Synonyms : 2,3,3,3-Tetrafluoro-2-(trifluoromethoxy)propanoyl fluoride

Other means of identification : MFCD32011153

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

1.3. Supplier

SynQuest Laboratories, Inc. Inc.

P.O. Box 309

Alachua, FL, Alachua, 32615 United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Gases under pressure Liquefied gas H280 Contains gas under pressure; may explode if heated

Acute toxicity (oral) Category 4 H302 Harmful if swallowed
Acute toxicity (dermal) Category 3 H311 Toxic in contact with skin

Acute toxicity (inhalation) Category 3 H331 Toxic if inhaled

Skin corrosion/irritation Category 1B H314 Causes severe skin burns and eye damage

Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage Specific target organ toxicity – Single exposure, Category 3, H335 May cause respiratory irritation

Respiratory tract irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)









Signal word (GHS US) : Danger

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard statements (GHS US) : H280 - Contains gas under pressure; may explode if heated

H302 - Harmful if swallowed

H311+H331 - Toxic in contact with skin or if inhaled H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage H335 - May cause respiratory irritation

Precautionary statements (GHS US) : P260 - Do not breathe fumes, gas, mist, spray, vapors.

P264 - Wash skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 - If swallowed: Call a POISON CENTER or doctor/ physician if you feel unwell

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P302+P352 - If on skin: Wash with plenty of soap and water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor/ physician

P311 - Call a POISON CENTER or doctor/physician

P321 - Specific treatment (see supplemental first aid instructions on this label)

P322 - Specific treatment (see supplemental first aid instruction on this label)

P330 - Rinse mouth.

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.

P363 - Wash contaminated clothing before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Lachrymator.

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%	GHS US classification
Perfluoro-2-methyl-3-oxabutanoyl fluoride (Main constituent)	CAS-No.: 2927-83-5		Press. Gas (Liq.), H280 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general

: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.

First-aid measures after skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. In case of skin contact, wearing rubber gloves rub 2.5% calcium gluconate gel continuously into the affected area for 1.5 hours or until further medical care is available. Get immediate medical advice/attention.

First-aid measures after eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Immediately flush eyes thoroughly with water for at least 15 minutes. Get immediate medical advice/attention.

First-aid measures after ingestion

Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms

Symptoms/effects

:

: Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).

: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

Symptoms/effects after inhalation

: May cause drowsiness or dizziness. Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media

: Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

5.2. Specific hazards arising from the chemical

Fire hazard

 $: \ \, \hbox{Thermal decomposition generates: Carbon oxides. Hydrogen fluoride}.$

Explosion hazard

 Contains gas under pressure; may explode if heated. Use water spray or fog for cooling exposed containers.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions

: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting

: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.

6.1.1. For non-emergency personnel

Emergency procedures

: Only qualified personnel equipped with suitable protective equipment may intervene.

18.12.2023 (Revision date) EN (English US) 3/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground

level.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so.

Methods for cleaning up : Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Close valve after each use and

when empty.

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Ensure good

ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal

protective equipment. Avoid contact with skin and eyes.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or

smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed

when not in use. Moisture sensitive.

Incompatible materials : Refer to Section 10 on Incompatible Materials.

Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Perfluoro-2-methyl-3-oxabutanoyl fluoride (2927-83-5)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released. Gas detectors should be used when toxic gases may be released.

18.12.2023 (Revision date) EN (English US) 4/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Hand protection:

protective gloves. 29 CFR 1910.138: Hand Protection

Eye protection:

Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

Personal protective equipment symbol(s):









Thermal hazard protection:

Cold insulating gloves.

Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available

Boiling point : 12 - 13

Flash point : No data available : No data available Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) : No data available Vapor pressure : No data available Relative vapor density at 20 °C : No data available Relative density : No data available Molecular mass 232,0288 g/mol Solubility : No data available Partition coefficient n-octanol/water (Log Pow) No data available Auto-ignition temperature No data available Decomposition temperature No data available Viscosity, kinematic : No data available : No data available Viscosity, dynamic : No data available **Explosion limits** Explosive properties : No data available Oxidizing properties : No data available

18.12.2023 (Revision date) EN (English US) 5/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Toxic in contact with skin.

Acute toxicity (inhalation) : Toxic if inhaled.

Skin corrosion/irritation : Causes severe skin burns.
Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Potential Adverse human health effects and symptoms : Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2)

and/or in section 11.

Symptoms/effects after inhalation : May cause drowsiness or dizziness. Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

18.12.2023 (Revision date) EN (English US) 6/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

Perfluoro-2-methyl-3-oxabutanoyl fluoride (2927-83-5)

Persistence and degradability

Not readily biodegradable. May cause long-term adverse effects in the environment. PBT - Persistent, Bioaccumulative and Toxic.

12.3. Bioaccumulative potential

Perfluoro-2-methyl-3-oxabutanoyl fluoride (2927-83-5)

Bioaccumulative potential

Perfluorinated alkanes (PFAs, "forever chemicals") are long lasting, widely used chemicals that break down slowly over time. The potential hazards of PFAs are under investigation and have not been established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods

Sewage disposal recommendations

: See the EPA's Interim Guidance on PFAS Destruction and Disposal.

Prevent runoff from entering drains, sewers or waterways. See the EPA's Interim Guidance on

PFAS Destruction and Disposal.

Product/Packaging disposal recommendations

Additional information

See the EPA's Interim Guidance on PFAS Destruction and Disposal.

: EPA's Interim Guidance on PFAS Destruction and Disposal (Dec. 18, 2020 |

https://downloads.regulations.gov/EPA-HQ-OLEM-2020-0527-0002/content.pdf). The National Defense Authorization Act for Fiscal Year 2020, Public Law No: 116-92 (hereafter, "FY 2020 NDAA"), was signed into law on December 19, 2019. Section 7361 of the FY 2020 NDAA directs the U.S. Environmental Protection Agency (EPA) to publish interim guidance on the destruction and disposal of perfluoroalkyl and polyfluoroalkyl substances (PFAS) and materials containing PFAS. This interim guidance fulfills that direction. EPA will review the interim guidance at least every 3 years and revise it, if appropriate based on the availability of new information or other

factors.

Ecology - waste materials

: Avoid release to the environment. Do not discharge into drains. Take all necessary measures to avoid accidental discharge of products into drains and waterways due to the rupture of

containers or transfer systems.

SECTION 14: Transport information

14.1. UN number

DOT NA No : UN3308 UN-No. (TDG) : Not applicable

UN-No. (IMDG) : 3308 UN-No. (IATA) : 3308

18.12.2023 (Revision date) EN (English US) 7/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Liquefied gas, toxic, corrosive, n.o.s.

Proper Shipping Name (TDG) : Not applicable

Proper Shipping Name (IMDG) : LIQUEFIED GAS, TOXIC, CORROSIVE, N.O.S.

Proper Shipping Name (IATA) : Liquefied gas, toxic, corrosive, n.o.s.

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 2.3 (8) Hazard labels (DOT) : 2.3, 8





TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : 2.3 (8) Hazard labels (IMDG) : 2.3, 8





IATA

Transport hazard class(es) (IATA) : 2.3 (8)

14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (TDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN3308

DOT Special Provisions (49 CFR 172.102) : 2 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zone B (see

173.116(a) or 173.133(a) of this subchapter), and must be described as an inhalation hazard under the provisions of this subchapter.

B9 - Bottom outlets are not authorized.

B14 - Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insulated with an insulating material so that the overall thermal conductance at 15.5 C (60 F) is no more than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour per square foot per degree Fahrenheit) temperature differential. Insulating materials must not

promote corrosion to steel when wet.

DOT Packaging Exceptions (49 CFR 173.xxx) : None
DOT Packaging Non Bulk (49 CFR 173.xxx) : 304
DOT Packaging Bulk (49 CFR 173.xxx) : 314, 315
DOT Quantity Limitations Passenger aircraft/rail (49 : Forbidden

CFR 173.27)

Safety Data Sheet

DOT Vessel Stowage Location

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

: D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel

carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger

vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

TDG

Not applicable

IMDG

Special provision (IMDG) : 274
Limited quantities (IMDG) : 0
Excepted quantities (IMDG) : E0
Packing instructions (IMDG) : P200

EmS-No. (Fire) : F-C - FIRE SCHEDULE Charlie - NON-FLAMMABLE GASES

: Forbidden

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : D Stowage and handling (IMDG) : SW2

IATA

PCA Limited quantities (IATA) : Forbidden PCA limited quantity max net quantity (IATA) : Forbidden PCA packing instructions (IATA) : Forbidden PCA max net quantity (IATA) : Forbidden CAO packing instructions (IATA) : Forbidden CAO max net quantity (IATA) : Forbidden Special provision (IATA) : A2 ERG code (IATA) 2CP

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

Perfluoro-2-methyl-3-oxabutanoyl fluoride (2927-83-5)

Listed on the Canadian NDSL (Non-Domestic Substances List)

EU-Regulations

Perfluoro-2-methyl-3-oxabutanoyl fluoride (2927-83-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Perfluoro-2-methyl-3-oxabutanoyl fluoride (2927-83-5)

Listed on the Japanese ISHL (Industrial Safety and Health Law)

18.12.2023 (Revision date) EN (English US) 9/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 18.12.2023

Full text of H-phrases		
H280	Contains gas under pressure; may explode if heated	
H302	Harmful if swallowed	
H311	Toxic in contact with skin	
H314	Causes severe skin burns and eye damage	
H318	Causes serious eye damage	
H331	Toxic if inhaled	
H335	May cause respiratory irritation	

NFPA health hazard

 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard


: 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and

sand.

NFPA reactivity

: 1 - Materials that in themselves are normally stable but can become

unstable at elevated temperatures and pressures.



Hazard Rating

Health

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability

Physical

- : 0 Minimal Hazard Materials that will not burn
- : 1 Slight Hazard Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous

polymerization in the absence of inhibitors.

Safety Data Sheet (SDS), USA