

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations SDS ID: 2116501

Issue date: 3/30/2022 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form Substance Substance name acetyl chloride Chemical name acetyl chloride CAS-No. : 75-36-5 Product code : 2116-5-01 Formula : C2H3CIO Other means of identification : MFCD00000719

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

1.3. Supplier

SynQuest Laboratories, Inc. Inc. P.O. Box 309

Alachua, FL, Alachua, 32615 United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

1.4. Emergency telephone number

: (844) 523-4086 (3E Company - Account 10069) Emergency number

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

H225 Flammable liquids Category 2 Highly flammable liquid and vapor

Acute toxicity (oral) Category 4 H302 Harmful if swallowed Acute toxicity (inhalation) Category 4 H332 Harmful if inhaled

Skin corrosion/irritation Category 1B H314 Causes severe skin burns and eye damage

Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage Specific target organ toxicity - Single exposure, Category 3, H335 May cause respiratory irritation

Respiratory tract irritation

Hazardous to the aquatic environment - Acute Hazard Category 3 H402 Harmful to aquatic life

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)







Signal word (GHS US) : Danger

Precautionary statements (GHS US)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor

H302+H332 - Harmful if swallowed or if inhaled

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage H335 - May cause respiratory irritation

H402 - Harmful to aquatic life

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe fumes, mist, spray, vapors.

P264 - Wash skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 - If swallowed: Call a POISON CENTER or doctor/ physician if you feel unwell

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor/ physician

P321 - Specific treatment (see supplemental first aid instructions on this label)

P330 - Rinse mouth.

P363 - Wash contaminated clothing before reuse.

P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Lachrymator. Reacts violently with water. Stench. Contact with water liberates toxic gas.

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent

3/30/2022 (Issue date) EN (English US) 2/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
acetyl chloride (Main constituent)	CAS-No.: 75-36-5	≤ 100	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label where

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.

possible). Move the affected personnel away from the contaminated area.

First-aid measures after skin contact : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Get immediate

medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

Symptoms/effects after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Dry powder. Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen chloride.

Explosion hazard : Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed

containers. May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

3/30/2022 (Issue date) EN (English US) 3/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes,

vapor or spray.

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground

level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of

ignition.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

Methods for cleaning up : Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into

appropriate container for disposal. Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep container closed when not in use. Keep away from ignition sources. Moisture sensitive.

Keep contents under inert gas.

Incompatible materials : Refer to Section 10 on Incompatible Materials.

Information on mixed storage : Do not store with: Water.

Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

3/30/2022 (Issue date) EN (English US) 4/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

acetyl chloride (75-36-5)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

protective gloves. 29 CFR 1910.138: Hand Protection

Eye protection:

Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

Personal protective equipment symbol(s):









Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Colorless liquid.
Color : Colorless
Odor : sharp

Odor threshold : No data available pH : No data available Melting point : -112.8 °C Freezing point : No data available

Boiling point : $50.7 \,^{\circ}\text{C}$ Flash point : $4 \,^{\circ}\text{C}$

Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : No data available
Vapor pressure : 320 hPa (at 20 °C)
Relative vapor density at 20 °C : No data available
Relative density : No data available
Density : 1.1051 g/cm³ (at 20 °C)

Molecular mass : 78.49 g/mol Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available

Auto-ignition temperature : 390 °C

Decomposition temperature : No data available

3/30/2022 (Issue date) EN (English US) 5/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available

9.2. Other information

Refractive index : 1.389 (@ 20 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Reacts violently with water.

10.4. Conditions to avoid

Keep away from heat, sparks and flame. Moisture.

10.5. Incompatible materials

Bases. Strong oxidizing agents. Water.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

acetyl chloride (75-36-5)	
LD50 oral rat	910 mg/kg
ATE US (oral)	910 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns.
Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2)

and/or in section 11.

Symptoms/effects after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea.

SECTION 12: Ecological information

12.1. Toxicity

acetyl chloride (75-36-5)

LC50 - Fish [1] 25.2 – 70 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste) : U.S. - RCRA (Resource Conservation Recovery Act) - U Series Wastes - Acutely Toxic Wastes

Other Hazardous Characteristics. U.S. - RCRA (Resource Conservation Recovery Act) -

Hazardous Constituents - Appendix VIII to 40 CFR 261.

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

: 1717

SECTION 14: Transport information

14.1. UN number

UN-No. (IATA)

DOT NA No : UN1717
UN-No. (TDG) : Not applicable
UN-No. (IMDG) : 1717

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Acetyl chloride
Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : ACETYL CHLORIDE

3/30/2022 (Issue date) EN (English US) 7/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (IATA) : Acetyl chloride

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 3 (8) Hazard labels (DOT) : 3, 8





TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : 3 (8) Hazard labels (IMDG) : 3, 8



IATA

Transport hazard class(es) (IATA) : 3 (8) Hazard labels (IATA) : 3, 8





14.4. Packing group

Packing group (DOT) : II

Packing group (TDG) : Not applicable

Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1717

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: A3 - For combination packaging, if glass inner packaging (including ampoules) are used, they must be packed with absorbent material in tightly closed metal receptacles before packing in outer packaging.

A6 - For combination packaging, if plastic inner packaging are used, they must be packed in tightly closed metal receptacles before packing in outer packaging.

A7 - Steel packaging must be corrosion-resistant or have protection against corrosion.

IB1 - Authorized IBCs: Metal (31A, 31B and 31N). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

N34 - Aluminum construction materials are not authorized for any part of a packaging which is normally in contact with the hazardous material.

T8 - 4 178.274(d)(2) Normal..... Prohibited

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP12 - This material is considered highly corrosive to steel.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 243
DOT Quantity Limitations Passenger aircraft/rail (49 : 1 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 5 L

CFR 175.75)

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

TDG

Emergency Response Guide (ERG) Number : 155

IMDG

Limited quantities (IMDG) : 1 L

Excepted quantities (IMDG) : E2

Packing instructions (IMDG) : P001

IBC packing instructions (IMDG) : IBC02

IBC special provisions (IMDG) : B20

Tank instructions (IMDG) : T8

Tank special provisions (IMDG) : TP2

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS EmS-No. (Spillage) : S-C - SPILLAGE SCHEDULE Charlie - FLAMMABLE CORROSIVE LIQUIDS

Stowage category (IMDG) : B
Stowage and handling (IMDG) : SW2
Flash point (IMDG) : 5°C c.c.

IATA

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y340
PCA limited quantity max net quantity (IATA) : 0.5L
PCA packing instructions (IATA) : 352
PCA max net quantity (IATA) : 1L
CAO packing instructions (IATA) : 363

3/30/2022 (Issue date) EN (English US) 9/11

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CAO max net quantity (IATA) : 5L ERG code (IATA) : 3C

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

acetyl chloride (75-36-5)

CERCLA RQ 5000 lb

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

acetyl chloride (75-36-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

acetyl chloride (75-36-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

acetyl chloride (75-36-5)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Japanese ENCS (Existing New Chemical Substances) inventory

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

Listed on the NCI (Vietnam - National Chemical Inventory)

15.3. US State regulations

acetyl chloride (75-36-5)	
J	U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List U.S Massachusetts - Right To Know List U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H332	Harmful if inhaled
H335	May cause respiratory irritation
H402	Harmful to aquatic life

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can

be ignited under almost all ambient temperature conditions.

: 2 - Materials that readily undergo violent chemical change at elevated

temperatures and pressures.

NFPA specific hazard : W - Materials that react violently or explosively with water.

3 3 W

Hazard Rating

NFPA reactivity

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

giveri

Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well

as liquids with flash points between 73 F and 100 F. (Classes IB IC)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous

polymerization in the absence of inhibitors.

Safety Data Sheet (SDS), USA

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

3/30/2022 (Issue date) EN (English US) 11/11