

# Hexafluoroacetone

## Safety Data Sheet 2117204

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 07/11/2016

Revision date: 11/28/2017

Version: 1.1

### SECTION 1: Identification

#### 1.1. Identification

Product form	: Substance
Substance name	: Hexafluoroacetone
CAS No	: 684-16-2
Product code	: 2117-2-04
Formula	: C3F6O
Synonyms	: 1,1,1,3,3,3-Hexafluoro-2-propanone
Other means of identification	: MFCD00000422

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
------------------------------	--

#### 1.3. Details of the supplier of the safety data sheet

SynQuest Laboratories, Inc.  
P.O. Box 309  
Alachua, FL 32615 - United States of America  
T (386) 462-0788 - F (386) 462-7097  
[info@synquestlabs.com](mailto:info@synquestlabs.com) - [www.synquestlabs.com](http://www.synquestlabs.com)

#### 1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Liquefied gas	H280 - Contains gas under pressure; may explode if heated
Acute Tox. 3 (Oral)	H301 - Toxic if swallowed
Acute Tox. 3 (Dermal)	H311 - Toxic in contact with skin
Acute Tox. 2 (Inhalation)	H330 - Fatal if inhaled
Skin Corr. 1B	H314 - Causes severe skin burns and eye damage
Eye Dam. 1	H318 - Causes serious eye damage
Repr. 1B	H360 - May damage fertility or the unborn child
STOT SE 3	H335 - May cause respiratory irritation

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H280 - Contains gas under pressure; may explode if heated  
H301+H311 - Toxic if swallowed or in contact with skin  
H314 - Causes severe skin burns and eye damage  
H330 - Fatal if inhaled  
H335 - May cause respiratory irritation  
H360 - May damage fertility or the unborn child

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P260 - Do not breathe fumes, gas, mist, spray, vapors  
P264 - Wash skin thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P284 - In case of inadequate ventilation wear respiratory protection

# Hexafluoroacetone

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P301+P310 - If swallowed: Immediately call a poison center/doctor/...  
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting  
P302+P352 - If on skin: Wash with plenty of soap and water  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P310 - Immediately call a POISON CENTER or doctor/ physician  
P320 - Specific treatment is urgent (see supplemental first aid instructions on this label)  
P321 - Specific treatment (see supplemental first aid instructions on this label)  
P330 - Rinse mouth  
P361 - Take off immediately all contaminated clothing  
P363 - Wash contaminated clothing before reuse  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P405 - Store locked up  
P410+P403 - Protect from sunlight. Store in a well-ventilated place  
P501 - Dispose of contents/container to an approved waste disposal plant

### 2.3. Other hazards

Other hazards not contributing to the classification : Reacts violently with water.

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
Hexafluoroacetone (Main constituent)	(CAS No) 684-16-2	<= 100	Liquefied gas, H280 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Repr. 1B, H360 STOT SE 3, H335

Full text of H-phrases: see section 16

### 3.2. Mixture

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.

First-aid measures after skin contact : Thaw frosted parts with lukewarm water. Do not rub affected area. Remove contaminated clothing and shoes. Get immediate medical advice/attention.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention. Immediately flush eyes thoroughly with water for at least 15 minutes.

First-aid measures after ingestion : Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

Symptoms/injuries after inhalation : May cause drowsiness or dizziness. Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

Symptoms/injuries after skin contact : Contact with the liquid the may cause cold burns/frostbite.

Symptoms/injuries after eye contact : Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

# Hexafluoroacetone

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Dry powder. Use extinguishing media appropriate for surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen fluoride.  
Explosion hazard : Contains gas under pressure; may explode if heated. Use water spray or fog for cooling exposed containers.

### 5.3. Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.  
Protection during firefighting : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.

#### 6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so.  
Methods for cleaning up : Ventilate area.  
Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Close valve after each use and when empty.  
Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes.  
Safe handling of the gas receptacle : Securely chain cylinders when in use and protect against physical damage.  
Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.  
Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed when not in use. Moisture sensitive.  
Incompatible materials : Refer to Section 10 on Incompatible Materials.  
Storage area : Store in dry, cool, well-ventilated area.

# Hexafluoroacetone

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Hexafluoroacetone (684-16-2)		
ACGIH	ACGIH TWA (ppm)	0.1 ppm
ACGIH	Remark (ACGIH)	Testicular dam; kidney dam

#### 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularly checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released. Gas detectors should be used when toxic gases may be released.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Thermal hazard protection	: Cold insulating gloves.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Colorless gas.
Color	: Colorless
Odor	: No data available
Odor threshold	: No data available
pH	: No data available
Melting point	: -129 °C
Freezing point	: No data available
Boiling point	: -28 °C
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: 87.0 psig (@ 21 °C)
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.32 g/ml (@ 25 °C)
Molecular mass	: 166.02 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

#### 9.2. Other information

No additional information available

# Hexafluoroacetone

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

#### 10.3. Possibility of hazardous reactions

Reacts violently with water.

#### 10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

#### 10.5. Incompatible materials

Strong oxidizing agents. Water.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation: Fatal if inhaled.

Hexafluoroacetone (684-16-2)	
LC50 inhalation rat (ppm)	300 ppm/4h
ATE US (gases)	300.000 ppmV/4h

Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: May damage fertility or the unborn child.
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness. Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.
Symptoms/injuries after skin contact	: Contact with the liquid the may cause cold burns/frostbite.
Symptoms/injuries after eye contact	: Direct contact with the liquefied gas may cause severe and possibly permanent eye injury due to frostbite from rapid liquid evaporation.

### SECTION 12: Ecological information

#### 12.1. Toxicity

No additional information available

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

# Hexafluoroacetone

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

- Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
- Waste disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Additional information : Recycle the material as far as possible.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

- Transport document description : UN2420 Hexafluoroacetone, 2.3
- UN-No.(DOT) : UN2420
- Proper Shipping Name (DOT) : Hexafluoroacetone
- Transport hazard class(es) (DOT) : 2.3 - Class 2.3 - Poisonous gas 49 CFR 173.115
- Hazard labels (DOT) : 2.3 - Poison gas  
8 - Corrosive



- DOT Packaging Non Bulk (49 CFR 173.xxx) : 304
- DOT Packaging Bulk (49 CFR 173.xxx) : 314;315
- DOT Special Provisions (49 CFR 172.102) : 2 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zone B (see 173.116(a) or 173.133(a) of this subchapter), and must be described as an inhalation hazard under the provisions of this subchapter.  
B9 - Bottom outlets are not authorized.  
B14 - Each bulk packaging, except a tank car or a multi-unit-tank car tank, must be insulated with an insulating material so that the overall thermal conductance at 15.5 C (60 F) is no more than 1.5333 kilojoules per hour per square meter per degree Celsius (0.075 Btu per hour per square foot per degree Fahrenheit) temperature differential. Insulating materials must not promote corrosion to steel when wet.
- DOT Packaging Exceptions (49 CFR 173.xxx) : None
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : Forbidden
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : Forbidden
- DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.
- DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"
- Emergency Response Guide (ERG) Number : 125 (UN2420);151 (UN2552)
- Other information : No supplementary information available.

#### TDG

No additional information available

#### Transport by sea

- UN-No. (IMDG) : 2420
- Proper Shipping Name (IMDG) : HEXAFLUOROACETONE
- Class (IMDG) : 2 - Gases

#### Air transport

- UN-No. (IATA) : 2420
- Proper Shipping Name (IATA) : Hexafluoroacetone
- Class (IATA) : 2

# Hexafluoroacetone

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### Hexafluoroacetone (684-16-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### 15.2. International regulations

##### CANADA

##### Hexafluoroacetone (684-16-2)

Listed on the Canadian NDSL (Non-Domestic Substances List)

WHMIS Classification

Class A - Compressed Gas  
Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects  
Class D Division 2 Subdivision A - Very toxic material causing other toxic effects  
Class E - Corrosive Material

##### EU-Regulations

No additional information available

##### National regulations

##### Hexafluoroacetone (684-16-2)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the Canadian IDL (Ingredient Disclosure List)  
Listed on INSQ (Mexican national Inventory of Chemical Substances)

#### 15.3. US State regulations

##### Hexafluoroacetone (684-16-2)

U.S. - California - Proposition 65 - Carcinogens List

No

U.S. - California - Proposition 65 - Developmental Toxicity

Yes

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

No

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

Yes

State or local regulations

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

### SECTION 16: Other information

Revision date

: 11/28/2017

# Hexafluoroacetone

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Full text of H-phrases:

Acute Tox. 2 (Inhalation)	Acute toxicity (inhalation) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Liquefied gas	Gases under pressure Liquefied gas
Repr. 1B	Reproductive toxicity Category 1B
Skin Corr. 1B	Skin corrosion/irritation Category 1B
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H330	Fatal if inhaled
H335	May cause respiratory irritation
H360	May damage fertility or the unborn child

### NFPA health hazard


: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

### NFPA fire hazard

: 1 - Must be preheated before ignition can occur.

### NFPA reactivity

: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



### HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

### Flammability

: 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

### Physical

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

### SDS US (GHS HazCom 2012)

*The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.*