

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS ID: 2117503

Issue date: 10/31/2022 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form Substance

1,1-Dichloroacetone Substance name

CAS-No. 513-88-2 : 2117-5-03 Product code Formula : C3H4Cl2O Other means of identification : MFCD00009677

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

1.3. Supplier

SynQuest Laboratories, Inc. Inc.

P.O. Box 309

Alachua, FL, Alachua, 32615

United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

1.4. Emergency telephone number

: (844) 523-4086 (3E Company - Account 10069) Emergency number

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 3 H226 Flammable liquid and vapor

Skin corrosion/irritation Category 1A Causes severe skin burns and eye damage H314

Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage Specific target organ toxicity - Single exposure, Category 3, H335 May cause respiratory irritation

Respiratory tract irritation

Hazardous to the aquatic environment - Acute Hazard Category 1 H400 Very toxic to aquatic life

Hazardous to the aquatic environment - Chronic Hazard Category 1 H410 Very toxic to aquatic life with long lasting effects

Full text of H statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)









Signal word (GHS US)

: Danger Hazard statements (GHS US)

H226 - Flammable liquid and vapor

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

Precautionary statements (GHS US)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H335 - May cause respiratory irritation

H410 - Very toxic to aquatic life with long lasting effects

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P264 - Wash skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

 ${\tt P305+P351+P338-IF\ IN\ EYES: Rinse\ cautiously\ with\ water\ for\ several\ minutes.\ Remove}$

contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor/ physician

P321 - Specific treatment (see supplemental first aid instructions on this label)

P363 - Wash contaminated clothing before reuse.

P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P391 - Collect spillage.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Lachrymator, vapors may form explosive mixture with air.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%	GHS US classification
1,1-Dichloroacetone (Main constituent)	CAS-No.: 513-88-2	≤ 100	Flam. Liq. 3, H226 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

10/31/2022 (Issue date) EN (English US) 2/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial

respiration. Get immediate medical advice/attention.

First-aid measures after skin contact : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Get immediate

medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2)

and/or in section 11.

Symptoms/effects after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

5.2. Specific hazards arising from the chemical

Explosion hazard : Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes, vapor or spray.

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

10/31/2022 (Issue date) EN (English US) 3/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency procedures

: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment

Other information

: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

Methods for cleaning up

Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosionproof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.

: For disposal of solid materials or residues refer to section 13: "Disposal considerations".

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

- : Handle empty containers with care because residual vapors are flammable.
- Precautions for safe handling
- : Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Hygiene measures

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Comply with applicable regulations.

Storage conditions

: Keep container closed when not in use. Keep away from ignition sources. Hygroscopic. Keep

contents under inert gas.

Incompatible materials

: Refer to Section 10 on Incompatible Materials.

Storage area

: Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1,1-Dichloroacetone (513-88-2)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

protective gloves. 29 CFR 1910.138: Hand Protection

10/31/2022 (Issue date) EN (English US) 4/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection:

Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

Personal protective equipment symbol(s):









Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : 117 – 120 °C

Flash point : 46 °C

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Vapor pressure : No data available Relative vapor density at 20 °C : No data available Relative density No data available Density 1.299 g/ml (@ 20 °C) Molecular mass 126.969 g/mol Solubility No data available Partition coefficient n-octanol/water (Log Pow) No data available : No data available Auto-ignition temperature Decomposition temperature : No data available Viscosity, kinematic No data available No data available Viscosity, dynamic **Explosion limits** No data available Explosive properties No data available

9.2. Other information

Oxidizing properties

Refractive index : 1.4472 (@ 20 °C)

No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with water, generates gases or heat. Reacts on exposure to water with some metals to release highly explosive/flammable hydrogen gas.

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from heat, sparks and flame. Moisture.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Causes severe skin burns.
Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2)

and/or in section 11.

Symptoms/effects after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

10/31/2022 (Issue date) EN (English US) 6/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

SECTION 14: Transport information

14.1. UN number

DOT NA No : UN1992
UN-No. (TDG) : Not applicable
UN-No. (IMDG) : 1992
UN-No. (IATA) : 1992

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Flammable liquids, toxic, n.o.s.

Proper Shipping Name (TDG) : Not applicable

Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, TOXIC, N.O.S. Proper Shipping Name (IATA) : Flammable liquid, toxic, n.o.s.

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 3 (6.1) Hazard labels (DOT) : 3, 6.1



TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : 3 (6.1) Hazard labels (IMDG) : 3, 6.1



Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IATA

Transport hazard class(es) (IATA) : 3 (6.1) Hazard labels (IATA) : 3, 6.1



14.4. Packing group

Packing group (DOT) : 111

Packing group (TDG) : Not applicable

Packing group (IMDG) : III : 111 Packing group (IATA)

14.5. Environmental hazards

Dangerous for the environment : Yes Marine pollutant : Yes



Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1992

DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a

flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this

subchapter are applicable.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

: 220 L

DOT Packaging Exceptions (49 CFR 173.xxx) 150 DOT Packaging Non Bulk (49 CFR 173.xxx) 203 DOT Packaging Bulk (49 CFR 173.xxx) 242 DOT Quantity Limitations Passenger aircraft/rail (49 : 60 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

TDG

Emergency Response Guide (ERG) Number : 131

10/31/2022 (Issue date) EN (English US) 8/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IMDG

Special provision (IMDG) : 223, 274

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : P001

IBC packing instructions (IMDG) : IBC03

Tank instructions (IMDG) : T7

Tank special provisions (IMDG) : TP1, TP28

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS

EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS

Stowage category (IMDG) : A

Properties and observations (IMDG) : Flammable toxic liquid which is not specified by name in this class or, on account of its characteristics, in some other class. Toxic if swallowed, by skin contact or by inhalation.

IATA

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Y343 PCA limited quantity max net quantity (IATA) : 2L PCA packing instructions (IATA) : 355 PCA max net quantity (IATA) : 60L CAO packing instructions (IATA) : 366 : 220L CAO max net quantity (IATA) Special provision (IATA) : A3 ERG code (IATA) 3P

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

1,1-Dichloroacetone CAS-No. 513-88-2 100%

15.2. International regulations

CANADA

No additional information available

EU-Regulations

1,1-Dichloroacetone (513-88-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

1,1-Dichloroacetone (513-88-2)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Japanese ENCS (Existing New Chemical Substances) inventory

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

10/31/2022 (Issue date) EN (English US) 9/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases		
H226	Flammable liquid and vapor	
H314	Causes severe skin burns and eye damage	
H318	Causes serious eye damage	
H335	May cause respiratory irritation	
H400	Very toxic to aquatic life	
H410	Very toxic to aquatic life with long lasting effects	


NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or

permanent injury.

NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

: 1 - Materials that in themselves are normally stable but can become

unstable at elevated temperatures and pressures.



Hazard Rating

NFPA reactivity

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F

but below 200 F. (Classes II IIIA)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous

polymerization in the absence of inhibitors.

Safety Data Sheet (SDS), USA

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.