

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations SDS ID: 2118318

Issue date: 12/19/2022 Version: 1.0

# **SECTION 1: Identification**

### 1.1. Identification

Product form : Substance

Substance name 1,1,1-Trifluorohexane-2,4-dione

CAS-No. 400-54-4 Product code : 2118-3-18 Formula : C6H7F3O2

Synonyms : 1-(Trifluoroacetyl)butan-2-one; 2,4-Dioxo-1,1,1-trifluorohexane

Other means of identification : MFCD00051306

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

## 1.3. Supplier

SynQuest Laboratories, Inc. Inc.

P.O. Box 309

Alachua, FL, Alachua, 32615

United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

## 1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

## **SECTION 2: Hazard(s) identification**

## 2.1. Classification of the substance or mixture

#### **GHS US classification**

Flammable liquids Category 3	H226	Flammable liquid and vapor
Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Acute toxicity (dermal) Category 4	H312	Harmful in contact with skin
Acute toxicity (inhalation) Category 4	H332	Harmful if inhaled
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319	Causes serious eye irritation
Specific target organ toxicity – Single exposure, Category 3,	H335	May cause respiratory irritation

Respiratory tract irritation

H402 Harmful to aquatic life Hazardous to the aquatic environment - Acute Hazard Category 3

Full text of H statements : see section 16

# 2.2. GHS Label elements, including precautionary statements

#### **GHS US labeling**

Hazard pictograms (GHS US)





Signal word (GHS US) : Warning

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard statements (GHS US) : H226 - Flammable liquid and vapor

H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled

H315 - Causes skin irritation

H319 - Causes serious eye irritation H335 - May cause respiratory irritation

H402 - Harmful to aquatic life

Precautionary statements (GHS US) : P210 - Keep away from heat, hot sur

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing fumes, mist, spray, vapors.

P264 - Wash skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 - If swallowed: Call a POISON CENTER or doctor/ physician if you feel unwell

P302+P352 - If on skin: Wash with plenty of soap and water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell

P321 - Specific treatment (see supplemental first aid instructions on this label)

P322 - Specific treatment (see supplemental first aid instruction on this label)

P330 - Rinse mouth.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to an approved waste disposal plant

## 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

# **SECTION 3: Composition/Information on ingredients**

### 3.1. Substances

Substance type : Mono-constituent

12/19/2022 (Issue date) EN (English US) 2/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
1,1,1-Trifluorohexane-2,4-dione (Main constituent)	CAS-No.: 400-54-4		Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Acute 3, H402

Full text of hazard classes and H-statements : see section 16

#### 3.2. Mixtures

Not applicable

### **SECTION 4: First-aid measures**

## 4.1. Description of first aid measures

First-aid measures after eye contact

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial

respiration. Get immediate medical advice/attention.

First-aid measures after skin contact : Wash with plenty of soap and water. Get immediate medical advice/attention.

Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth

out with water. Get immediate medical advice/attention.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2)

and/or in section 11.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## **SECTION 5: Fire-fighting measures**

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media

appropriate for surrounding fire.

## 5.2. Specific hazards arising from the chemical

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen fluoride.

Explosion hazard When mixed with air and exposed to an ignition source, dust may burn in the open air or explode

if confined.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

12/19/2022 (Issue date) EN (English US) 3/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes,

vapor or spray.

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground

level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of

ignition.

## 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

Methods for cleaning up : Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-

proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

#### 6.4. Reference to other sections

No additional information available

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or

smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep container closed when not in use. Keep away from ignition sources. Moisture sensitive.

Keep contents under inert gas.

Incompatible materials : Refer to Section 10 on Incompatible Materials. Storage temperature : 2 – 8 °C Use explosion proof refrigerator

Storage area : Store in dry, well-ventilated area.

# SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

12/19/2022 (Issue date) EN (English US) 4/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 1,1,1-Trifluorohexane-2,4-dione (400-54-4)

No additional information available

#### 8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

protective gloves. 29 CFR 1910.138: Hand Protection

#### Eye protection:

Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

#### Personal protective equipment symbol(s):









#### Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

No data available Color Odor No data available Odor threshold No data available рН No data available Melting point No data available Freezing point : No data available Boiling point : 123 - 125 °C Flash point 28 °C

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) No data available No data available Vapor pressure Relative vapor density at 20 °C No data available Relative density No data available 1.22 g/ml Density Molecular mass 168.1138 g/mol Solubility No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available

Decomposition temperature : No data available Viscosity, kinematic : No data available

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, dynamic : No data available
Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available

### 9.2. Other information

Refractive index : 1.395 (@ 20 °C)

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

## 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

Keep away from heat, sparks and flame.

### 10.5. Incompatible materials

Bases. Strong oxidizing agents.

## 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

# **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Harmful in contact with skin.

Acute toxicity (inhalation) : Harmful if inhaled.

1,1,1-Trifluorohexane-2,4-dione (400-54-4)		
ATE US (oral)	500 mg/kg body weight	
ATE US (dermal)	1100 mg/kg body weight	
ATE US (gases)	4500 ppmV/4h	
ATE US (vapors)	11 mg/l/4h	
ATE US (dust, mist)	1.5 mg/l/4h	

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

12/19/2022 (Issue date) EN (English US) 6/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2)

and/or in section 11.

# **SECTION 12: Ecological information**

## 12.1. Toxicity

No additional information available

## 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Waste treatment methods

Product/Packaging disposal recommendations

Additional information

: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Dispose of contents/container in accordance with licensed collector's sorting instructions.

: Recycle the material as far as possible.

# **SECTION 14: Transport information**

#### **14.1. UN number**

DOT NA No : UN1224 UN-No. (TDG) : Not applicable UN-No. (IMDG) : 1224 UN-No. (IATA) : 1224

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Ketones, liquid, n.o.s. Proper Shipping Name (TDG) : Not applicable

Proper Shipping Name (IMDG) : KETONES, LIQUID, N.O.S. Proper Shipping Name (IATA) : Ketones, liquid, n.o.s.

#### 14.3. Transport hazard class(es)

# DOT

Transport hazard class(es) (DOT) : 3 Hazard labels (DOT) : 3

12/19/2022 (Issue date) EN (English US) 7/10

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



#### **TDG**

Transport hazard class(es) (TDG) : Not applicable

#### **IMDG**

Transport hazard class(es) (IMDG) : 3
Hazard labels (IMDG) : 3



#### IATA

Transport hazard class(es) (IATA) : 3
Hazard labels (IATA) : 3



## 14.4. Packing group

Packing group (DOT) : III

Packing group (TDG) : Not applicable

Packing group (IMDG) : III
Packing group (IATA) : III

### 14.5. Environmental hazards

Other information : No supplementary information available.

## 14.6. Special precautions for user

#### DOT

UN-No.(DOT) : UN1224

DOT Special Provisions (49 CFR 172.102)

: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : 60 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

**TDG** 

Emergency Response Guide (ERG) Number : 127

**IMDG** 

Special provision (IMDG) : 223, 274
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01

IBC packing instructions (IMDG): IBC03Tank instructions (IMDG): T4Tank special provisions (IMDG): TP1, TP29

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS

EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS

Stowage category (IMDG) : A

**IATA** 

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Y344 PCA limited quantity max net quantity (IATA) : 10L PCA packing instructions (IATA) 355 PCA max net quantity (IATA) 60L CAO packing instructions (IATA) 366 CAO max net quantity (IATA) 220L Special provision (IATA) : A3 ERG code (IATA) : 3L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## **SECTION 15: Regulatory information**

## 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

1,1,1-Trifluorohexane-2,4-dione CAS-No. 400-54-4 100%

## 15.2. International regulations

#### CANADA

#### 1,1,1-Trifluorohexane-2,4-dione (400-54-4)

Listed on the Canadian NDSL (Non-Domestic Substances List)

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **EU-Regulations**

### 1,1,1-Trifluorohexane-2,4-dione (400-54-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### **National regulations**

#### 1,1,1-Trifluorohexane-2,4-dione (400-54-4)

Listed on the NCI (Vietnam - National Chemical Inventory)

## 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

### **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases		
H226	Flammable liquid and vapor	
H302	Harmful if swallowed	
H312	Harmful in contact with skin	
H315	Causes skin irritation	
H319	Causes serious eye irritation	
H332	Harmful if inhaled	
H335	May cause respiratory irritation	
H402	Harmful to aquatic life	

NFPA health hazard

: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.


NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire

conditions.



Hazard Rating

Health

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

Flammability

3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB IC)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Safety Data Sheet (SDS), USA

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.