

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations SDS ID: 212131N Issue date: 13.11.2020 Revision date: 18.12.2023 Version: 1.1

#### **SECTION 1: Identification** 1.1. Identification Product form · Substance Perfluoro-2,5-dimethyl-3,6-dioxaheptanoic acid Substance name · CAS-No. : 2479-73-4 Product code : 2121-3-1N Formula : C7HF13O4 Synonyms : 2,3,3,3-Tetrafluoro-2-[1,1,2,3,3,3-hexafluoro-2-(trifluoromethoxy)propoxy]propanoic acid Other means of identification : MFCD32011159 1.2. Recommended use and restrictions on use Use of the substance/mixture : Laboratory chemicals Manufacture of substances Scientific research and development 1.3. Supplier SvnQuest Laboratories. Inc. Inc. P.O. Box 309 Alachua, FL, Alachua, 32615 United States of America T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlabs.com 1.4. Emergency telephone number : (844) 523-4086 (3E Company - Account 10069) Emergency number SECTION 2: Hazard(s) identification 2.1. Classification of the substance or mixture **GHS US classification** H314 Skin corrosion/irritation Category 1B Causes severe skin burns and eye damage Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage Specific target organ toxicity - Single exposure, Category 3, May cause respiratory irritation H335 Respiratory tract irritation Full text of H statements : see section 16 2.2. GHS Label elements, including precautionary statements

#### **GHS US labeling**

Hazard pictograms (GHS US)

:		
:	Danger	

Signal word (GHS US) Hazard statements (GHS US)

Precautionary statements (GHS US)

H335 - May cause respiratory irritation : P260 - Do not breathe fumes, mist, spray, vapors. P264 - Wash skin thoroughly after handling

: H314 - Causes severe skin burns and eye damage

P271 - Use only outdoors or in a well-ventilated area.

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor/ physician

P321 - Specific treatment (see supplemental first aid instructions on this label)

P363 - Wash contaminated clothing before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container to an approved waste disposal plant

#### 2.3. Other hazards which do not result in classification

#### No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

#### **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Substance type

: Mono-constituent

Name	Product identifier	%	GHS US classification
Perfluoro-2,5-dimethyl-3,6-dioxaheptanoic acid (Main constituent)	CAS-No.: 2479-73-4		Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

#### 3.2. Mixtures

Not applicable

SECTION 4: First-aid measures		
4.1. Description of first aid measures		
First-aid measures general	: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.	
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.	
First-aid measures after skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Get immediate medical advice/attention.	
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.	
First-aid measures after ingestion	: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.	
4.2. Most important symptoms and effe	ects (acute and delayed)	

 Symptoms/effects
 : The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after inhalation	
-----------------------------------	--

: Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures		
5.1. Suitable (and unsuitable) extinguishing r	nedia	
Suitable extinguishing media :	Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.	
5.2. Specific hazards arising from the chemic	al	
Fire hazard:Explosion hazard:	Thermal decomposition generates: Carbon oxides. Hydrogen fluoride. Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed containers.	
5.3. Special protective equipment and precau	itions for fire-fighters	
Firefighting instructions       :         Protection during firefighting       :	In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".	

SECTION 6: Accidental release measures 6.1. Personal precautions, protective equipment and emergency procedures			
			General measures
6.1.1. For non-emergency personnel			
Emergency procedures	Only qualified personnel equipped with suitable protective equipment may intervene.		
6.1.2. For emergency responders			
Protective equipment	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".		
Emergency procedures	Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.		

#### **6.2. Environmental precautions**

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up		
For containment	: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.	
Methods for cleaning up	: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion- proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.	
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".	
6.4. Reference to other sections		

No additional information available

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage				
7.1. Precautions for safe handling	7.1. Precautions for safe handling			
U U	Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.			
7.2. Conditions for safe storage, including an	y incompatibilities			
Storage conditions : Incompatible materials :	Comply with applicable regulations. Keep container closed when not in use. Refer to Section 10 on Incompatible Materials. Store in dry, cool, well-ventilated area.			

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Perfluoro-2,5-dimethyl-3,6-dioxaheptanoic acid (2479-73-4)	
No additional information available	
8.2. Appropriate engineering controls	

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

protective gloves. 29 CFR 1910.138: Hand Protection

#### Eye protection:

Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection

#### Skin and body protection:

Wear suitable protective clothing

#### **Respiratory protection:**

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

#### Personal protective equipment symbol(s):



#### Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.1. Information on basic physical and ch	emical properties
Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 68 °C (@ 16 mmHg)
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Molecular mass	: 396,0597 g/mol
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

No additional information available

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No additional information available

**10.2. Chemical stability** 

The product is stable at normal handling and storage conditions.

**10.3. Possibility of hazardous reactions** 

No additional information available

**10.4. Conditions to avoid** 

Keep away from heat, sparks and flame.

**10.5. Incompatible materials** 

Strong oxidizing agents.

#### **10.6. Hazardous decomposition products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 11: Toxicological information 11.1. Information on toxicological effects		
Acute toxicity (dermal)	: Not classified	
Acute toxicity (inhalation)	: Not classified	
Skin corrosion/irritation	: Causes severe skin burns.	
Serious eye damage/irritation	: Causes serious eye damage.	
Respiratory or skin sensitization	: Not classified	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Reproductive toxicity	: Not classified	
STOT-single exposure	: May cause respiratory irritation.	
STOT-repeated exposure	: Not classified	
Aspiration hazard	: Not classified	
Viscosity, kinematic	: No data available	
Symptoms/effects	: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.	
Symptoms/effects after inhalation	: Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.	

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

No additional information available

12.2. Persistence and degradability		
Perfluoro-2,5-dimethyl-3,6-dioxaher	otanoic acid (2479-73-4)	
Persistence and degradability Not readily biodegradable. May cause long-term adverse effects in the environment. PBT - Persistent, Bioaccumulative and Toxic.		
12.3. Bioaccumulative potential		
Perfluoro-2,5-dimethyl-3,6-dioxaher	otanoic acid (2479-73-4)	
Bioaccumulative potential	Perfluorinated alkanes (PFAs, "forever chemicals") are long lasting, widely used chemicals that break down slowly over time. The potential hazards of PFAs are under investigation and have not been established.	
12.4. Mobility in soil		
No additional information available		

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations			
13.1. Disposal methods			
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.		
Sewage disposal recommendations Product/Packaging disposal recommendations	<ul> <li>See the EPA's Interim Guidance on PFAS Destruction and Disposal.</li> <li>Dispose of contents/container in accordance with licensed collector's sorting instructions.</li> </ul>		

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Additional information	: Recycle the material as far as possible.
Ecology - waste materials	: This material is considered to be a "Forever chemical". Prevent any possible release to the environment. Do not discharge into drains. Take all necessary measures to prevent accidental
	discharge of products into drains and waterways due to the rupture of containers or transfer
	systems, or emergency response.

SECTION 14: Transport information	
14.1. UN number	
DOT NA No UN-No. (TDG) UN-No. (IMDG) UN-No. (IATA)	: UN3265 : Not applicable : 3265 : 3265
14.2. UN proper shipping name	
Proper Shipping Name (DOT) Proper Shipping Name (TDG) Proper Shipping Name (IMDG) Proper Shipping Name (IATA)	<ul> <li>Corrosive liquid, acidic, organic, n.o.s.</li> <li>Not applicable</li> <li>CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.</li> <li>Corrosive liquid, acidic, organic, n.o.s.</li> </ul>
14.3. Transport hazard class(es)	
DOT Transport hazard class(es) (DOT) Hazard labels (DOT)	: 8 : 8 CORROSIVE
TDG Transport hazard class(es) (TDG)	: Not applicable
IMDG Transport hazard class(es) (IMDG) Hazard labels (IMDG)	: 8 : 8
IATA Transport hazard class(es) (IATA) Hazard labels (IATA)	: 8 : 8
14.4. Packing group	
Packing group (DOT) Packing group (TDG) Packing group (IMDG) Packing group (IATA)	: III : Not applicable : III : III

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

No supplementary information available. UN3265 386 - Notwithstanding the provisions of §177.834(I) of this subchapter, cargo heaters may be used when weather conditions are such that the freezing of a wetted explosive material is likely. Shipments must be made by private, leased or contract carrier vehicles under exclusive use of the offeror. Cargo heaters must be reverse refrigeration (heat pump) units. Shipments made in accordance with this Special provision are excepted from the requirements of §173.60(b)(4) of this subchapter. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HD2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T7 - 4 178.274(d)(2) Normal
<ul> <li>386 - Notwithstanding the provisions of §177.834(I) of this subchapter, cargo heaters may be used when weather conditions are such that the freezing of a wetted explosive material is likely. Shipments must be made by private, leased or contract carrier vehicles under exclusive use of the offeror. Cargo heaters must be reverse refrigeration (heat pump) units. Shipments made in accordance with this Special provision are excepted from the requirements of §173.60(b)(4) of this subchapter.</li> <li>IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).</li> <li>IT7 - 4 178.274(d)(2) Normal</li></ul>
<ul> <li>386 - Notwithstanding the provisions of §177.834(I) of this subchapter, cargo heaters may be used when weather conditions are such that the freezing of a wetted explosive material is likely. Shipments must be made by private, leased or contract carrier vehicles under exclusive use of the offeror. Cargo heaters must be reverse refrigeration (heat pump) units. Shipments made in accordance with this Special provision are excepted from the requirements of §173.60(b)(4) of this subchapter.</li> <li>IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).</li> <li>IT7 - 4 178.274(d)(2) Normal</li></ul>
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
154 203 241 5 L 60 L A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
40 - Stow "clear of living quarters"
223, 274 5 L E1 P001, LP01 IBC03 T7 TP1, TP28 F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES A E1 Y841 1L 852
1225 6 4 9 4 2 5 E P IE T T F S A E Y 1

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CAO packing instructions (IATA)	: 856
CAO max net quantity (IATA)	: 60L
Special provision (IATA)	: A3, A803
ERG code (IATA)	: 8L

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

#### Not applicable

### **SECTION 15: Regulatory information**

#### **15.1. US Federal regulations**

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Perfluoro-2,5-dimethyl-3,6-dioxaheptanoic acid	CAS-No. 2479-73-4	100%
--	-------------------	------

#### **15.2. International regulations**

#### CANADA

No additional information available

#### **EU-Regulations**

No additional information available

#### **National regulations**

No additional information available

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

#### **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date : 18.12.2023

Full text of H-phr	ases	
H314	Causes severe skin burns and eye damage	
H318	Causes serious eye damage	
H335	May cause respiratory irritation	
NFPA health hazar NFPA fire hazard NFPA reactivity	<ul> <li>d : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.</li> <li>: 1 - Materials that must be preheated before ignition can occur.</li> <li>: 0 - Material that in themselves are normally stable, even under fire conditions.</li> </ul>	
Hazard Rating Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given	

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability	: 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
Safety Data Sheet (SDS), USA	

18.12.2023 (Revision date)