



SynQuest Laboratories, Inc.
PO Box 309, Alachua, FL 32616-0309
Tel. 386/462-0788; FAX 386/462-7097

Material Safety Data Sheet

Transportation Emergency: 1-800-451-8346

Date last revised: December 21, 2012

Date printed: December 21, 2012

SECTION 1. ----- CHEMICAL IDENTIFICATION-----

CATALOG #: 2121-5-S1
NAME: (2S)-2-CHLOROPROPANOIC ACID
SYNONYMS: (2S)-2-CHLOROPROPIONIC ACID

SECTION 2. ----- COMPOSITION/INFORMATION ON INGREDIENTS -----

CAS NUMBER: 29617-66-1
MOLECULAR FORMULA: $C_3H_5ClO_2$
MOLECULAR WEIGHT: 108.52

SECTION 3. ----- HAZARDS IDENTIFICATION -----

LABEL PRECAUTIONARY STATEMENTS

FLAMMABLE LIQUID.

HARMFUL.

HARMFUL BY INHALATION, IN CONTACT WITH SKIN AND IF SWALLOWED.

CORROSIVE.

CAUSES SKIN BURNS AND EYE DAMAGE. DESTRUCTIVE TO THE RESPIRATORY TRACT.

SECTION 4. ----- FIRST-AID MEASURES-----

ORAL EXPOSURE

IF SWALLOWED, WASH OUT MOUTH WITH COPIOUS AMOUNTS OF WATER PROVIDED PERSON IS CONSCIOUS.

INHALATION EXPOSURE

IF INHALED, REMOVE EXPOSED TO FRESH AIR. IF BREATHING IS DIFFICULT, CALL A PHYSICIAN.

DERMAL EXPOSURE

IN CASE OF EXPOSURE, IMMEDIATELY WASH SKIN WITH SOAP AND COPIOUS AMOUNTS OF WATER.

EYE EXPOSURE

IN CASE OF CONTACT WITH EYES, FLUSH WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. ASSURE ADEQUATE FLUSHING BY SEPARATING THE EYELIDS WITH FINGERS.

SECTION 5. ----- FIRE FIGHTING MEASURES -----

FLASH POINT

107 °C

EXTINGUISHING MEDIA

SUITABLE: FOR SMALL (INCIPIENT) FIRES, USE MEDIA SUCH AS "ALCOHOL" FOAM, DRY CHEMICAL, OR CARBON DIOXIDE. FOR LARGE FIRES, APPLY WATER FROM AS FAR AS POSSIBLE. USE VERY LARGE QUANTITIES (FLOODING) OF WATER APPLIED AS A MIST OR SPRAY; SOLID STREAMS OF WATER MAY BE INEFFECTIVE. COOL ALL AFFECTED CONTAINERS WITH FLOODING QUANTITIES OF WATER.

FIREFIGHTING

PROTECTIVE EQUIPMENT: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN AND EYES.

SPECIFIC HAZARD(S): EMITS TOXIC FUMES UNDER FIRE CONDITIONS.

SECTION 6. ----- ACCIDENTAL RELEASE MEASURES-----

PERSONAL PROTECTION

AVOID BREATHING VAPOR MIST, OR GAS. ENSURE ADEQYATE VENTILATION.

WEAR PROTECTIVE EQUIPMENT INCLUDING RUBBER GLOVES, AND EYE PROTECTION. KEEP UNPROTECTED PERSONS AWAY.

REMOVE ALL SOURCES OF IGNITION. BEWARE OF VAPORS ACCUMULATING TO FORM EXPLOSIVE CONCENTRATIONS. VAPORS CAN ACCUMULATE IN LOW AREAS.

ENVIRONMENTAL PROTECTION

PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. TAKE PRECAUTIONS TO ENSURE PRODUCT DOES NOT CONTAMINATE THE GROUND OR ENTER THE DRAINAGE SYSTEM.

COLLECTION

CONTAIN SPILLAGE, AND THEN COLLECT WITH AN ELECTRICALLY PROTECTED VACUUM CLEANER OR BY WET-BRUSHING AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS.

SECTION 7. ----- HANDLING AND STORAGE-----

HANDLING

USER EXPOSURE: AVOID INHALATION. AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. AVOID PROLONGED OR REPEATED EXPOSURE.

USE EXPLOSION-PROOF EQUIPMENT. KEEP AWAY FROM SOURCES OF IGNITION.

TAKE MEASURES TO PREVENT THE BUILD UP OF ELECTROSTATIC CHARGE.

STORAGE

SUITABLE: TIGHTLY CLOSED CONTAINERS IN A DRY AND WELL-VENTILATED PLACE.

CONTAINERS WHICH ARE OPENED MUST BE CAREFULLY RESEALED AND KEPT UPRIGHT TO PREVENT LEAKAGE. STORE IN COOL, DRY PLACE. STORE UNDER NITROGEN. MOISTURE SENSITIVE. RECOMMENDED STORAGE TEMPERATURE: 2 - 8 °C.

SECTION 8. ----- EXPOSURE CONTROLS/PERSONAL PROTECTION-----

ENGINEERING CONTROLS

SAFETY SHOWER AND EYE BATH. MECHANICAL EXHAUST REQUIRED.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY: USE A FULL-FACE RESPIRATOR WITH MULTI-PURPOSE COMBINATION (US) OR TYPE ABEK (EN 14387) RESPIRATOR CARTRIDGES AS A BACKUP TO ENGINEERING CONTROLS. IF THE RESPIRATOR IS THE SOLE MEANS OF PROTECTION, USE A FULL-FACE SUPPLIED AIR RESPIRATOR. USE RESPIRATORS AND COMPONENTS TESTED AND APPROVED UNDER APPROPRIATE GOVERNMENT STANDARDS SUCH AS NIOSH (US) OR CEN (EU).

HAND: PROTECTIVE GLOVES. GLOVES MUST BE INSPECTED PRIOR TO USE.

EYE: CHEMICAL SAFETY GOGGLES.

SKIN AND BODY: IMPERVIOUS CLOTHING, FLAME RETARDANT ANTISTATIC PROTECTIVE CLOTHING, THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.

GENERAL HYGIENE MEASURES

WASH THOROUGHLY AFTER HANDLING.

SECTION 9. ----- PHYSICAL AND CHEMICAL PROPERTIES -----

APPEARANCE AND ODOR

CLEAR LIQUID.

PHYSICAL PROPERTIES

MELTING POINT: 4 °C
BOILING POINT: 77 °C @ 10 mmHg
FLASH POINT: 107 °C- CLOSED CUP
DENSITY: 1.249 g/ml @ 20 °C
REFRACTIVE INDEX: 1.43 @ 20 °C

SECTION 10. -----STABILITY AND REACTIVITY-----

STABILITY

STABLE: STABLE UNDER RECOMMENDED STORAGE CONDITIONS.

MATERIALS TO AVOID: STRONG OXIDIZING AGENTS, STRONG BASES.

CONDITIONS TO AVOID: HEAT, FLAMES AND SPARKS, EXTREMES OF TEMPERATURE, MOISTURE AND DIRECT SUNLIGHT.

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON OXIDES, HYDROGEN CHLORIDE GAS.

HAZARDOUS POLYMERIZATION

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION 11. ----- TOXICOLOGICAL INFORMATION -----

ROUTE OF EXPOSURE

INHALATION: HARMFUL IF INHALED. MATERIAL IS EXTREMELY DESTRUCTIVE TO THE TISSUE OF THE MUCOUS MEMBRANES AND UPPER RESPIRATORY TRACT.

INGESTION: HARMFUL IF SWALLOWED.

SKIN: HARMFUL IF ABSORBED THROUGH SKIN. CAUSES SKIN BURNS.

EYES: CAUSES EYE BURNS.

SIGNS AND SYMPTOMS OF EXPOSURE

TO THE BEST OF OUR KNOWLEDGE, THE TOXICOLOGICAL PROPERTIES OF THIS PRODUCT HAVE NOT BEEN FULLY DETERMINED.

SECTION 12. ----- ECOLOGICAL INFORMATION -----

NOT YET AVAILABLE.

SECTION 13. ----- DISPOSAL CONSIDERATIONS -----

APPROPRIATE METHOD OF DISPOSAL OF SUBSTANCE OR PREPARATION

BURN IN A CHEMICAL INCINERATOR EQUIPPED WITH AN AFTERBURNER AND SCRUBBER BUT EXERT EXTRA CARE IN IGNITING AS THIS MATERIAL IS HIGHLY FLAMMABLE. OFFER SURPLUS AND NON-RECYCLABLE SOLUTIONS TO A LICENSED DISPOSAL COMPANY. CONTACT A LICENSED PROFESSIONAL WASTE DISPOSAL SERVICE TO DISPOSE OF THIS MATERIAL. OBSERVE ALL FEDERAL, STATE, AND LOCAL ENVIRONMENTAL REGULATIONS.

SECTION 14. ----- TRANSPORT INFORMATION -----

DOT

UN2511 - HC: 8 - PG: III

SECTION 15. ----- REGULATORY INFORMATION -----

EU ADDITIONAL CLASSIFICATION

SYMBOL OF DANGER: Xn, C

INDICATION OF DANGER: HARMFUL. CORROSIVE.

RISK STATEMENTS: 20/21/22-34-41

SAFETY STATEMENTS: 13-16-23-24/25-33-36/37/39-45

UNITED STATES REGULATORY INFORMATION

TSCA: NOT LISTED ON TSCA INVENTORY; FOR R&D USE ONLY

SECTION 16. ----- OTHER INFORMATION-----

THE ABOVE INFORMATION IS BELIEVED TO BE CORRECT BUT DOES NOT PURPORT TO BE ALL INCLUSIVE AND SHALL BE USED ONLY AS A GUIDE. SYNQUEST LABS, INC. SHALL NOT BE HELD LIABLE FOR ANY DAMAGE RESULTING FROM HANDLING OR FROM CONTACT WITH THE ABOVE PRODUCT.