

# Safety Data Sheet 2123113

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 05/08/2020 Version: 1.0

# **SECTION 1: Identification**

Identification

Product form : Substance Substance name Diethyl malonate CAS No 105-53-3 Product code 2123-1-13

Diethyl malonate / Diethyl propanedioate / Malonic acid, diethyl ester / Propanedioic acid, 1,3-Synonyms

diethyl ester

: C7H12O4

: MFCD00009195 Other means of identification

#### Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

#### Details of the supplier of the safety data sheet

SynQuest Laboratories, Inc.

P.O. Box 309

Formula

Alachua, FL 32615 - United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

#### **Emergency telephone number**

Emergency number : (844) 523-4086 (3E Company - Account 10069)

## SECTION 2: Hazard(s) identification

# Classification of the substance or mixture

## **Classification (GHS-US)**

H227 - Combustible liquid Flam. Liq. 4 Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye irritation **STOT SE 3** H335 - May cause respiratory irritation

Aquatic Acute 3 H402 - Harmful to aquatic life

Full text of H-phrases: see section 16

# **Label elements**

# **GHS-US** labeling

Hazard pictograms (GHS-US)



GHS07

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H227 - Combustible liquid

H315 - Causes skin irritation H319 - Causes serious eye irritation

H335 - May cause respiratory irritation H402 - Harmful to aquatic life

Precautionary statements (GHS-US) P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking

P261 - Avoid breathing fumes, mist, spray, vapors P264 - Wash skin thoroughly after handling P271 - Use only outdoors or in a well-ventilated area

P273 - Avoid release to the environment

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P302+P352 - If on skin: Wash with plenty of soap and water

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER or doctor/physician if you feel unwell

05/08/2020 EN (English US) SDS ID: 2123113 Page 1

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P321 - Specific treatment (see supplemental first aid instructions on this label)

P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention

P362+P364 - Take off contaminated clothing and wash it before reuse

P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to an approved waste disposal plant

#### 2.3. Other hazards

No additional information available

# **Unknown acute toxicity (GHS US)**

Not applicable

# **SECTION 3: Composition/information on ingredients**

#### **Substance**

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
Diethyl malonate (Main constituent)	(CAS No) 105-53-3	<= 100	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Acute 3, H402

Full text of H-phrases: see section 16

#### **Mixture** 3.2.

Not applicable

# **SECTION 4: First aid measures**

#### **Description of first aid measures**

: In case of accident or if you feel unwell, seek medical advice immediately (show the label First-aid measures general

where possible). Move the affected personnel away from the contaminated area.

Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial First-aid measures after inhalation

respiration. Get medical advice/attention.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if First-aid measures after eye contact

present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse

mouth out with water. Get medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : The most important known symptoms and effects are described in the labelling (see section

2.2) and/or in section 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

#### 5.1. **Extinguishing media**

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

#### Special hazards arising from the substance or mixture 5.2.

Fire hazard : Thermal decomposition generates: Carbon oxides.

Explosion hazard Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed

containers.

#### 5.3 **Advice for firefighters**

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

: Wear gas tight chemically protective clothing in combination with self contained breathing Protection during firefighting

apparatus. For further information refer to section 8: "Exposure controls/personal protection".

05/08/2020 EN (English US) SDS ID: 2123113 2/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes,

vapor or spray.

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground

level.

## 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

## 6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

Methods for cleaning up : Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use

explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel

spills into appropriate container for disposal. Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

#### 6.4. Reference to other sections

No additional information available

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Ensure good

ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal

protective equipment. Avoid contact with skin and eyes.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or

smoke when using this product. Always wash hands after handling the product.

# 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep container closed when not in use. Air sensitive. Moisture sensitive. Keep contents under

inert gas.

Incompatible materials : Refer to Section 10 on Incompatible Materials.

Storage area : Store in dry, well-ventilated area.

# SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

No additional information available

# 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers

should be available in the immediate vicinity of any potential exposure.

Hand protection : Protective gloves. 29 CFR 1910.138: Hand Protection.

Eye protection : Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory

Protection.

Other information : Safety shoes. 29 CFR 1910.136: Foot Protection.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : No data available
Odor : No data available

05/08/2020 EN (English US) SDS ID: 2123113 3/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odor threshold : No data available pH : No data available

Melting point : -50 °C

Freezing point : No data available

Boiling point : 199 °C

Flash point : 93 °C (open cup) : No data available Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) : No data available **Explosion limits** : No data available : No data available Explosive properties Oxidizing properties : No data available : 0.35 hPa (at 20 °C) Vapor pressure Relative density : No data available Relative vapor density at 20 °C : No data available Specific gravity / density : 1.06 g/cm3 (at 20 °C)

Molecular mass : 160.16 g/mol

Solubility : Water: 18 g/l (at 20 °C)

Log Pow : 0.96

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

9.2. Other information

Refractive index : 1.413 1.0

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No additional information available

## 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

#### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

Keep away from heat, sparks and flame.

#### 10.5. Incompatible materials

Acids. Bases. Oxidizing agents. Reducing agents.

# 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

# SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

Acute toxicity : Not classified

Diethyl malonate (105-53-3)			
LD50 oral rat	14900 μl/kg		
LD50 dermal rabbit	16880 mg/kg		
Skin corrosion/irritation	: Causes skin irritation.		
Serious eye damage/irritation	: Causes serious eye irritation.		
Respiratory or skin sensitization	: Not classified		
Germ cell mutagenicity	: Not classified		
05/08/2020	EN (English US)	SDS ID: 2123113	1/7

05/08/2020 EN (English US) SDS ID: 2123113 4/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity : Not classified Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

# **SECTION 12: Ecological information**

#### 12.1. **Toxicity**

Diethyl malonate (105-53-3)		
LC50 fish 1	10.3 - 13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
EC50 Daphnia 1	202.3 mg/l (Exposure time: 48 h - Species: Daphnia magna)	

# Persistence and degradability

No additional information available

#### 12.3. **Bioaccumulative potential**

Diethyl malonate (105-53-3)	
Log Pow	0.96

#### Mobility in soil

No additional information available

#### Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

#### Waste treatment methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber. Waste disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

# **SECTION 14: Transport information**

#### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : NA1993 Combustible liquid, n.o.s., 3, III

UN-No.(DOT) : NA1993

Proper Shipping Name (DOT) : Combustible liquid, n.o.s.

3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120 Transport hazard class(es) (DOT)

Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 241

**DOT Symbols** : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN

requiring a technical name

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table

2 for UN2672).

T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2) T4 - 2.65 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

05/08/2020 EN (English US) SDS ID: 2123113 5/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Other information : No supplementary information available.

#### **TDG**

No additional information available

#### Transport by sea

No additional information available

#### Air transport

No additional information available

### **SECTION 15: Regulatory information**

## 15.1. US Federal regulations

#### Diethyl malonate (105-53-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### 15.2. International regulations

#### **CANADA**

### Diethyl malonate (105-53-3)

Listed on the Canadian DSL (Domestic Sustances List)

WHMIS Classification Class B Division 3 - Combustible Liquid

#### **EU-Regulations**

No additional information available

# National regulations

## Diethyl malonate (105-53-3)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on INSQ (Mexican national Inventory of Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

# 15.3. US State regulations

## Diethyl malonate (105-53-3)

State or local regulations

U.S. - New Jersey - Right to Know Hazardous Substance List

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

# **SECTION 16: Other information**

05/08/2020 EN (English US) SDS ID: 2123113 6/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Full text of H-phrases:

Hazardous to the aquatic environment - Acute Hazard Category 3
Serious eye damage/eye irritation Category 2A
Flammable liquids Category 4
Skin corrosion/irritation Category 2
Specific target organ toxicity (single exposure) Category 3
Combustible liquid
Causes skin irritation
Causes serious eye irritation
May cause respiratory irritation
Harmful to aquatic life

: 1 - Exposure could cause irritation but only minor residual NFPA health hazard

injury even if no treatment is given.

: 2 - Must be moderately heated or exposed to relatively high NFPA fire hazard

temperature before ignition can occur.

: 0 - Normally stable, even under fire exposure conditions, NFPA reactivity

and are not reactive with water.



**HMIS III Rating** 

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient

temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F

but below 200 F. (Classes II & IIIA)

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high Physical

temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

05/08/2020 EN (English US) SDS ID: 2123113 7/7