

Safety Data Sheet 212334T

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 02/20/2018 Version: 1.0

SECTION 1: Identification

Identification

: Substance Product form

Substance name : Methyl fluoroformyl-2,2-difluoroacetate

CAS No. 69116-71-8 Product code : 2123-3-4T Formula : C4H3F3O3

Synonyms : Methyl 2,2,3-trifluoro-3-oxopropionate

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

1.3. Details of the supplier of the safety data sheet

SynQuest Laboratories, Inc.

P.O. Box 309

Alachua, FL 32615 - United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

Classification (GHS-US)

H226 - Flammable liquid and vapour Flam. Liq. 3 H302 - Harmful if swallowed Acute Tox. 4 (Oral) H312 - Harmful in contact with skin Acute Tox. 4 (Dermal)

Acute Tox. 4 (Inhalation) H332 - Harmful if inhaled

H314 - Causes severe skin burns and eye damage Skin Corr. 1A

Eye Dam. 1 H318 - Causes serious eye damage STOT SE 3 H335 - May cause respiratory irritation

Full text of H-phrases: see section 16

Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS02

GHS05

GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) H226 - Flammable liquid and vapor

H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled

H314 - Causes severe skin burns and eye damage

H335 - May cause respiratory irritation

P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking Precautionary statements (GHS-US)

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ventilating/lighting equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge P260 - Do not breathe dust/fume/gas/mist/vapors/spray P264 - Wash skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301+P312 - If swallowed: Call a POISON CENTER or doctor/ physician if you feel unwell

SDS ID: 212334T 02/21/2018 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P302+P352 - If on skin: Wash with plenty of soap and water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/ physician

P321 - Specific treatment (see supplemental first aid instructions on this label)

P330 - Rinse mouth

P362+P364 - Take off contaminated clothing and wash it before reuse

P363 - Wash contaminated clothing before reuse

P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards

Other hazards not contributing to the classification

: Contact with acids liberates toxic gas. Contact with water liberates toxic gas.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Substance type : Mono-constituent

| Name | Product identifier | % | Classification (GHS-US) |
|--|---------------------|--------|---|
| Methyl fluoroformyl-2,2-difluoroacetate (Main constituent) | (CAS No) 69116-71-8 | <= 100 | Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 |

Full text of H-phrases: see section 16

3.2. Mixture

Not applicable

SECTION 4: First aid measures

| 4.4 | Danasi | | fine a select | |
|------|--------|----------|---------------|----------|
| 4.1. | Descri | ption of | tirst aid | measures |

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial

respiration. Get immediate medical advice/attention.

First-aid measures after skin contact : Wash with plenty of soap and water. Remove contaminated clothing and shoes. In case of skin contact, wearing rubber gloves rub 2.5% calcium gluconate gel continuously into the affected

area for 1.5 hours or until further medical care is available. Get immediate medical

advice/attention

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : The most important known symptoms and effects are described in the labelling (see section

2.2) and/or in section 11.

Symptoms/injuries after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).

02/21/2018 EN (English US) SDS ID: 212334T 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

Special hazards arising from the substance or mixture

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen fluoride.

Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed Explosion hazard

containers.

Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Wear gas tight chemically protective clothing in combination with self contained breathing Protection during firefighting

apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes,

vapor or spray.

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

: Do not attempt to take action without suitable protective equipment. For further information Protective equipment

refer to section 8: "Exposure controls/personal protection".

Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground **Emergency procedures** level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of

ianition.

6.2. **Environmental precautions**

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

Methods for cleaning up Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use

explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel

spills into appropriate container for disposal. Ventilate area.

For disposal of solid materials or residues refer to section 13: "Disposal considerations". Other information

Reference to other sections

No additional information available

SECTION 7: Handling and storage

Precautions for safe handling

: Handle empty containers with care because residual vapors are flammable. Additional hazards when processed

: Do not handle until all safety precautions have been read and understood. Ensure good Precautions for safe handling ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal

protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or Hygiene measures smoke when using this product. Always wash hands after handling the product.

Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions Keep container closed when not in use. Keep away from ignition sources. Moisture sensitive.

Keep contents under inert gas.

Incompatible materials Refer to Section 10 on Incompatible Materials.

Storage area Store in dry, cool, well-ventilated area.

Special rules on packaging Do not store in glass.

02/21/2018 EN (English US) SDS ID: 212334T 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers

should be available in the immediate vicinity of any potential exposure.

Hand protection : Protective gloves. 29 CFR 1910.138: Hand Protection.

Eye protection : Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory

Protection.

Other information : Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available

Boiling point : 84 °C

: No data available Flash point : No data available Relative evaporation rate (butyl acetate=1) Flammability (solid, gas) No data available **Explosion limits** : No data available Explosive properties No data available : No data available Oxidizing properties : No data available Vapor pressure Relative density No data available Relative vapor density at 20 °C : No data available Molecular mass 156.06 g/mol Solubility : No data available No data available Log Pow Auto-ignition temperature No data available No data available Decomposition temperature : No data available Viscosity No data available Viscosity, kinematic : No data available Viscosity, dynamic

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

02/21/2018 EN (English US) SDS ID: 212334T 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

Keep away from heat, sparks and flame.

10.5. Incompatible materials

Acids. Glass. Strong bases. Strong oxidizing agents. Water.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Dermal: Harmful in contact with skin. Inhalation: Harmful if inhaled.

| Methyl fluoroformyl-2,2-difluoroacetate (69116-71-8) | | |
|--|----------------------------|--|
| ATE US (oral) | 500.000 mg/kg body weight | |
| ATE US (dermal) | 1100.000 mg/kg body weight | |
| ATE US (gases) | 4500.000 ppmV/4h | |
| ATE US (vapors) | 11.000 mg/l/4h | |
| ATE US (dust, mist) | 1.500 mg/l/4h | |

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

 Absorption of excessive F- can result in acute systemic fluorosis with hypocalcemia, interference with various metabolic functions and organ damage (heart, liver, kidneys).

Symptoms/injuries after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Waste disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

02/21/2018 EN (English US) SDS ID: 212334T 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3265 Corrosive liquid, acidic, organic, n.o.s., 8, II

UN-No.(DOT) : UN3265

Proper Shipping Name (DOT) : Corrosive liquid, acidic, organic, n.o.s.

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) : 8 - Corrosive

Packing group (DOT) : II - Medium Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are

not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T11 - 6 178.274(d)(2) Normal...... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters" Other information : No supplementary information available.

No additional information available

Transport by sea

UN-No. (IMDG) 3265

Proper Shipping Name (IMDG) : CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.

Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : II - substances presenting medium danger

Air transport

UN-No. (IATA) : 3265

Proper Shipping Name (IATA) : Corrosive liquid, acidic, organic, n.o.s.

02/21/2018 EN (English US) SDS ID: 212334T 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Class (IATA) : 8 - Corrosives
Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Methyl fluoroformyl-2,2-difluoroacetate (69116-71-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Methyl fluoroformyl-2,2-difluoroacetate (69116-71-8)

Listed on the Canadian NDSL (Non-Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Methyl fluoroformyl-2,2-difluoroacetate (69116-71-8)

Listed on the Japanese ISHL (Industrial Safety and Health Law)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

| Acute Tox. 4 (Dermal) | Acute toxicity (dermal) Category 4 |
|---------------------------|---|
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhalation) Category 4 |
| Acute Tox. 4 (Oral) | Acute toxicity (oral) Category 4 |
| Eye Dam. 1 | Serious eye damage/eye irritation Category 1 |
| Flam. Liq. 3 | Flammable liquids Category 3 |
| Skin Corr. 1A | Skin corrosion/irritation Category 1A |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3 |
| H226 | Flammable liquid and vapor |
| H302 | Harmful if swallowed |
| H312 | Harmful in contact with skin |
| H314 | Causes severe skin burns and eye damage |
| H318 | Causes serious eye damage |
| H332 | Harmful if inhaled |
| H335 | May cause respiratory irritation |

NFPA health hazard

: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given

NFPA fire hazard

: 0 - Materials that will not burn.

NFPA reactivity

: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.

3 1

02/21/2018 EN (English US) SDS ID: 212334T 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high

temperatures and pressures. Materials may react non-violently with water or undergo

hazardous polymerization in the absence of inhibitors.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

02/21/2018 EN (English US) SDS ID: 212334T 8/8