

## Safety Data Sheet 21291Y5

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## **SECTION 1: Identification**

### 1.1. Identification

Product form : Substance
Substance name : Ethyl L-lactate
CAS No : 687-47-8
Product code : 2129-1-Y5
Formula : C5H10O3

Synonyms : Ethyl (2S)-2-hydroxypropanoate

Other means of identification : MFCD00004518

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

#### 1.3. Details of the supplier of the safety data sheet

SynQuest Laboratories, Inc.

P.O. Box 309

Alachua, FL 32615 - United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

#### 1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

## SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

#### **Classification (GHS-US)**

Flam. Liq. 3
Skin Irrit. 2
H315 - Causes skin irritation
Eye Dam. 1
STOT SE 3
H326 - Flammable liquid and vapour
H315 - Causes skin irritation
H318 - Causes serious eye damage
H335 - May cause respiratory irritation

Full text of H-phrases: see section 16

## 2.2. Label elements

### **GHS-US** labeling

Hazard pictograms (GHS-US)





GHS02 GHS05

GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H226 - Flammable liquid and vapor

H315 - Causes skin irritation

H318 - Causes serious eye damage H335 - May cause respiratory irritation

Precautionary statements (GHS-US) : P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ventilating/lighting equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

P261 - Avoid breathing fumes, mist, spray, vapors

P264 - Wash skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P302+P352 - If on skin: Wash with plenty of soap and water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

02/22/2017 EN (English US) SDS ID: 21291Y5 Page 1

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/ physician

P321 - Specific treatment (see supplemental first aid instructions on this label)

P332+P313 - If skin irritation occurs: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse

P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to an approved waste disposal plant

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substance

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
Ethyl L-lactate (Main constituent)	(CAS No) 687-47-8	<= 100	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335

Full text of H-phrases: see section 16

### 3.2. Mixture

Not applicable

#### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label

where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial

respiration. Get immediate medical advice/attention.

First-aid measures after skin contact : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Get immediate

medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse

mouth out with water. Get immediate medical advice/attention.

## 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : The most important known symptoms and effects are described in the labelling (see section

2.2) and/or in section 11.

Symptoms/injuries after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media

appropriate for surrounding fire.

## 5.2. Special hazards arising from the substance or mixture

Fire hazard : Thermal decomposition generates: Carbon oxides.

Explosion hazard : Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed

containers. May form flammable/explosive vapor-air mixture.

#### 5.3. Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting : Wear gas tight chemically protective clothing in combination with self contained breathing

apparatus. For further information refer to section 8: "Exposure controls/personal protection".

02/22/2017 EN (English US) SDS ID: 21291Y5 2/7

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### SECTION 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes, vapor or spray.

#### 6.1.1. For non-emergency personnel

**Emergency procedures** 

: Only qualified personnel equipped with suitable protective equipment may intervene.

## 6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

**Emergency procedures** 

: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters

#### 6.3. Methods and material for containment and cleaning up

For containment

: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

Methods for cleaning up

: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.

\_ ... ... ... ... ... ... ...

Other information

: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

#### 6.4. Reference to other sections

No additional information available

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Protection grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Hygiene measures

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Comply with applicable regulations.

Storage conditions

: Keep container closed when not in use. Keep away from ignition sources.

Incompatible materials

: Refer to Section 10 on Incompatible Materials.

Storage area

: Store in dry, cool, well-ventilated area.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

No additional information available

#### 8.2. Exposure controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection

: Protective gloves. 29 CFR 1910.138: Hand Protection.

Eye protection

: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection

: Wear suitable protective clothing.

Respiratory protection

: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory

Protection.

Other information

: Safety shoes. 29 CFR 1910.136: Foot Protection.

02/22/2017 EN (English US) SDS ID: 21291Y5 3/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available

Melting point : -25 °C

Freezing point : No data available
Boiling point : 152 - 155 °C
Flash point : 46 °C

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available : No data available **Explosion limits** Explosive properties : No data available : No data available Oxidizing properties Vapor pressure : 2 mm Hg (@ 20 °C) Relative density : No data available Relative vapor density at 20 °C : No data available Specific gravity / density 1.042 g/ml (@ 25 °C) Molecular mass : 118.13 g/mol : No data available Solubility

Log Pow : 0.06 Auto-ignition temperature : 400 °C

Decomposition temperature : No data available Viscosity : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available

9.2. Other information

Refractive index : 1.413 (@ 20 °C)

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

The product is stable at normal handling and storage conditions.

## 10.3. Possibility of hazardous reactions

No additional information available

# 10.4. Conditions to avoid

Keep away from heat, sparks and flame.

# 10.5. Incompatible materials

Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Ethyl L-lactate (687-47-8)	
LD50 oral rat	> 2000 mg/kg

02/22/2017 EN (English US) SDS ID: 21291Y5 4/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethyl L-lactate (687-47-8)	
LC50 inhalation rat (mg/l)	> 5.4 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified

Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated

exposure)

: Not classified

: Not classified

Aspiration hazard

Symptoms/injuries after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

thyl L-lactate (687-47-8)	
LC50 fish 1	320 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
EC50 Daphnia 1	683 mg/l (Exposure time: 48 h - Species: Daphnia magna)

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

Ethyl L-lactate (687-47-8)		
BCF fish 1	(hydrolysis)	
Log Pow	0.06	

## 12.4. Mobility in soil

No additional information available

## 12.5. Other adverse effects

No additional information available

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Waste disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

## **SECTION 14: Transport information**

## **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN1192 Ethyl lactate, 3, III

UN-No.(DOT) : UN1192
Proper Shipping Name (DOT) : Ethyl lactate

Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger

02/22/2017 EN (English US) SDS ID: 21291Y5 5/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102)

: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Other information : No supplementary information available.

**TDG** 

No additional information available

Transport by sea

UN-No. (IMDG) : 1192

Proper Shipping Name (IMDG) : ETHYL LACTATE
Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : III - substances presenting low danger

Air transport

UN-No. (IATA) : 1192
Proper Shipping Name (IATA) : Ethyl lactate

Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : III - Minor Danger

## **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

## Ethyl L-lactate (687-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag P - P - indicates a commenced PMN substance.

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

## 15.2. International regulations

### CANADA

#### Ethyl L-lactate (687-47-8)

Listed on the Canadian DSL (Domestic Sustances List)

### **EU-Regulations**

No additional information available

02/22/2017 EN (English US) SDS ID: 21291Y5 6/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **National regulations**

#### Ethyl L-lactate (687-47-8)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

## 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

## **SECTION 16: Other information**

#### Full text of H-phrases:

Eye Dam. 1	Serious eye damage/eye irritation Category 1	
Flam. Liq. 3	Flammable liquids Category 3	
Skin Irrit. 2	Skin corrosion/irritation Category 2	
STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
H226	Flammable liquid and vapor	
H315	Causes skin irritation	
H318	Causes serious eye damage	
H335	May cause respiratory irritation	

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt


medical attention is given.

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high

temperature before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient

temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F

but below 200 F. (Classes II & IIIA)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

02/22/2017 EN (English US) SDS ID: 21291Y5 7/7