

Methyl 2-(trifluoromethyl)acrylate Safety Data Sheet 2324343 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 12/09/2015 Version: 1.0

SECTION 1: Identification	
1.1. Identification	
Product form	: Substance
Substance name	: Methyl 2-(trifluoromethyl)acrylate
CAS No	: 382-90-1
Product code	: 2324-3-43
Formula	: C5H5F3O2
Synonyms	: Methyl 2-(trifluoromethyl)propenoate
Other means of identification	: MFCD00068659
	substance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the sa	afety data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of Ameri T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlab	
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identificat	tion
2.1. Classification of the substance	e or mixture
Flam. Liq. 3 Skin Irrit. 2 H226 - Flammable liquid an H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye	n . irritation
Flam. Liq. 3 H226 - Flammable liquid an Skin Irrit. 2 H315 - Causes skin irritatior Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirato Full text of H-phrases: see section 16	n . irritation
Flam. Liq. 3 H226 - Flammable liquid an Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirato Full text of H-phrases: see section 16 2.2. Label elements	n . irritation
Flam. Liq. 3 H226 - Flammable liquid an Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirato Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	n . irritation
Flam. Liq. 3 H226 - Flammable liquid an Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirato Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling	n irritation bry irritation
Flam. Liq. 3 H226 - Flammable liquid an Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirato Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	n irritation bry irritation : $_{GHS02} _{GHS07} _{GHS07}$
Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirato Full text of H-phrases: see section 16	n irritation bry irritation
Flam. Liq. 3 H226 - Flammable liquid an Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirato Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	n irritation bry irritation

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

		 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P312 - Call a POISON CENTER or doctor/physician if you feel unwell P321 - Specific treatment (see supplemental first aid instructions on this label) P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish P403+P235 - Store in a well-ventilated place. Keep cool P405 - Store locked up P501 - Dispose of contents/container to an approved waste disposal plant 			
2.3.	Other hazards				
No addit	lo additional information available				
2.4.	Unknown acute toxicity (GHS US)				
Not app	licable				
SECTI	ON 3: Composition/information	on in	gredients		
3.1.	Substance				
Substan		Mono	-constituent		
Name			Product identifier	%	Classification (GHS-US)
	2-(trifluoromethyl)acrylate		(CAS No) 382-90-1	70 <= 100	Flam. Liq. 3, H226
(Main co				~ 100	Skin Irit. 2, H315 Eye Irit. 2A, H319 STOT SE 3, H335
Full text	of H-phrases: see section 16				
3.2.	Mixture				
Not app	licable				
SECTI	ON 4: First aid measures				
4.1.	Description of first aid measures				
First-aid	First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.				
First-aid	measures after inhalation :	Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get medical advice/attention.			
			with plenty of soap and water. Get med		
	-	prese	diately flush eyes thoroughly with water int and easy to do. Continue rinsing. Get	medical advice/	attention.
First-aid	measures after ingestion :				
4.2.	Most important symptoms and effects	otoms and effects, both acute and delayed			
Symptor	ns/injuries :	 The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11. 			
4.3.	Indication of any immediate medical at	ttentio	n and special treatment needed		
Treat sy	mptomatically.				
SECT	ON 5: Firefighting measures				
5.1.					
	5.1. Extinguishing media Suitable extinguishing media : Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.				
5.2.	Special hazards arising from the subst	tance	or mixture		
Fire haz				ides. Hydroaen	fluoride.
		Thermal decomposition generates: Carbon oxides. Hydrogen fluoride. Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.			
5.3.	Advice for firefighters				
Firefight	· · · · · · · · · · · · · · · · · · ·	In cas	se of fire: Evacuate area. Fight fire remot	ely due to the ris	sk of explosion.
-	-	Wear	gas tight chemically protective clothing i atus. For further information refer to sec	n combination w	vith self contained breathing

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures				
6.1. Personal precautions, protective equip				
6.1.1. For non-emergency personnel				
No additional information available				
6.1.2. For emergency responders				
No additional information available				
6.2. Environmental precautions				
No additional information available				
6.3. Methods and material for containment	and cleaning up			
No additional information available				
6.4. Reference to other sections				
No additional information available				
SECTION 7: Handling and storage				
7.1. Precautions for safe handling				
Additional hazards when processed :	Handle empty containers with care because residual vapors are flammable.			
Precautions for safe handling :	Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.			
Hygiene measures :	Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.			
7.2. Conditions for safe storage, including any incompatibilities				
Technical measures :	Comply with applicable regulations.			
Storage conditions : Keep container closed when not in use. Keep away from ignition sources.				
Incompatible materials :	Refer to Section 10 on Incompatible Materials.			
Storage temperature :	Storage temperature : 2 - 8 °C Use explosion proof refrigerator			
Storage area :	Store in dry, well-ventilated area.			

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

No additional information available

8.2. Exposure controls	
Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTIO	SECTION 9: Physical and chemical properties			
9.1.	Information on basic physica	l and chemical properties		
Physical s	tate	: Liquid		
Color		: No data available		
Odor		: No data available		
Odor three	shold	: No data available		
рН		: No data available		
Melting po	vint	: No data available		
Freezing p	point	: No data available		
Boiling poi	int	: 104 - 105		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flash point	: 25 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Molecular mass	: 154.09 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
9.2. Other information	

9.2. Other information Refractive index

: 1.3528 (@ 20 °C)

SECTION 10: Stability and reactivity				
10.1. Reactivity				
No additional information available				
10.2. Chemical stability				
The product is stable at normal handling and storage conditions.				
10.3. Possibility of hazardous reactions				
May polymerize.				
10.4. Conditions to avoid				
No additional information available				
10.5. Incompatible materials				
Strong acids. Strong bases. Strong oxidizing agents. Strong reducing agents.				

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitization Germ cell mutagenicity	 Causes skin irritation. Causes serious eye irritation. Not classified Not classified
Carcinogenicity Reproductive toxicity	: Not classified : Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

0	
SECT	ION 12: Ecological information
12.1.	Toxicity
No add	itional information available
12.2.	Persistence and degradability
No add	itional information available
12.3.	Bioaccumulative potential
No add	itional information available
12.4.	Mobility in soil
No add	itional information available
12.5.	Other adverse effects
	itional information available

SECTION 13: Disposal considerations				
13.1. Waste treatment methods				
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.			
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.			
Additional information	: Recycle the material as far as possible.			

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT Transport document description

UN-No.(DOT)

Proper Shipping Name (DOT) Transport hazard class(es) (DOT) Hazard labels (DOT)

Packing group (DOT) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Special Provisions (49 CFR 172.102)

- : UN3272 Esters, n.o.s., 3, III
- : UN3272
- : Esters, n.o.s.
- : 3 Class 3 Flammable and combustible liquid 49 CFR 173.120
- : 3 Flammable liquid



- : III Minor Danger
- : 203
- : 242
- : B1 If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Quantity Limitations Passenger aircraft/rail : 60 L (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 \pm 220 L CFR 175.75)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 3272
Proper Shipping Name (IMDG)	: ESTERS, N.O.S.
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: III - substances presenting low danger
Air transport	
UN-No. (IATA)	: 3272
Proper Shipping Name (IATA)	: Esters, n.o.s.
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Methyl 2-(trifluoromethyl)acrylate	CAS No 382-90-1	100%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard	: 3 - Liquids and solids that can be ignited under almost all ambient conditions.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.
HMIS III Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.