

Methyl 3,3-difluoroacrylate Safety Data Sheet 2324362 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 12/09/2015 Version: 1.0

| SECTION 1: Identification | |
|---|---|
| 1.1. Identification | |
| Product form | : Substance |
| Substance name | : Methyl 3,3-difluoroacrylate |
| CAS No | : 406-05-3 |
| Product code | : 2324-3-62 |
| Formula | : C4H4F2O2 |
| Synonyms | : Methyl 3,3-Difluoropropenoate |
| Other means of identification | |
| | : MFCD07772050 |
| | substance or mixture and uses advised against |
| Use of the substance/mixture | : Laboratory chemicals Manufacture of substances Scientific research and development |
| 1.3. Details of the supplier of the sa | ifety data sheet |
| SynQuest Laboratories, Inc. Ρ.Ο. Box 309 Alachua, FL 32615 - United States of Amer Γ (386) 462-0788 - F (386) 462-7097 | |
| nfo@synquestlabs.com - www.synquestlab | <u>os.com</u> |
| 1.4. Emergency telephone number | |
| Emergency number | : (844) 523-4086 (3E Company - Account 10069) |
| SECTION 2: Hazard(s) identificat | ion |
| | |
| 2.1. Classification of the substance | or mixture |
| Flam. Liq. 3 H226 - Flammable liquid an | |
| Flam. Liq. 3H226 - Flammable liquid anSkin Irrit. 2H315 - Causes skin irritationEye Irrit. 2AH319 - Causes serious eyeSTOT SE 3H335 - May cause respirato | n İrritation |
| Flam. Liq. 3 H226 - Flammable liquid an Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirato Full text of H-phrases: see section 16 | n İrritation |
| Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirato Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling | n İrritation |
| Flam. Liq. 3 H226 - Flammable liquid an Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirato Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling | n irritation ary irritation |
| Flam. Liq. 3 H226 - Flammable liquid an Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirato Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) | n irritation my irritation : $($ $($ $)$ $($ |
| Flam. Liq. 3H226 - Flammable liquid an Skin Irrit. 2Skin Irrit. 2H315 - Causes skin irritation Eye Irrit. 2AH319 - Causes serious eye STOT SE 3H335 - May cause respirato Full text of H-phrases: see section 162.2.Label elements | n irritation ary irritation |
| Flam. Liq. 3 H226 - Flammable liquid an Skin Irrit. 2 H315 - Causes skin irritation Eye Irrit. 2A H319 - Causes serious eye STOT SE 3 H335 - May cause respirato Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) | n irritation irritation irritation irritation : : : : : : : : : : : : : |

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | lense: P312 P321 P332- | +P351+P338 - If in eyes: Rinse cautiousl s, if present and easy to do. Continue rin - Call a POISON CENTER or doctor/phy - Specific treatment (see supplemental fi +P313 - If skin irritation occurs: Get medi | sing sician if you fee rst aid instructio | l unwell ns on this label) |
|---|---|--|---|---|
| | P362- P370- P403- P403- P403- P405 | +P313 - If eye irritation persists: Get med +P364 - Take off contaminated clothing a +P378 - In case of fire: Use dry sand, dry +P233 - Store in a well-ventilated place. I +P235 - Store in a well-ventilated place. I - Store locked up - Dispose of contents/container to an application. | ical advice/atter nd wash it befor chemical or alc Keep container t Keep cool | ntion re reuse ohol-resistant foam to extinguish tightly closed |
| 2.3. Other hazards | | | | |
| No additional information available | | | | |
| 2.4. Unknown acute toxicity (GHS US) | | | | |
| Not applicable | | | | |
| SECTION 3: Composition/information | on on in | gredients | | |
| 3.1. Substance | | | | |
| Substance type | : Mono | -constituent | | |
| Name | | Product identifier | % | Classification (GHS-US) |
| Methyl 3,3-difluoroacrylate (Main constituent) | | (CAS No) 406-05-3 | <= 100 | Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 |
| Full text of H-phrases: see section 16 | | | | |
| B.2. Mixture | | | | |
| Not applicable | | | | |
| SECTION 4: First aid measures | | | | |
| 4.1. Description of first aid measures | | | | |
| First-aid measures general | | e of accident or if you feel unwell, seek r possible). Move the affected personnel | | |
| First-aid measures after inhalation | : Remo | we person to fresh air and keep comforta ation. Get medical advice/attention. | | |
| First-aid measures after skin contact | : Wash | with plenty of soap and water. Get medi | cal advice/atten | tion. |
| First-aid measures after eye contact | | diately flush eyes thoroughly with water f nt and easy to do. Continue rinsing. Get | | |
| First-aid measures after ingestion | | OT induce vomiting. Never give anything out with water. Get medical advice/atter | | unconscious person. Rinse |
| 4.2. Most important symptoms and effe | | | | |
| Symptoms/injuries | | nost important known symptoms and effe nd/or in section 11. | cts are describe | ed in the labelling (see section |
| 4.3. Indication of any immediate medica | al attentio | n and special treatment needed | | |
| Freat symptomatically. | | | | |
| SECTION 5: Firefighting measures | | | | |
| 5.1. Extinguishing media | | | | |
| Suitable extinguishing media | | ol resistant foam. Carbon dioxide. Dry po priate for surrounding fire. | wder. Water sp | ray. Use extinguishing media |
| 5.2. Special hazards arising from the su | ibstance o | or mixture | | |
| Fire hazard | : Thern | nal decomposition generates: Carbon oxi | des. Hydrogen f | fluoride. |
| Explosion hazard | | of explosion if heated under confinement. iners. May form flammable/explosive vap | | y or fog for cooling exposed |
| | | | | |
| 5.3. Advice for firefighters | In case of fire: Evenueto area. Eight fire remetaly due to the risk of evaluation | | | |
| Firefighting instructions | In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection". | | | |

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| SECTI | ON 6: Accidental release measu | res |
|--|--|---|
| 6.1. | Personal precautions, protective equip | pment and emergency procedures |
| 6.1.1. No addit | For non-emergency personnel ional information available | |
| 6.1.2. No addit | For emergency responders ional information available | |
| 6.2. | Environmental precautions | |
| No addit | ional information available | |
| 6.3. | Methods and material for containment | and cleaning up |
| No addit | ional information available | |
| 6.4. | Reference to other sections | |
| No addit | ional information available | |
| SECTI | ON 7: Handling and storage | |
| 7.1. | | |
| | Precautions for safe handling | |
| Additiona | Ŭ | Handle empty containers with care because residual vapors are flammable. |
| | Ŭ | Handle empty containers with care because residual vapors are flammable. Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools. |
| Precautio | al hazards when processed : | Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be |
| Precautio | al hazards when processed : ons for safe handling : | Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools. Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |
| Precautie Hygiene 7.2. | al hazards when processed : ons for safe handling : measures : Conditions for safe storage, including | Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools. Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |
| Precautie Hygiene 7.2. Technica | al hazards when processed : ons for safe handling : measures : Conditions for safe storage, including | Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools. Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. any incompatibilities |
| Precautie Hygiene 7.2. Technica Storage | al hazards when processed : ons for safe handling : measures : Conditions for safe storage, including al measures : conditions : | Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools. Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. any incompatibilities Comply with applicable regulations. |
| Precautie Hygiene 7.2. Technica Storage Incompa | al hazards when processed : ons for safe handling : measures : Conditions for safe storage, including al measures : conditions : tible materials : | Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools. Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. any incompatibilities Comply with applicable regulations. Keep container closed when not in use. Keep away from ignition sources. |

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

| 8.2. Exposure controls | |
|----------------------------------|--|
| Appropriate engineering controls | : Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. |
| Hand protection | : Protective gloves. 29 CFR 1910.138: Hand Protection. |
| Eye protection | : Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection. |
| Skin and body protection | : Wear suitable protective clothing. |
| Respiratory protection | : In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection. |
| Other information | : Safety shoes. 29 CFR 1910.136: Foot Protection. |

| SECTION 9: Physical and chemical properties | | | |
|---|--------------------|-----------------------|-------------------|
| 9.1. | Information on bas | sic physical and chem | nical properties |
| Physica | l state | : | Liquid |
| Color | | : | No data available |
| Odor | | : | No data available |
| Odor the | reshold | : | No data available |
| рН | | : | No data available |
| Melting | point | : | No data available |
| Freezing | g point | : | No data available |
| Boiling p | point | : : | 82 - 83 |

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Flash point | : No data available |
|---|---------------------|
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : No data available |
| Explosion limits | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |
| Vapor pressure | : No data available |
| Relative density | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Specific gravity / density | : 1.1993 (@ 20 °C) |
| Molecular mass | : 122.07 g/mol |
| Solubility | : No data available |
| Log Pow | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| 9.2. Other information | |

Refractive index

: 1.3375 (@ 20 °C)

| SECTION | 10: Stability and reactivity | |
|----------------------------|-------------------------------------|--|
| 10.1. Re | activity | |
| No additional | information available | |
| 10.2. Ch | emical stability | |
| The product i | s stable at normal handling and sto | rage conditions. |
| 10.3. Po | ssibility of hazardous reactions | |
| May polymer | ize. | |
| 10.4. Co | nditions to avoid | |
| No additional | information available | |
| 10.5. Inc | ompatible materials | |
| Strong acids. | Strong bases. Strong oxidizing age | ents. Strong reducing agents. |
| 10.6. Ha | zardous decomposition products | ; |
| Under norma fire, see Sect | | zardous decomposition products should not be produced. Hazardous decomposition products in case of |
| SECTION | 11: Toxicological informat | ion |
| 11.1. Inf | ormation on toxicological effects | |
| | | |
| Acute toxicity | , | : Not classified |
| Skin corrosio | n/irritation | : Causes skin irritation. |
| Serious eye o | damage/irritation | : Causes serious eye irritation. |
| - | | |

exposure)

Aspiration hazard

Respiratory or skin sensitization

Specific target organ toxicity (single exposure)

Specific target organ toxicity (repeated

Germ cell mutagenicity

Reproductive toxicity

Carcinogenicity

: Not classified

: Not classified

: Not classified

: Not classified

: Not classified

: Not classified

: May cause respiratory irritation.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| SECT | ION 12: Ecological information |
|---------|--------------------------------|
| 12.1. | Toxicity |
| No addi | tional information available |
| 12.2. | Persistence and degradability |
| No addi | tional information available |
| 12.3. | Bioaccumulative potential |
| No addi | tional information available |
| 12.4. | Mobility in soil |
| No addi | tional information available |
| 12.5. | Other adverse effects |
| No addi | tional information available |

| SECTION 13: Disposal considera | ations |
|--------------------------------|---|
| 13.1. Waste treatment methods | |
| Waste treatment methods | : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber. |
| Waste disposal recommendations | : Dispose of contents/container in accordance with licensed collector's sorting instructions. |
| Additional information | : Recycle the material as far as possible. |

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT Transport document description

UN-No.(DOT)

Proper Shipping Name (DOT) Transport hazard class(es) (DOT) Hazard labels (DOT)

Packing group (DOT) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Special Provisions (49 CFR 172.102)

- : UN3272 Esters, n.o.s., 3, III
- : UN3272
- : Esters, n.o.s.
- : 3 Class 3 Flammable and combustible liquid 49 CFR 173.120
- : 3 Flammable liquid



- : III Minor Danger
- : 203
- : 242
- : B1 If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Quantity Limitations Passenger aircraft/rail : 60 L (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 \pm 220 L CFR 175.75)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| DOT Vessel Stowage Location | : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. | |
|-------------------------------------|--|--|
| Other information | : No supplementary information available. | |
| TDG | | |
| No additional information available | | |
| Transport by sea | | |
| UN-No. (IMDG) | : 3272 | |
| Proper Shipping Name (IMDG) | : ESTERS, N.O.S. | |
| Class (IMDG) | : 3 - Flammable liquids | |
| Packing group (IMDG) | : III - substances presenting low danger | |
| Air transport | | |
| JN-No. (IATA) | : 3272 | |
| Proper Shipping Name (IATA) | : Esters, n.o.s. | |
| Class (IATA) | : 3 - Flammable Liquids | |
| Packing group (IATA) | : III - Minor Danger | |

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

| Methyl 3,3-difluoroacrylate | CAS No 406-05-3 | 100% |
|-----------------------------|-----------------|------|
| | | |

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

| Eye Irrit. 2A | Serious eye damage/eye irritation Category 2A |
|---------------|---|
| Flam. Liq. 3 | Flammable liquids Category 3 |
| Skin Irrit. 2 | Skin corrosion/irritation Category 2 |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3 |
| H226 | Flammable liquid and vapor |
| H315 | Causes skin irritation |
| H319 | Causes serious eye irritation |
| H335 | May cause respiratory irritation |

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| NFPA health hazard | : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given. |
|--------------------|---|
| NFPA fire hazard | : 3 - Liquids and solids that can be ignited under almost all ambient conditions. |
| NFPA reactivity | : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water. |
| HMIS III Rating | |
| Health | : 2 Moderate Hazard - Temporary or minor injury may occur |
| Flammability | : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC) |
| Physical | : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives. |

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.