

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations SDS ID: 2324388 Issue date: 09.02.2016 Revision date: 18.12.2023 Version: 1.1

SECTION 1: Identification

SECTION 1: Identification			
1.1. Identification			
Product form Substance name CAS-No. Product code Formula Synonyms Other means of identification	 Substance 1H,1H,2H,2H-Perfluorododecyl acrylate 17741-60-5 2324-3-88 C15H7F21O2 1H,1H,2H,2H-Henicosafluorododecyl acrylate; 3,3,4,4,5,5,6,6,7,7,8,8,9,9,10,10,11,11,12,12,12- Henicosafluorododecyl prop-2-enoate MFCD00236108 		
1.2. Recommended use and restrictions of	on use		
Use of the substance/mixture		v chemicals are of substances research and dev	
1.3. Supplier			
SynQuest Laboratories, Inc. Inc. P.O. Box 309 Alachua, FL, Alachua, 32615 United States of America T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlabs.com			
1.4. Emergency telephone number			
Emergency number	: (844) 523-	4086 (3E Compa	any - Account 10069)
SECTION 2: Hazard(s) identification			
2.1. Classification of the substance or mi	xture		
GHS US classification Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2A Specific target organ toxicity – Single exposure, C Respiratory tract irritation Full text of H statements : see section 16	ategory 3,	H315 H319 H335	Causes skin irritation Causes serious eye irritation May cause respiratory irritation
2.2. GHS Label elements, including preca	utionary state	ements	
GHS US labeling Hazard pictograms (GHS US)			
Signal word (GHS US)	: Warning	usas akin irritatia	_

Hazard statements (GHS US)

H319 - Causes serious eye irritation H335 - May cause respiratory irritation

: H315 - Causes skin irritation

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US)	 P261 - Avoid breathing dust, mist, spray. P264 - Wash skin thoroughly after handling P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 - If on skin: Wash with plenty of soap and water P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTER or doctor/physician if you feel unwell P321 - Specific treatment (see supplemental first aid instructions on this label) P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type

: Mono-constituent

Name	Product identifier	%	GHS US classification
1H,1H,2H,2H-Perfluorododecyl acrylate (Main constituent)	CAS-No.: 17741-60-5		Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures		
4.1. Description of first aid measures		
First-aid measures general	: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.	
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get medical advice/attention.	
First-aid measures after skin contact	: Wash with plenty of soap and water. Get medical advice/attention.	
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.	
First-aid measures after ingestion	: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get medical advice/attention.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and effects (a	cute and delayed)
Symptoms/effects :	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.
4.3. Immediate medical attention and special	treatment, if necessary
Treat symptomatically.	
SECTION 5: Fire-fighting measures	
5.1. Suitable (and unsuitable) extinguishing r	nedia
Suitable extinguishing media :	Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.
5.2. Specific hazards arising from the chemic	al de la constante de la const
Fire hazard :	Thermal decomposition generates: Carbon oxides. Hydrogen fluoride.
5.3. Special protective equipment and precau	utions for fire-fighters
Firefighting instructions : Protection during firefighting :	In case of fire: Evacuate area. Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures 6.1. Personal precautions, protective equipment and emergency procedures			
6.1.1. For non-emergency personnel			
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.		
6.1.2. For emergency responders			
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer		

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for contain	nment and cleaning up
For containment Methods for cleaning up Other information	 Stop leak if safe to do so. Sweep or shovel spills into appropriate container for disposal. Minimize generation of dust. For disposal of solid materials or residues refer to section 13 : "Disposal considerations".
6.4. Reference to other sections	

No additional information available

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe dust, mist, spray. Wear personal protective equipment. Avoid contact with skin and eyes.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.	
7.2. Conditions for safe storage, including	any incompatibilities	
Technical measures Storage conditions Incompatible materials Storage temperature Storage area	 Comply with applicable regulations. Keep container closed when not in use. Refer to Section 10 on Incompatible Materials. 2 - 8 °C Store in dry, well-ventilated area. 	

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1H,1H,2H,2H-Perfluorododecyl acrylate (17741-60-5)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

protective gloves. 29 CFR 1910.138: Hand Protection

Eye protection:

Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

Personal protective equipment symbol(s):



Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
рН	: No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Malting a sint	. 40 50 %
Melting point	: 48 – 50 °C
Freezing point	: No data available
Boiling point	: 122 °C (@ 4 mm Hg)
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 1,32 g/ml (@ 20 °C)
Molecular mass	: 618,18 g/mol
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

May polymerize.

10.4. Conditions to avoid

Keep away from heat, sparks and flame.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information		
11.1. Information on toxicologic	al effects	
Acute toxicity (oral)	: Not classified	
Acute toxicity (dermal)	: Not classified	
Acute toxicity (inhalation)	: Not classified	
Skin corrosion/irritation	: Causes skin irritation.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects	: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability	
1H,1H,2H,2H-Perfluorododecyl acrylate (17741-60-5)	
Persistence and degradability	Not readily biodegradable. May cause long-term adverse effects in the environment. PBT - Persistent, Bioaccumulative and Toxic.
12.3. Bioaccumulative potential	
1H,1H,2H,2H-Perfluorododecyl acrylate (17741-60-5)	
Bioaccumulative potential	Perfluorinated alkanes (PFAs, "forever chemicals") are long lasting, widely used chemicals that break down slowly over time. The potential hazards of PFAs are under investigation and have not been established.
12.4. Mobility in soil	
No additional information available	

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods Sewage disposal recommendations Product/Packaging disposal recommendations Additional information Ecology - waste materials	 Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber. See the EPA's Interim Guidance on PFAS Destruction and Disposal. Dispose of contents/container in accordance with licensed collector's sorting instructions. Recycle the material as far as possible. This material is considered to be a "Forever chemical". Prevent any possible release to the
Ecology - waste materials	It is material is considered to be a "Forever chemical". Prevent any possible release to the environment. Do not discharge into drains. Take all necessary measures to prevent accidental discharge of products into drains and waterways due to the rupture of containers or transfer
	systems, or emergency response.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information	
14.1. UN number	
DOT NA No UN-No. (TDG) UN-No. (IMDG) UN-No. (IATA)	: UN3077 : Not applicable : 3077 : 3077
14.2. UN proper shipping name	
Proper Shipping Name (DOT) Proper Shipping Name (TDG) Proper Shipping Name (IMDG) Proper Shipping Name (IATA)	 Environmentally hazardous substances, solid, n.o.s. Not applicable ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. Environmentally hazardous substance, solid, n.o.s.
14.3. Transport hazard class(es)	
DOT Transport hazard class(es) (DOT) Hazard labels (DOT)	: 9 : 9
TDG Transport hazard class(es) (TDG)	: Not applicable
IMDG Transport hazard class(es) (IMDG) Hazard labels (IMDG)	: 9 : 9
IATA Transport hazard class(es) (IATA) Hazard labels (IATA)	: 9 : 9
14.4. Packing group	
Packing group (DOT) Packing group (TDG) Packing group (IMDG) Packing group (IATA)	: III : Not applicable : III : III
14.5. Environmental hazards	
Other information	: No supplementary information available.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.6. Special precautions for user

11	C 1	

UN-No.(DOT)	: UN3077
DOT Special Provisions (49 CFR 172.102)	 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies.
	146 - This description may be used for a material that poses a hazard to the environment but
	does not meet the definition for a hazardous waste or a hazardous substance, as defined in
	171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is
	designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.
	335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging.
	384 - For transportation by motor vehicle, substances meeting the conditions for high viscosity flammable liquids as prescribed in §173.121(b)(1)(i), (b)(1)(ii), and (b)(1)(iv) of this subchapter, may be reassigned to Packing Group III under the following conditions:
	A112 - Notwithstanding the quantity limits shown in Column (9A) and (9B) for this entry, the following IBCs are authorized for transportation aboard passenger and cargo-only aircraft. Each IBC may not exceed a maximum net quantity of 1,000 kg: a. Metal: 11A, 11B, 11N, 21A, 21B and 21N
	b. Rigid plastics: 11H1, 11H2, 21H1 and 21H2
	c. Composite with plastic inner receptacle: 11HZ1, 11HZ2, 21HZ1 and 21HZ2
	d. Fiberboard: 11G
	e. Wooden: 11C, 11D and 11F (with inner liners)
	f. Flexible: 13H2, 13H3, 13H4, 13H5, 13L2, 13L3, 13L4, 13M1 and 13M2 (flexible IBCs must be sift-proof and water resistant or must be fitted with a sift-proof and water resistant liner). B54 - Open-top, sift-proof rail cars are also authorized.
	B120 - The use of flexible bulk containers conforming to the requirements in subpart R and subpart S of part 178 of this subchapter is permitted.
	IB8 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1, 13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2).
	IP3 - Flexible IBCs must be sift-proof and water-resistant or must be fitted with a sift-proof and water-resistant liner.
	N20 - A 5M1 multi-wall paper bag is authorized if transported in a closed transport vehicle.
	N91 - The use of a non specification sift-proof, non-bulk, metal can with or without lid, or a non specification sift-proof, non-bulk fiber drum, with or without lid is authorized when transporting coal tar pitch compounds by motor vehicle or rail freight. The fiber drum must to be fabricated
	with a three ply wall, as a minimum. The coal tar pitch compound must be in a solid mass during transportation.
	T1 - 1.5 178.274(d)(2) Normal 178.275(d)(2)
	TP33 - The portable tank instruction assigned for this substance applies for granular and
	powdered solids and for solids which are filled and discharged at temperatures above their
	melting point which are cooled and transported as a solid mass. Solid substances transported or
	offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group
	III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or
	bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in
	accordance with the applicable requirements of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 155

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Non Bulk (49 CFR 173.xxx)	: 213
DOT Packaging Bulk (49 CFR 173.xxx)	: 240
DOT Quantity Limitations Passenger aircraft/rail (49	: No limit
CFR 173.27)	
DOT Quantity Limitations Cargo aircraft only (49	: No limit
CFR 175.75)	
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a
C C	passenger vessel.
TDG	
No data available	
IMDG	
Special provision (IMDG)	: 274, 335, 966, 967, 969
Limited quantities (IMDG)	: 5 kg
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP02, P002
Packing provisions (IMDG)	: PP12
IBC packing instructions (IMDG)	: IBC08
IBC special provisions (IMDG)	: B3
Tank instructions (IMDG)	: BK1, BK2, BK3, T1
Tank special provisions (IMDG)	: TP33
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS
Stowage category (IMDG)	: A
IATA	
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y956
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 956
PCA max net quantity (IATA)	: 400kg
CAO packing instructions (IATA)	: 956
CAO max net quantity (IATA)	: 400kg
Special provision (IATA)	: A97, A158, A179, A197, A215
ERG code (IATA)	: 9L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

1H,1H,2H,2H-Perfluorododecyl acrylate (17741-60-5)

Listed on the Canadian DSL (Domestic Substances List)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EU-Regulations

1H,1H,2H,2H-Perfluorododecyl acrylate (17741-60-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

1H,1H,2H,2H-Perfluorododecyl acrylate (17741-60-5)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date : 18.12.2023

Full text of H-phra	ases	
H315	Causes skin irritation	
H319	Causes serious eye irritation	
H335	May cause respiratory irritation	
NFPA health hazard	t t	 3 - Materials that, under emergency conditions, can cause serious or permanent injury.
NFPA fire hazard NFPA reactivity		 1 - Materials that must be preheated before ignition can occur. 0 - Material that in themselves are normally stable, even under fire conditions.
Hazard Rating		
Health	:	2 Moderate Hazard - Temporary or minor injury may occur
Flammability	:	1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physical	:	0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
Safety Data Sheet	SDS), USA	