

2-Chlorobenzoyl chloride Safety Data Sheet 26165X1 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 09/06/2017 Version: 1.0

SECTION 1: Identification	
1.1. Identification	
Product form	: Substance
Substance name	2-Chlorobenzoyl chloride
CAS No	: 609-65-4
Product code	: 2616-5-X1
Formula	: C7H4Cl2O
Other means of identification	MFCD0000660
1.2. Relevant identified uses of the substa	nce or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the safety da	ata sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of America T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com	
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identification	
2.1. Classification of the substance or mix	ture
Classification (GHS-US)	
Eye Dam. 1 H318 - Causes serious eye dama STOT SE 3 H335 - May cause respiratory irri Full text of H-phrases: see section 16 2.2. Label elements	
GHS-US labeling	
Hazard pictograms (GHS-US)	GHS05 GHS07
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	 H314 - Causes severe skin burns and eye damage H335 - May cause respiratory irritation
Precautionary statements (GHS-US)	 P260 - Do not breathe fumes, mist, spray, vapors P264 - Wash skin thoroughly after handling P271 - Use only outdoors or in a well-ventilated area P280 - Wear protective gloves/protective clothing/eye protection/face protection P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P310 - Immediately call a POISON CENTER or doctor/ physician P321 - Specific treatment (see supplemental first aid instructions on this label) P363 - Wash contaminated clothing before reuse P403+P233 - Store in a well-ventilated place. Keep container tightly closed P405 - Store locked up P501 - Dispose of contents/container to an approved waste disposal plant

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3.	Other hazards

Other hazards not contributing to the	: Lachrymator.
classification	

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Substance type		: Mono-constituent			
Name		Product identifier	%	Classification (GHS-US)	
2-Chlorobenzoyl chloride (Main constituent)		(CAS No) 609-65-4	<= 100	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	
Full text of H-phrases: see section 16					
3.2. Mixture					
Not applicable					
SECTION 4: First aid measures					
4.1. Description of first aid measures					
First-aid measures general		se of accident or if you feel unwell, seek is possible). Move the affected personnel			
First-aid measures after inhalation		ove person to fresh air and keep comforta ation. Get immediate medical advice/atte		g. If not breathing, give artificial	
First-aid measures after skin contact		with plenty of soap and water. Remove cal advice/attention.	contaminated cl	othing and shoes. Get immediate	
First-aid measures after eye contact		diately flush eyes thoroughly with water in and easy to do. Continue rinsing. Get			
First-aid measures after ingestion		OT induce vomiting. Never give anything n out with water. Get immediate medical			
4.2. Most important symptoms and effects	, both	acute and delayed			
Symptoms/injuries :		nost important known symptoms and effe and/or in section 11.	ects are describe	ed in the labelling (see section	
Symptoms/injuries after inhalation		ial is destructive to tissue of the mucuou ness of breath, headache, nausea.	s membranes a	nd upper respiratory tract. Cough	

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures			
5.1. Extinguishing media			
Suitable extinguishing media	: Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.		
5.2. Special hazards arising from the s	ubstance or mixture		
Fire hazard	: Thermal decomposition generates: Carbon oxides. Hydrogen chloride.		
Explosion hazard	: Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed containers.		
5.3. Advice for firefighters			
Firefighting instructions	: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.		
Protection during firefighting	: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".		
SECTION 6: Accidental release measures			

SECT	CTION 0. ACCIDENTAL TELEASE MEASURES			
6.1.	6.1. Personal precautions, protective equipment and emergency procedures			
General	measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes, vapor or spray.		
6.1.1. Emerge	For non-emergency personnel ncy procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.		

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5	
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.
6.2. Environmental precautions	
Avoid release to the environment. Notify au	thorities if product enters sewers or public waters.
6.3. Methods and material for conta	inment and cleaning up
For containment	: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.
Methods for cleaning up	: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".
6.4. Reference to other sections	
No additional information available	
SECTION 7: Handling and storage	je
7.1. Precautions for safe handling	
Precautions for safe handling	Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, inc	cluding any incompatibilities
Technical measures	: Comply with applicable regulations.
Storage conditions	: Keep container closed when not in use. Moisture sensitive. Keep contents under inert gas.
	: Refer to Section 10 on Incompatible Materials.
Incompatible materials	

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

0.0

No additional information available

8.2. Exposure controls	
Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

9.1. I	nformation on basic physical and o	hemical properties
Physical st	ate	: Liquid
Color		: No data available
Odor		: No data available
Odor thres	hold	: No data available
pН		: No data available
Melting po	int	: -43 °C
Freezing p	oint	: No data available
Boiling poi	nt	: 237 - 239 °C
Flash poin	t	: 125 °C
Relative ev	vaporation rate (butyl acetate=1)	: No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability (solid, gas)	:	No data available
Explosion limits	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Vapor pressure	:	No data available
Relative density	:	No data available
Relative vapor density at 20 °C	:	No data available
Specific gravity / density	:	1.38 g/ml (@ 25 °C)
Molecular mass	:	175.01 g/mol
Solubility	:	No data available
Log Pow	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	No data available
Viscosity, kinematic	:	No data available
Viscosity, dynamic	:	No data available
9.2 Other information		

9.2. Other information

Refractive index

: 1.57 (@ 20 °C)

SECTION 10: Stability and reactivity					
0.1. Reactivity					
No additional information available					
10.2. Chemical stability					
The product is stable at normal handling and stor	rage conditions.				
10.3. Possibility of hazardous reactions					
No additional information available					
10.4. Conditions to avoid					
Keep away from heat, sparks and flame.					
10.5. Incompatible materials					
Alcohols. Amines. Bases. Oxidizing agents.					
10.6. Hazardous decomposition products					
Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.					
SECTION 11: Toxicological informat	ion				
11.1. Information on toxicological effects					
Acute toxicity	: Not classified				
Skin corrosion/irritation	: Causes severe skin burns and eye damage.				
Serious eye damage/irritation	Causes serious eye damage.				

Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified

Specific target organ toxicity (single exposure)	:	May cause respiratory irritation.
--	---	-----------------------------------

Specific target organ toxicity (repeated : Not classified exposure)

Aspiration hazard	: Not classified
-------------------	------------------

Symptoms/injuries after inhalation

: Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information		
12.1.	Toxicity	
No add	itional information available	
12.2.	Persistence and degradability	
No additional information available		
12.3.	Bioaccumulative potential	
No add	itional information available	
12.4.	Mobility in soil	
No add	itional information available	
12.5.	Other adverse effects	
No additional information available		

SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Recycle the material as far as possible.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT Transport document description

UN-No.(DOT)

Proper Shipping Name (DOT) Transport hazard class(es) (DOT) Hazard labels (DOT)

Packing group (DOT)

- DOT Packaging Non Bulk (49 CFR 173.xxx)
- DOT Packaging Bulk (49 CFR 173.xxx)
- DOT Symbols
- DOT Special Provisions (49 CFR 172.102)

- : UN3265 Corrosive liquid, acidic, organic, n.o.s., 8, II
- : UN3265
- : Corrosive liquid, acidic, organic, n.o.s.
- : 8 Class 8 Corrosive material 49 CFR 173.136
- : 8 Corrosive



- : II Medium Danger
- : 202
- : 242
- : G Identifies PSN requiring a technical name
- : B2 MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail : 1 L (49 CFR 173.27)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

.		
DOT Quantity Limitations Cargo aircraft o CFR 175.75)	nly (49 : 30 L	
DOT Vessel Stowage Location	B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.	
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"	
Other information	: No supplementary information available.	
TDG		
No additional information available		
Transport by sea		
UN-No. (IMDG)	: 3265	
Proper Shipping Name (IMDG)	: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.	
Class (IMDG)	: 8 - Corrosive substances	
Packing group (IMDG)	: II - substances presenting medium danger	
Air transport		
UN-No. (IATA)	: 3265	
Proper Shipping Name (IATA)	: Corrosive liquid, acidic, organic, n.o.s.	
Class (IATA)	: 8 - Corrosives	
Packing group (IATA)	: II - Medium Danger	
SECTION 15: Regulatory inform	nation	
15.1. US Federal regulations		
2-Chlorobenzoyl chloride (609-65-4)	2-Chlorobenzoyl chloride (609-65-4)	

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

	15.2. International regulations		
	CANADA		
2-Chlorobenzoyl chloride (609-65-4)			
	Listed on the Canadian NDSL (Non-Domestic Substances List)		

EU-Regulations

No additional information available

National regulations

2-Chlorobenzoyl chloride (609-65-4) Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye Dam. 1 Serious eye damage/eye irritation Category 1 Skin Corr. 1B Skin corrosion/irritation Category 1B STOT SE 3 Specific target organ toxicity (single exposure) Category 3 H314 Causes severe skin burns and eye damage H318 Causes serious eye damage H335 May cause respiratory irritation NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given. NFPA fire hazard : 1 - Must be preheated before ignition can occur. NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.	Full text of H-phrases:		
STOT SE 3 Specific target organ toxicity (single exposure) Category 3 H314 Causes severe skin burns and eye damage H318 Causes serious eye damage H335 May cause respiratory irritation NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given. NFPA fire hazard : 1 - Must be preheated before ignition can occur. NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,	· · · · · · · · · · · · · · · · · · ·	Serious eye damage/eye irritation Category 1	
H314 Causes severe skin burns and eye damage H318 Causes serious eye damage H335 May cause respiratory irritation NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given. NFPA fire hazard : 1 - Must be preheated before ignition can occur. NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,	Skin Corr. 1B	Skin corrosion/irritation Category 1B	
H318 Causes serious eye damage H335 May cause respiratory irritation NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given. NFPA fire hazard : 1 - Must be preheated before ignition can occur. NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,	STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
H335 May cause respiratory irritation NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given. NFPA fire hazard : 1 - Must be preheated before ignition can occur. NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,	H314	Causes severe skin burns and eye damage	
NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given. NFPA fire hazard : 1 - Must be preheated before ignition can occur. NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,	H318	Causes serious eye damage	
residual injury even though prompt medical attention was given.NFPA fire hazard: 1 - Must be preheated before ignition can occur.NFPA reactivity: 0 - Normally stable, even under fire exposure conditions,	H335	May cause respiratory irritation	
	NFPA fire hazard	residual injury even though prompt medical attention was given. : 1 - Must be preheated before ignition can occur. : 0 - Normally stable, even under fire exposure conditions,	
HMIS III Rating	HMIS III Rating		
Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treati given	Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given	
Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liqu solids and semi solids having a flash point above 200 F. (Class IIIB)	Flammability	 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB) 	
Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and w react with water, polymerize, decompose, condense, or self-react. Non-Explosives.	Physical		

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.