

**3,4-Difluorobenzoyl chloride** Safety Data Sheet 2616734 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 02/23/2016 Version: 1.0

CECTION 4. Howelffoot	
SECTION 1: Identification	
1.1. Identification	
Product form	: Substance
Substance name	: 3,4-Difluorobenzoyl chloride
CAS No	: 76903-88-3
Product code	: 2616-7-34
Formula	: C7H3CIF2O
Other means of identification	: MFCD00009930
1.2. Relevant identified uses of the subs	tance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the safety	data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of America T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlabs.com	<u>n</u>
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identification	
2.1. Classification of the substance or m	lixture
Classification (GHS-US)	
Flam. Liq. 4H227 - Combustible liquidSkin Corr. 1AH314 - Causes severe skin burEye Dam. 1H318 - Causes serious eye dar	
<ul> <li>STOT SE 3 H335 - May cause respiratory i</li> <li>Full text of H-phrases: see section 16</li> <li>2.2. Label elements</li> </ul>	rritation
Full text of H-phrases: see section 16	rritation
Full text of H-phrases: see section 16         2.2.       Label elements	$: \qquad \qquad$
Full text of H-phrases: see section 16         2.2.       Label elements         GHS-US labeling	
Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US)	: CHS05 CHS07
Full text of H-phrases: see section 16 2.2. Label elements GHS-US labeling Hazard pictograms (GHS-US) Signal word (GHS-US)	: GHS05 GHS07 : Danger : H227 - Combustible liquid H314 - Causes severe skin burns and eye damage

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

		P403+P235 - Store in a well-ventilated place. Keep cool P405 - Store locked up P501 - Dispose of contents/container to an approved waste disposal plant			
2.3. Other	hazards				
Other hazards n classification	ot contributing to the :	Lachi	ymator.		
2.4. Unkno	own acute toxicity (GHS US)				
Not applicable					
<b>SECTION 3:</b>	<b>Composition/information</b>	on in	gredients		
3.1. Subst	ance		-		
Substance type	:	Mond	o-constituent		
Name			Product identifier	%	Classification (GHS-US)
3,4-Difluorobenz (Main constituent)	oyl chloride		(CAS No) 76903-88-3	<= 100	Flam. Liq. 4, H227 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335
Full text of H-ph	rases: see section 16				
3.2. Mixtu	re				
Not applicable					
<b>SECTION 4:</b>	First aid measures				
4.1. Descr	iption of first aid measures				
First-aid measur	res general :	s general : In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.			
First-aid measur	res after inhalation :	Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.			
First-aid measur	res after skin contact :	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Get immediate medical advice/attention.			
First-aid measur	res after eye contact :	Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.			
First-aid measur	res after ingestion :	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.			
4.2. Most	important symptoms and effects	ms and effects, both acute and delayed			
Symptoms/injuri	es :	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.			
Symptoms/injuri	es after inhalation :	<ul> <li>Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.</li> </ul>			
4.3. Indica	ation of any immediate medical a	ttentio	n and special treatment needed		
Treat symptoma					
SECTION 5	Firefighting measures				<u></u>
	guishing media				
Suitable extingu			ol resistant foam. Carbon dioxide. D	ry powder. Water	spray. Use extinguishing media
5.2. Speci	al hazards arising from the subs				
Fire hazard			nal decomposition generates: Carbo	n oxides Hydrog	en chloride.
Explosion hazar		Risk	of explosion if heated under confiner iners. May form flammable/explosive	ment. Use water s	pray or fog for cooling exposed
Reactivity	:	Reac	ts with water, generates gases or he se highly explosive/flammable hydro	at. Reacts on exp	
5.3. Advic	e for firefighters				
Firefighting instr	uctions :	In cas	se of fire: Evacuate area. Fight fire re	emotely due to the	e risk of explosion.
Protection during	g firefighting :		gas tight chemically protective cloth ratus. For further information refer to		

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION & Assidental release measures				
SECTION 6: Accidental release measures				
6.1. Personal precautions, protective equipment and emergency procedures				
General measures	: Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes, vapor or spray.			
6.1.1. For non-emergency personnel				
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.			
6.1.2. For emergency responders				
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".			
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.			
6.2. Environmental precautions				
Avoid release to the environment. Notify authoriti	es if product enters sewers or public waters.			
6.3. Methods and material for containme	nt and cleaning up			
For containment	: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.			
Methods for cleaning up	: Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.			
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".			
6.4. Reference to other sections				
No additional information available				
SECTION 7: Handling and storage				
7.1. Precautions for safe handling				
Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.			
Precautions for safe handling	: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools.			
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.			
7.2. Conditions for safe storage, includin	g any incompatibilities			
Technical measures	: Comply with applicable regulations.			
Storage conditions	: Keep container closed when not in use. Keep away from ignition sources. Moisture sensitive. Keep contents under inert gas.			
Incompatible materials	: Refer to Section 10 on Incompatible Materials.			
Storage area	: Store in dry, cool, well-ventilated area.			
-				

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. **Control parameters**

No additional information available

8.2. Exposure controls	
Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties			
I. Information on basic physical and chemical properties			
Physical state	: Liquid		
Color	: No data available		
Odor	: No data available		
Odor threshold	: No data available		
рН	: No data available		
Melting point	: No data available		
Freezing point	: No data available		
Boiling point	: 185 - 186 °C		
Flash point	: 78 °C		
Relative evaporation rate (butyl acetate=1)	: No data available		
Flammability (solid, gas)	: No data available		
Explosion limits	: No data available		
Explosive properties	: No data available		
Oxidizing properties	: No data available		
Vapor pressure	: No data available		
Relative density	: No data available		
Relative vapor density at 20 °C	: No data available		
Specific gravity / density	: 1.402 g/ml (@ 20 °C)		
Molecular mass	: 176.55 g/mol		
Solubility	: No data available		
Log Pow	: No data available		
Auto-ignition temperature	: No data available		
Decomposition temperature	: No data available		
Viscosity	: No data available		
Viscosity, kinematic	: No data available		
Viscosity, dynamic	: No data available		
9.2. Other information			
Refractive index	: 1.5114 (@ 20 °C)		

#### SECTION 10: Stability and reactivity 10.1. Reactivity

Reacts with water, generates gases of	or heat. Reacts on exposure to water with sor	ne metals to release highly explosive/flammable	e hydrogen gas.
10.2. Chemical stability			
The product is stable at normal hand	ing and storage conditions.		
10.3. Possibility of hazardous	reactions		
No additional information available			
10.4. Conditions to avoid			
Keep away from heat, sparks and fla	ne. Moisture.		
10.5. Incompatible materials			
Alcohols. Oxidizing agents. Strong ba	ses. Water.		
10.6. Hazardous decompositio	n products		
Under normal conditions of storage a fire, see Section 5.	nd use, hazardous decomposition products s	nould not be produced. Hazardous decomposit	ion products in case of
<b>SECTION 11: Toxicological</b>	information		
11.1. Information on toxicologi	cal effects		
Acute toxicity	: Not classified		
Skin corrosion/irritation	: Causes severe skin burns and	l eye damage.	
Serious eye damage/irritation	: Causes serious eye damage.		
12/06/2016	EN (English US)	SDS ID: 2616734	4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

SECT	ON 12: Ecological information
12.1.	Toxicity
No addi	ional information available
12.2.	Persistence and degradability
No addi	ional information available
12.3.	Bioaccumulative potential
No addi	ional information available
12.4.	Mobility in soil
No addi	ional information available
12.5.	Other adverse effects

No additional information available

SECTION 13: Disposal considerations				
13.1. Waste treatment methods				
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.			
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.			
Additional information	: Recycle the material as far as possible.			
SECTION 14: Transport information				

### Department of Transportation (DOT)

Bobaranoni er franoportation (B
In accordance with DOT
Transport document description

#### UN-No.(DOT) Proper Shipping Name (DOT) Transport hazard class(es) (DOT) Hazard labels (DOT)

Packing group (DOT) DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx) DOT Symbols

- : UN3265 Corrosive liquid, acidic, organic, n.o.s., 8, II
- : UN3265
- : Corrosive liquid, acidic, organic, n.o.s.
- : 8 Class 8 Corrosive material 49 CFR 173.136
- : 8 Corrosive



- : II Medium Danger
- : 202
- : 242
- : G Identifies PSN requiring a technical name

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	<ul> <li>B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.</li> <li>IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.</li> <li>T11 - 6 178.274(d)(2) Normal</li></ul>
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 30 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Other information	: No supplementary information available.
<b>TDG</b> No additional information available	
Transport by sea	
UN-No. (IMDG)	: 3265
Proper Shipping Name (IMDG)	: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.
Class (IMDG)	: 8 - Corrosive substances
Packing group (IMDG)	: II - substances presenting medium danger
Air transport	
UN-No. (IATA)	: 3265
Proper Shipping Name (IATA)	: Corrosive liquid, acidic, organic, n.o.s.
Class (IATA)	: 8 - Corrosives
Packing group (IATA)	: II - Medium Danger
<b>SECTION 15: Regulatory information</b>	1

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

3,4-Difluorobenzoyl chloride	CAS No 76903-88-3	100%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### 15.2. International regulations

CANADA

No additional information available

EU-Regulations No additional information available

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **National regulations**

No additional information available

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

#### **SECTION 16: Other information**

Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1A	Skin corrosion/irritation Category 1A
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H335	May cause respiratory irritation
NFPA health hazard NFPA fire hazard	<ul> <li>: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.</li> <li>: 2 - Must be moderately heated or exposed to relatively high</li> </ul>
	temperature before ignition can occur.
NFPA reactivity	: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.
HMIS III Rating	
Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	<ul> <li>2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II &amp; IIIA)</li> </ul>
Physical	: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.