

4-Fluoro-3-methylbenzoyl chloride Safety Data Sheet 2716743 according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 04/28/2016 Version: 1.0

SECTION 1: Identification	
1.1. Identification	
Product form	: Substance
Substance name	: 4-Fluoro-3-methylbenzoyl chloride
CAS No	: 455-84-5
Product code	: 2716-7-43
Formula	: C8H6CIFO
Other means of identification	: MFCD01631426
1.2. Relevant identified uses of the sub	ostance or mixture and uses advised against
Use of the substance/mixture	: Laboratory chemicals Manufacture of substances Scientific research and development
1.3. Details of the supplier of the safety	y data sheet
SynQuest Laboratories, Inc. P.O. Box 309 Alachua, FL 32615 - United States of America T (386) 462-0788 - F (386) 462-7097 info@synquestlabs.com - www.synquestlabs.com	<u>om</u>
1.4. Emergency telephone number	
Emergency number	: (844) 523-4086 (3E Company - Account 10069)
SECTION 2: Hazard(s) identification	n
2.1. Classification of the substance or	
Classification (GHS-US)	
STOT SE 3 H335 - May cause respiratory Full text of H-phrases: see section 16 2.2. Label elements	
GHS-US labeling	
Hazard pictograms (GHS-US)	: GHS05 GHS07
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	: H314 - Causes severe skin burns and eye damage H335 - May cause respiratory irritation
Precautionary statements (GHS-US)	 P260 - Do not breathe fumes, mist, spray, vapors P264 - Wash skin thoroughly after handling P271 - Use only outdoors or in a well-ventilated area P280 - Wear protective gloves/protective clothing/eye protection/face protection P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P310 - Immediately call a POISON CENTER or doctor/ physician P321 - Specific treatment (see supplemental first aid instructions on this label) P363 - Wash contaminated clothing before reuse P403+P233 - Store in a well-ventilated place. Keep container tightly closed P405 - Store locked up P501 - Dispose of contents/container to an approved waste disposal plant

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

,	,,				
2.3. Other hazards					
Other hazards not contributing to the classification	: Lachi	ymator.			
2.4. Unknown acute toxicity (GHS US)					
Not applicable					
SECTION 3: Composition/information	on on in	gredients			
3.1. Substance					
Substance type	: Mono	-constituent			
Name		Product identifier	%	Classification (GHS-US	5)
4-Fluoro-3-methylbenzoyl chloride (Main constituent)		(CAS No) 455-84-5	<= 100	Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	
Full text of H-phrases: see section 16				·	
3.2. Mixture					
Not applicable					
SECTION 4: First aid measures					
4.1. Description of first aid measures					
First-aid measures general		se of accident or if you feel unwell, seek is possible). Move the affected personnel			el
First-aid measures after inhalation	respii	ove person to fresh air and keep comforta ation. Get immediate medical advice/atte	ention.		
First-aid measures after skin contact		with plenty of soap and water. Remove cal advice/attention.	contaminated c	lothing and shoes. Get imn	nediate
First-aid measures after eye contact		diately flush eyes thoroughly with water the and easy to do. Continue rinsing. Get			nses, if
First-aid measures after ingestion		OT induce vomiting. Never give anything n out with water. Get immediate medical			e
4.2. Most important symptoms and effe	cts, both	acute and delayed			
Symptoms/injuries		nost important known symptoms and effe nd/or in section 11.	ects are describe	ed in the labelling (see sec	tion
Symptoms/injuries after inhalation		ial is destructive to tissue of the mucuou ness of breath, headache, nausea.	s membranes a	nd upper respiratory tract.	Cough,
4.3. Indication of any immediate medica	al attentio	n and special treatment needed			
Treat symptomatically.					
SECTION 5: Firefighting measures					
5.1. Extinguishing media					
Suitable extinguishing media		ol resistant foam. Carbon dioxide. Dry po priate for surrounding fire.	owder. Water sp	oray. Use extinguishing me	dia
5.2. Special hazards arising from the su	Ibstance	or mixture			
Fire hazard		nal decomposition generates: Carbon ox			
Explosion hazard	: Risk conta	of explosion if heated under confinement iners.	. Use water spra	ay or fog for cooling expose	ed
Reactivity		ts with water, generates gases or heat. R se highly explosive/flammable hydrogen		ure to water with some me	etals to
5.3. Advice for firefighters					
Firefighting instructions	: In cas	se of fire: Evacuate area. Fight fire remot	ely due to the ri	sk of explosion.	
Protection during firefighting		gas tight chemically protective clothing i atus. For further information refer to sec			
SECTION 6: Accidental release mea	sures		·		
6.1. Personal precautions, protective ed		and emergency procedures			
General measures	: Evac	uate unnecessary personnel. Ensure ade or spray.	equate air ventila	ation. Do not breathe gas, t	fumes,
6.1.1. For non-emergency personnel					
Emergency procedures	: Only	qualified personnel equipped with suitabl	e protective equ	upment may intervene.	
12/06/2016	EN (En	lish US)	SDS ID: 2716743		2/7

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.
6.2. Environmental precautions	
Avoid release to the environment. Notify auth	norities if product enters sewers or public waters.
6.3. Methods and material for contain	nment and cleaning up
For containment	: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.
Methods for cleaning up	Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.
Other information	: For disposal of solid materials or residues refer to section 13 : "Disposal considerations".
6.4. Reference to other sections	
No additional information available	
SECTION 7: Handling and storage	e de la companya de l
7.1. Precautions for safe handling	
Precautions for safe handling	Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, incl	uding any incompatibilities
	: Comply with applicable regulations.
Technical measures	: Comply with applicable regulations. : Keep container closed when not in use. Moisture sensitive. Keep contents under inert gas.
Technical measures Storage conditions Incompatible materials	

8.1. **Control parameters**

No additional information available

8.2. Exposure controls	
Appropriate engineering controls	: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Protective gloves. 29 CFR 1910.138: Hand Protection.
Eye protection	: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection.
Other information	: Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and	chemical properties
Physical state	: Liquid
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
рН	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 129 - 133 °C (@ 17 mm Hg)
Flash point	: 98 °C
Relative evaporation rate (butyl acetate=1)	: No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.215 g/ml (@ 25 °C)
Molecular mass	: 172.58 g/mol
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
9.2. Other information	

Refractive index

: 1.532 (@ 20 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with water, generates gases or heat. Reacts on exposure to water with some metals to release highly explosive/flammable hydrogen gas.

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from heat, sparks and flame. Moisture.

10.5. Incompatible materials

Alcohols. Oxidizing agents. Strong bases. Water.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity Specific target organ toxicity (single exposure)	: Not classified : May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTI	ON 12: Ecological information
12.1.	Toxicity
No addit	ional information available
12.2.	Persistence and degradability
No addit	ional information available
12.3.	Bioaccumulative potential
No addit	ional information available
12.4.	Mobility in soil
No addit	ional information available
12.5.	Other adverse effects
No addit	ional information available

SECTION 13: Disposal considerat	lions
13.1. Waste treatment methods	
Waste treatment methods	: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.
Waste disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Recycle the material as far as possible.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT Transport document description

UN-No.(DOT)

Packing group (DOT)

DOT Symbols

Proper Shipping Name (DOT) Transport hazard class(es) (DOT) Hazard labels (DOT)

- : UN3265 Corrosive liquid, acidic, organic, n.o.s., 8, III
- : UN3265
- : Corrosive liquid, acidic, organic, n.o.s.
- : 8 Class 8 Corrosive material 49 CFR 173.136
- : 8 Corrosive



- : III Minor Danger
- DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)

DOT Special Provisions (49 CFR 172.102)

- : 203 : 241
- : G Identifies PSN requiring a technical name
- : IB3 Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail : 5 L (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75) DOT Vessel Stowage Location

ion : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Other information	: No supplementary information available.
TDG	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: 3265
Proper Shipping Name (IMDG)	: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.
Class (IMDG)	: 8 - Corrosive substances
Packing group (IMDG)	: III - substances presenting low danger
Air transport	
UN-No. (IATA)	: 3265
Proper Shipping Name (IATA)	: Corrosive liquid, acidic, organic, n.o.s.
Class (IATA)	: 8 - Corrosives
Packing group (IATA)	: III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

4-Fluoro-3-methylbenzoyl chloride	CAS No 455-84-5	100%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

Eye Dam. 1	Serious eye damage/eye irritation Category 1	
Skin Corr. 1B	Skin corrosion/irritation Category 1B	
STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
H314	Causes severe skin burns and eye damage	
H318	Causes serious eye damage	
H335	May cause respiratory irritation	

NFPA health hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard	: 1 - Must be preheated before ignition can occur.
NFPA reactivity	: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HMIS III Rating	
Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physical	: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.