

Safety Data Sheet 2816702

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification

1.1. Identification

Product form : Substance

Substance name : 2-(Trifluoromethyl)benzoyl chloride

 CAS No
 : 312-94-7

 Product code
 : 2816-7-02

 Formula
 : C8H4CIF3O

 Synonyms
 : OTF-BOC

 Other means of identification
 : MFCD00000667

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

1.3. Details of the supplier of the safety data sheet

SynQuest Laboratories, Inc.

P.O. Box 309

Alachua, FL 32615 - United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 4 H227 - Combustible liquid

Skin Corr. 1A H314 - Causes severe skin burns and eye damage

Eye Dam. 1 H318 - Causes serious eye damage STOT SE 3 H335 - May cause respiratory irritation

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS05

GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H227 - Combustible liquid

H314 - Causes severe skin burns and eye damage

H335 - May cause respiratory irritation

Precautionary statements (GHS-US) : P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking

P260 - Do not breathe fumes, mist, spray, vapors P264 - Wash skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/ physician

P321 - Specific treatment (see supplemental first aid instructions on this label)

P363 - Wash contaminated clothing before reuse

P370+P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

12/08/2016 EN (English US) SDS ID: 2816702 Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards

Other hazards not contributing to the classification

: Lachrymator.

Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

Substance

Substance type : Mono-constituent

Name	Product identifier	%	Classification (GHS-US)
2-(Trifluoromethyl)benzoyl chloride (Main constituent)	(CAS No) 312-94-7	<= 100	Flam. Liq. 4, H227 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of H-phrases: see section 16

Mixture

Not applicable

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general : In case of accident or if you feel unwell, seek medical advice immediately (show the label

where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.

First-aid measures after skin contact

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Get immediate

medical advice/attention.

Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if First-aid measures after eye contact

present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse First-aid measures after ingestion mouth out with water. Get immediate medical advice/attention.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section Symptoms/injuries

2.2) and/or in section 11.

Symptoms/injuries after inhalation Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea,

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. **Extinguishing media**

Suitable extinguishing media Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media

appropriate for surrounding fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Thermal decomposition generates: Carbon oxides. Hydrogen chloride.

Explosion hazard Risk of explosion if heated under confinement. Use water spray or fog for cooling exposed

containers. May form flammable/explosive vapor-air mixture.

: Reacts with water, generates gases or heat. Reacts on exposure to water with some metals to Reactivity

release highly explosive/flammable hydrogen gas.

Advice for firefighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

: Wear gas tight chemically protective clothing in combination with self contained breathing Protection during firefighting

apparatus. For further information refer to section 8: "Exposure controls/personal protection".

12/08/2016 EN (English US) SDS ID: 2816702 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures

: Evacuate unnecessary personnel. Ensure adequate air ventilation. Do not breathe gas, fumes, vapor or spray.

6.1.1. For non-emergency personnel

Emergency procedures

: Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures

: Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of ignition.

6.2. **Environmental precautions**

Avoid release to the environment. Notify authorities if product enters sewers or public waters

Methods and material for containment and cleaning up

For containment

Other information

: Stop leak if safe to do so. Dike for recovery or absorb with appropriate material.

Methods for cleaning up

Take up large spills with pump or vacuum and finish with dry chemical absorbent. Use explosion-proof equipment. Take up small spills with dry chemical absorbent. Sweep or shovel spills into appropriate container for disposal. Ventilate area.

: For disposal of solid materials or residues refer to section 13: "Disposal considerations".

Reference to other sections

No additional information available

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Hygiene measures

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Conditions for safe storage, including any incompatibilities

Technical measures

: Comply with applicable regulations.

Storage conditions

Keep container closed when not in use. Keep away from ignition sources. Moisture sensitive.

Keep contents under inert gas.

Incompatible materials

: Refer to Section 10 on Incompatible Materials.

Storage area

: Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

Control parameters

No additional information available

Exposure controls

Appropriate engineering controls

Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection

: Protective gloves. 29 CFR 1910.138: Hand Protection.

Eye protection

: Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection.

Skin and body protection

: Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory

Protection

Other information

: Safety shoes. 29 CFR 1910.136: Foot Protection.

12/08/2016 EN (English US) SDS ID: 2816702 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : No data available
Odor : No data available
Odor threshold : No data available
pH : No data available

Melting point : -21.7 °C

Freezing point : No data available
Boiling point : 72 °C (@ 7 mm Hg)

Flash point : 95 °C

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available **Explosion limits** : No data available Explosive properties No data available : No data available Oxidizing properties Vapor pressure No data available Relative density : No data available : No data available Relative vapor density at 20 °C Specific gravity / density 1.416 g/ml (@ 20 °C) Molecular mass : 208.57 g/mol Solubility : No data available : No data available Log Pow Auto-ignition temperature : No data available Decomposition temperature No data available Viscosity No data available : No data available Viscosity, kinematic Viscosity, dynamic : No data available

9.2. Other information

Refractive index : 1.4815 (@ 20 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with water, generates gases or heat. Reacts on exposure to water with some metals to release highly explosive/flammable hydrogen gas.

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from heat, sparks and flame. Moisture.

10.5. Incompatible materials

Alcohols. Oxidizing agents. Strong bases. Water.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

12/08/2016 EN (English US) SDS ID: 2816702 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough,

shortness of breath, headache, nausea.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

Waste disposal recommendations : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Recycle the material as far as possible.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3265 Corrosive liquid, acidic, organic, n.o.s., 8, II

UN-No.(DOT) : UN3265

Proper Shipping Name (DOT) : Corrosive liquid, acidic, organic, n.o.s.

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) : 8 - Corrosive

8

Packing group (DOT) : II - Medium Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Symbols : G - Identifies PSN requiring a technical name

12/08/2016 EN (English US) SDS ID: 2816702 5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154 DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

DOT Vessel Stowage Other 40 - Stow "clear of living quarters" Other information : No supplementary information available.

TDG

No additional information available

Transport by sea

UN-No. (IMDG) : 3265

Proper Shipping Name (IMDG) : CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.

Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : II - substances presenting medium danger

Air transport

UN-No. (IATA)

Proper Shipping Name (IATA) : Corrosive liquid, acidic, organic, n.o.s.

Class (IATA) : 8 - Corrosives Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

2-(Trifluoromethyl)benzoyl chloride CAS No 312-94-7	100%
---	------

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

12/08/2016 EN (English US) SDS ID: 2816702 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations

2-(Trifluoromethyl)benzoyl chloride (312-94-7)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the Korean ECL (Existing Chemicals List)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Full text of H-phrases:

Eye Dam. 1	Serious eye damage/eye irritation Category 1	
Flam. Liq. 4	Flammable liquids Category 4	
Skin Corr. 1A	Skin corrosion/irritation Category 1A	
STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
H227	Combustible liquid	
H314	Causes severe skin burns and eye damage	
H318	Causes serious eye damage	
H335	May cause respiratory irritation	

NFPA health hazard : 3 - Short exposure could cause serious temporary or

residual injury even though prompt medical attention was

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high

temperature before ignition can occur.

: 1 - Normally stable, but can become unstable at elevated NFPA reactivity temperatures and pressures or may react with water with

some release of energy, but not violently.



HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

: 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient Flammability temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F

but below 200 F. (Classes II & IIIA)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo

hazardous polymerization in the absence of inhibitors.

SDS US (GHS HazCom 2012)

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

12/08/2016 EN (English US) SDS ID: 2816702 7/7