

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS ID: 3131101

Issue date: 10/31/2024 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Substance

Substance name : Dimethylamine, anhydrous

 CAS-No.
 : 124-40-3

 Product code
 : 3131-1-01

 Formula
 : C2H7N

 Other means of identification
 : MFCD00008288

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Laboratory chemicals

Manufacture of substances

Scientific research and development

1.3. Supplier

SynQuest Laboratories, Inc.

P.O. Box 309

Alachua, FL, Alachua, 32615

United States of America

T (386) 462-0788 - F (386) 462-7097

info@synquestlabs.com - www.synquestlabs.com

1.4. Emergency telephone number

Emergency number : (844) 523-4086 (3E Company - Account 10069)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable gases Category 1 H220 Extremely flammable gas

Gases under pressure Liquefied gas H280 Contains gas under pressure; may explode if heated

Acute toxicity (inhalation:gas) Category 4

Skin corrosion/irritation Category 2

H315

Serious eye damage/eye irritation Category 1

H318

Causes skin irritation

Causes serious eye damage

Specific target organ toxicity – Single exposure, Category 3,

H335

May cause respiratory irritation

Respiratory tract irritation

Hazardous to the aquatic environment – Acute Hazard Category 3 H402 Harmful to aquatic life

Hazardous to the aquatic environment – Chronic Hazard Category 3 H412 Harmful to aquatic life with long lasting effects

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)









Signal word (GHS US) : Danger

Safety Data Sheet

Precautionary statements (GHS US)

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard statements (GHS US) : H220 - Extremely flammable gas

H280 - Contains gas under pressure; may explode if heated

H315 - Causes skin irritation

H318 - Causes serious eye damage

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

H412 - Harmful to aquatic life with long lasting effects

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 - Avoid breathing fumes, gas, mist, spray, vapors.

P264 - Wash skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 - If on skin: Wash with plenty of soap and water

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor/ physician

P321 - Specific treatment (see supplemental first aid instructions on this label)

P332+P313 - If skin irritation occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.

P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 - Eliminate all ignition sources if safe to do so.

P403 - Store in a well-ventilated place.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P410+P403 - Protect from sunlight. Store in a well-ventilated place.

P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Lachrymator.

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%	GHS US classification
Dimethylamine, anhydrous (Main constituent)	CAS-No.: 124-40-3	≤ 100	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Acute Tox. 4 (Inhalation:gas), H332 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402 Aquatic Chronic 3, H412

Full text of hazard classes and H-statements : see section 16

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general

: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Move the affected personnel away from the contaminated area.

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial respiration. Get immediate medical advice/attention.

First-aid measures after skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Get immediate medical advice/attention.

First-aid measures after eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Immediately flush eyes thoroughly with water for at least 15 minutes. Get immediate medical advice/attention.

First-aid measures after ingestion

: Due to its physical form, exposure to this chemical is not likely. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth out with water. Get immediate medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects

: The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11.

Symptoms/effects after inhalation

: May cause drowsiness or dizziness. Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media

: Alcohol resistant foam. Carbon dioxide. Dry powder. Water spray. Use extinguishing media appropriate for surrounding fire.

5.2. Specific hazards arising from the chemical

Fire hazard

: Thermal decomposition generates: Carbon oxides. Nitrogen oxides.

Explosion hazard

: Contains gas under pressure; may explode if heated. Use water spray or fog for cooling exposed containers. May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions

: In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection during firefighting

: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Evacuate unnecessary personnel. Ensure adequate air ventilation. May cause suffocation by reducing oxygen available for breathing. Do not breathe gas, fumes, vapor or spray.

6.1.1. For non-emergency personnel

Emergency procedures

: Only qualified personnel equipped with suitable protective equipment may intervene.

10/31/2024 (Issue date) EN (English US) 3/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Emergency procedures : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground

level. Consider the risk of potentially explosive atmospheres. Eliminate every possible source of

ignition.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so.

Methods for cleaning up : Ventilate area.

Other information : For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

6.4. Reference to other sections

No additional information available

Precautions for safe handling

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Handle empty containers with care

because residual vapors are flammable. Close valve after each use and when empty.

: Do not handle until all safety precautions have been read and understood. Ensure good ventilation of the work station. Do not breathe fumes, gas, mist, spray, vapors. Wear personal protective equipment. Avoid contact with skin and eyes. Keep away from ignition sources (including static discharges). Proper grounding procedures to avoid static electricity should be

followed. Use only non-sparking tools.

Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or

smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep container closed

when not in use. Keep away from ignition sources.

Incompatible materials : Refer to Section 10 on Incompatible Materials.

Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Systems under pressure should be regularily checked for leakage. Oxygen detectors should be used when asphyxiating gases may be released. Gas detectors should be used when toxic gases may be released.

10/31/2024 (Issue date) EN (English US) 4/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures/Personal protective equipment

Hand protection:

protective gloves. 29 CFR 1910.138: Hand Protection

Eye protection:

Chemical goggles or safety glasses. Face shield. 29 CFR 1910.133: Eye and Face Protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. 29 CFR 1910.134: Respiratory Protection

Personal protective equipment symbol(s):









Thermal hazard protection:

Cold insulating gloves.

Other information:

Safety shoes. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Color: No data availableOdor: No data availableOdor threshold: No data availablepH: No data available

Melting point : -92 °C

Freezing point : No data available

Boiling point : $6.9 \, ^{\circ}\mathrm{C}$ Flash point : $-6.8 \, ^{\circ}\mathrm{C}$

Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : No data available
Vapor pressure : 39.5 psia (@ 20 °C)
Relative vapor density at 20 °C : No data available
Relative density : No data available
Density : 0.6804 g/ml (@ 0 °C)
Molecular mass : 45.085 g/mol
Solubility : No data available

No data available Partition coefficient n-octanol/water (Log Pow) No data available Auto-ignition temperature No data available Decomposition temperature : No data available : No data available Viscosity, kinematic : No data available Viscosity, dynamic **Explosion limits** : No data available Explosive properties : No data available Oxidizing properties : No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive vapors.

Carcinogenicity

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Keep away from heat, sparks and flame.

10.5. Incompatible materials

Strong oxidizing agents. Nitrates. nitrites. nitrous acid. Mercury/mercury oxides. Finely divided metals (AI, Mg, Zn). This material may attack some forms of plastics, rubbers and coatings.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Hazardous decomposition products in case of fire, see Section 5.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Inhalation: gas: Harmful if inhaled.

Acute toxicity (illitalation)	milation.gas. Harmar i ililatoa.
Dimethylamine, anhydrous (124-40-3)	
LC50 Inhalation - Rat [ppm]	4540 ppm
ATE US (gases)	4540 ppmV/4h
Skin corrosion/irritation :	Causes skin irritation.
Serious eye damage/irritation :	Causes serious eye damage.
Respiratory or skin sensitization :	Not classified
Germ cell mutagenicity :	Not classified
Skin corrosion/irritation : Serious eye damage/irritation : Respiratory or skin sensitization :	Causes skin irritation. Causes serious eye damage. Not classified

Reproductive toxicity : Not classified STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not applicable
Viscosity, kinematic : No data available

Symptoms/effects : The most important known symptoms and effects are described in the labelling (see section 2.2)

and/or in section 11.

: Not classified

Symptoms/effects after inhalation : May cause drowsiness or dizziness. Material is destructive to tissue of the mucuous membranes and upper respiratory tract. Cough, shortness of breath, headache, nausea.

10/31/2024 (Issue date) EN (English US) 6/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

Dimethylamine, anhydrous (124-40-3)

Persistence and degradability Rapidly degradable

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods

Product/Packaging disposal recommendations

Additional information

: Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber.

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

: Recycle the material as far as possible.

SECTION 14: Transport information

14.1. UN number

DOT NA No : UN1032 UN-No. (TDG) : UN1032 UN-No. (IMDG) : 1032 UN-No. (IATA) : 1032

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Dimethylamine, anhydrous
Proper Shipping Name (TDG) : DIMETHYLAMINE, ANHYDROUS
Proper Shipping Name (IMDG) : DIMETHYLAMINE, ANHYDROUS
Proper Shipping Name (IATA) : Dimethylamine, anhydrous

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 2.1 Hazard labels (DOT) : 2.1



TDG

Transport hazard class(es) (TDG) : 2.1

10/31/2024 (Issue date) EN (English US) 7/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (TDG) : 2.1



IMDG

Transport hazard class(es) (IMDG) : 2.1 Hazard labels (IMDG) : 2.1



IATA

Transport hazard class(es) (IATA) : 2.1 Hazard labels (IATA) : 2.1



14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (TDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1032

DOT Special Provisions (49 CFR 172.102) : N87 - The use of copper valves on UN pressure receptacles is prohibited.

T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in

accordance with the requirements of 173.313 of this subchapter.

DOT Packaging Non Bulk (49 CFR 173.xxx) : 304
DOT Packaging Bulk (49 CFR 173.xxx) : 314, 315
DOT Quantity Limitations Passenger aircraft/rail (49 : Forbidden

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel

carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger

vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters",52 - Stow "separated from" acids

TDG

UN-No. (TDG) : UN1032
ERAP Index : 3000
Explosive Limit and Limited Quantity Index : 0
Excepted quantities (TDG) : E0

10/31/2024 (Issue date) EN (English US) 8/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Passenger Carrying Ship Index
Passenger Carrying Road Vehicle or Passenger

Carrying Railway Vehicle Index

: Forbidden : Forbidden

Emergency Response Guide (ERG) Number : 118

IMDG

Limited quantities (IMDG) : 0

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P200

Tank instructions (IMDG) : T50

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES

EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)

Stowage category (IMDG) : D
Stowage and handling (IMDG) : SW2
Segregation (IMDG) : SG35

Properties and observations (IMDG) : Liquefied, flammable gas with an ammonia-like odour. Heavier than air (1.6). Boiling point: 7°C.

Suffocating in low concentrations.

IATA

PCA Excepted quantities (IATA) : E0 PCA Limited quantities (IATA) : Forbidden PCA limited quantity max net quantity (IATA) : Forbidden PCA packing instructions (IATA) : Forbidden PCA max net quantity (IATA) : Forbidden CAO packing instructions (IATA) 200 CAO max net quantity (IATA) 150kg Special provision (IATA) Α1 ERG code (IATA) 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Dimethylamine, anhydrous CAS-No. 124-40-3 100%

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases		
H220	Extremely flammable gas	
H280	Contains gas under pressure; may explode if heated	
H315	Causes skin irritation	
H318	Causes serious eye damage	
H332	Harmful if inhaled	
H335	May cause respiratory irritation	
H402	Harmful to aquatic life	
H412	Harmful to aquatic life with long lasting effects	

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



Hazard Rating

Physical

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

give

Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions.

Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB IC)

: 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Safety Data Sheet (SDS), USA

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is offered solely for your consideration, investigation, and verification. It does not represent any guarantee of the properties of the product nor that the hazard precautions or procedures described are the only ones which exist. SynQuest shall not be held liable or any damage resulting from handling or from contact with the above product.

10/31/2024 (Issue date) EN (English US) 10/10